

1. Wyzwalacze.

```
CREATE [ CONSTRAINT ] TRIGGER name { BEFORE | AFTER | INSTEAD OF } { event [ OR ... ] }  
ON table  
[ FROM referenced_table_name ]  
[ NOT DEFERRABLE | [ DEFERRABLE ] { INITIALLY IMMEDIATE | INITIALLY DEFERRED } ]  
[ FOR [ EACH ] { ROW | STATEMENT } ]  
[ WHEN ( condition ) ]  
EXECUTE PROCEDURE function_name ( arguments )  
  
where event can be one of:  
  
INSERT  
UPDATE [ OF column_name [, ... ] ]  
DELETE  
TRUNCATE
```

OLD – wiersz przed modyfikacją lub NULL

dla FOR EACH STATEMENT

Występuje dla UPDATE lub DELETE;

NEW – wiersz po modyfikacji lub NULL dla FOR EACH STATEMENT.

występuje dla INSERT lub UPDATE.

TG_NAME – Nazwa wykonywanego wyzwalacza.

TG_WHEN – BEFORE lub AFTER

TG_LEVEL – ROW lub STATEMENT

TG_OP – INSERT, UPDATE, lub DELETE

TG_RELID, TG_RELNAME – OID i nazwa tabeli, dla której uruchomiono wyzwalacz

TGTG _NARGS, TG_ARGV[] – Liczba argumentów i argumenty (napisy), przekazane do funkcji wyzwalacza.