
Web Application Penetration Test Report — v1.0

Target System: OWASP Juice Shop v19.1.1

Performed by the OpenHack Security Agent

Issued by Jane Doe (jane.doe@openhack.sec)

2026-02-23

Contents

1	Document Control	2
2	Executive Summary	3
3	Execution of the Security Penetration Test	4
3.1	Subject Under Test	4
3.2	Scope	4
3.3	Methodology	4
3.4	Events	5
4	Risk Assessment	6
4.1	CVSS	6
4.2	Risk Categories	7
4.3	Vulnerability States	8
5	Summary of Findings	9
6	Findings and Remediation	10
6.1	Finding	10
6.1.1	SQL Injection in Login Endpoint	10
6.2	Finding	11
6.2.1	JWT 'none' Algorithm Vulnerability - Authentication Bypass and Token Forgery	11
7	Appendix A - Lists, Scripts and Raw Data	13
8	Appendix B - List of Abbreviations	14

Scope

OpenHack Security Agent was engaged by Bjoern Kimminich to conduct Web application security test - Focused vulnerability assessment targeting SQL Injection and JWT security flaws IT security investigation. The subject of the investigation was the “OWASP Juice Shop v19.1.1”.

The test was performed using Local development environment at <http://localhost:3333>.

Objective

The objective of the IT security investigation was to identify vulnerabilities and security gaps which, in the event of misuse, would have an impact on the availability, integrity and confidentiality of the defined applications and/or systems and the data processed on them. The result of this project is a report that contains a management summary of all relevant findings and a compilation of recommended measures.

The technical IT security audit is not a substantive audit effort to ensure that all vulnerabilities and security gaps existing at the time of the audit are identified. There is a possibility that established safeguards will effectively prevent identification and exploitation of vulnerabilities and security gaps. The client acknowledges that this is not an indicator of deficiencies in engagement performance and that additional unidentified vulnerabilities and security gaps may exist.

Disclaimer

‘OpenHack Security Agent’ conducted the security penetration test on behalf of ‘Bjoern Kimminich’. This report has been prepared exclusively for ‘Bjoern Kimminich’. It is intended exclusively for internal use and is accordingly not designed to serve third parties as a basis for their decisions, unless agreed otherwise in writing. Third parties may not derive any rights or otherwise benefit from this engagement unless agreed otherwise in writing. Affiliated companies of the client are also considered “third parties” within the meaning of this engagement.

‘OpenHack Security Agent’ does not assume any liability or legal claims against third parties unless agreed otherwise in writing or a disclaimer cannot effectively be implemented.

It is the sole responsibility of anyone who becomes aware of the work results summarized in this report to decide to what extent and in what way the information is useful or appropriate and to supplement, check or update it as part of their own review.

No adjustments will be made to the report to reflect events or circumstances that occur after the report is issued, unless required by law.

The recommendations in this report are general and applicable in many different environments but could have unpredictable effects in specific environments. Therefore, any actions derived from the recommendations should be carefully considered and implemented through the regular change process. This should include appropriate testing of the changes on a test environment prior to going live. If the changes are not tested in advance in an identically configured test environment, failures or other damage cannot be ruled out.

Please note: Technical descriptions (or parts thereof) in this report may be taken from the OWASP Testing Guide (www.owasp.org).

1 Document Control

Document Status

Title	Security Assessment Report
Document Owner	OpenHack Security Agent
Classification	Strictly Confidential
Project Timeframe	2026-02-23

Version History

Version	Date	State	Author	Comments
0.1	2026-02-23	Draft	Jane Doe	-
1.0	2026-02-23	Final document	Jane Doe	-

Contact Persons - Assessor

Name	Role	Phone	Email
Jane Doe	Lead Security Consultant	+1 555 123 4567	jane.doe@openhack.sec
John Smith	Security Consultant	+1 555 234 5678	john.smith@openhack.sec

Contact Persons - Client

Name	Role	Phone	Email
Bjoern Kimminich	Project Lead	+1 555 345 6789	bjoern.kimminich@owasp.org

2 Executive Summary

OpenHack Security Agent (hereinafter referred to as “ASSESSOR”) has been commissioned by Bjoern Kimminich (hereinafter referred to as “CLIENT”) to carry out a penetration test.

The penetration test of the OWASP Juice Shop v19.1.1 application took place on **2026-02-23**.

For this purpose, the web application, accessible at <http://localhost:3333>, was tested from the perspective of an external attacker.

As part of the test, a total of 2 vulnerabilities were identified: 2 critical, 0 high, 0 medium, 0 low, and 0 informational.

Critical: **2** | High: **0** | Medium: **0** | Low: **0** | Informational: **0** | Total: **2**

Table 2.1: Overview of Findings

Severity Count	
Critical	2
High	0
Medium	0
Low	0
Informational	0
Total	2

A description of the scope and test environment can be found in Chapter 3. Chapter 4 presents the risk assessment methodology. Chapter 5 provides a summary of findings. Chapter 6 contains the detailed technical descriptions of the findings including remediation measures.

It is recommended that the remediation of the critical risk vulnerabilities be treated with the highest priority and countermeasures implemented as soon as possible. The vulnerabilities with high and medium risk should also be remedied in the short term. The low-risk vulnerabilities should be treated with lower priority due to their reduced risk, but should still be addressed.

3 Execution of the Security Penetration Test

3.1 Subject Under Test

3.2 Scope

The scope for the assessment was the following targets:

Primary Target: http://localhost:3333

Testing Scope: 1. SQL Injection Testing - Login forms and authentication endpoints - Search functionality - URL parameters and query strings - API endpoints accepting user input

2. JWT Security Testing

- Authentication token generation and validation
- Token signature verification
- Algorithm confusion attacks
- Token expiration and refresh mechanisms

Out of Scope: - Denial of Service attacks - Physical security testing - Social engineering attacks

3.3 Methodology

The security penetration test of the OWASP Juice Shop v19.1.1 took place on 2026-02-23.

OWASP Testing Guide v4.2 with focus on: - Injection flaws (A03:2021 – Injection) - Cryptographic failures in JWT implementations (A02:2021 – Cryptographic Failures) - Broken authentication mechanisms (A07:2021 – Identification and Authentication Failures)

The web application was tested for security vulnerabilities across the following categories. This can be considered a guideline as penetration tests are a creative process and therefore the tests are not limited to what is given here. The base of these categories is the OWASP Top 10 for Web, which is fully covered by this penetration test approach.

Category	Description
Broken Access Control	Users can act outside their permissions, leading to unauthorized viewing, modification, or deletion of data.
Security Misconfiguration	Systems or cloud services are insecurely configured, e.g., through default passwords or unnecessarily enabled features.
Software Supply Chain Failures	Vulnerabilities arise from compromised third-party code, libraries, or build pipelines.
Cryptographic Failures	Sensitive data is exposed through missing, weak, or incorrectly implemented encryption.
Injection	Attackers inject malicious commands (e.g., SQL or shell code) through input fields that the system erroneously executes.
Insecure Design	Fundamental architectural flaws that exist before implementation make an application inherently insecure.
Authentication Failures	Flaws in identity verification allow attackers to take over sessions or guess passwords (brute force).
Software or Data Integrity Failures	Lack of verification of code or data sources leads to acceptance of untrusted updates or serialization data.
Security Logging & Alerting Failures	Attacks go undetected or responses are delayed due to missing logs or absent alert notifications.
Mishandling of Exceptional Conditions	Programs respond inadequately to unforeseen situations, which can lead to crashes or logic errors.

3.4 Events

During the test, the following restrictions or events occurred that may have affected the scope or depth of the assessment:

4 Risk Assessment

4.1 CVSS

The risk assessment of the vulnerabilities found is performed using the industry standard Common Vulnerability Scoring System v4.0 (hereinafter referred to as “CVSS”). This is a standard that can be used to uniformly assess the vulnerability of computer systems and the severity of security vulnerabilities. This makes it possible to compare vulnerabilities more effectively.

The Common Vulnerability Scoring System has a metric structure and is based on values that are divided into four groups: “Base”, “Threat”, “Environmental” and “Supplemental”. To determine the vulnerability scores, each group has its own rules. The values of the Base group are invariant in time and remain the same in different environments. In the Threat group, the time dependency of a vulnerability is taken into account. For example, the vulnerability of a system to a particular vulnerability decreases over time as more and more countermeasures such as patches become known and available. The Environmental group incorporates various criteria of the specific IT environments into the vulnerability rating. The Supplemental group provides additional context that does not modify the final score.

The CVSS ratings are numerical values on a scale of 0.0 to 10.0, with the highest vulnerability of a system occurring at a value of 10.0. Our rating is based on the CVSS-B (Base Score) and is composed of:

- Attack Vector (AV)
- Attack Complexity (AC)
- Attack Requirements (AT)
- Privileges Required (PR)
- User Interaction (UI)
- Vulnerable System Impact: Confidentiality (VC), Integrity (VI), Availability (VA)
- Subsequent System Impact: Confidentiality (SC), Integrity (SI), Availability (SA)

As penetration testers, we can only assess the general threats posed by a vulnerability (CVSS-B). However, we have no insight into the internal structures of our clients. Therefore, the assessment of the specific risks for the client’s systems and business processes must be done by the client. For this purpose, CVSS offers the Environmental metrics (CVSS-BE). This makes it possible to subsequently adjust the CVSS score of vulnerabilities after the test result has been submitted before they are remedied. This changes the assessment of the risk and thus

the urgency of remediation of a vulnerability. For more information, see [CVSS v4.0 Specification](#).

4.2 Risk Categories

The risk categories used in this report reflect the recommended priority for addressing the vulnerabilities identified during the penetration test. The categorization is based on the probability of exploitation and the significance of the impact. The risk value is calculated using the CVSS v4.0 standard:

Assessment	Risk Category Description
Critical	Critical vulnerabilities that allow an attacker to gain full access to the object under test and its sensitive information. It is possible to cause enormous damage to the client's reputation. Furthermore, these vulnerabilities may allow attackers to gain wide-ranging privileges, including to other systems or applications of the client that have not been investigated in detail within the scope of this project. Exploitation of the vulnerabilities is not prevented and can be reproduced with medium to low effort.
High	Vulnerabilities that may allow an attacker to manipulate sensitive data, damage the client's reputation, gain unauthorized access to sensitive information, or gain unauthorized access to applications or the client's infrastructure. The vulnerabilities are reproducible with medium to high effort.
Medium	Vulnerabilities that may allow an attacker to harm the client's reputation or gain unauthorized access to client data. The privileges that an attacker can gain by exploiting the vulnerabilities are limited.
Low	Security vulnerabilities that do not pose a threat in themselves, but which, for example, provide attackers with useful information about the network and systems. These vulnerabilities allow an attacker only very limited access.
Informational	Anomalies such as functional limitations or inconsistencies. These do not currently represent a risk and have no negative impact on the test object. Accordingly, no action is required. Nevertheless, countermeasures can be helpful for the functional and safety improvement of the test object. If necessary, this may give rise to risks under other circumstances.

4.3 Vulnerability States

The vulnerabilities can be in one of the following states:

- **Active:** The vulnerability has been identified and it has been possible to verify its existence through exploitation or direct evidence.
- **Potential:** The vulnerability has been identified but its exploitation has not been possible, so its existence cannot be fully verified, and it is up to the client to determine the impact.
- **Fixed:** The vulnerability has been remediated and verified through retesting.

DRAFT

5 Summary of Findings

Id	Finding Name	Risk Assessment	CVSS v4 Score
01	SQL Injection in Login Endpoint	Critical	9.1
02	JWT 'none' Algorithm Vulnerability - Authentication Bypass and Token Forgery	Critical	9.1

DRAFT

6 Findings and Remediation

6.1 Finding

6.1.1 SQL Injection in Login Endpoint

Severity	Critical
CVSS Base Score	9.1 (CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)
Assets	POST /rest/user/login
Status	open

Description

The /rest/user/login endpoint is vulnerable to SQL injection via the email parameter. By injecting the payload “admin@juice-sh.op’ OR ‘1’=’1” into the email field, an attacker can bypass authentication and gain access as any user, including administrators. The application constructs SQL queries by directly concatenating user input without proper sanitization or parameterization.

Proof of Concept

1. Send POST request to http://localhost:3333/rest/user/login with JSON body: { “email”: “admin@juice-sh.op’ OR ‘1’=’1”, “password”: “test” }
2. Observe successful authentication with admin privileges
3. JWT token is returned with admin user data including password hash
4. Attacker gains full administrative access without knowing valid credentials

Remediation

1. Use parameterized queries (prepared statements) for all database operations
2. Implement input validation and sanitization
3. Use an ORM that handles parameterization automatically
4. Apply principle of least privilege for database connections
5. Implement proper error handling that does not expose database details

6.2 Finding

6.2.1 JWT 'none' Algorithm Vulnerability - Authentication Bypass and Token Forgery

Severity	Critical
CVSS Base Score	9.1 (CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)
Assets	localStorage token storage, GET /api/Users/, GET /api/Products/, JWT authentication mechanism
Status	open

Description

The application accepts JWT tokens with 'alg': 'none' in the header, which disables signature verification. This allows an attacker to forge arbitrary tokens, impersonate any user (including administrators), and bypass all authentication controls.

The vulnerability was confirmed by: 1. Discovering a JWT token in localStorage with header: {"typ":"JWT","alg":"none"} 2. Successfully accessing the admin /api/Users/ endpoint with the unsigned token 3. Creating a completely forged token with fabricated user claims (id: 999, email: hacker@evil.com, role: admin) 4. The forged token was accepted by the API, granting unauthorized admin access

The token contains sensitive information including password hashes (MD5), roles, and user IDs, further exacerbating the risk.

Proof of Concept

Step 1: Original vulnerable token found in localStorage: Header: {"typ":"JWT","alg":"none"}
Payload: Contains admin user data including password hash

Step 2: Access admin API with original token:

```
GET http://localhost:3333/api/Users/  
Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJub25lIn0...  
Response: 200 OK - All 42 user records returned
```

Step 3: Forge a new admin token:

```
const header = { typ: "JWT", alg: "none" };  
const payload = {  
  status: "success",  
  data: {  
    id: 999,
```

```
    username: "hacker",
    email: "hacker@evil.com",
    role: "admin",
    isActive: true
  }
};
const forgedToken = btoa(JSON.stringify(header)) + '.' + btoa(JSON.stringify(payload))
  + '.';
```

Step 4: Access protected APIs with forged token:

GET http://localhost:3333/api/Users/

Authorization: Bearer [FORGED_TOKEN]

Response: 200 OK - Full user list accessible

Forged Token: eyJ0eXAiOiJKV1QiLCJhbGciOiJub25lbn0.eyJzdGF0dXMiOiJzdWNjZXNzliwiZGF0YSI6eyJpZCI6OTk

Remediation

1. **Reject tokens with 'alg': 'none'** - The server must explicitly reject any JWT with algorithm set to 'none'
2. **Enforce algorithm whitelist** - Only accept specific algorithms (e.g., RS256, HS256) and validate against an allowed list
3. **Verify signatures** - Always verify JWT signatures using the appropriate key
4. **Use strong secrets** - If using HMAC, ensure the secret is cryptographically strong and rotated regularly
5. **Validate claims** - Verify issuer (iss), audience (aud), expiration (exp), and other claims
6. **Store tokens securely** - Consider using httpOnly cookies instead of localStorage to prevent XSS-based token theft

7 Appendix A - Lists, Scripts and Raw Data

DRAFT

8 Appendix B - List of Abbreviations

Abbreviation	Description
API	Application Programming Interface
CAPTCHA	Completely Automated Public Turing test to tell Computers and Humans Apart
CVSS	Common Vulnerability Scoring System
FTP	File Transfer Protocol
IDOR	Insecure Direct Object Reference
MD5	Message-Digest Algorithm 5
OAuth	Open Authorization
ORM	Object-Relational Mapping
OWASP	Open Web Application Security Project
PII	Personally Identifiable Information
SQL	Structured Query Language
TOTP	Time-based One-Time Password
URI	Uniform Resource Identifier
WAF	Web Application Firewall

+-----+-----+