
Web Application Penetration Test Report — v1.0

Target System: Acme Web Pentest

Performed by the OpenHack Security Agent

Issued by Alex Tester (alex@example.com)

2026-02-17

Contents

1 Document Control	2
2 Executive Summary	3
3 Execution of the Security Penetration Test	4
3.1 Subject Under Test	4
3.2 Scope	4
3.3 Methodology	4
3.4 Events	5
4 Risk Assessment	6
4.1 CVSS	6
4.2 Risk Categories	7
4.3 Vulnerability States	8
5 Summary of Findings	9
6 Findings and Remediation	10
6.1 Findings	10
6.1.1 F-0001: Broken Access Control	10
7 Appendix A - Lists, Scripts and Raw Data	11
8 Appendix B - List of Abbreviations	12

Scope

OpenHack was engaged by Acme Corp to conduct gray-box IT security investigation. The subject of the investigation was the “Acme Web Pentest”.

The test was performed using staging.

Objective

The objective of the IT security investigation was to identify vulnerabilities and security gaps which, in the event of misuse, would have an impact on the availability, integrity and confidentiality of the defined applications and/or systems and the data processed on them. The result of this project is a report that contains a management summary of all relevant findings and a compilation of recommended measures.

The technical IT security audit is not a substantive audit effort to ensure that all vulnerabilities and security gaps existing at the time of the audit are identified. There is a possibility that established safeguards will effectively prevent identification and exploitation of vulnerabilities and security gaps. The client acknowledges that this is not an indicator of deficiencies in engagement performance and that additional unidentified vulnerabilities and security gaps may exist.

Disclaimer

OpenHack conducted the security penetration test on behalf of Acme Corp. This report has been prepared exclusively for Acme Corp. It is intended exclusively for internal use and is accordingly not designed to serve third parties as a basis for their decisions, unless agreed otherwise in writing. Third parties may not derive any rights or otherwise benefit from this engagement unless agreed otherwise in writing. Affiliated companies of the client are also considered “third parties” within the meaning of this engagement.

OpenHack does not assume any liability or legal claims against third parties unless agreed otherwise in writing or a disclaimer cannot effectively be implemented.

It is the sole responsibility of anyone who becomes aware of the work results summarized in this report to decide to what extent and in what way the information is useful or appropriate and to supplement, check or update it as part of their own review.

No adjustments will be made to the report to reflect events or circumstances that occur after the report is issued, unless required by law.

The recommendations in this report are general and applicable in many different environments but could have unpredictable effects in specific environments. Therefore, any actions derived from the recommendations should be carefully considered and implemented through the regular change process. This should include appropriate testing of the changes on a test environment prior to going live. If the changes are not tested in advance in an identically configured test environment, failures or other damage cannot be ruled out.

Please note: Technical descriptions (or parts thereof) in this report may be taken from the OWASP Testing Guide (www.owasp.org).

1 Document Control

Document Status

Title	Security Assessment Report
Document Owner	OpenHack
Classification	Strictly Confidential
Project Timeframe	2026-02-17

Version History

Version	Date	State	Author	Comments
0.1	2026-02-17	Draft	Alex Tester	-
1.0	2026-02-17	Final document	Alex Tester	-

Contact Persons - Assessor

Name	Role	Phone	Email
Alex Tester	Lead	-	alex@example.com

Contact Persons - Client

Name	Role	Phone	Email
Pat Client	CISO	-	pat@acme.example

2 Executive Summary

OpenHack (hereinafter referred to as “ASSESSOR”) has been commissioned by Acme Corp (hereinafter referred to as “CLIENT”) to carry out a penetration test.

The penetration test of the Acme Web Pentest application took place on **2026-02-17**.

For this purpose, the web application, accessible at <https://app.acme.example>, was tested from the perspective of an external attacker. gray-box with test account

A total of 1 findings were included: 0 critical, 1 high, 0 medium, 0 low, and 0 informational.

Critical=0, High=1, Medium=0, Low=0, Informational=0, Total=1.

Table 2.1: Overview of Findings

Severity Count	
Critical	0
High	1
Medium	0
Low	0
Informational	0
Total	1

A description of the scope and test environment can be found in Chapter 3. Chapter 4 presents the risk assessment methodology. Chapter 5 provides a summary of findings. Chapter 6 contains the detailed technical descriptions of the findings including remediation measures.

It is recommended that the remediation of the critical risk vulnerabilities be treated with the highest priority and countermeasures implemented as soon as possible. The vulnerabilities with high and medium risk should also be remedied in the short term. The low-risk vulnerabilities should be treated with lower priority due to their reduced risk, but should still be addressed.

3 Execution of the Security Penetration Test

3.1 Subject Under Test

Customer portal

3.2 Scope

The scope for the assessment was the following targets:

- <https://app.acme.example> - Main application

3.3 Methodology

The security penetration test of the Acme Web Pentest took place on 2026-02-17.

Manual plus targeted automation.

The web application was tested for security vulnerabilities across the following categories. This can be considered a guideline as penetration tests are a creative process and therefore the tests are not limited to what is given here. The base of these categories is the OWASP Top 10 for Web, which is fully covered by this penetration test approach.

Category	Description
Broken Access Control	Users can act outside their permissions, leading to unauthorized viewing, modification, or deletion of data.
Security Misconfiguration	Systems or cloud services are insecurely configured, e.g., through default passwords or unnecessarily enabled features.
Software Supply Chain Failures	Vulnerabilities arise from compromised third-party code, libraries, or build pipelines.
Cryptographic Failures	Sensitive data is exposed through missing, weak, or incorrectly implemented encryption.

Category	Description
Injection	Attackers inject malicious commands (e.g., SQL or shell code) through input fields that the system erroneously executes.
Insecure Design	Fundamental architectural flaws that exist before implementation make an application inherently insecure.
Authentication Failures	Flaws in identity verification allow attackers to take over sessions or guess passwords (brute force).
Software or Data Integrity Failures	Lack of verification of code or data sources leads to acceptance of untrusted updates or serialization data.
Security Logging & Alerting Failures	Attacks go undetected or responses are delayed due to missing logs or absent alert notifications.
Mishandling of Exceptional Conditions	Programs respond inadequately to unforeseen situations, which can lead to crashes or logic errors.

3.4 Events

During the test, the following restrictions or events occurred that may have affected the scope or depth of the assessment: N/A

4 Risk Assessment

4.1 CVSS

The risk assessment of the vulnerabilities found is performed using the industry standard Common Vulnerability Scoring System v4.0 (hereinafter referred to as “CVSS”). This is a standard that can be used to uniformly assess the vulnerability of computer systems and the severity of security vulnerabilities. This makes it possible to compare vulnerabilities more effectively.

The Common Vulnerability Scoring System has a metric structure and is based on values that are divided into four groups: “Base”, “Threat”, “Environmental” and “Supplemental”. To determine the vulnerability scores, each group has its own rules. The values of the Base group are invariant in time and remain the same in different environments. In the Threat group, the time dependency of a vulnerability is taken into account. For example, the vulnerability of a system to a particular vulnerability decreases over time as more and more countermeasures such as patches become known and available. The Environmental group incorporates various criteria of the specific IT environments into the vulnerability rating. The Supplemental group provides additional context that does not modify the final score.

The CVSS ratings are numerical values on a scale of 0.0 to 10.0, with the highest vulnerability of a system occurring at a value of 10.0. Our rating is based on the CVSS-B (Base Score) and is composed of:

- Attack Vector (AV)
- Attack Complexity (AC)
- Attack Requirements (AT)
- Privileges Required (PR)
- User Interaction (UI)
- Vulnerable System Impact: Confidentiality (VC), Integrity (VI), Availability (VA)
- Subsequent System Impact: Confidentiality (SC), Integrity (SI), Availability (SA)

As penetration testers, we can only assess the general threats posed by a vulnerability (CVSS-B). However, we have no insight into the internal structures of our clients. Therefore, the assessment of the specific risks for the client’s systems and business processes must be done by the client. For this purpose, CVSS offers the Environmental metrics (CVSS-BE). This makes it possible to subsequently adjust the CVSS score of vulnerabilities after the test result has been submitted before they are remedied. This changes the assessment of the risk and thus

the urgency of remediation of a vulnerability. For more information, see [CVSS v4.0 Specification](#).

4.2 Risk Categories

The risk categories used in this report reflect the recommended priority for addressing the vulnerabilities identified during the penetration test. The categorization is based on the probability of exploitation and the significance of the impact. The risk value is calculated using the CVSS v4.0 standard:

Assessment	Risk Category Description
Critical	Critical vulnerabilities that allow an attacker to gain full access to the object under test and its sensitive information. It is possible to cause enormous damage to the client's reputation. Furthermore, these vulnerabilities may allow attackers to gain wide-ranging privileges, including to other systems or applications of the client that have not been investigated in detail within the scope of this project. Exploitation of the vulnerabilities is not prevented and can be reproduced with medium to low effort.
High	Vulnerabilities that may allow an attacker to manipulate sensitive data, damage the client's reputation, gain unauthorized access to sensitive information, or gain unauthorized access to applications or the client's infrastructure. The vulnerabilities are reproducible with medium to high effort.
Medium	Vulnerabilities that may allow an attacker to harm the client's reputation or gain unauthorized access to client data. The privileges that an attacker can gain by exploiting the vulnerabilities are limited.
Low	Security vulnerabilities that do not pose a threat in themselves, but which, for example, provide attackers with useful information about the network and systems. These vulnerabilities allow an attacker only very limited access.
Informational	Anomalies such as functional limitations or inconsistencies. These do not currently represent a risk and have no negative impact on the test object. Accordingly, no action is required. Nevertheless, countermeasures can be helpful for the functional and safety improvement of the test object. If necessary, this may give rise to risks under other circumstances.

4.3 Vulnerability States

The vulnerabilities can be in one of the following states:

- **Active:** The vulnerability has been identified and it has been possible to verify its existence through exploitation or direct evidence.
- **Potential:** The vulnerability has been identified but its exploitation has not been possible, so its existence cannot be fully verified, and it is up to the client to determine the impact.
- **Fixed:** The vulnerability has been remediated and verified through retesting.

DRAFT

5 Summary of Findings

Id	Finding Name	Risk Assessment	CVSS v4 Score
----	--------------	-----------------	---------------

N/A

DRAFT

6 Findings and Remediation

6.1 Findings

6.1.1 F-0001: Broken Access Control

Severity	High
CVSS Base Score	8.6 (CVSS:4.0/AV:N/AC:L/AT:N/PR:L/UI:N/VC:H/VI:H/VA:N/SC:N/SI:N/SA:N)
Assets	https://app.acme.example/orders
Status	Active

Description Unauthorized record access via IDOR.

Access to other users orders. **Proof of Concept** Changed order id in request and accessed data.



Remediation - Enforce object-level authorization checks.

7 Appendix A - Lists, Scripts and Raw Data

TODO: Add supplementary data such as raw scan output, extracted data, scripts used, or other supporting evidence. Use N/A if not applicable.

DRAFT

8 Appendix B - List of Abbreviations

Abbreviation	Description
API	Application Programming Interface
CAPTCHA	Completely Automated Public Turing test to tell Computers and Humans Apart
CVSS	Common Vulnerability Scoring System
FTP	File Transfer Protocol
IDOR	Insecure Direct Object Reference
MD5	Message-Digest Algorithm 5
OAuth	Open Authorization
ORM	Object-Relational Mapping
OWASP	Open Web Application Security Project
PII	Personally Identifiable Information
SQL	Structured Query Language
TOTP	Time-based One-Time Password
URI	Uniform Resource Identifier
WAF	Web Application Firewall
XSS	Cross-Site Scripting