

Model No: TC5FB00-04
Product Line: Tymphany


Rev: 4
Last Update: 2017-03-03 20:44:58

Product Description

This TC family 1.5 inch 4 ohm full-range driver, with ferrite magnet, paper cone and PU surround, and steel basket, is designed to be a cost-effective high performance full range driver. The product was designed with portable and other compact applications in mind.




Mechanical Drawing



Specifications

| | | | | | | | |
|-------------------------------|-------------|--------|--------|-----------|----------------------------|-------------|--------------|
| DC Resistance | Revc | Ohms | 3.58 | 5.0% | Energy Bandwidth Product | EBP | (1/Qes)*fs |
| Minimum Impedance | Zmin | Ohms | 3.94 | 7.5% | Moving Mass | Mms | g |
| Voice Coil Inductance | Le | mH | 0.04 | | Suspension Compliance | Cms | um/N |
| Resonant Frequency | Fs | Hz | 234.82 | 15% | Effective Cone diameter | D | cm |
| Mechanical Q Factor | Qms | | 4.71 | | Effective Piston Area | Sd | cm^2 |
| Electrical Q Factor | Qes | 2.64 | | | Effective Volume | Vas | L |
| Total Q Factor | Qts | | 1.69 | | Motor Force Factor | BL | Tm |
| Ratio Fs/Qts | F | Fs/Qts | 138.87 | | Motor Efficiency Factor | β | (T*M^2)/Ohms |
| Half Space Sensitivity @2.83V | db@2.83V/1M | dB | 83.22 | +/- 1.0db | Voice coil former Material | VCfm | ASV |
| Half Space Sensitivity @1W/1M | db@1W/1M | dB | 80.1 | +/- 1.0db | Voice coil inner diameter | VCd | mm |
| Gap Height | Gh | mm | 2 | | Rated Noise Power | P | W |
| Maximum Linear Excursion | Xmax | mm | 0.6 | | Test Spectrum Bandwidth | 250Hz-20KHz | |
| Ferrofluid Type | FF | | | | Driver Size | Inch | 1.5 in |
| Driver Mass | Kg | 0.07 | | | | | |

Frequency and Impedance Response



Highcharts.com