

Contents

whoami . . . . .	1
echo \$PATH . . . . .	1
find / -type d -iname texmf-dist . . . . .	2
find /usr/share/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf . . . . .	2
find /usr/local/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf . . . . .	2
find /usr/share/texlive -type d -iname “roboto” . . . . .	2
find /usr/local/texlive -type d -iname “roboto” . . . . .	2
find /usr/share/texlive -type d -iname “cascadia*code” . . . . .	3
find /usr/local/texlive -type d -iname “cascadia*code” . . . . .	3
ls -F /usr/share/texlive/texmf-dist/fonts . . . . .	3
ls -F /usr/local/texlive/texmf-dist/fonts . . . . .	3
ls -F /usr/share/texlive/texmf-dist/fonts/opentype . . . . .	3
ls -F /usr/local/texlive/texmf-dist/fonts/opentype . . . . .	3
ls -F /usr/share/texlive/texmf-dist/fonts/opentype/public . . . . .	3
ls -F /usr/local/texlive/texmf-dist/fonts/opentype/public . . . . .	4
ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google . . . . .	4
ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google . . . . .	4
ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google/roboto . . . . .	4
ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google/roboto . . . . .	4
ls -F /usr/share/texlive/texmf-dist/fonts/truetype . . . . .	4
ls -F /usr/local/texlive/texmf-dist/fonts/truetype . . . . .	4
ls -F /usr/share/texlive/texmf-dist/fonts/truetype/public . . . . .	5
ls -F /usr/local/texlive/texmf-dist/fonts/truetype/public . . . . .	5
ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google . . . . .	5
ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google . . . . .	5
ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google/roboto . . . . .	5
ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google/roboto . . . . .	5
find /usr/share/texlive -type f -iname “roboto” . . . . .	5
find /usr/local/texlive -type f -iname “roboto” . . . . .	6
find /usr/share/texlive -type f -iname “robotomono*.?tf” . . . . .	6
find /usr/local/texlive -type f -iname “robotomono*.?tf” . . . . .	6
find /usr/share/texlive -type d -iname “inconsolata” . . . . .	6
find /usr/local/texlive -type d -iname “inconsolata” . . . . .	6
find /usr/share/texlive -type f -iname “inconsolata.?tf” . . . . .	6
find /usr/local/texlive -type f -iname “inconsolata.?tf” . . . . .	6
find /usr/share/texlive -type d -iname “cascadia*code” . . . . .	6
find /usr/local/texlive -type d -iname “cascadia*code” . . . . .	6
find /usr/share/texlive -type f -iname “cascadia.?tf” . . . . .	7
find /usr/local/texlive -type f -iname “cascadia.?tf” . . . . .	7

```
% env1
env1$info$info_system_info$machine_nodename = “15687d125320” @Rocker
env1$info$info_system_info$machine_nodename = “application-12164735-deployment-22732286-l5pm” @Posit.Cloud
env1$info$info_system_info$Sys.getlocale$LC_COLLATE = “en_US.utf8”

#@@ START -----
## @ whoami -----
Cf) Ctrl+Alt+Enter @ Rstudio
```

whoami

```
"whoami" |>
  system(intern = TRUE) |>
  cat("\n")
rstudio

rstudio@Rocker
r149319@SharedWorkspace@MKim0710@Posit.Cloud
r2179046@SharedWorkspace@V@Posit.Cloud
r2179052@SharedWorkspace@MHKim710@Posit.Cloud
```

echo \$PATH

```
"echo $PATH" |>
  system(intern = TRUE) |>
  cat("\n")
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/local/texlive/bin/linux
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/local/texlive/bin/linux:/usr/lib/rstudio-server/bin/quarto/bin:/usr/lib/rstudio-server/bin/postback

##@ find -type d texlive -----
## find / -type d -iname texlive
```

```
"find / -type d -iname texlive" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find / -type d -iname texlive", intern = TRUE): running command 'find / -type d -iname texlive' had
status 1
c("/usr/local/texlive",
  "/usr/local/texlive/tlpkg/TeXLive",
  "/usr/local/texlive/texmf-dist/tex/context/texlive",
  "/usr/local/texlive/texmf-dist/scripts/texlive",
  "/opt/texlive")
```

c(“/usr/local/texlive”, “/usr/local/texlive/tlpkg/TeXLive”, “/usr/local/texlive/texmf-dist/tex/context/texlive”, “/usr/local/texlive/texmf-dist/scripts/texlive”, “/opt/texlive”)

**find / -type d -iname texmf-dist**

```
"find / -type d -iname texmf-dist" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find / -type d -iname texmf-dist", intern = TRUE): running command 'find / -type d -iname
texmf-dist' had status 1
c("/usr/local/texlive/texmf-dist")
```

c(“/usr/local/texlive/texmf-dist”)

```
##@ find -type d packages -----
### find /usr/share/texlive -type d -iname “fontspec”
### find /usr/local/texlive -type d -iname “fontspec”
```

```
"find /usr/share/texlive -type d -iname \"fontspec\"" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"fontspec\"", : running command 'find /usr/share/texlive
-type d -iname "fontspec" had status 1
c("")

"find /usr/local/texlive -type d -iname \"fontspec\"" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

c(“/usr/share/texlive/texmf-dist/tex/latex/fontspec”) c(“/usr/local/texlive/texmf-dist/tex/latex/fontspec”)

**find /usr/share/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf**

**find /usr/local/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf**

```
"find /usr/share/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf \"%f\\n\"" |>
  system(intern = TRUE) |>
  sort() |>
  dput()
Warning in system("find /usr/share/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf \"%f\\n\"", : running command 'find /usr/share/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf \"%f\\n\"' had status 1
character(0)
"find /usr/local/texlive/texmf-dist/tex/latex -maxdepth 1 -type d -printf \"%f\\n\"" |>
  system(intern = TRUE) |>
  sort() |>
  dput()
c("ae", "amsfonts", "amsmath", "atveryend", "auxhook", "base",
  "bookmark", "epstopdf-pkg", "etoolbox", "fancyvrb", "firstaid",
  "framed", "geometry", "graphics", "graphics-cfg", "graphics-def",
  "hycolor", "hyperref", "inconsolata", "koma-script", "kvoptions",
  "kvsetkeys", "l3backend", "l3kernel", "latex", "latexconfig",
  "letltxmacro", "listings", "lm", "mdwtools", "parskip", "refcount",
  "rerunfilecheck", "stmaryrd", "tex-ini-files", "tikzfill", "tools",
  "url", "xcolor", "xkeyval", "xpatch", "zapfding")
```

c(“ae”, “amsfonts”, “amsmath”, “atveryend”, “auxhook”, “base”, “bookmark”, “cascadia-code”, “cjk”, “cjk-ko”, “epstopdf-pkg”, “etoolbox”, “euenc”, “fancyvrb”, “fira”, “firstaid”, “fonts-tlwg”, “fontspec”, “framed”, “geometry”, “graphics”, “graphics-cfg”, “graphics-def”, “hycolor”, “hyperref”, “inconsolata”, “koma-script”, “kvoptions”, “kvsetkeys”, “l3backend”, “l3kernel”, “l3packages”, “latex”, “latexconfig”, “letltxmacro”, “listings”, “lm”, “mdwtools”, “parskip”, “refcount”, “rerunfilecheck”, “roboto”, “stmaryrd”, “tex-ini-files”, “tikzfill”, “tipa”, “tools”, “unicode-math”, “url”, “xcolor”, “xkeyval”, “xpatch”, “zapfding”)

**find /usr/share/texlive -type d -iname “roboto”**

**find /usr/local/texlive -type d -iname “roboto”**

```
"find /usr/share/texlive -type d -iname \"roboto\"" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"roboto\"", intern = TRUE): running command 'find
/usr/share/texlive -type d -iname "roboto" had status 1
c("")

"find /usr/local/texlive -type d -iname \"roboto\"" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

```
find /usr/share/texlive -type d -iname "cascadia*code"
find /usr/local/texlive -type d -iname "cascadia*code"
```

```
"find /usr/share/texlive -type d -iname \"cascadia*code\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"cascadia*code\"", : running command 'find
/usr/share/texlive -type d -iname "cascadia*code"' had status 1
c("")

"find /usr/local/texlive -type d -iname \"cascadia*code\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

```
##@ find -type d fonts -----
## find /usr/share/texlive -type d -iname "font[s]"
## find /usr/local/texlive -type d -iname "font[s]"
```

```
"find /usr/share/texlive -type d -iname \"font[s ]\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"font[s ]\"", : running command 'find /usr/share/texlive
-type d -iname "font[s ]"' had status 1
c("")

"find /usr/local/texlive -type d -iname \"font[s ]\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("/usr/local/texlive/texmf-dist/tex/context/fonts",
  "/usr/local/texlive/texmf-dist/metapost/context/fonts",
  "/usr/local/texlive/texmf-dist/fonts")
```

```
c("/usr/local/texlive/texmf-dist/tex/context/fonts", "/usr/local/texlive/texmf-dist/metapost/context/fonts", "/usr/local/texlive/texmf-dist/fonts")
```

```
ls -F /usr/share/texlive/texmf-dist/fonts
ls -F /usr/local/texlive/texmf-dist/fonts
```

```
"ls -F /usr/share/texlive/texmf-dist/fonts" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts", intern = TRUE): running command 'ls -F
/usr/share/texlive/texmf-dist/fonts' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("afm/",
  "cid/",
  "cmap/",
  "enc/",
  "map/",
  "misc/",
  "opentype/",
  "pk/",
  "source/",
  "tfm/",
  "type1/",
  "vf/")
```

```
c("afm/", "cid/", "cmap/", "enc/", "map/", "misc/", "opentype/", "pk/", "source/", "tfm/", "type1/", "vf/")
```

```
ls -F /usr/share/texlive/texmf-dist/fonts/opentype
ls -F /usr/local/texlive/texmf-dist/fonts/opentype
```

```
"ls -F /usr/share/texlive/texmf-dist/fonts/opentype" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/opentype", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/opentype' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/opentype" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("public/")
```

```
c("google/", "public/")
```

```
ls -F /usr/share/texlive/texmf-dist/fonts/opentype/public
```

```
"ls -F /usr/share/texlive/texmf-dist/fonts/opentype/public" |>
  system(intern = TRUE) |>
```

```
env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/opentype/public", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/opentype/public' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/opentype/public" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("context-companion-fonts/",
  "inconsolata/",
  "lm/",
  "lm-math/")
```

**ls -F /usr/local/texlive/texmf-dist/fonts/opentype/public** c(“cascadia-code/”, “context-companion-fonts/”, “fira/”, “fonts-tlwg/”, “inconsolata/”, “lm/”, “lm-math/”)

**ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google**

```
"ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/opentype/google' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/opentype/google' had status 2
c("")
```

**ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google** c(“roboto/”)

**ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google/roboto**

```
"ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google/roboto" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/opentype/google/roboto", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/opentype/google/roboto' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google/roboto" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google/roboto", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto' had status 2
c("")
```

**ls -F /usr/local/texlive/texmf-dist/fonts/opentype/google/roboto** c(“Roboto-BlackItalic.otf”, “Roboto-Black.otf”, “Roboto-BoldItalic.otf”, “Roboto-Bold.otf”, “RobotoCondensed-BoldItalic.otf”, “RobotoCondensed-Bold.otf”, “RobotoCondensed-Italic.otf”, “RobotoCondensed-LightItalic.otf”, “RobotoCondensed-Light.otf”, “RobotoCondensed-Regular.otf”, “Roboto-Italic.otf”, “Roboto-LightItalic.otf”, “Roboto-Light.otf”, “Roboto-MediumItalic.otf”, “Roboto-Medium.otf”, “RobotoMono-BoldItalic.otf”, “RobotoMono-Bold.otf”, “RobotoMono-Italic.otf”, “RobotoMono-LightItalic.otf”, “RobotoMono-Light.otf”, “RobotoMono-MediumItalic.otf”, “RobotoMono-Medium.otf”, “RobotoMono-Regular.otf”, “RobotoMono-ThinItalic.otf”, “RobotoMono-Thin.otf”, “Roboto-Regular.otf”, “RobotoSerif-BlackItalic.otf”, “RobotoSerif-Black.otf”, “RobotoSerif-BoldItalic.otf”, “RobotoSerif-Bold.otf”, “RobotoSerif\_Condensed-BlackItalic.otf”, “RobotoSerif\_Condensed-Black.otf”, “RobotoSerif\_Condensed-BoldItalic.otf”, “RobotoSerif\_Condensed-Bold.otf”, “RobotoSerif\_Condensed-ExtraBoldItalic.otf”, “RobotoSerif\_Condensed-ExtraBold.otf”, “RobotoSerif\_Condensed-ExtraLightItalic.otf”, “RobotoSerif\_Condensed-ExtraLight.otf”, “RobotoSerif\_Condensed-Italic.otf”, “RobotoSerif\_Condensed-LightItalic.otf”, “RobotoSerif\_Condensed-Light.otf”, “RobotoSerif\_Condensed-MediumItalic.otf”, “RobotoSerif\_Condensed-Medium.otf”, “RobotoSerif\_Condensed-Regular.otf”, “RobotoSerif\_Condensed-SemiBoldItalic.otf”, “RobotoSerif\_Condensed-SemiBold.otf”, “RobotoSerif\_Condensed-ThinItalic.otf”, “RobotoSerif\_Condensed-Thin.otf”, “RobotoSerif-ExtraBoldItalic.otf”, “RobotoSerif-ExtraBold.otf”, “RobotoSerif-ExtraLightItalic.otf”, “RobotoSerif-ExtraLight.otf”, “RobotoSerif-Italic.otf”, “RobotoSerif-LightItalic.otf”, “RobotoSerif-Light.otf”, “RobotoSerif-MediumItalic.otf”, “RobotoSerif-Medium.otf”, “RobotoSerif-Regular.otf”, “RobotoSerif-SemiBoldItalic.otf”, “RobotoSerif-SemiBold.otf”, “RobotoSerif-ThinItalic.otf”, “RobotoSerif-Thin.otf”, “RobotoSlab-Bold.otf”, “RobotoSlab-Light.otf”, “RobotoSlab-Regular.otf”, “RobotoSlab-Thin.otf”, “Roboto-ThinItalic.otf”, “Roboto-Thin.otf”)

**ls -F /usr/share/texlive/texmf-dist/fonts/truetype**

**ls -F /usr/local/texlive/texmf-dist/fonts/truetype**

```
"ls -F /usr/share/texlive/texmf-dist/fonts/truetype" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/truetype", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/truetype' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/truetype" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/truetype", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/truetype' had status 2
c("")
```

c(“ “)

ls -F /usr/share/texlive/texmf-dist/fonts/truetype/public

```
"ls -F /usr/share/texlive/texmf-dist/fonts/truetype/public" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/truetype/public", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/truetype/public' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/truetype/public" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/truetype/public", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/truetype/public' had status 2
c("")
```

ls -F /usr/local/texlive/texmf-dist/fonts/truetype/public

ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google

```
"ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/truetype/google' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/truetype/google' had status 2
c("")
```

ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google

ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google/roboto

```
"ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google/roboto" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/share/texlive/texmf-dist/fonts/truetype/google/roboto", : running command 'ls -F
/usr/share/texlive/texmf-dist/fonts/truetype/google/roboto' had status 2
c("")

"ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google/roboto" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google/roboto", : running command 'ls -F
/usr/local/texlive/texmf-dist/fonts/truetype/google/roboto' had status 2
c("")
```

ls -F /usr/local/texlive/texmf-dist/fonts/truetype/google/roboto   ##@ find -type d/f fontname ————  
### find /usr/share/texlive -type d -iname “roboto”  
### find /usr/local/texlive -type d -iname “roboto”

```
"find /usr/share/texlive -type d -iname \"*roboto*\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"*roboto*\"", : running command 'find /usr/share/texlive
-type d -iname "*roboto*" had status 1
c("")

"find /usr/local/texlive -type d -iname \"*roboto*\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

c(“/usr/local/texlive/texmf-dist/tex/latex/roboto”, “/usr/local/texlive/texmf-dist/fonts/enc/dvips/roboto”, “/usr/local/texlive/texmf-dist/fonts/map/dvips/roboto”,  
“/usr/local/texlive/texmf-dist/fonts/type1/google/roboto”, “/usr/local/texlive/texmf-dist/fonts/vf/google/roboto”, “/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto”,  
“/usr/local/texlive/texmf-dist/fonts/tfm/google/roboto”)

find /usr/share/texlive -type f -iname “roboto”

```
"find /usr/share/texlive -type d -iname \"*roboto*\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"*roboto*\"", : running command 'find /usr/share/texlive
-type d -iname "*roboto*" had status 1
c("")

"find /usr/local/texlive -type d -iname \"*roboto*\" |>
  system(intern = TRUE) |>
```



```
env1$f_vec.dput_line_by_line()
c("")
```

```
find /usr/local/texlive -type f -iname “roboto” c(“/usr/local/texlive/texmf-dist/tex/latex/roboto”, “/usr/local/texlive/texmf-dist/fonts/enc/dvips/roboto”,
“/usr/local/texlive/texmf-dist/fonts/map/dvips/roboto”, “/usr/local/texlive/texmf-dist/fonts/type1/google/roboto”, “/usr/local/texlive/texmf-dist/fonts/vf/google/roboto”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto”, “/usr/local/texlive/texmf-dist/fonts/tfm/google/roboto”)
```

```
find /usr/share/texlive -type f -iname “robotomono*.?tf”
```

```
"find /usr/share/texlive -type f -iname \"*robotomono*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type f -iname \"*robotomono*.?tf\"", : running command 'find
/usr/share/texlive -type f -iname "*robotomono*.?tf"' had status 1
c("")

"find /usr/local/texlive -type f -iname \"*robotomono*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

```
find /usr/local/texlive -type f -iname “robotomono*.?tf” c(“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Light.otf”, “/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Medium.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-MediumItalic.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Bold.otf”, “/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-ThinItalic.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Regular.otf”, “/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-BoldItalic.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Thin.otf”, “/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-Italic.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/google/roboto/RobotoMono-LightItalic.otf”)
```

```
find /usr/share/texlive -type d -iname “inconsolata”
```

```
find /usr/local/texlive -type d -iname “inconsolata”
```

```
"find /usr/share/texlive -type d -iname \"*inconsolata*\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"*inconsolata*\"", : running command 'find
/usr/share/texlive -type d -iname "*inconsolata*' had status 1
c("")

"find /usr/local/texlive -type d -iname \"*inconsolata*\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("/usr/local/texlive/texmf-dist/tex/latex/inconsolata",
"/usr/local/texlive/texmf-dist/fonts/enc/dvips/inconsolata",
"/usr/local/texlive/texmf-dist/fonts/map/dvips/inconsolata",
"/usr/local/texlive/texmf-dist/fonts/type1/public/inconsolata",
"/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata",
"/usr/local/texlive/texmf-dist/fonts/tfm/public/inconsolata")
```

```
find /usr/share/texlive -type f -iname “inconsolata.?tf”
```

```
"find /usr/share/texlive -type f -iname \"*inconsolata*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type f -iname \"*inconsolata*.?tf\"", : running command 'find
/usr/share/texlive -type f -iname "*inconsolata*.?tf"' had status 1
c("")

"find /usr/local/texlive -type f -iname \"*inconsolata*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/Inconsolatazi4-Bold.otf",
"/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/InconsolataN-Bold.otf",
"/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/InconsolataN-Regular.otf",
"/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/Inconsolatazi4-Regular.otf")
```

```
find /usr/local/texlive -type f -iname “inconsolata.?tf” c(“/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/Inconsolatazi4-Bold.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/InconsolataN-Bold.otf”, “/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/InconsolataN-Regular.otf”,
“/usr/local/texlive/texmf-dist/fonts/opentype/public/inconsolata/Inconsolatazi4-Regular.otf”)
```

```
find /usr/share/texlive -type d -iname “cascadia*code”
```

```
find /usr/local/texlive -type d -iname “cascadia*code”
```

```
"find /usr/share/texlive -type d -iname \"cascadia*code\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type d -iname \"cascadia*code\"", : running command 'find
/usr/share/texlive -type d -iname "cascadia*code"' had status 1
c("")

"find /usr/local/texlive -type d -iname \"cascadia*code\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
```

c("")

find /usr/share/texlive -type f -iname “cascadia.?tf”

```
"find /usr/share/texlive -type f -iname \"*cascadia*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
Warning in system("find /usr/share/texlive -type f -iname \"*cascadia*.?tf\"", : running command 'find
/usr/share/texlive -type f -iname "*cascadia*.?tf"' had status 1
c("")

"find /usr/local/texlive -type f -iname \"*cascadia*.?tf\" |>
  system(intern = TRUE) |>
  env1$f_vec.dput_line_by_line()
c("")
```

find /usr/local/texlive -type f -iname “cascadia.?tf” #@@@ END ———

```
# | _____ |#
# |%%%%%%%%%%%%%%%%%%%%%%|# @@ END -----
# | _____ |#
# |%%%%%%%%%%%%%%|#
# | ~~~~~ |#
# | ++++++ |#
# | ~~~~~ |#
# | _____ |#
# |%%%%%%%%%%%%%%|#
```