Voltrieve Atlas technical specifications



Atlas dimensions and weights

Atlas dimension	Value
Length	5 100 mm
Width, without mirrors	1 990 mm
Height	1 780 mm
Wheelbase	3 100 mm
Ground clearance	190 mm
Kerb weight	2 650 kg
Towing capacity	2 500 kg (braked)
Roof load	100 kg

Atlas volumes

Atlas volume	Value
Boot	720 litres
Boot with the rear seats folded	2 050 litres
Frunk	90 litres
Seats	7, in three rows

Atlas battery and range

Atlas battery	Value
Battery capacity (usable)	112 kWh
Range (WLTP)	610 km
Energy use (WLTP, combined)	18.4 kWh per 100 km
Platform	V2
System voltage	800 V

Atlas charging

Atlas charging	Value
Peak DC charging power	320 kW
DC charging from 10 to 80 %	about 20 minutes
Onboard AC charger	22 kW
AC charging, empty to full	about 5.1 hours
Charge port	CCS2

The Atlas DC charging curve: the charge power the car accepts at each state of charge, at a charger that delivers at least 320 kW and with the battery at its working temperature.

State of charge	Charge power
10 %	320 kW
50 %	260 kW
80 %	120 kW

Atlas performance per drive

Drive	Power	Torque	0 to 100 km/h	Top speed
Atlas AWD	420 kW	780 Nm	4.9 s	210 km/h

Atlas chassis, climate and software

Atlas item	Value
Drive	AWD
Front brake discs	400 mm
Rear brake discs	360 mm
Heat pump	standard
Voltrieve Pilot	version 3: adaptive cruise, lane keeping, traffic jam assist, automatic lane change (with Pilot Plus)
Option packs available	Winter, Pilot Plus, Tow, Sound
Feature	seven seats
Feature	3.5 kW vehicle to load outlet
Feature	rear wheel steering

Atlas wheels and tyres per trim

Trim	Wheels
Atlas Pure	21 inch Monolith: six wide aero spokes in silver
Atlas Plus	22 inch Monolith: six wide aero spokes, gloss black with machined silver faces
Atlas Prime	22 inch Monolith: six wide aero spokes, gloss black with machined silver faces

Range, energy use and charging times are measured to WLTP or under test conditions. Real figures depend on speed, temperature, load, tyres and driving style.