Voltrieve Ragn technical specifications

Ragn dimensions and weights

Ragn dimension	Value
Length	4 600 mm
Width, without mirrors	1 920 mm
Height	1 720 mm
Wheelbase	2 820 mm
Ground clearance	205 mm
Kerb weight	2 150 kg
Towing capacity	1 800 kg (braked)
Roof load	100 kg

Ragn volumes

Ragn volume	Value
Boot	520 litres
Boot with the rear seats folded	1 580 litres
Frunk	60 litres
Seats	5

Ragn battery and range

Ragn battery	Value
Battery capacity (usable)	84 kWh
Range (WLTP)	530 km
Energy use (WLTP, combined)	15.8 kWh per 100 km
Platform	V2
System voltage	800 V

Ragn charging

Ragn charging	Value
Peak DC charging power	240 kW
DC charging from 10 to 80 %	about 21 minutes
Onboard AC charger	22 kW
AC charging, empty to full	about 3.8 hours
Charge port	CCS2

The Ragn DC charging curve: the charge power the car accepts at each state of charge, at a charger that delivers at least 240 kW and with the battery at its working temperature.

State of charge	Charge power
10 %	240 kW
50 %	190 kW
80 %	90 kW

Ragn performance per drive

Drive	Power	Torque	0 to 100 km/h	Top speed
Ragn AWD	300 kW	560 Nm	5.4 s	190 km/h

Ragn chassis, climate and software

Ragn item	Value
Drive	AWD
Front brake discs	350 mm
Rear brake discs	330 mm
Heat pump	standard
Voltrieve Pilot	version 3: adaptive cruise, lane keeping, traffic jam assist, automatic lane change (with Pilot Plus)
Option packs available	Winter, Pilot Plus, Tow, Sound
Feature	ground clearance of 205 mm
Feature	off road mode
Feature	22 kW onboard charger

Ragn wheels and tyres per trim

Trim	Wheels
Ragn Pure	19 inch Trail: five thick spokes in gunmetal grey, on all-terrain tyres
Ragn Plus	19 inch Trail: five thick spokes in gunmetal grey, on all-terrain tyres
Ragn Prime	20 inch Trail: five thick spokes in matte black, on all-terrain tyres

Range, energy use and charging times are measured to WLTP or under test conditions. Real figures depend on speed, temperature, load, tyres and driving style.