Voltrieve Fjord technical specifications



Fjord dimensions and weights

Fjord dimension	Value
Length	4 900 mm
Width, without mirrors	1 900 mm
Height	1 500 mm
Wheelbase	2 980 mm
Ground clearance	150 mm
Kerb weight	2 180 kg
Towing capacity	2 100 kg (braked)
Roof load	100 kg

Fjord volumes

Fjord volume	Value
Boot	640 litres
Boot with the rear seats folded	1 720 litres
Frunk	50 litres
Seats	5

Fjord battery and range

Fjord battery	Value
Battery capacity (usable)	84 kWh
Range (WLTP)	575 km
Energy use (WLTP, combined)	14.6 kWh per 100 km
Platform	V2
System voltage	800 V

Fjord charging

Fjord charging	Value
Peak DC charging power	240 kW
DC charging from 10 to 80 %	about 20 minutes
Onboard AC charger	22 kW
AC charging, empty to full	about 3.8 hours
Charge port	CCS2

The Fjord DC charging curve: the charge power the car accepts at each state of charge, at a charger that delivers at least 240 kW and with the battery at its working temperature.

State of charge	Charge power
10 %	240 kW
50 %	200 kW
80 %	95 kW

Fjord performance per drive

Drive	Power	Torque	0 to 100 km/h	Top speed
Fjord RWD	250 kW	450 Nm	6.1 s	200 km/h
Fjord AWD	360 kW	680 Nm	4.6 s	200 km/h

Fjord chassis, climate and software

Fjord item	Value
Drive	RWD, AWD
Front brake discs	345 mm (RWD), 370 mm (AWD)
Rear brake discs	330 mm
Heat pump	standard
Voltrieve Pilot	version 3: adaptive cruise, lane keeping, traffic jam assist, automatic lane change (with Pilot Plus)
Option packs available	Winter, Pilot Plus, Tow, Sound
Feature	boot of 640 litres
Feature	roof load of 100 kg
Feature	air suspension

Fjord wheels and tyres per trim

Trim	Wheels
Fjord Pure	19 inch Birch: ten spokes in silver
Fjord Plus	20 inch Fern: fifteen thin straight spokes in diamond-cut silver
Fjord Prime	20 inch Fern: fifteen thin straight spokes in diamond-cut silver

Range, energy use and charging times are measured to WLTP or under test conditions. Real figures depend on speed, temperature, load, tyres and driving style.