Voltrieve Spark technical specifications



Spark dimensions and weights

Spark dimension	Value
Length	3 700 mm
Width, without mirrors	1 780 mm
Height	1 590 mm
Wheelbase	2 560 mm
Ground clearance	160 mm
Kerb weight	1 390 kg
Towing capacity	not rated for towing
Roof load	50 kg

The Voltrieve Spark is not rated for towing.

Spark volumes

Spark volume	Value
Boot	310 litres
Boot with the rear seats folded	1 050 litres
Frunk	no frunk
Seats	5

Spark battery and range

Spark battery	Value
Battery capacity (usable)	42 kWh
Range (WLTP)	310 km
Energy use (WLTP, combined)	13.5 kWh per 100 km
Platform	V1
System voltage	400 V

Spark charging

Spark charging	Value
Peak DC charging power	95 kW
DC charging from 10 to 80 %	about 25 minutes
Onboard AC charger	11 kW
AC charging, empty to full	about 3.8 hours
Charge port	CCS2

The Spark DC charging curve: the charge power the car accepts at each state of charge, at a charger that delivers at least 95 kW and with the battery at its working temperature.

State of charge	Charge power
10 %	95 kW
50 %	80 kW
80 %	40 kW

Spark performance per drive

Drive	Power	Torque	0 to 100 km/h	Top speed
Spark RWD	100 kW	220 Nm	9.2 s	150 km/h

Spark chassis, climate and software

Spark item	Value
Drive	RWD
Front brake discs	280 mm
Rear brake discs	265 mm
Heat pump	with the Winter pack (standard on Plus and Prime)
Voltrieve Pilot	version 2: adaptive cruise, lane keeping
Option packs available	Winter, Sound
Feature	turning circle of 9.8 m
Feature	2 ISOFIX seats
Feature	one pedal driving

Spark wheels and tyres per trim

Trim	Wheels
Spark Pure	17 inch Pebble: flat aero wheel covers in white and light grey with five small holes
Spark Plus	17 inch Pebble: flat aero wheel covers in white and light grey with five small holes
Spark Prime	17 inch Pebble: flat aero wheel covers in graphite with five small holes

Range, energy use and charging times are measured to WLTP or under test conditions. Real figures depend on speed, temperature, load, tyres and driving style.