GraphAide: Advanced Graph-Assisted Query and Reasoning System

Sumit Purohit, George Chin, Patrick S Mackey, Joseph A Cottam
Pacific Northwest National Laboratory
Richland, Washington 99352
{sumit.purohit, george.chin, patrick.mackey, joseph.cottam}@pnnl.gov

2024 IEEE International Conference on Big Data (BigData) | 979-8-3503-6248-0/24/$31.00 ©2024 IEEE | DOI: 10.1109/BigData62323.2024.10825705

***Abstract*—Curating knowledge from multiple siloed sources that contain both structured and unstructured data is a major challenge in many real-world applications. Pattern matching and querying represent fundamental tasks in modern data analytics that leverage this curated knowledge. The development of such applications necessitates overcoming several research challenges, including data extraction, named entity recognition, data modeling, and designing query interfaces. Moreover, the explainability of these functionalities is critical for their broader adoption.**

The emergence of Large Language Models (LLMs) has accelerated the development lifecycle of new capabilities. Nonetheless, there is an ongoing need for domain-specific tools tailored to user activities. The creation of such digital assistants has gained considerable traction in recent years, with LLMs offering a promising avenue to develop such assistants utilizing domain-specific knowledge and assumptions.

In this context, we introduce an advanced query and reasoning system, *GraphAide*, which constructs a knowledge graph (KG) from diverse sources and allows to query and reason over the resulting KG. *GraphAide* harnesses both the KG and LLMs to rapidly develop domain-specific digital assistants. It integrates design patterns from retrieval augmented generation (RAG) and the semantic web to create an agentic LLM application. *GraphAide* underscores the potential for streamlined and efficient development of specialized digital assistants, thereby enhancing their applicability across various domains.

I. Introduction

Large Language Models (LLMs) [1] represent the cutting edge of generative artificial intelligence (GenAI) and machine learning research and development. They have been adopted at an extraordinary rate across a range of disciplines, including scientific research, engineering, economics, and social sciences. By enabling domain experts to utilize pre-trained, ready-to-use models, LLMs have democratized the application development process, catalyzing innovations in both scientific and technological domains. The development of LLM-based applications remains a dynamic area of research, offering superior performance in tasks such as summarization, correlation, and inference across various input sources [2].

Knowledge Graphs (KGs) are formal representations of key concepts as entities and the relationships between them [3], [4]. KGs serve as powerful tools that can be employed in diverse user environments as foundational reference knowledge sources. However, constructing these KGs presents substantial challenges due to the scale of input data, the heterogeneity of use-case-specific concepts, and the costs associated with KG construction. LLMs have demonstrated higher accuracy in extracting relevant entities and forming relationships, significantly contributing to KG construction [5].

A major challenge in developing accurate and consistent capabilities based on LLMs is *hallucination* [6], which occurs when LLMs generate non-existent facts in response to user queries. The memorization of training data by LLMs and the subsequent reliance on corpus-based heuristics are significant factors contributing to hallucinations [7]. Addressing this issue is crucial for the reliability and trustworthiness of LLM-derived applications.

Retrieval-augmented generation (RAG) [8] is a well-established design pattern aimed at mitigating hallucination in Large Language Models (LLMs) by providing additional context during the generation of responses to user queries. This additional *context* is domain-specific and acts as *grounding* for the model's generative capabilities. A foundational RAG-based system employs a vector database to store *embeddings* of a domain-specific knowledge corpus and utilizes semantic similarity algorithms to retrieve the context relevant to the user query. The semantic similarity algorithms measure how closely the meanings of two concepts align. This context is then combined with the user query and forwarded to the LLM, serving as a guardrail for its generation process. The RAG-based approach has demonstrated efficacy in reducing hallucination by constraining the LLM's generative output to the localized region of the provided context.

However, a vector search-based method is constrained by the semantic similarity between the query and the corpus. It fails to leverage the structural context, such as the relationships between documents within the corpus, their metadata, or the associated reasoning. Knowledge Graphs (KGs) offer a robust solution to these limitations by efficiently storing domain-specific information and establishing relationships between information sources dispersed across documents in the corpus. KGs can also significantly enhance various components of an LLM-based application, including retrieval, summarization, and inference.

By integrating KGs into the design pattern, the system can utilize both the semantic and structural context, thereby improving the accuracy and consistency of the generated responses. This comprehensive approach enables a more nuanced understanding and utilization of the knowledge corpus, offering a sophisticated strategy to further reduce hallucination

979-8-3503-6248-0/24/$31.00 ©2024 IEEE
Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.1)

연구 목적

- 여러 출처의 자료로 지식그래프(KG)를 만들고, 그 KG에 자연어로 질의하고 추론하는 시스템 GraphAide를 제안한다
- KG와 LLM을 함께 써서 특정 분야의 디지털 조수를 빠르게 만드는 것이 목표다
- RAG의 설계 방식과 시맨틱 웹 기술(온톨로지)을 합친 에이전트형 LLM 응용이다

연구 배경

- LLM은 요약, 연관, 추론에서 성능이 좋아 여러 분야에 빠르게 쓰이고 있다
- KG는 개념을 개체로, 개체 사이를 관계로 나타낸 것이다. 만드는 데는 자료 규모, 분야마다 다른 개념, 구축 비용의 어려움이 있다
- LLM 응용의 큰 문제는 환각(없는 사실을 만들어 냄)이다

기본 RAG의 한계와 KG의 역할

- RAG는 질문과 관련된 문맥을 찾아 LLM에 함께 넣어 환각을 줄인다. 기본 RAG는 벡터 DB에서 의미가 비슷한 조각을 찾는다
- 한계: 벡터 검색은 질문과 문서의 의미 유사도에만 의존한다. 문서 사이의 관계, 메타데이터 같은 구조 정보를 쓰지 못한다
- KG는 여러 문서에 흩어진 정보를 관계로 이어 저장하므로 이 한계를 보완한다

→ 의미 문맥(벡터)과 구조 문맥(그래프)을 함께 쓰자는 것이 이 논문의 출발점이다

and enhance the application's overall performance.

We introduce GraphAide, an advanced capability based on Large Language Models (LLMs) that offers insights into domain-specific data and allows users to ask natural language questions. GraphAide presents a methodology and reference architecture to develop advanced GenAI applications using different components such as LLMs, vector database, and graph database. GraphAide employs a modular, extensible, and user-friendly retrieval-augmented generation (RAG) approach, incorporating both vector and graph databases. The novelty of GraphAide lies in its comprehensive design for integrating GenAI and semantic web technologies. GraphAide curates multi-source data and constructs ontology-guided knowledge graphs to address the challenges faced by baseline LLM-only applications. The platform also provides efficient data persistence, enabling interactions via a natural language question-answering interface.

GraphAide combines a robust graph matching approach with the semantic similarity provided by vector databases to enhance the accuracy and explainability of LLM-generated responses. Developed as an extensible agentic RAG application, GraphAide reuses data ingestion, entity disambiguation, storage, query, and reasoning components throughout the application lifecycle. Key capabilities of GraphAide include:

- **Ontology-guided Knowledge Graph construction:** Handles multi-value, multi-source, temporal attributes from common data formats such as .txt, .html, .pdf, etc.
- **Generation and maintenance of embeddings:** Configures vector databases for storage and retrieval, maintaining multiple vector databases and dynamically selecting sources based on user queries.
- **Template-based ontology configuration:** Enables dynamic input ontology configuration and generation of multiple KG versions for a given source dataset.
- **Enhanced context generation:** Combines vector-based retrieval with graph-based subgraph matching to improve the relevancy of LLM-generated responses.
- **External function execution capability:** Enriches context by retrieving multi-modal data sources, such as temporal data from time-series databases.

GraphAide represents a significant advancement in the development of domain-specific digital assistants, integrating state-of-the-art GenAI and semantic technologies for improved performance and extensibility. Section II provides an overview of related work, while Section III details the GraphAide architecture along with its key components. Section IV showcases a real-world use case, presenting experimental results and evaluation metrics.

II. Related Work

The integration of generative artificial intelligence (GenAI) and semantic technologies is an active and burgeoning area of research. Existing Knowledge Graph (KG)-based LLM capabilities often focus on specific applications. A baseline RAG approach [9] transforms unstructured data into multiple chunks, creates embeddings for these chunks, and stores them in a vector database. These embeddings are then used to perform semantic similarity matching for an input user query, retrieving the most similar chunks. This retrieval process constructs the *context* to augment user queries sent to the LLM. The RAG approach has shown promising results in addressing challenges such as hallucination, outdated knowledge, and the explainability of generated responses. However, the baseline RAG is limited by its reliance on semantic similarity.

GraphRAG [10] advances this field by presenting a query-focused summarization task (QFS) that builds efficient text indices over a KG. GraphRAG leverages community detection to partition the graph index and uses it to generate "global answers" to user queries. Other approaches, such as the work by Trajanoska et al. [11], focus on creating KGs from sustainability-related text and evaluating their quality with specialized models for joint entity and relation extraction. Similarly, Ban et al. [12] introduce a set of prompts to extract causal graphs for causal structural learning. A common challenge with these approaches is their limited extensibility, as they do not leverage state-of-the-art open-source application development frameworks. There exists a significant opportunity to utilize KGs more effectively in various phases of LLM-based application development and usage.

III. Architecture

GraphAide is a retrieval-augmented generation (RAG)-based system that employs multiple LLM instances and knowledge graphs (KGs) to perform diverse tasks. An *Agent*-based LLM application leverages its reasoning capabilities to determine the appropriate sequence of actions in response to user queries. Unlike hardcoded instructions (i.e., *chains*), an *agentic application* can comprehend the LLM's response and construct subsequent queries dynamically. GraphAide is a hybrid application leveraging both chains and agents to handle a variety of user queries. GraphAide's hybrid approach enables the system to effectively manage a wide array of user queries, ensuring accurate and contextually relevant responses.

Figure 1 details GraphAide architecture and highlights use of ontology, vector database, and multiple LLM agents to perform different tasks. GraphAide delineates specific *phases* corresponding to the set of features required to complete a user task. As illustrated in Figure 1, the *generation* phase combines information from multiple sources to construct a Knowledge Graph (KG), which serves as a knowledge repository alongside the vector database. In the *query* phase, GraphAide provides a user interface that allows querying the knowledge sources and generating responses in a user-specified format, accompanied by explanations and reasoning.

GraphAide decomposes the query and reasoning research problem into following sub-problems and addresses them using a graph-based RAG approach:

- Data ETL and Normalization
- Named-Entity Recognition
- Domain-aware semantic annotation
- Graph Modeling and Storage
- Query interpretation and context generation

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.2)

GraphAide의 주요 기능

- 온톨로지에 맞춘 KG 구축: txt, html, pdf 등에서 여러 값, 여러 출처, 시간 속성을 다룬다
- 임베딩 생성과 관리: 벡터 DB를 여러 개 두고 질문에 따라 고른다
- 온톨로지 설정을 틀(template)로 바꿔 끼울 수 있다. 같은 자료로 KG를 여러 판 만들 수 있다
- 문맥 생성 강화: 벡터 검색과 그래프의 부분 그래프 매칭을 합친다
- 외부 함수 실행: 시계열 DB의 시간 자료 같은 다른 형태의 자료를 가져와 문맥에 더한다

관련 연구와의 차이

- 기본 RAG: 문서를 조각내 임베딩하고 비슷한 조각을 찾는다. 의미 유사도에만 의존한다
- GraphRAG: KG 위에 색인을 만들고 커뮤니티 탐지로 나눠 전체를 아우르는 답을 만든다
- 그 밖에 특정 분야 글에서 KG를 만드는 연구, 인과 그래프를 뽑는 연구가 있다
- 저자들이 본 공통 한계: 특정 응용에 묶여 있고 확장하기 어렵다

구조 개요: 두 단계

- 생성 단계: 여러 출처의 정보를 합쳐 KG를 만든다. KG는 벡터 DB와 함께 지식 저장소가 된다
- 질의 단계: 사용자 질문으로 지식 저장소를 조회하고, 설명과 근거를 붙여 답한다
- 정해진 순서로 실행하는 체인과, LLM의 응답을 보고 다음 질의를 스스로 정하는 에이전트를 섞어 쓴다
- 풀어야 할 문제를 8가지로 나눴다: 자료 적재와 정규화, 개체명 인식, 분야에 맞는 의미 주석, 그래프 모델링과 저장, 질의 해석과 문맥 생성, 질의 확장과 후보 생성, 요약과 설명 가능한 응답 생성

- Query expansion and candidate generation
- Summarization and explainable response generation

A. Data Ingestion

Domain-specific datasets are available in multiple structured and unstructured formats, depending on the use cases. GraphAide creates an abstraction layer that allows end users to work with commonly used data formats such as plain text, CSV, PDF, etc. A collection of source data (i.e., files) is ingested into GraphAide, followed by a process of text splitting and chunking to support efficient search over vector data and to manage data larger than the maximum context window size (in number of tokens) of an LLM. GraphAide employs a byte pair encoding (BPE)-based tokenizer [13] that segments input text into sub-word units, enabling the system to handle a wide variety of languages. The BPE-based encoding is also supported by OpenAI embedding models [14] and has been shown to perform well across different query scenarios due to its lossless, reversible, and efficient encoding. Additionally, GraphAide uses the $RecursiveCharacterTextSplitter$, which recursively examines characters in the input data to dynamically identify the optimal splitting strategy. GraphAide employs static $chunk_size$ and $chunk_overlap$ values, as suggested in related work [15], and also allows users to configure the text splitter for specific application domains.

B. Data Storage

Persistence of knowledge curated from multiple sources is critical for the reproducibility and incremental updates of the underlying digital assistant. In contrast to basic RAG, GraphAide persists contextual knowledge in both vector and graph databases. After splitting and chunking, as discussed in Section III-A, the source data is converted into a collection of $documents$, where each $document$ serves as an atomic knowledge source used to answer user queries. In a RAG-based LLM application, *embedding*-based semantic similarity is a key feature. Embeddings are numerical representations of information, where semantically similar content is placed closer together in the embedding space. GraphAide uses a vector database to store embeddings of domain-specific reference datasets or general-purpose knowledge bases, such as WikiData [16]. GraphAide provides a simple API to ingest datasets into the vector database and persist them locally for future use. The novelty of GraphAide lies in its use of a graph database to store additional structural information. GraphAide's API offers domain-specific graph modeling and graph persistence functionality. The graph database is used in subsequent phases to enhance the performance of retrieval operations.

C. Knowledge Graph Generation

Generation of an ontology-guided Knowledge Graph (KG) from heterogeneous sources is one of the key contributions of GraphAide. GraphAide defines a KG generation phase that supports operations such as named entity extraction, relationship extraction, entity disambiguation, KG encoding, and KG maintenance. It employs a prompt-based, few-shot approach to instruct an LLM to generate a knowledge graph. GraphAide supports the dynamic selection of an ontology or a list of node and edge types as input to the generation phase, which restricts the LLM's response schema, ensuring it generates an attributed subgraph for a given input text. For the KG generation phase, an example query could be a paragraph from an unstructured source, such as a news article. GraphAide uses Pydantic [17], an annotation-based schema validator, to maintain the consistency of the generated subgraph throughout the entire KG generation phase.

GraphAide Component	Metrics
Named Entity Mention Extraction	Answer Accuracy
Semantic Annotation	Context Relevancy, Context Accuracy, Answer Relevancy, Answer Accuracy, Semantic Similarity
Entity Disambiguation	Context Precision, Context Recall, ROC Curve
Query Expansion	Answer Relevancy
Graph Query Generation	Answer Accuracy, Answer Relevancy

TABLE I: Metrics for Different Components in GraphAide

D. Subgraph Query Generation

GraphAide's *query phase* begins with a natural language user query, as shown in Figure 1. User queries are often incomplete and imprecise, which can lead to reduced retrieval accuracy and relevance when using vector databases. To address query-document mismatch in sparse retrieval, LLM-based query expansion has been shown to alleviate these challenges [18]. GraphAide applies a similar approach to embedding-based dense retrieval, using a template-based method to generate additional versions of the input query while preserving the key entities and relationships mentioned in the original query. Subsequently, GraphAide leverages LLMs to convert the expanded set of queries into attributed subgraph matching templates, as illustrated in Figure 1. By combining expressive subgraph matching with vector-based semantic similarity, GraphAide enhances retrieval accuracy. The GraphAide API supports commonly used graph databases, such as Neo4J [19], and can auto-generate Cypher queries for the expanded query set. Moreover, the GraphAide API provides different prompt templates to generate queries for domain-specific graph data models based on custom schema.

E. Metrics and Evaluation

Evaluation of a comprehensive GenAI application with multiple components (aka *agents*) requires a collection of relevant quantitative metrics, as a single metric is often insufficient to explain the performance of all components. There is also a need to identify relevant metrics for each agent based on its functionality, role, and the type of data it processes. Both phases of GraphAide involve multiple sub-problems, each with different metric requirements as shown in table I. GraphAide leverages RAGAS [20] to prepare evaluation dataset and compute a collection of relevant quantitative metrics. Future work will focus on developing an API to auto-generate evaluation datasets and metrics. Additionally,

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.3)

A. 자료 적재
- 텍스트, CSV, PDF 등 흔한 형식을 그대로 받는다
- 적재한 자료를 나누고 조각낸다. 벡터 검색을 빠르게 하고, LLM이 한 번에 받을 수 있는 길이를 넘는 자료를 다루기 위해서다
- 조각 크기와 겹치는 길이는 고정값을 쓰고, 분야에 맞게 바꿀 수 있다

B. 저장
- 기본 RAG와 달리 벡터 DB와 그래프 DB 양쪽에 저장한다
- 벡터 DB: 분야 자료나 범용 지식(WikiData)의 임베딩을 저장한다
- 그래프 DB: 구조 정보를 추가로 저장한다. 저자들은 이것을 이 시스템의 새로운 점이라고 했다

C. KG 생성
- 하는 일: 개체 추출, 관계 추출, 개체 구분(같은 것인지 가리기), KG 부호화, KG 유지
- 방법: 예시 몇 개를 넣은 프롬프트로 LLM에 KG를 만들게 한다
- 온톨로지(또는 노드·엣지 유형 목록)를 입력으로 준다. 이것이 LLM이 낼 수 있는 응답의 형식을 제한한다
- 만든 부분 그래프가 형식에 맞는지는 Pydantic(형식 검사 도구)으로 확인한다
→ 온톨로지는 KG를 만들 때 LLM의 출력을 묶는 틀로 쓰인다. 온톨로지 자체를 어떻게 만드는지는 이 논문이 다루지 않는다

D. 부분 그래프 질의 생성
- 사용자 질문은 불완전하고 부정확한 경우가 많아 검색 정확도가 떨어진다
- 질의 확장: 원래 질문의 핵심 개체와 관계는 유지하면서 질문을 여러 판으로 늘린다(틀 기반)
- 늘린 질문들을 LLM이 부분 그래프 매칭 틀로 바꾼다. Neo4j를 지원하고 Cypher 질의를 자동으로 만든다
→ 그래프 질의문을 LLM이 만든다

E. 지표와 평가
- 구성요소가 여럿인 시스템은 지표 하나로는 성능을 설명하기 어렵다. 구성요소마다 역할과 다루는 자료에 맞는 지표가 필요하다
- 표 I: 개체 추출은 답 정확도, 의미 주석은 문맥 관련성·정확도와 답 관련성·정확도와 의미 유사도, 개체 구분은 문맥 정밀도·재현율과 ROC 곡선, 질의 확장은 답 관련성, 그래프 질의 생성은 답 정확도·관련성
- 평가 자료 준비와 지표 계산에는 RAGAS를 쓴다
- 표 I은 어떤 지표를 쓸지를 정한 것이고, 표의 지표 전부에 대한 결과값은 논문에 없다




Fig. 1: GraphAide Architecture, representing different phases and agentic workflow

qualitative metrics are required to evaluate generated responses in application domains with a *human-in-the-loop* approach. GraphAide provides methods to configure different retrieval and LLM models, producing comparable results for subject matter expert (SME) evaluation. Examples of different metrics are presented in section IV.

F. Explainable Result Generation

GraphAide simplifies the execution of the templates generated in section III-D for a given graph database and facilitates subgraph matching. It offers an API to combine subgraph matching results with vector-based semantic similarity, creating a local context for the LLM during the query phase. Unlike the KG-generation phase, the query phase uses templates to summarize and explain results from multiple retrieval sources, rather than focusing on entity disambiguation. GraphAide executes multiple parallel requests to the LLM for the expanded query set and makes a secondary call to aggregate all the responses, generating a single coherent response for the user query. Auto-generation of complex templates with multiple constraints and clauses is a part of our future work. We plan to use a few-shot prompt approach to enhance the template generation process.

IV. Experiment

For our experiment, we instantiated GraphAide using OpenAI LLM, Chroma vector database, Neo4j graph database, and LangChain application development framework. We used GPT-4o model that has larger context window and improved reasoning and deduction capabilities. GPT-4o has also shown improved multi-lingual support and that makes it relevant for our use case discussed below. We leveraged the work of two existing DARPA efforts. Active Interpretation of Disparate Alternatives (AIDA) [21] developed multi-hypothesis semantic engines to generates and understand different interpretations of events, situations, and trends from a variety of unstructured sources. Generating Alternative Interpretations for Analysis (GAIA) [22] developed automated solutions to extract entities, emerging events, situations, and trends of interest for Ukraine-Russia political conflict scenario. An ontology [23] is also constructed containing approximately 190 entity types, 140 event types, and 50 relation types. A DARPA version of WikiData (DWD) is also developed as a reference knowledge base for the entity disambiguation process focused on geopolitical scenarios.

To demonstrate GraphAide's capabilities, we used AIDA source data in text format and a Web Ontology Language (OWL) ontology in Terse RDF Triple Language (TURTLE)

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.4)

정성 평가
- 사람이 참여해 응답을 평가하는 정성 지표도 필요하다고 했다
- 검색 모델과 LLM을 바꿔 가며 비교할 수 있는 결과를 만들어, 분야 전문가가 평가할 수 있게 한다

F. 설명 가능한 결과 생성
- 부분 그래프 매칭 결과와 벡터 검색 결과를 합쳐 LLM에 줄 문맥을 만든다
- 늘린 질문마다 LLM에 따로 묻고, 한 번 더 호출해 응답들을 하나로 합친다
- 조건이 여러 개인 복잡한 질의 틀을 자동으로 만드는 것은 향후 과제다

실험 구성
- 구성: GPT-4o, Chroma(벡터 DB), Neo4j(그래프 DB), LangChain
- 자료: DARPA AIDA 사업의 뉴스 기사(우크라이나·러시아 분쟁)
- 온톨로지: 기존에 만들어진 것을 가져다 썼다. 개체 유형 약 190개, 사건 유형 약 140개, 관계 유형 약 50개
- 개체 구분의 기준 지식으로 DARPA판 WikiData(DWD)를 썼다




Fig. 2: DARPA WikiData (DWD) Embeddings Used in Retrieval

format to generate a KG. We evaluated the quality of the generated KG by comparing it with a GAIA-generated KG. We also used DWD as a reference knowledge base, stored in Chroma vector database for retrieval during KG generation phase. We curated natural language description of DWD identifiers (i.e., QIDs) and constructed *documents* to store in the vector database. We use QIDs as the document identifier and use LLMs to disambiguate mentions to top-ranked QID. GraphAide also generate UMAP embeddings of vector database to visualize the clusters of topics discussed in the KG, as shown in Figure 2. The embeddings display distinct clusters of concepts such as music, sports, politics, etc. Additionally, they show high similarity between named entities, which is used in the entity disambiguation process. Future work will also incorporate the temporal properties of these named entities to perform disambiguation during the KG generation phase.

GraphAide's *generation* phase processed 1,846 news articles and generated a KG, as shown in Figure 3. An ontology-guided and DWD-based disambiguation agent extracts entity mentions from the text and performs RAG-based node re-ranking to identify the closest matched QID. GraphAide iteratively performed text chunking, generated partial KGs from the given chunks, and loaded them into the Neo4j graph database.

In contrast to the basic RAG, GraphAide's KG-based hybrid-RAG approach provides higher specificity and cross-document inference to construct a richer context for LLM queries. Additionally, GraphAide's modular design allows dynamic selection from multiple retrieval sources for benchmarking purposes. We performed a qualitative evaluation of the generated responses in each phase. For the generation phase, LLM query templates were designed to extract natural language mentions from the input text, perform entity disambiguation using DWD, and perform type assignment (nodes and edges) based on the input ontology. As shown in Figure 3, the KG schema is constrained by the domain-specific ontology. The resulting KG has demonstrated better NER and relation extraction quality than the baseline KG [22], [24]. An extracted node type follows a hierarchical schema to represent the most specific concept about the node. For example, $GPE_UrbanArea_City$ represents a class $City$, which is a subclass of an urban area, itself a subclass of a geopolitical entity. Similarly, $ConflictAttack_FirearmAttack$ represents an attack event related to some conflict that involves firearms. As shown in Figure 5, the baseline KG shows a node type imbalance, where the most frequently extracted type is "PER" and the rest of the node types constitute a small fraction of semantic annotations. Similarly, non-binary relationship

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.5)

KG 생성 결과

- 뉴스 기사 1,846건을 처리해 KG를 만들었다
- 글을 조각내고, 조각마다 부분 KG를 만들어 Neo4j에 넣기를 반복했다
- 글에서 뽑은 개체 언급은 DWD에서 가장 가까운 항목을 찾아 같은 개체로 묶었다

KG 품질 평가 방법

- 만든 KG를 기존 시스템(GAIA)이 만든 KG와 비교했다
- 비교한 것은 노드 유형과 관계 유형의 분포다(그림 4, 그림 5)
- 기준 KG는 노드 유형이 사람(PER)에 쏠려 있고, GraphAide의 KG는 유형이 더 다양하고 고르게 나왔다고 했다
- 개체 추출과 관계 추출의 품질이 기준 KG보다 좋다고 했으나, 정밀도나 재현율 같은 수치는 없다

→ KG에 들어간 내용이 맞는지를 확인한 것이 아니라, 유형이 얼마나 다양하게 뽑혔는지를 본 것이다

노드 유형의 계층 표기

- 노드 유형은 온톨로지의 계층을 따라 가장 구체적인 개념까지 적는다
- 예: GPE_UrbanArea_City는 지정학적 개체 아래 도시 지역 아래 도시를 뜻한다




Fig. 3: GraphAide generated KG from News Sources

types such as “Evaluate” and “GeneralAffiliation” dominate the relationship extraction. In contrast, GraphAide extracts a more diverse and dense node type distribution, as shown in Figure 4. Similarly, for the edge types, GraphAide performs better in extracting event-based types, given the input data describes many temporal events.

We evaluated the semantic annotation process of assigning node types using answer relevancy, answer correctness, and semantic similarity metrics, leveraging the RAGAS library. As shown in figure 6, we observed some anomalous node type assignments that cannot be explained using answer relevancy or correctness alone. In such cases, semantic similarity can be used to explain the assignment made by the LLM, as discussed next.

For a user input “The Illinois Traction Building serves dual functions as both a railway terminal and commercial structure in Champaign, USA. The architectural design allows for its dual functionality. As such, the building is a marked example of multi-use infrastructure in the region.”, answer correctness is measured as 0.230700, but further evaluation reveals that the LLM’s prediction about this node, *FAC.Building, ORG.Government.Railway*, is semantically similar to the ground truth, *FAC.Building.OfficeBuilding, FAC.Installation.TrainStation*, which leads to a high semantic similarity of 0.922801.

In the query phase, we used GraphAide to analyze the input data from multiple sources and provide responses to user queries that rely upon the curated knowledge, providing contextual information to the LLM. To demonstrate GraphAide’s modularity, we set up a pipeline to use different levels of augmentation in responding to user queries. In addition to using OpenAI’s GPT-4o as the baseline LLM, we also utilized WikiData, a domain-specific dataset, and an enriched KG from the domain-specific dataset to answer user queries. For the qualitative evaluation of the generated responses, we compared outputs from different augmentation levels. As shown in Figure 7, the specificity of the generated response increases as we enrich the *context* shared with LLMs. Figure 7 shows that a direct query to the LLM endpoint may fail to provide a relevant response either because the LLM is not trained on data about the specific fact or because the fact is more recent than the LLM’s cutoff date. Using a reference KB may improve the response as it grounds the user query into a set of disambiguated entities. Additionally, the use of domain-specific ground-truth documents enables sharing the provenance of the generated response. As shown in Figure 7, the AIDA document corpus contains ground-truth related to the query and allows the LLM to provide a highly relevant response. Taking this a step further, the KG-based retrieval improves *context relevancy* by including entities and concepts spread across documents in the corpus. Entities such as “Donetsk People’s Republic” and “Russian Volunteer” are not necessarily mentioned in the same document in the vector database but are rather connected through a subgraph. The context generated from the subgraph is crucial for the LLM to generate additional evidence and explanations in the response. In addition to the qualitative evaluation based on user feedback, we have also identified individual components of GraphAide suitable for quantitative evaluation to measure the impact of the domain ontology and reference knowledge base. Future work will leverage

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.6)

의미 주석(유형 부여) 평가

- 노드에 유형을 붙이는 과정을 RAGAS의 답 관련성, 답 정확도, 의미 유사도로 평가했다
- 답 정확도만으로는 설명되지 않는 경우가 있었다. 예: 정확도는 0.23인데 LLM이 붙인 유형(건물, 철도 기관)이 정답 유형(사무용 건물, 기차역)과 뜻이 가까워 의미 유사도는 0.92였다
- 논문에 나온 수치는 이 예시 하나의 값이고, 전체 평균은 없다

질의 단계 평가

- 문맥을 네 수준으로 늘려 가며 같은 질문의 응답을 비교했다(그림 7): LLM만 → 기준 지식(WikiData) 추가 → 분야 문서 추가 → KG 추가
- 문맥을 늘릴수록 응답이 구체적이 된다고 했다
- KG를 쓰면 한 문서에 함께 나오지 않는 개체도 부분 그래프로 이어져 문맥에 들어간다
- 이 비교는 질문 하나에 대한 정성 비교다




Fig. 4: Type Distributions (Top-10) of GraphAide generated KG




Fig. 5: Type Distributions of Baseline KG. Node (left), Relationship (right)

quantitative metrics such as precision, recall, and retrieval relevancy to measure improvements in entity disambiguation, semantic type assignment, and KG generation tasks for a KG-based hybrid RAG.

V. Conclusion

Large Language Models (LLMs) offer exciting opportunities to develop digital assistents for domain-specific tasks. Advanced Retrieval Augmentation Generation (RAG) addresses explainability, scalability, and usability concerns in using LLMs and increases user confidence in the technology adoption. We present GraphAide, that leverages knowledge graph and subgraph matching capabilities to improve the accuracy of RAG-based applications. We present the reference architecture and its key components. We also demonstrate an instance of GraphAide to generate a Knowledge Graph (KG) from news articles describing historical ukraine-russian political conflict scenario. Future work will focus on formal evaluation to report quantitative improvements in metrics such as accuracy and relevancy.

Acknowledgement

The research described in this paper is partially supported by the Resilience Through Data Driven, Intelligently Designed Control (RD2C) Initiative at Pacific Northwest National Laboratory (PNNL) and the United States federal government. Pacific Northwest National Laboratory is a multiprogram national laboratory operated for the US Department of Energy (DOE) by Battelle Memorial Institute under Contract No. DE-AC05-76RL01830. PNNL Information Release PNNL-SA-205147.

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.7)

한계와 향후 과제

- 정량 평가는 하지 않았다. 정밀도, 재현율, 검색 관련성으로 개체 구분, 유형 부여, KG 생성의 개선을 재는 것은 향후 과제다
- 정확도와 관련성의 정량적 개선을 보고하는 정식 평가도 향후 과제다
- 평가 자료와 지표를 자동으로 만드는 API도 향후 과제다(3쪽)

정리

- 이 논문이 제시한 것: KG와 벡터 DB를 함께 쓰는 RAG 시스템의 참조 구조와 구성요소
- 온톨로지의 쓰임: 이미 있는 온톨로지를 입력으로 받아, LLM이 KG를 만들 때 낼 수 있는 유형을 제한한다
- 검증: KG는 유형 분포를 기존 KG와 비교했고, 응답은 질문 하나로 정성 비교했다. 정량 결과는 예시 값 하나뿐이다
- 구성요소마다 지표를 따로 둬야 한다는 생각(표 I)은 제시했으나 실제로 측정하지는 않았다

우리 연구와의 비교

- 같은 점: 온톨로지를 먼저 두고 그에 맞춰 KG를 만든다. KG는 Neo4j에 저장한다. 질문에 맞는 부분을 KG에서 찾아 LLM의 문맥으로 준다
- 다른 점 1: GraphAide는 그래프 질의문(Cypher)을 LLM이 만든다. 우리는 CQ마다 정해 둔 조회문을 쓰고, LLM은 의도와 값만 뽑는다
- 다른 점 2: GraphAide는 벡터 DB를 함께 쓴다. 우리는 쓰지 않고, 수문 측정값은 따로 둔 저장소에서 댐 코드와 시각으로 조회한다
- 다른 점 3: GraphAide는 기존 온톨로지를 가져다 썼다. 우리는 가져다 쓸 온톨로지가 없어 CQ에서 출발해 직접 설계했다
- 다른 점 4: GraphAide의 KG는 뉴스 글에서 LLM으로 뽑았다. 우리 KG는 승인 기록 같은 정형 자료를 규칙으로 옮긴 부분이 대부분이다




Fig. 6: Evaluation of Semantic Annotation Process




Fig. 7: GraphAide results for a user query ‘Describe the role of Russia in the of war of Odessa in 100 words and list how many deaths and damage happened there. Also list other key actors involved.’

REFERENCES

[1] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, “Language models are few-shot learners,” *Advances in neural information processing systems*, vol. 33, pp. 1877–1901, 2020.

[2] T. Zhang, F. Ladhak, E. Durmus, P. Liang, K. McKeown, and T. B. Hashimoto, “Benchmarking large language models for news summarization,” *Transactions of the Association for Computational Linguistics*,

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.8)

vol. 12, pp. 39–57, 2024.
[3] T. Berners-Lee, J. Hendler, and O. Lassila, “The semantic web: A new form of web content that is meaningful to computers will unleash a revolution of new possibilities,” in *Linking the World’s Information: Essays on Tim Berners-Lee’s Invention of the World Wide Web*, 2023, pp. 91–103.
[4] C. Bizer, T. Heath, and T. Berners-Lee, “Linked data-the story so far,” in *Linking the World’s Information: Essays on Tim Berners-Lee’s Invention of the World Wide Web*, 2023, pp. 115–143.
[5] A. Bosselut, H. Rashkin, M. Sap, C. Malaviya, A. Celikyilmaz, and Y. Choi, “Comet: Commonsense transformers for automatic knowledge graph construction,” *arXiv preprint arXiv:1906.05317*, 2019.
[6] J.-Y. Yao, K.-P. Ning, Z.-H. Liu, M.-N. Ning, and L. Yuan, “Llm lies: Hallucinations are not bugs, but features as adversarial examples,” *arXiv preprint arXiv:2310.01469*, 2023.
[7] N. McKenna, T. Li, L. Cheng, M. J. Hosseini, M. Johnson, and M. Steedman, “Sources of hallucination by large language models on inference tasks,” *arXiv preprint arXiv:2305.14552*, 2023.
[8] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel *et al.*, “Retrieval-augmented generation for knowledge-intensive nlp tasks,” *Advances in Neural Information Processing Systems*, vol. 33, pp. 9459–9474, 2020.
[9] Y. Gao, Y. Xiong, X. Gao, K. Jia, J. Pan, Y. Bi, Y. Dai, J. Sun, and H. Wang, “Retrieval-augmented generation for large language models: A survey,” *arXiv preprint arXiv:2312.10997*, 2023.
[10] D. Edge, H. Trinh, N. Cheng, J. Bradley, A. Chao, A. Mody, S. Truitt, and J. Larson, “From local to global: A graph rag approach to query-focused summarization,” *arXiv preprint arXiv:2404.16130*, 2024.
[11] M. Trajanoska, R. Stojanov, and D. Trajanov, “Enhancing knowledge graph construction using large language models,” *arXiv preprint arXiv:2305.04676*, 2023.
[12] T. Ban, L. Chen, X. Wang, and H. Chen, “From query tools to causal architects: Harnessing large language models for advanced causal discovery from data,” *arXiv preprint arXiv:2306.16902*, 2023.
[13] P. Gage, “A new algorithm for data compression,” *The C Users Journal*, vol. 12, no. 2, pp. 23–38, 1994.
[14] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever *et al.*, “Language models are unsupervised multitask learners,” *OpenAI blog*, vol. 1, no. 8, p. 9, 2019.
[15] V. Karpukhin, B. Oğuz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen, and W.-t. Yih, “Dense passage retrieval for open-domain question answering,” *arXiv preprint arXiv:2004.04906*, 2020.
[16] D. Vrandečić and M. Krötzsch, “Wikidata: a free collaborative knowledgebase,” *Communications of the ACM*, vol. 57, no. 10, pp. 78–85, 2014.
[17] S. Colvin, “Pydantic,” 2023, version 2.x. [Online]. Available: https://github.com/pydantic/pydantic
[18] M. A. K. Ayoub, Z. Su, and Q. Li, “A case study of enhancing sparse retrieval using llms,” in *Companion Proceedings of the ACM on Web Conference 2024*, 2024, pp. 1609–1615.
[19] Neo4j, Inc., *Neo4j Graph Database*, Neo4j, Inc., San Mateo, CA, 2024, available at: https://neo4j.com. [Online]. Available: https://neo4j.com
[20] S. Es, J. James, L. Espinosa-Anke, and S. Schockaert, “Ragas: Automated evaluation of retrieval augmented generation,” *arXiv preprint arXiv:2309.15217*, 2023.
[21] “Active interpretation of disparate alternatives (aida),” https://www.darpa.mil/program/active-interpretation-of-disparate-alternatives, accessed: 2024-10-09.
[22] T. Zhang, A. Subburathinam, G. Shi, L. Huang, D. Lu, X. Pan, M. Li, B. Zhang, Q. Wang, S. Whitehead *et al.*, “Gaia-a multi-media multilingual knowledge extraction and hypothesis generation system.” in *TAC*, 2018.
[23] Next Century Corporation, “Aida interchange format,” https://github.com/NextCenturyCorporation/AIDA-Interchange-Format, 2023, accessed: 2024-10-09.
[24] S. Purohit, N. Van, and G. Chin, “Semantic property graph for scalable knowledge graph analytics,” in *2021 IEEE International Conference on Big Data (Big Data)*, 2021, pp. 2672–2677.

Authorized licensed use limited to: Kookmin University. Downloaded on August 31,2026 at 11:15:48 UTC from IEEE Xplore. Restrictions apply.

메모 (p.9)