

Statement of Responses to the Editor and the Reviewers of Paper-TNSM

We would like to thank the editor and reviewers for their constructive comments on our manuscript. It has been beneficial in revising this paper, and we have improved both the technical content and presentation quality through their assistance. We greatly appreciate their generous help. Moreover, we have reviewed and incorporated all the comments and suggestions. We hope that the modifications we have made to the manuscript and the responses we have provided herein will alleviate the reviewers' concerns. Below, please find our detailed responses to the editor and reviewers' comments and suggestions.

Editor
Comments to the Author “I think the paper should undergo a major revision. It is important to take special attention to the comments of reviewer 2.”

Response:

We would like to thank the Editor for his comments and concluding the revisions on our manuscript and for giving us this opportunity to improve our paper. We have used the comments to improve our paper and eliminate problems.

Reviewer 1

Comments to the Author “ The authors have addressed the comments provided in a previous review. The contributions are clear and the results are compared to some related work, so the reader can somewhat contextualize the proposed solution. ”

Response:

We would like to thank the reviewer for the careful and thorough reading of this manuscript. We hope that the responses provided herein can alleviate the reviewer’s concerns.

Comment1: “However, the paper still needs some improvement in terms of readability. Some paragraphs are too long ”

Response:

We have changed the paper’s introduction and checked the text entirely according to this comment.

Comment2: “ the figures are difficult to locate from their reference in the text (figures at top, as typical IEEE template is better), the text in the figures is too small ”

Response:

Thank you for this comment. We changed the paper’s figures totally according to this comment.

Comment3: “the contributions discussed in the introduction are not easily found in the other parts of the paper. ”

Response:

We thank the reviewer for adding clarity to our paper and reducing ambiguity in this condition. We changed the contribution in a better way based on this comment. We have removed some sentences and rewritten the contribution in order to our paper’s section. Below we write the whole contribution section.

This paper aims to optimize the resource utilization of a downlink O-RAN system to develop an isolated network slicing outline for the three 5G service classes. We use mathematical methods to decompose and convexify the problem and solve it using hierarchical algorithms. The main contributions of this paper are summarized as follows:

- We examine the problem of radio resource allocation and VNF activation within the O-RAN architecture. Based on the three types of 5G service classes, i.e., eMBB, URLLC and mMTC, and their corresponding QoS requirements and service priorities, we formulate a problem for allocating baseband resources such as power, physical resource blocks (PRBs), O-RUs, and activating VNFs to maximize the weighted throughput of the O-RAN.
- We propose a two-step resource management algorithm for solving the optimization problem. In the first step, we reformulate and simplify the problem so as to find an upper and lower

bound for the number of activated VNFs. Moreover, we use the Lagrangian function and Karush-Kuhn-Tucker (KKT) conditions to obtain the optimal power and PRB allocation. In the second step, the problem of O-RU association is converted to a multiple knapsack problem and solved by a greedy algorithm.

- We provide insights into the complexity of the proposed algorithms and demonstrate their convergence. Additionally, we analyze the feasibility region of our problem and introduce a fast algorithm to check its feasibility numerically.
- We show via numerical results that the proposed algorithm outperforms two baseline schemes, in terms of achievable data rate. Remarkably, the proposed algorithm performs close to the optimal solution in low-interference conditions.

Reviewer 2

Comments to the Author “ The Reviewer would like to thank the authors for their revision of the paper with respect to the comments and suggestions in the previous submission. Whereas the authors have considered parts of the suggestions and improved specific areas of the work, there are still a lot of remaining issues of concern in the current version of the paper. ”

Response:

It is our pleasure to thank the reviewer for the careful reading of this manuscript, providing thoughtful comments, and offering constructive suggestions that strengthened and enhanced its quality. We hope that the responses provided herein can alleviate the reviewer’s concerns.

Comment1: “While the authors have taken into consideration the Reviewer’s comments about the re-structuring of the Introduction, I am afraid that the current version is not in the adequate state for publication. Initially, the paragraphs of the Introduction have no logical connection among them. It seems that until the Related Literature subsection all paragraphs are disconnected and only introduce concepts. ”

Response:

We would like to thank the reviewer for the careful and thorough reading of our manuscript and the thoughtful comment and constructive suggestions that helped us improve the quality of this manuscript and make it more readable. We changed the introduction and add it below

Network slicing is a key technology in 5G wireless systems. Specifically, network slicing provides the isolation of network resources into slices, e.g., via core slicing and/or radio access network (RAN) slicing, for serving multiple and heterogeneous service classes [1]–[3]. There are three main service classes in 5G, namely enhanced mobile broadband (eMBB), ultra-reliable low latency communications (URLLC), and massive machine-to-machine communications (mMTC). Depending on their corresponding quality of service (QoS) requirements, each service is assigned to a slice of the network. For instance, the eMBB service demands high capacity and throughput, e.g., 8K video streaming and immersive gaming. Meanwhile, the URLLC service, leveraged, e.g., by autonomous vehicles, Tactile Internet, and remote surgery services, is concerned with providing ultra-reliable and low-latency connectivity. Finally, mMTC services require connectivity for a large number of Internet of Things (IoT) devices that transmit small payloads [4]–[6].

Unfortunately, the existing radio access network (RAN) architecture still lacks adequate flexibility and openness to manage these demands for various services simultaneously. In view of this, a new RAN paradigm, called open RAN (O-RAN), which is schematically represented in Fig. 1, is introduced to deal with these issues.

A key feature of the O-RAN architecture is that the hardware is disaggregated from the software,

leading to network function virtualization (NFV). Additionally, each component is implemented as a virtual network function (VNF), the system function block in NFV, that can be deployed on a virtual machine (VM) or container [7],[8]. As a result, some O-RAN components defined in Section III, such as user plane function (UPF), O-RAN central unit (O-CU), O-RAN distributed unit (O-DU), and RAN intelligent controller (RIC)-near real-time, are virtualized and implemented as VNFs.

Comment2: “ Moreover, I find the ORAN explanation in the Introduction very lengthy and unnecessary. I would definitely suggest to move that as a background Section. ”

Response:

I would appreciate your comments to enhance and clarify this section of the paper. I moved the background as a section.

Comment3: “ Furthermore, it is surprising how the Introduction does not contain a single research challenge. Why is the problem relevant at all? Why do you even need to study this problem and why is it hard to solve? ”

Response:

We add the motivation subsection and answer these questions in it. Below we rewrite this section.

The problem of finding the optimal resource allocation, independently of the specific RAN technology, is vital for reducing the cost of the system and improving the QoS of the user equipments (UEs). In case of 5G systems, there are many related significant challenges such as interference alignment, limited capacity of fronthaul links, energy restrictions on virtual machines, etc [2],[9],[10].

Many studies have investigated resource allocation in cloud RAN (C-RAN) by considering the power, data rate and delay limitations of a single service. Due to the contemporary need to serve services with different QoS simultaneously, e.g., as in 5G and beyond, this architectural model is inefficient. In this regard, the O-RAN architecture has emerged as a flexible, layered, and modular design architecture that can simultaneously support multiple services at a lower cost. Nevertheless, RAN slicing in the O-RAN architecture still faces various challenges. One of the fundamental problems lies in attaining a balance between different services with different QoS, resource requirements, and priorities [1],[11]–[13].

The purpose of this paper is to design a system in the O-RAN architecture to support the three types of 5G services, namely, eMBB, URLLC, and mMTC via network slicing and resource allocation. Specifically, we aim to maximize the total achievable data rate and satisfy the minimum achievable data rate for eMBB services while meeting the URLLC requirements in the presence of numerous low-power IoT devices.

Comment4: “ In turn, in the main contributions subsection, the initial sentences of almost all contribution paragraphs cannot be considered as contributions. For instance:

1) “We have carefully considered the processing delay and the VNF resources needed for the slice compared to other papers.” 2) “ Different services need to consider varying QoS conditions, including delay, power, and throughput.” 3) “The main problem is mixed-integer non-linear programming that is extremely difficult to solve.” ”

Response:

We removed these sentences and rewrite the main contribution. Below we write the modified main contribution.

This paper aims to optimize the resource utilization of a downlink O-RAN system to develop an isolated network slicing outline for the three 5G service classes. We use mathematical methods to decompose and convexify the problem and solve it using hierarchical algorithms. The main contributions of this paper are summarized as follows:

- We examine the problem of radio resource allocation and VNF activation within the O-RAN architecture. Based on the three types of 5G service classes, i.e., eMBB, URLLC and mMTC, and their corresponding QoS requirements and service priorities, we formulate a problem for allocating baseband resources such as power, physical resource blocks (PRBs), O-RUs, and activating VNFs to maximize the weighted throughput of the O-RAN.
- We propose a two-step resource management algorithm for solving the optimization problem. In the first step, we reformulate and simplify the problem so as to find an upper and lower bound for the number of activated VNFs. Moreover, we use the Lagrangian function and Karush-Kuhn-Tucker (KKT) conditions to obtain the optimal power and PRB allocation. In the second step, the problem of O-RU association is converted to a multiple knapsack problem and solved by a greedy algorithm.
- We provide insights into the complexity of the proposed algorithms and demonstrate their convergence. Additionally, we analyze the feasibility region of our problem and introduce a fast algorithm to check its feasibility numerically.
- We show via numerical results that the proposed algorithm outperforms two baseline schemes, in terms of achievable data rate and mean total delay. Remarkably, the proposed algorithm performs close to the optimal solution in low-interference conditions.

Comment5: “ In a similar fashion, the authors have not considered the Reviewer’s suggestion to move the Related Work as a separate Section in order to improve the flow and clarity of the Introduction. ”

Response:

Thank you for this comment. I modified the background from sub-section to the section part.

Comment6: “ Regarding the Reviewer’s comment with respect to the network slice management, whereas the authors have introduced the 4 stages of the life cycle of a network slice, the connection to their approach is very vague. It is still not clear how this process is achieved and how it is linked to their method. I was expecting at least a connection or introduction to Fig.1 where the system is shown. Additionally, more information with respect to the interaction with the system would have been required in that regard. ”

Response:

We add the following part to the slice management section.

In the preparation phase, firstly, the evaluation of requirements is considered. Therefore, In this phase, we need an algorithm to estimate the number of UEs and UE traffic in the system at different times. Moreover, based on this estimation, we need to evaluate resources, including the optimal number of VNFs for each slice, the optimal number of PRBs for each slice, and the analysis of power allocation. In this phase, we can use our algorithm after estimating the system’s traffic. As shown in figure 1, we have three different slices for eMBB, URLLC, and mMTC. For each slice, the system must prepare MAC/RLC protocols for O-DU, PDCP/SDAP protocols for O-CU, UPF, SMF, and AMF. Moreover, O-RU, high PHY in O-DU, and O-CU-CP are shared between slices. Thus, we do not require estimating and preparing for the share environments and platforms in the network slicing cycles. After evaluating, assessing, and preparing the resources and environments for each slice, the commissioning phase is started. In this phase, the slices are created based on the previous phase. If the evaluation changes, the slice’s resources can be modified. We can use our algorithm to assign resources to the services in the operation phase. If we need to remove a slice or any service is not used in a zone, and we need to remove the corresponding slice, the unshared resources are removed in the decommissioning phase.

Comment6: “With respect to the convergence time of the algorithm, the Reviewer had made a suggestion to the authors to include it in the current version of the manuscript, yet the authors do not seem to have done that. The authors’ response points to Fig. 11. However if one looks at Fig.11 carefully, understands that only the Aggregate throughput is shown there. Even if one considers the Section III-C1 and III-C2 that the authors demonstrate as their convergence analysis and proof, there is no evidence or clarification of any delay value with respect to their algorithm’s convergence. On the one hand it is very beneficial to have a mathematical proof that the algorithm converges. On the other hand, it is equally important to portray these findings with numerical values. In any case, this is not applicable in the current version of the manuscript. ”

Response:

