

Writing Scientific Papers and Software

Cheng Soon Ong

Department of Computer Science, ETH Zurich, Switzerland

Abstract—A critical part of scientific discovery is the communication of research findings to peers or the general public. Mastery of the process of scientific communication improves the visibility and impact of research. While this guide is a necessary tool for learning how to write in a manner suitable for publication at a scientific venue, it is by no means sufficient, on its own, to make its reader an accomplished writer. We also describe the rules for submission in the computational intelligence laboratory. This guide should be a starting point for further development of writing skills.

I. INTRODUCTION

Recommender systems have gained increasing popularity in the last 10-15 years, mainly due to their immediate market applications. The huge selection of products online offer retailers the opportunity to attract a wide-range of clients. However, it also means that users can no longer be expected to browse through everything available until they find the film, song or book they like the most. Good recommendations are key to both making the correct products available to the appropriate audience, but also to creating a unique, personalised experience which will attract new clients. These ideas are fundamental for many leading online businesses [ref netflix, ref amazon, ref something else].

In this paper, we concentrate on the collaborative-filtering approach to recommender systems, which relies on previous user experiences (ratings), rather than pre-defined user profile [some ref about the two types]. We use the Netflix dataset with ratings from 10000 users on 1000 films, which has driven a lot of the innovation in the area and allows us to compare our solutions to the state-of-the-art.

Our main contributions are two-fold: we first combine latent factor models (SVD, SGD SVD, RBM) and neighbourhood models (user- and item-based kNN) to produce a robust recommender system which optimises the RMSE of predicted ratings on X [how many films] from B_{laa} to B_{llaa} . Second, we show that the addition of a more complex learning rate heuristic on stochastic gradient descent and restricted Boltzmann machines improves the score significantly, to X .

In Section II we describe the idea and the implementation of our systems. We present the results from the local evaluation of the models and from the validation set on Kaggle in Section III. Finally, in Section IV we interpret the improvements we achieved and discuss potential weaknesses and future work.

II. MODELS AND METHODS

All work is done on the Netflix dataset provided for the project. The data is a collection of $(user, film, rating)$ tuples. For training, we have 1176953 ratings available. The online evaluation on Kaggle is performed on another 1176953 ratings. We were able to see the prediction accuracy on 50% of that online dataset and our goal was to improve that as it is believed to be very similar to the other 50% of the data.

A. Data Model

The provided dataset can be most naturally seen as an $N \times M$ matrix, with N being the number of users ($N = 10000$), and M the number of films ($M = 1000$). If every user had rated every film, the matrix would have 10^7 entries. However, in this realistic scenario, this is not the case and our matrix is quite sparse. From here stems the difficulty of the problem - we attempt to predict more than a million ratings based on a very incomplete dataset.

There are two main views which yield different methods for tackling this problem.

Latent factor models: These models attempt to explain film ratings by users as being influenced by a set of unknown (also called *latent*) factors.

One approach characterizes users and films by low-dimensional feature vectors in a latent feature space. The rating of a given film by a given user is then modeled by the dot product between the corresponding user and film feature vectors. The different methods then aim to infer the underlying film and user feature vectors from the available ratings, most successfully through matrix factorization techniques and approximations. As examples of this approach, we discuss Singular Value Decomposition and Stochastic Gradient Descent.

It is also possible to model missing ratings through neural networks which are composed by visible and latent units. In particular, we discuss Restricted Boltzmann Machines. At a high level, for each user-film pair whose rating is missing, the neural network learns a probability distribution over the possible ratings (1 to 5) from the known ratings. The prediction is then simply the expected value of this distribution.

Neighbourhood-based models: Another approach to the collaborative filtering problem is to view the ratings as features of either the users (user-based) or the films (item-based). In the former case, a user A is represented as a sparse feature vector of their ratings and we would base

our prediction on other users who have rated those films similarly. In the latter scenario, we would use the similarity between the new film and the films already rated by A to estimate the new rating. Each film is a feature vector of all users' ratings. We review an implementation of both in the next subsection.

B. Algorithms

We investigated three algorithms which concentrate on solving the latent-factor model problem and two which work on the neighbourhood model:

Singular Value Decomposition (SVD): Given the latent factor model described above, the rating matrix is produced by the multiplication of the users matrix and films matrix which are all on the same feature space. The most natural way to infer the users and films representation is using a matrix factorisation approach so SVD comes directly to mind[some refs here]. The main issue is that SVD works on full matrices and as mentioned above, this is not the case. Hence, we need to impute the missing values before we can proceed. This introduces noise and leads to sub-optimal results. We hope to minimize the noise and the overfitting by looking for a low-rank (k) approximation of the rating matrix.

We experimented with input strategies, different number of latent features and values for k using a local validation set. We concluded that the best results were accomplished using XX features and Equation 1 for imputation:

$$R_{ij} = 0.5 \cdot \text{AvgUser}[i] + 0.5 \cdot \text{AvgFilm}[j] \quad (1)$$

A missing rating of user i for film j is calculated as a linear combination of the average rating given by user i , $\text{AvgUser}[i]$, and the average rating received by film j from all other users, $\text{AvgFilm}[j]$. If any of those values is missing due to a film with no ratings or user with no rated films, the other value is used.

We have used the Numpy built-in SVD algorithm for this. Despite the optimization strategies, we expect the results achieved with SVD to be suboptimal due to the large number of missing values, and the inaccuracy introduced by the imputation of those values. We use this algorithm as a baseline and we try to improve it with better strategies for matrix factorization or alternative approaches of finding the latent factor representation.

Stochastic Gradient Descent (SGD) for SVD: The main idea of the algorithm is to avoid the need of filling in the missing values in the k -rank approximation of the rating matrix.

Instead of doing the standard SVD which requires a full matrix, we use only the available ratings in a Stochastic Gradient Descent method. The function we minimize is :

$$\text{equation for SGD} \quad (2)$$

The approximation should be much more representative of the data as it only uses real ratings. The algorithm was very sensitive to hyper-parameters so those were optimized on both a local validation set and the online Kaggle score.

Restricted Boltzmann Machines (RBM's): RBM's are neural networks consisting of a layer of visible units and a layer of hidden units. Each unit has a stochastic binary random variable associated with it. There may be undirected connections between hidden and visible units, but no hidden-hidden or visible-visible connections are allowed. Thus, an RBM takes the form of a bipartite graph, where each layer corresponds to a different bipartition. These networks are a restricted version of Boltzmann machines (hence the name), introduced in [?].

Recently, RBM's have found applications in collaborative filtering, as illustrated in [?]. Our method is based on this paper, although there are some differences.

We first build an RBM with 5000 visible units v_i^k , for $k \in \{1, \dots, 5\}$ and $i \in \{1, \dots, 1000\}$, and F hidden units h_1, \dots, h_F , where F is a hyperparameter of the algorithm. Furthermore, for each hidden unit h_j we add connections to every visible unit v_i^k . Each connection between h_j and v_i^k has an associated weight W_{ij}^k . For each (i, j, k) triple, the initial value of W_{ij}^k is sampled from a zero-mean normal distribution with small variance.

To train our RBM, we divide the users into small batches

Note that we train only a single RBM by feeding it users' data vectors in batches, and then updating the weights. In [?], the presented method consists of building a different RBM for each user, which all share a global weight matrix. The observed ratings of each user are then used to train its associated RBM. After going through a batch, the global weight matrix is updated. In the end we obtain an RBM with the same structure as the one which we get through our method (i.e. with connections between every hidden unit and every visible unit). The prediction algorithm is the same in our method and in [?].

We make use of the built-in BernoulliRBM algorithm in sklearn to create our RBM and train it. Furthermore, we modified the source code to add an heuristic for the learning rate of the RBM, which improved its performance.

User-based k -Nearest Neighbors: Find the top k most similar users using a Pearson distance metric. The rating is the weighted average of the top k users' rating for the film.

Item-based k -Nearest Neighbors: Calculate the similarity between the films a user has already rated and the film in question. The predicted rating is then a weighted average of their ratings using the similarities as weights.

C. The bold driver heuristic

One of the biggest boosts to our score came from incorporating the bold driver heuristic for the learning rate in both SGD and RBM. This technique works as follows: Suppose we start with learning rate λ . After each epoch we

compute the current error on the validation set and compare it with the error of the previous epoch. If the error increased from one epoch to the other, we decrease λ to $d\lambda$, where $d \in [0, 1]$ is a parameter we must set. On the other hand, if the error decreased, we increase λ to $(1 + c)\lambda$, where $c \geq 0$ is a parameter we must also set. Intuitively, the bold driver heuristic speeds up the convergence when we are going in the right direction and breaks quite sharply when we have missed a minimum and must turn around, so we do not miss it again by much. Thus, the bold driver heuristic adapts the learning rate to the surface we are trying to maneuver.

By playing with the parameters λ , c and d we can increase the performance of our methods significantly. In our case, for SGD, we obtained our best scores by setting $\lambda = 0.001$, $c = 0.05$, and $d = 0.7$.

It is interesting to note that usual implementations of the bold driver heuristic also erase an update when it increases the error. In our implementation we opted to keep all such updates. Through experimentation we came to the conclusion that erasing “bad” updates did not lead to any increase of performance for our methods. **Should we test this further?**

D. Parameter optimization and validation

The general protocol for training and testing followed the steps below:

- 1) Choose a random subset of the test samples for a local validation set if not already chosen. This was in most cases 5% of the data, so xxxx samples and was only done by the first algorithm, so that all algorithms are trained on the same data.
- 2) Train each individual algorithm on the leftover test dataset. In some cases, such as in the item-base kNN, the validation set was used to automatically choose the optimal k in the predefined range. In the iterative algorithms like SGD and RBM, we used the validation set as an early indication on whether the error is really falling with every step. We would often optimise certain parameters using this validation data, such as number of features to user or algorithm iterations (see results for details).
- 3) Each algorithm generates predictions for the local validation set and the test set which would be uploaded on Kaggle.
- 4) The predictions from all algorithms are combined using linear regression. The regressor is trained on the predictions generated for local validation set for which we have ground truth. The coefficients which fit the results best are then used to generate a final prediction from all individual predictions for the online test dataset.




Figure 1. Signal compression and denoising using the Fourier basis.




Figure 2. Signal compression and denoising using the Daubechies wavelet basis.

III. RESULTS

Use examples and illustrations to clarify ideas and results. For example, by comparing Figure 1 and Figure 2, we can see the two different situations where Fourier and wavelet basis perform well.

IV. DISCUSSION

The models and methods section should describe what was done to answer the research question, describe how it was done, justify the experimental design, and explain how the results were analyzed.

The model refers to the underlying mathematical model or structure which you use to describe your problem, or that your solution is based on. The methods on the other hand, are the algorithms used to solve the problem. In some cases, the suggested method directly solves the problem, without

having it stated in terms of an underlying model. Generally though it is a better practice to have the model figured out and stated clearly, rather than presenting a method without specifying the model. In this case, the method can be more easily evaluated in the task of fitting the given data to the underlying model.

The methods part of this section, is not a step-by-step, directive, protocol as you might see in your lab manual, but detailed enough such that an interested reader can reproduce your work [?], [?].

The methods section of a research paper provides the information by which a study's validity is judged. Therefore, it requires a clear and precise description of how an experiment was done, and the rationale for why specific experimental procedures were chosen. It is usually helpful to structure the methods section by [?]:

- 1) Layout the model you used to describe the problem or the solution.
- 2) Describing the algorithms used in the study, briefly including details such as hyperparameter values (e.g. thresholds), and preprocessing steps (e.g. normalizing the data to have mean value of zero).
- 3) Explaining how the materials were prepared, for example the images used and their resolution.
- 4) Describing the research protocol, for example which examples were used for estimating the parameters (training) and which were used for computing performance.
- 5) Explaining how measurements were made and what calculations were performed. Do not reproduce the full source code in the paper, but explain the key steps.

A. Results

Organize the results section based on the sequence of table and figures you include. Prepare the tables and figures as soon as all the data are analyzed and arrange them in the sequence that best presents your findings in a logical way. A good strategy is to note, on a draft of each table or figure, the one or two key results you want to address in the text portion of the results. The information from the figures is summarized in Table I.

When reporting computational or measurement results, always report the mean (average value) along with a measure of variability (standard deviation(s) or standard error of the mean).

1) *Installation:* There are various different packages available for processing L^AT_EX documents. On Windows, use the MikT_EX package (<http://miktex.org/>), and on OSX use MacT_EX (<http://www.tug.org/mactex/2009/>). Alternatively, on OSX, you can install the t_et_ex package via Fink¹ or Macports².

¹<http://www.finkproject.org/>

²<http://www.macports.org/>

2) *Compiling L^AT_EX:* Your directory should contain at least 4 files, in addition to image files. Images should be in .png, .jpg or .pdf format.

- IEEEtran.cls
- IEEEtran.bst
- groupXX-submission.tex
- groupXX-literature.bib

Note that you should replace groupXX with your chosen group name. Then, from the command line, type:

```
$ pdflatex groupXX-submission
$ bibtex groupXX-literature
$ pdflatex groupXX-submission
$ pdflatex groupXX-submission
```

This should give you a PDF document groupXX-submission.pdf.

3) *Equations:* There are three types of equations available: inline equations, for example $y = mx + c$, which appear in the text, unnumbered equations

$$y = mx + c,$$

which are presented on a line on its own, and numbered equations

$$y = mx + c \tag{3}$$

which you can refer to at a later point (Equation (3)).

4) *Tables and Figures:* Tables and figures are “floating” objects, which means that the text can flow around it. Note that figure* and table* cause the corresponding figure or table to span both columns.

B. Grading

There are two different types of grading criteria applied to your project, with the corresponding weights shown in brackets.

Competitive

The following criteria is scored based on your rank in comparison with the rest of the class.

- time taken for computation (10%)
- average rank for all other criteria relevant to the task, for example reconstruction error and sparsity (20%)

The ranks will then be converted on a linear scale into a grade between 4 and 6.

Non-competitive

The following criteria is scored based on an evaluation by the teaching assistants.

- quality of paper (30%)
- quality of implementation (20%)
- creativity of solution (20%)

Basis	Support	Suitable signals	Unsuitable signals
Fourier	global	sine like	localized
wavelet	local	localized	sine like

Table I
CHARACTERISTICS OF FOURIER AND WAVELET BASIS.

C. Submission System

The deadline for submitting your project report is Friday, 22 June 2012. You need to submit:

- PDF of paper.
- Archive (.tar.gz or .zip) of software. Please do not forget to include author information in the source archive.

Important: Please check the submission instructions on the webpage as it is the most updated instructions.

V. SUMMARY

The aim of a scientific paper is to convey the idea or discovery of the researcher to the minds of the readers. The associated software package provides the relevant details, which are often only briefly explained in the paper, such that the research can be reproduced. To write good papers, identify your key idea, make your contributions explicit, and use examples and illustrations to describe the problems and solutions.

ACKNOWLEDGEMENTS

The author thanks Christian Sigg for his careful reading and helpful suggestions.

REFERENCES