

# Styllus Linear® Series

Styllus Linear® LED Wall Direct/Indirect Architectural Grade Luminaire

Rev. Date: V15 03/05/2025

## Product Description

The Styllus Linear® Series is a full range linear architectural portfolio. Its sleek minimalistic design provides clean uniform lines of light for any application such as: offices, healthcare, education and interior design. With smooth full-range dimming down to 1%, the Styllus Linear® Series allows each space with the appropriate light level needed for any activity. Available in up to 72 feet of continuous rows of seamless light in two-foot increments. Being versatile for lighting design, it is configurable in straight linear rows or geometric patterns, and compatible with Cree Lighting's SmartCast® Technology, Lutron Vive, and Lutron EcoSystem controls systems. Specifiable in three colors: white, black and graphite, the Styllus Linear® Series is perfect for any application.

**Applications:** Wall applications for new construction and upgrade

## Performance Summary

**Initial Delivered Lumens:** 510-1,150 lumens per foot Downlight / 450-1,025 lumens per foot Uplight

**Efficacy:** Up to 119 LPW Downlight / 131 LPW Uplight

**CRI:** 80+ CRI

**CCT:** 3000K, 3500K, 4000K

**Input Voltage:** 120-277 VAC or 347 VAC

**L<sub>70</sub> Lifetime:** > 100,000 hours at 35°C

**Limited Warranty\*:** 10 years for luminaire; 5 years for SmartCast® and Lutron controls; up to 5 years for SmartCast® accessories


**Limited Warranty Emergency Back Up (EB) Battery and Generator Transfer Device:** 1 Year. Test regularly in accordance with local codes. Contains Self-Diagnostic Emergency Battery Back-up

**Dimensions with End Caps:** H 4.5" (114mm) x W 3.625" (92mm) x L up to 72.02' (21.95m)

**Weight:** 3.5 LB/FT (1.6kg)

**Dimming:** 0-10V dimming to 1%, DALI dimming to 5%, SmartCast® Technology dimming to 5%, Lutron EcoSystem dimming to 1%, Lutron Vive dimming to 5%

Assembled in the USA from US and imported parts



\* See <https://www.creelighting.com/resources/warranties/> for warranty terms. For SmartCast accessories, consult SmartCast spec sheets for details on warranty terms.

## Accessories

Field-Installed		
<b>SmartCast® Technology Configuration Tool</b> <a href="#">CCT-CWC-1</a> - One required per project when SC5 control is selected	<b>SmartCast® 5-Button Wireless Scene Controller</b> <a href="#">CSC-SC-A-5B-UNVN-WH</a> (w/o text) <a href="#">CSC-SC-A-5S-UNVN-WH</a> (w/scene text) <a href="#">CSC-SC-A-5X-UNVN-WH</a> (w/custom text) <b>SmartCast® Technology Wireless Dimmer</b> <a href="#">CSC-CWD-UNVN-WH</a> (neutral wire required) <a href="#">CSC-CWD-UNV-WH</a> (no neutral required) <b>SmartCast® Technology Wireless Switch</b> <a href="#">CSC-CWS-UNVN-WH</a> (neutral wire required) <a href="#">CSC-CWS-UNV-WH</a> (no neutral required) <b>SmartCast® Technology Wireless Plug Load Controller</b> <a href="#">CPLC-JB-CWC</a>	<b>SmartCast 10V Zone Controller</b> <a href="#">CSC-ZC-10V-CWC</a> - Intelligent sensing and control of 0-10V luminaires

## Ordering Information

Example: ST3-WI-02-L-L-8-30K-L-10V-WH

ST3	WI												
Family	Mounting	Length	Plan*	Uplight Output	Downlight Output	CRI	CCT	Voltage	Downlight Option	Controls		Finish	Options
ST3 Styllus Linear® 3"	WI Wall Direct/ Indirect	02 ~ 2' increments up to 72'	Blank Linear L_X_ L Shape C_ Custom	L Low (450 Lumens/FT) M Medium (745 Lumens/FT) H High (1025 Lumens/ FT)	L Low (510 Lumens/FT) M Medium (830 Lumens/FT) H High (1150 Lumens/FT)	8 80 CRI	30K 3000K 35K 3500K 40K 4000K	Blank 120-277 Volt 34 347 Volt	L Lambertian	10V 0-10V dimming to 1% DALI DALI dimming to 5% - Not available with 2' lengths or 347V SC5 SmartCast Wireless control and integral sensors. - Dimming to 5% - Not available in 2' lengths LDE1 Lutron EcoSystem (Lutron HiLume 1% EcoSystem LED Driver with Soft-on, Fade to Black Dimming Technology) - Not available in 2' or 347v	VDO Lutron Vive (5% Dimming) - Not available in 2', section lengths - Not available for corners - Not available in 347V	WH White BK Black GR Graphite	EB 10W Emergency Battery Backup** - 120-277V only - Standard 1EB/Run; for additional emergency units per run, consult sales - Illuminates first 4' of fixture - Not available in 2' fixtures GT Generator Transfer Device** - 120/277V only - Not available in 2' fixtures DF Dual Feed - Allows for independent control of direct and indirect light - Not available with GT option - Not supported with SmartCast Wireless***

\* Refer to page 5 for Plan Diagram for Corners.

\*\* GT and EB cannot be used together.

\*\*\*SmartCast supports independent wireless control of direct and indirect lights without Dual Feed.



Website: [creelighting.com](https://www.creelighting.com)

US: (800) 236-6800 Canada: (800) 473-1234

**CREE**  **LIGHTING®**

## Product Specifications

### SMARTCAST® TECHNOLOGY

SmartCast® Technology is the most intuitive and easiest to install intelligent light solution on the market. SmartCast® Technology delivers up to 70% energy savings at up to half the cost of other solutions. Luminaires combine best-in-class light with onboard sensors and intelligence to deliver a better light experience. Extreme energy productivity, code compliance and a better light experience without any extra design, installation or setup work.

### CONSTRUCTION & MATERIALS

- 6063 marine grade extruded aluminum housing
- Matte acrylic lens
- Bead suspended acrylic lens
- Textured powder coat paint with a matte white, black or graphite finish
- Luminaires mount to wall with two 5.9" W extruded aluminum wall cleats. Wall cleats have (2) 0.75" wireway holes and (2) 0.31" holes to secure luminaire to wall; hardware by others. Wall cleats secure to luminaire with (2) Phillips head screws provided
- End caps are extruded aluminum and come installed on individually mounted luminaires (2'-12')
- One set of end caps is included to accommodate runs from 14'-72'
- Continuous rows include quick connect wiring harnesses for ease of installation. Alignment pins between luminaires create seamless appearance and straighter rows
- **Weight:** 3.5 lbs./ft.; for GTD, add 0.50 lbs. each; for EB, add 2.8 lbs. each

### OPTICAL SYSTEM

- Forward throw distribution to evenly illuminate wall and ceiling
- Multiple lumen intensities along with various up/down light options to provide the correct level of illumination within each space
- High efficiency diffuser designed to minimize glare and provide uniform light distribution

### ELECTRICAL SYSTEM

- **Power Factor:** > 0.9 at full load
- **Input Power:** Stays constant over life
- **Input Voltage:** 120-277V or 347V, 50/60Hz
- **Operating Temperature Range:** -20°C - +35°C (-4°F - +95°F); minimum operating temperature with EB14 option is 0°C (32°F)
- **Total Harmonic Distortion:** < 20% at full load

### 10V DIMMING AND CONTROL

- Continuous dimming to 1% with 0-10V DC control protocol
- **10V Source Current:** 0.60mA maximum up to 12'
- Use only lighting controls with neutral connection or controls intended for use with LED fixtures
- Reference <https://cree.widen.net/s/b6gdfqzrd9/0-10v-and-step-dimming-controls-spec-sheet-cr-flex-zr-troffers-ls-ur-styllus-ws-cdr-kbl> for recommended dimming controls and wiring diagrams
- Luminaires with DALI, SmartCast and Lutron Vive dim to 5%. Lutron EcoSystem dims to 1%

### REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus listed
- Suitable for damp locations
- Designed for indoor use only
- Suitable for continuous row mounting
- Not intended for use in environments containing airborne corrosive agents such as chemical solvents, cleaners, or cutting fluids
- UL924 (EB option). Maximum mounting height: 15.0' (4.6m)
- RoHS compliant. Consult factory for additional details
- Meets FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions
- Assembled in the USA from US and imported parts
- Meets the requirements for Buy American Act (BAA) because it qualifies as a commercially-available off-the-shelf (COTS) item. Please refer to [www.creelighting.com/BAA-BABA](http://www.creelighting.com/BAA-BABA)
- **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

## SmartCast® Technology

### INTEGRAL MOTION SENSOR

- Passive infrared (PIR)
- Coverage area: Please refer to the PIR motion sensor coverage table
- Not intended to be mounted higher than 20 ft.
- **Operation:**
  - Grouped with a wall control: Luminaire will operate in vacancy mode (manual-on/auto-off)
  - Not grouped with a wall control: Luminaire will operate in occupancy mode (auto-on/auto-off)
- Luminaires operate at full intensity until OneButton™ Setup is initiated by the Cree Lighting Configuration Tool

### AMBIENT LIGHT SENSOR

- Sensor response matches response of human eye
- Not intended to be mounted higher than 20 ft. (6.1m)
- Luminaires operate at full intensity until OneButton™ Setup is initiated by the Cree Lighting Configuration Tool
- Daylight harvesting calibration performed automatically during OneButton™ Setup

### INTEGRAL WIRELESS COMMUNICATION

- 2.4GHz wireless mesh technology with AES 128-bit encryption
- Self assigns to quietest channel during OneButton™ Setup
- **Range:**
  - 30 ft. (9.1m) in typical commercial applications
  - 300 ft. (91.4m) open air without obstructions
- **Network:** 250 devices max.
- **Space:** 100 devices max. per group
- FCC and IC certifications


### LUMINAIRE

- Luminaires operate at full intensity until OneButton™ Setup is initiated by the Cree Lighting Configuration Tool
- Independent wireless control of direct and indirect lights through SmartCast wall dimmers and SmartCast Touchscreen
- 10-year power fail memory of settings
- **NOTE:** SmartCast luminaires must be installed on unswitched AC power. Constant power is required to maintain all luminaires on the SmartCast network. If wall control or manual dimming is required, a SmartCast wall control dimmer must be used for manual on, off, and dimming.

### DEPLOYMENT

- Please refer to the SmartCast® Deployment Guide at <https://cree.widen.net/s/mvxtfd2pcz/smartcast-wireless-deployment-guide>

### PIR Motion Sensor Coverage



Mounting Height - H (Feet)	Motion Sensor Coverage Diameter - D (Feet)		
	Sensitivity - High (Default)	Sensitivity - Medium	Sensitivity - Low
10	20	10	8
12	26	14	12
14	28	15	13
20	38	Not Recommended	Not Recommended

## Styllus Linear® LED Wall Direct/Indirect Architectural Grade Luminaire

Initial Delivered Lumens (30K/35K/40K)					
Indirect Lumen Package - 80 CRI					
Low		Medium		High	
Downlight	Uplight	Downlight	Uplight	Downlight	Uplight
510	450	510	745	510	1025
830	450	830	745	830	1025
1150	450	1150	745	1150	1025

Percentage of Downlight/Uplight						
Direct Lumen Package	Indirect Lumen Package					
	Low		Medium		High	
	% Downlight	% Uplight	% Downlight	% Uplight	% Downlight	% Uplight
L	53%	47%	41%	59%	33%	67%
M	65%	35%	53%	47%	45%	55%
H	72%	28%	61%	39%	53%	47%

Styllus Linear® Series Ambient Adjusted Lumen Maintenance¹					
Ambient	Initial LMF	25K hr Reported² LMF	50K hr Estimated³ LMF	75K hr Estimated³ LMF	100K hr Estimated³ LMF
5°C (41°F)	1.03	1.00	0.95	0.91	0.87
15°C (59°F)	1.01	0.98	0.93	0.89	0.85
25°C (77°F)	1.00	0.97	0.92	0.88	0.84
30°C (86°F)	0.99	0.96	0.91	0.87	0.83
35°C (95°F)	0.99	0.96	0.91	0.87	0.83

¹ Lumen maintenance values at 25°C (77°F) are calculated per IES TM-21 based on IES LM-80 report data for the LED package and in-situ luminaire testing. Luminaire ambient temperature factors (LATF) have been applied to all lumen maintenance factors.

² In accordance with IES TM-21, Reported values represent interpolated values based on time durations that are up to 6x the tested duration in the IES LM-80 report for the LED.

³ Estimated values are calculated and represent time durations that exceed the 6x test duration of the LED.

Electrical Data*							
Length	Direct Lumen Package	Indirect Lumen Package					
		Low Lumen Package					
		System Watts		Total Current (A)			
		120-347V	120V	208V	240V	277V	347V
2'	L	20	0.17	0.10	0.08	0.07	0.06
	M	25	0.21	0.12	0.11	0.09	0.08
	H	31	0.26	0.15	0.13	0.11	0.09
4'	L	35	0.28	0.16	0.14	0.12	0.09
	M	46	0.38	0.22	0.19	0.16	0.13
	H	57	0.48	0.27	0.24	0.20	0.16
6'	L	49	0.41	0.24	0.21	0.18	0.14
	M	66	0.55	0.32	0.27	0.24	0.19
	H	82	0.69	0.40	0.34	0.30	0.23
8'	L	64	0.54	0.31	0.27	0.23	0.18
	M	86	0.71	0.41	0.36	0.31	0.24
	H	109	0.91	0.52	0.45	0.39	0.31
10'	L	81	0.67	0.39	0.34	0.29	0.24
	M	107	0.90	0.51	0.45	0.39	0.31
	H	139	1.16	0.66	0.57	0.50	0.40
12'	L	94	0.79	0.45	0.39	0.34	0.27
	M	129	1.07	0.62	0.54	0.46	0.37
	H	163	1.37	0.78	0.68	0.59	0.46


\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%. For electrical data for continuous runs to 72", please refer to the Initial Delivered Lumens & Electrical Data chart on pages 8 - 16.

Electrical Data*							
Length	Direct Lumen Package	Indirect Lumen Package					
		Medium Lumen Package					
		System Watts      Total Current (A)					
		120-347V	120V	208V	240V	277V	347V
2'	L	24	0.20	0.12	0.10	0.09	0.07
	M	29	0.24	0.14	0.12	0.11	0.09
	H	35	0.29	0.17	0.15	0.13	0.10
4'	L	43	0.36	0.21	0.18	0.16	0.12
	M	54	0.45	0.26	0.23	0.20	0.16
	H	65	0.55	0.31	0.27	0.24	0.19
6'	L	62	0.51	0.30	0.26	0.22	0.18
	M	79	0.65	0.38	0.33	0.28	0.23
	H	95	0.80	0.46	0.40	0.34	0.27
8'	L	81	0.68	0.39	0.34	0.29	0.23
	M	103	0.86	0.49	0.43	0.37	0.29
	H	126	1.06	0.60	0.52	0.45	0.36
10'	L	101	0.84	0.49	0.42	0.36	0.29
	M	127	1.07	0.61	0.53	0.46	0.36
	H	159	1.33	0.76	0.66	0.57	0.45
12'	L	120	1.01	0.58	0.50	0.44	0.35
	M	155	1.29	0.75	0.65	0.56	0.45
	H	189	1.59	0.91	0.79	0.68	0.54

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%. For electrical data for continuous runs to 72', please refer to the Initial Delivered Lumens & Electrical Data chart on pages 8 - 16.

Electrical Data*							
Length	Direct Lumen Package	Indirect Lumen Package					
		High Lumen Package					
		System Watts      Total Current (A)					
		120-347V	120V	208V	240V	277V	347V
2'	L	29	0.24	0.14	0.12	0.11	0.08
	M	34	0.29	0.17	0.14	0.12	0.10
	H	40	0.34	0.19	0.17	0.14	0.11
4'	L	53	0.44	0.25	0.22	0.19	0.15
	M	64	0.53	0.31	0.27	0.23	0.19
	H	75	0.63	0.36	0.31	0.27	0.22
6'	L	77	0.64	0.37	0.32	0.28	0.22
	M	94	0.78	0.45	0.39	0.34	0.27
	H	110	0.93	0.53	0.46	0.40	0.31
8'	L	101	0.85	0.49	0.42	0.37	0.29
	M	123	1.03	0.59	0.51	0.44	0.35
	H	146	1.23	0.70	0.61	0.53	0.42
10'	L	127	1.06	0.61	0.53	0.46	0.37
	M	153	1.29	0.74	0.64	0.55	0.44
	H	185	1.55	0.89	0.77	0.67	0.53
12'	L	153	1.28	0.74	0.64	0.55	0.44
	M	188	1.56	0.90	0.78	0.68	0.54
	H	222	1.86	1.07	0.92	0.80	0.63


\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%. For electrical data for continuous runs to 72', please refer to the Initial Delivered Lumens & Electrical Data chart on pages 8 - 16.



**NOTE:** Corner units are 4' in length, 2' for each leg.  
Actual dimensions for corner units are 24.75" for each leg.

Photometry

**ST3-WI-04-H-H-30K-L-10V-WH BASED ON RESTL REPORT TEST #: PL14231-001A**  
Luminaire photometry has been conducted in accordance with IES LM-79. IES LM-79 specifies the entire luminaire as the source resulting in a luminaire efficiency of 100%.



ST3-WI-04-H-H-30K-L-\*\*\*\*  
Initial Delivered Lumens: 6,624

Coefficients Of Utilization – Zonal Cavity Method				
RC %:	80			
RW %:	70	50	30	10
RCR: 0	107	107	107	107
1	98	94	90	86
2	89	82	76	70
3	81	72	65	59
4	75	64	56	50
5	68	57	49	43
6	63	51	43	37
7	58	46	38	32
8	54	42	34	29
9	50	38	31	26
10	47	35	28	23

Effective Floor Cavity Reflectance: 20%

Average Luminance Table (cd/m²)				
Vertical Angle	Horizontal Angle			
	0°	45°	90°	
	45°	12,849	12,582	10,048
	55°	12,007	11,759	9,324
	65°	11,061	10,886	8,669
	75°	9,602	9,831	7,882
85°	7,872	9,661	7,773	

Zonal Lumen Summary			
Zone	Lumens	% Lamp	Luminaire
0-30	997.43	N/A	15.10%
0-40	1599.25	N/A	24.10%
0-60	2715.81	N/A	41.00%
0-90	3388.99	N/A	51.20%
90-120	646.03	N/A	9.80%
90-150	2368.42	N/A	35.80%
90-180	3235.36	N/A	48.80%
0-180	6624.35	N/A	100.00%

Reference <https://www.creelighting.com/styllus-series/> for detailed photometric data.

## Application Reference

Based on ST3-WI-04-H-H-30K-L-\*\*\*\* Luminaire

Open Space						
Linear ft	80 CRI					
	Direct Lumen Package	Direct Lumens /ft	Indirect Lumen Package	Indirect Lumens /ft	Average FC	FC/ Linear ft
28	Low	510	Low	450	42	1.50
	Medium	830	Medium	745	69	2.46
	High	1150	High	1025	95	3.41
24	Low	510	Low	450	36	1.50
	Medium	830	Medium	745	59	2.46
	High	1150	High	1025	82	3.41
20	Low	510	Low	450	29	1.50
	Medium	830	Medium	745	49	2.46
	High	1150	High	1025	68	3.41
16	Low	510	Low	450	24	1.50
	Medium	830	Medium	745	40	2.46
	High	1150	High	1025	55	3.41

10' ceiling: 80/50/20 reflectances; 2.5' workplane, 8' mounting height. LLF: 1.0 Initial.

Open Space: 50' x 6' x 10'

Fixture spacing should typically not exceed 1x the mounting height in an open space.

Styllus Linear® Wall Mount Configuration Chart									
Length (feet)	Units						Aperture (inches)	End Cap to End Cap (inches)	1/8" End Cap Kits
	2'	4'	6'	8'	10'	12'			
2	1						24	24.25	
4		1					48	48.25	
6			1				72	72.25	
8				1			96	96.25	
10					1		120	120.25	1
12						1	144	144.25	1
14			1	1			168	168.25	1
16				2			192	192.25	1
18		1	1	1			216	216.25	1
20		1		2			240	240.25	1
22			1	2			264	264.25	1
24				3			288	288.25	1
26		1	1	2			312	312.25	1
28		1		3			336	336.25	1
30			1	3			360	360.25	1
32				4			384	384.25	1
34		1	1	3			408	408.25	1
36		1		4			432	432.25	1
38			1	4			456	456.25	1
40				5			480	480.25	1
42		1	1	4			504	504.25	1
44		1		5			528	528.25	1
46			1	5			552	552.25	1
48				6			576	576.25	1
50		1	1	5			600	600.25	1
52		1		6			625	625.25	1
54			1	6			648	648.25	1
56				7			672	672.25	1
58		1	1	6			696	696.25	1
60		1		7			720	720.25	1
62			1	7			744	744.25	1
64				8			768	768.25	1
66		1	1	7			792	792.25	1
68		1		8			816	816.25	1
70			1	8			840	840.25	1
72				9			864	864.25	1

# Styllus Linear® LED Wall Direct/Indirect Architectural Grade Luminaire

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Low Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downlight 80 CRI	Uplight 80 CRI	120V	208V	240V	277V	347V
2'	L	20	1,020	900	0.17	0.10	0.08	0.07	0.06
	M	25	1,660	900	0.21	0.12	0.11	0.09	0.08
	H	31	2,300	900	0.26	0.15	0.13	0.11	0.09
4'	L	35	2,050	1,790	0.28	0.16	0.14	0.12	0.09
	M	46	3,330	1,790	0.38	0.22	0.19	0.16	0.13
	H	57	4,610	1,790	0.48	0.27	0.24	0.20	0.16
6'	L	49	3,070	2,690	0.41	0.24	0.21	0.18	0.14
	M	66	4,990	2,690	0.55	0.32	0.27	0.24	0.19
	H	82	6,900	2,690	0.69	0.40	0.34	0.30	0.23
8'	L	64	4,100	3,580	0.54	0.31	0.27	0.23	0.18
	M	86	6,650	3,580	0.71	0.41	0.36	0.31	0.24
	H	109	9,225	3,580	0.91	0.52	0.45	0.39	0.31
10'	L	81	5,125	4,480	0.67	0.39	0.34	0.29	0.24
	M	107	8,325	4,480	0.90	0.51	0.45	0.39	0.31
	H	139	11,525	4,480	1.16	0.66	0.57	0.50	0.40
12'	L	94	6,150	5,375	0.79	0.45	0.39	0.34	0.27
	M	129	9,975	5,375	1.07	0.62	0.54	0.46	0.37
	H	163	13,825	5,375	1.37	0.78	0.68	0.59	0.46
14'	L	113	7,170	6,270	0.95	0.54	0.47	0.41	0.33
	M	152	11,640	6,270	1.26	0.73	0.63	0.55	0.44
	H	191	16,125	6,270	1.61	0.92	0.79	0.69	0.55
16'	L	128	8,200	7,160	1.07	0.61	0.53	0.46	0.36
	M	172	13,300	7,160	1.43	0.82	0.71	0.62	0.48
	H	218	18,450	7,160	1.83	1.04	0.90	0.78	0.62
18'	L	148	9,220	8,060	1.23	0.71	0.61	0.53	0.42
	M	198	14,970	8,060	1.64	0.94	0.82	0.71	0.57
	H	248	20,735	8,060	2.08	1.19	1.03	0.89	0.71
20'	L	163	10,250	8,950	1.35	0.78	0.68	0.58	0.46
	M	218	16,630	8,950	1.80	1.04	0.90	0.78	0.62
	H	275	23,060	8,950	2.30	1.31	1.14	0.99	0.79
22'	L	177	11,270	9,850	1.48	0.85	0.74	0.64	0.51
	M	238	18,290	9,850	1.97	1.14	0.99	0.85	0.68
	H	300	25,350	9,850	2.52	1.44	1.25	1.08	0.86
24'	L	192	12,300	10,740	1.61	0.92	0.80	0.69	0.55
	M	258	19,950	10,740	2.14	1.23	1.07	0.92	0.73
	H	327	27,675	10,740	2.74	1.56	1.35	1.17	0.94
26'	L	212	13,320	11,640	1.76	1.02	0.88	0.76	0.60
	M	284	21,620	11,640	2.35	1.35	1.17	1.02	0.81
	H	357	29,960	11,640	2.99	1.71	1.48	1.28	1.02

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.  
 \*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.



Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Low Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downlight	Uplight	120V	208V	240V	277V	347V
			80 CRI	80 CRI					
28'	L	227	14,350	12,530	1.89	1.09	0.94	0.82	0.64
	M	304	23,280	12,530	2.52	1.45	1.26	1.09	0.86
	H	384	32,285	12,530	3.22	1.83	1.59	1.38	1.10
30'	L	241	15,370	13,430	2.02	1.16	1.00	0.87	0.69
	M	324	24,940	13,430	2.69	1.55	1.34	1.16	0.92
	H	409	34,575	13,430	3.43	1.96	1.70	1.47	1.17
32'	L	256	16,400	14,320	2.14	1.23	1.07	0.92	0.73
	M	344	26,600	14,320	2.85	1.64	1.42	1.23	0.97
	H	436	36,900	14,320	3.65	2.08	1.80	1.56	1.25
34'	L	276	17,420	15,220	2.30	1.32	1.15	0.99	0.79
	M	370	28,270	15,220	3.06	1.77	1.53	1.33	1.06
	H	466	39,185	15,220	3.91	2.23	1.93	1.67	1.34
36'	L	291	18,450	16,110	2.42	1.39	1.21	1.05	0.82
	M	390	29,930	16,110	3.23	1.86	1.61	1.40	1.10
	H	493	41,510	16,110	4.13	2.35	2.04	1.77	1.41
38'	L	305	19,470	17,010	2.55	1.47	1.27	1.10	0.87
	M	410	31,590	17,010	3.40	1.96	1.70	1.47	1.16
	H	518	43,800	17,010	4.35	2.48	2.15	1.86	1.48
40'	L	320	20,500	17,900	2.68	1.54	1.33	1.15	0.91
	M	430	33,250	17,900	3.57	2.05	1.78	1.54	1.21
	H	545	46,125	17,900	4.57	2.60	2.25	1.95	1.56
42'	L	340	21,520	18,800	2.83	1.63	1.41	1.22	0.97
	M	456	34,920	18,800	3.78	2.18	1.89	1.63	1.30
	H	575	48,410	18,800	4.82	2.75	2.38	2.06	1.65
44'	L	355	22,550	19,690	2.96	1.70	1.47	1.28	1.01
	M	476	36,580	19,690	3.94	2.27	1.97	1.71	1.35
	H	602	50,735	19,690	5.04	2.87	2.49	2.16	1.73
46'	L	369	23,570	20,590	3.09	1.77	1.54	1.33	1.06
	M	496	38,240	20,590	4.11	2.37	2.05	1.78	1.41
	H	627	53,025	20,590	5.26	3.00	2.60	2.25	1.80
48'	L	384	24,600	21,480	3.21	1.84	1.60	1.38	1.09
	M	516	39,900	21,480	4.28	2.46	2.14	1.85	1.45
	H	654	55,350	21,480	5.48	3.12	2.71	2.34	1.87
50'	L	404	25,620	22,380	3.37	1.94	1.68	1.46	1.15
	M	542	41,570	22,380	4.49	2.59	2.24	1.94	1.54
	H	684	57,635	22,380	5.73	3.27	2.83	2.46	1.96
52'	L	419	26,650	23,270	3.49	2.01	1.74	1.51	1.19
		562	43,230	23,270	4.66	2.68	2.32	2.01	1.59
	H	711	59,960	23,270	5.96	3.39	2.94	2.55	2.04

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Low Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downlight 80 CRI	Uplight 80 CRI	120V	208V	240V	277V	347V
54'	L	433	27,670	24,170	3.62	2.08	1.80	1.56	1.24
	M	582	44,890	24,170	4.83	2.78	2.41	2.09	1.65
	H	736	62,250	24,170	6.17	3.52	3.05	2.64	2.11
56'	L	448	28,700	25,060	3.75	2.15	1.86	1.61	1.28
	M	602	46,550	25,060	4.99	2.87	2.49	2.16	1.70
	H	763	64,575	25,060	6.39	3.64	3.16	2.73	2.19
58'	L	468	29,720	25,960	3.90	2.25	1.95	1.69	1.33
	M	628	48,220	25,960	5.20	3.00	2.60	2.25	1.78
	H	793	66,860	25,960	6.65	3.79	3.29	2.85	2.27
60'	L	483	30,750	26,850	4.03	2.31	2.01	1.74	1.37
	M	648	49,880	26,850	5.37	3.09	2.68	2.32	1.83
	H	820	69,185	26,850	6.87	3.91	3.39	2.94	2.35
62'	L	497	31,770	27,750	4.16	2.39	2.07	1.79	1.42
	M	668	51,540	27,750	5.54	3.19	2.76	2.39	1.89
	H	845	71,475	27,750	7.09	4.04	3.50	3.03	2.42
64'	L	512	32,800	28,640	4.28	2.46	2.13	1.85	1.46
	M	688	53,200	28,640	5.71	3.28	2.85	2.47	1.94
	H	872	73,800	28,640	7.31	4.16	3.61	3.12	2.50
66'	L	532	33,820	29,540	4.44	2.55	2.21	1.92	1.52
	M	714	54,870	29,540	5.92	3.41	2.95	2.56	2.03
	H	902	76,085	29,540	7.56	4.31	3.74	3.24	2.59
68'	L	547	34,850	30,430	4.56	2.62	2.27	1.97	1.55
	M	734	56,530	30,430	6.08	3.50	3.04	2.63	2.07
	H	929	78,410	30,430	7.78	4.43	3.84	3.33	2.66
70'	L	561	35,870	31,330	4.69	2.70	2.34	2.02	1.60
	M	754	58,190	31,330	6.25	3.60	3.12	2.70	2.13
	H	954	80,700	31,330	8.00	4.56	3.95	3.42	2.73
72'	L	576	36,900	32,220	4.82	2.76	2.40	2.08	1.64
	M	774	59,850	32,220	6.42	3.70	3.20	2.77	2.18
	H	981	83,025	32,220	8.22	4.68	4.06	3.52	2.81

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Medium Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downlight 80 CRI	Uplight 80 CRI	120V	208V	240V	277V	347V
2'	L	24	1,020	1,490	0.20	0.12	0.10	0.09	0.07
	M	29	1,660	1,490	0.24	0.14	0.12	0.11	0.09
	H	35	2,300	1,490	0.29	0.17	0.15	0.13	0.10
4'	L	43	2,050	2,970	0.36	0.21	0.18	0.16	0.12
	M	54	3,330	2,970	0.45	0.26	0.23	0.20	0.16
	H	65	4,610	2,970	0.55	0.31	0.27	0.24	0.19
6'	L	62	3,070	4,450	0.51	0.30	0.26	0.22	0.18
	M	79	4,990	4,450	0.65	0.38	0.33	0.28	0.23
	H	95	6,900	4,450	0.80	0.46	0.40	0.34	0.27
8'	L	81	4,100	5,950	0.68	0.39	0.34	0.29	0.23
	M	103	6,650	5,950	0.86	0.49	0.43	0.37	0.29
	H	126	9,225	5,950	1.06	0.60	0.52	0.45	0.36
10'	L	101	5,125	7,425	0.84	0.49	0.42	0.36	0.29
	M	127	8,325	7,425	1.07	0.61	0.53	0.46	0.36
	H	159	11,525	7,425	1.33	0.76	0.66	0.57	0.45
12'	L	120	6,150	8,900	1.01	0.58	0.50	0.44	0.35
	M	155	9,975	8,900	1.29	0.75	0.65	0.56	0.45
	H	189	13,825	8,900	1.59	0.91	0.79	0.68	0.54
14'	L	143	7,170	10,400	1.19	0.69	0.60	0.52	0.41
	M	182	11,640	10,400	1.51	0.87	0.75	0.65	0.52
	H	221	16,125	10,400	1.85	1.06	0.92	0.80	0.63
16'	L	162	8,200	11,900	1.36	0.78	0.68	0.59	0.46
	M	206	13,300	11,900	1.72	0.99	0.86	0.74	0.58
	H	252	18,450	11,900	2.12	1.21	1.05	0.91	0.72
18'	L	186	9,220	13,370	1.55	0.89	0.78	0.67	0.53
	M	236	14,970	13,370	1.96	1.13	0.98	0.85	0.68
	H	286	20,735	13,370	2.40	1.38	1.19	1.03	0.82
20'	L	205	10,250	14,870	1.72	0.99	0.86	0.74	0.58
	M	260	16,630	14,870	2.17	1.25	1.08	0.94	0.74
	H	317	23,060	14,870	2.66	1.52	1.32	1.14	0.91
22'	L	224	11,270	16,350	1.87	1.08	0.93	0.81	0.64
	M	285	18,290	16,350	2.37	1.36	1.18	1.02	0.81
	H	347	25,350	16,350	2.91	1.66	1.44	1.25	0.99
24'	L	243	12,300	17,850	2.04	1.17	1.02	0.88	0.70
	M	309	19,950	17,850	2.57	1.48	1.28	1.11	0.88
	H	378	27,675	17,850	3.17	1.81	1.57	1.36	1.09
26'	L	267	13,320	19,320	2.23	1.29	1.11	0.96	0.76
	M	339	21,620	19,320	2.82	1.62	1.41	1.22	0.97
	H	412	29,960	19,320	3.46	1.98	1.71	1.49	1.18

\* Electrical data at 25°C [77°F]. Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C [77°F]. Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Medium Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current [A]				
		120-347V	Downlight	Uplight	120V	208V	240V	277V	347V
			80 CRI	80 CRI					
28'	L	286	14,350	20,820	2.40	1.38	1.19	1.03	0.82
	M	363	23,280	20,820	3.02	1.74	1.51	1.31	1.04
	H	443	32,285	20,820	3.72	2.13	1.84	1.60	1.28
30'	L	305	15,370	22,300	2.55	1.47	1.27	1.10	0.88
	M	388	24,940	22,300	3.22	1.86	1.61	1.39	1.11
	H	473	34,575	22,300	3.97	2.27	1.96	1.70	1.36
32'	L	324	16,400	23,800	2.72	1.56	1.35	1.17	0.93
	M	412	26,600	23,800	3.43	1.98	1.71	1.48	1.17
	H	504	36,900	23,800	4.23	2.41	2.09	1.81	1.45
34'	L	348	17,420	25,270	2.91	1.68	1.45	1.26	1.00
	M	442	28,270	25,270	3.67	2.12	1.84	1.59	1.27
	H	538	39,185	25,270	4.52	2.58	2.24	1.94	1.55
36'	L	367	18,450	26,770	3.07	1.77	1.53	1.33	1.05
	M	466	29,930	26,770	3.88	2.24	1.94	1.68	1.33
	H	569	41,510	26,770	4.78	2.73	2.36	2.05	1.64
38'	L	386	19,470	28,250	3.23	1.86	1.61	1.40	1.11
	M	491	31,590	28,250	4.08	2.35	2.04	1.76	1.40
	H	599	43,800	28,250	5.03	2.87	2.49	2.16	1.72
40'	L	405	20,500	29,750	3.40	1.95	1.69	1.47	1.16
	M	515	33,250	29,750	4.29	2.47	2.14	1.85	1.46
	H	630	46,125	29,750	5.29	3.02	2.61	2.27	1.81
42'	L	429	21,520	31,220	3.59	2.07	1.79	1.55	1.23
	M	545	34,920	31,220	4.53	2.61	2.26	1.96	1.56
	H	664	48,410	31,220	5.58	3.19	2.76	2.39	1.91
44'	L	448	22,550	32,720	3.75	2.16	1.87	1.62	1.28
	M	569	36,580	32,720	4.74	2.73	2.37	2.05	1.62
	H	695	50,735	32,720	5.84	3.33	2.89	2.50	2.00
46'	L	467	23,570	34,200	3.91	2.25	1.95	1.69	1.34
	M	594	38,240	34,200	4.94	2.84	2.47	2.14	1.69
	H	725	53,025	34,200	6.08	3.47	3.01	2.61	2.08
48'	L	486	24,600	35,700	4.08	2.34	2.03	1.76	1.39
	M	618	39,900	35,700	5.15	2.96	2.57	2.22	1.75
	H	756	55,350	35,700	6.35	3.62	3.14	2.72	2.17
50'	L	510	25,620	37,170	4.27	2.46	2.13	1.84	1.46
	M	648	41,570	37,170	5.39	3.10	2.69	2.33	1.85
	H	790	57,635	37,170	6.63	3.79	3.28	2.84	2.27
52'	L	529	26,650	38,670	4.43	2.55	2.21	1.91	1.51
	M	672	43,230	38,670	5.60	3.22	2.79	2.42	1.91
	H	821	59,960	38,670	6.89	3.94	3.41	2.95	2.36

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		Medium Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downtight	Uplight	120V	208V	240V	277V	347V
			80 CRI	80 CRI					
54'	L	548	27,670	40,150	4.59	2.64	2.29	1.98	1.57
	M	697	44,890	40,150	5.80	3.34	2.89	2.51	1.98
	H	851	62,250	40,150	7.14	4.08	3.53	3.06	2.44
56'	L	567	28,700	41,650	4.75	2.73	2.37	2.05	1.63
	M	721	46,550	41,650	6.00	3.46	3.00	2.60	2.05
	H	882	64,575	41,650	7.40	4.22	3.66	3.17	2.54
58'	L	591	29,720	43,120	4.95	2.85	2.47	2.14	1.69
	M	751	48,220	43,120	6.25	3.60	3.12	2.70	2.14
	H	916	66,860	43,120	7.69	4.39	3.81	3.30	2.63
60'	L	610	30,750	44,620	5.11	2.94	2.55	2.21	1.75
	M	775	49,880	44,620	6.45	3.72	3.22	2.79	2.21
	H	947	69,185	44,620	7.95	4.54	3.93	3.41	2.73
62'	L	629	31,770	46,100	5.27	3.03	2.63	2.28	1.81
	M	800	51,540	46,100	6.65	3.83	3.32	2.88	2.28
	H	977	71,475	46,100	8.20	4.68	4.06	3.51	2.81
64'	L	648	32,800	47,600	5.43	3.12	2.71	2.35	1.86
	M	824	53,200	47,600	6.86	3.95	3.42	2.97	2.34
	H	1008	73,800	47,600	8.46	4.83	4.18	3.62	2.90
66'	L	672	33,820	49,070	5.63	3.24	2.81	2.43	1.93
	M	854	54,870	49,070	7.10	4.09	3.55	3.07	2.44
	H	1042	76,085	49,070	8.75	5.00	4.33	3.75	3.00
68'	L	691	34,850	50,570	5.79	3.33	2.89	2.50	1.98
	M	878	56,530	50,570	7.31	4.21	3.65	3.16	2.50
	H	1073	78,410	50,570	9.01	5.14	4.46	3.86	3.09
70'	L	710	35,870	52,050	5.95	3.42	2.96	2.57	2.04
	M	903	58,190	52,050	7.51	4.33	3.75	3.25	2.57
	H	1103	80,700	52,050	9.26	5.28	4.58	3.97	3.17
72'	L	729	36,900	53,550	6.11	3.51	3.05	2.64	2.09
	M	927	59,850	53,550	7.72	4.44	3.85	3.34	2.63
	H	1134	83,025	53,550	9.52	5.43	4.71	4.08	3.26

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		High Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downtight	Uplight	120V	208V	240V	277V	347V
			80 CRI	80 CRI					
2'	L	29	1,020	2,050	0.24	0.14	0.12	0.11	0.08
	M	34	1,660	2,050	0.29	0.17	0.14	0.12	0.10
	H	40	2,300	2,050	0.34	0.19	0.17	0.14	0.11
4'	L	53	2,050	4,100	0.44	0.25	0.22	0.19	0.15
	M	64	3,330	4,100	0.53	0.31	0.27	0.23	0.19
	H	75	4,610	4,100	0.63	0.36	0.31	0.27	0.22
6'	L	77	3,070	6,150	0.64	0.37	0.32	0.28	0.22
	M	94	4,990	6,150	0.78	0.45	0.39	0.34	0.27
	H	110	6,900	6,150	0.93	0.53	0.46	0.40	0.31
8'	L	101	4,100	8,200	0.85	0.49	0.42	0.37	0.29
	M	123	6,650	8,200	1.03	0.59	0.51	0.44	0.35
	H	146	9,225	8,200	1.23	0.70	0.61	0.53	0.42
10'	L	127	5,125	10,250	1.06	0.61	0.53	0.46	0.37
	M	153	8,325	10,250	1.29	0.74	0.64	0.55	0.44
	H	185	11,525	10,250	1.55	0.89	0.77	0.67	0.53
12'	L	153	6,150	12,300	1.28	0.74	0.64	0.55	0.44
	M	188	9,975	12,300	1.56	0.90	0.78	0.68	0.54
	H	222	13,825	12,300	1.86	1.07	0.92	0.80	0.63
14'	L	178	7,170	14,350	1.49	0.86	0.75	0.65	0.51
	M	217	11,640	14,350	1.81	1.04	0.90	0.78	0.62
	H	256	16,125	14,350	2.15	1.23	1.07	0.92	0.73
16'	L	202	8,200	16,400	1.70	0.98	0.85	0.73	0.58
	M	246	13,300	16,400	2.05	1.18	1.02	0.89	0.70
	H	292	18,450	16,400	2.45	1.40	1.21	1.05	0.84
18'	L	231	9,220	18,450	1.93	1.11	0.97	0.84	0.66
	M	281	14,970	18,450	2.34	1.35	1.17	1.01	0.81
	H	331	20,735	18,450	2.78	1.59	1.38	1.20	0.95
20'	L	255	10,250	20,500	2.14	1.23	1.07	0.92	0.73
	M	310	16,630	20,500	2.58	1.49	1.29	1.12	0.89
	H	367	23,060	20,500	3.08	1.76	1.53	1.32	1.06
22'	L	279	11,270	22,550	2.34	1.35	1.17	1.01	0.81
	M	340	18,290	22,550	2.83	1.63	1.41	1.23	0.98
	H	402	25,350	22,550	3.38	1.93	1.67	1.45	1.16
24'	L	303	12,300	24,600	2.54	1.46	1.27	1.10	0.87
	M	369	19,950	24,600	3.08	1.77	1.54	1.33	1.05
	H	438	27,675	24,600	3.68	2.10	1.82	1.58	1.26
26'	L	332	13,320	26,650	2.78	1.60	1.39	1.20	0.95
	M	404	21,620	26,650	3.36	1.94	1.68	1.46	1.16
	H	477	29,960	26,650	4.01	2.29	1.99	1.72	1.37

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		High Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downtight	Uplight	120V	208V	240V	277V	347V
			80 CRI	80 CRI					
28'	L	356	14,350	28,700	2.98	1.72	1.49	1.29	1.02
	M	433	23,280	28,700	3.61	2.08	1.80	1.56	1.24
	H	513	32,285	28,700	4.31	2.46	2.14	1.85	1.48
30'	L	380	15,370	30,750	3.19	1.83	1.59	1.38	1.10
	M	463	24,940	30,750	3.86	2.22	1.93	1.67	1.33
	H	548	34,575	30,750	4.60	2.63	2.28	1.98	1.58
32'	L	404	16,400	32,800	3.39	1.95	1.69	1.46	1.16
	M	492	26,600	32,800	4.10	2.36	2.05	1.77	1.40
	H	584	36,900	32,800	4.90	2.80	2.43	2.10	1.68
34'	L	433	17,420	34,850	3.63	2.09	1.81	1.57	1.24
	M	527	28,270	34,850	4.39	2.53	2.19	1.90	1.51
	H	623	39,185	34,850	5.23	3.00	2.60	2.25	1.79
36'	L	457	18,450	36,900	3.83	2.20	1.91	1.66	1.31
	M	556	29,930	36,900	4.64	2.67	2.32	2.01	1.59
	H	659	41,510	36,900	5.54	3.16	2.74	2.38	1.90
38'	L	481	19,470	38,950	4.03	2.32	2.01	1.74	1.39
	M	586	31,590	38,950	4.88	2.81	2.44	2.11	1.68
	H	694	43,800	38,950	5.83	3.33	2.89	2.50	2.00
40'	L	505	20,500	41,000	4.24	2.44	2.11	1.83	1.45
	M	615	33,250	41,000	5.13	2.95	2.56	2.22	1.75
	H	730	46,125	41,000	6.13	3.50	3.04	2.63	2.10
42'	L	534	21,520	43,050	4.47	2.58	2.23	1.93	1.53
	M	650	34,920	43,050	5.42	3.12	2.71	2.34	1.86
	H	769	48,410	43,050	6.46	3.70	3.20	2.78	2.21
44'	L	558	22,550	45,100	4.68	2.69	2.33	2.02	1.60
	M	679	36,580	45,100	5.66	3.26	2.83	2.45	1.94
	H	805	50,735	45,100	6.76	3.86	3.35	2.90	2.32
46'	L	582	23,570	47,150	4.88	2.81	2.44	2.11	1.68
	M	709	38,240	47,150	5.91	3.40	2.95	2.56	2.03
	H	840	53,025	47,150	7.05	4.03	3.50	3.03	2.42
48'	L	606	24,600	49,200	5.09	2.93	2.54	2.20	1.74
	M	738	39,900	49,200	6.16	3.55	3.07	2.66	2.10
	H	876	55,350	49,200	7.36	4.20	3.64	3.16	2.52
50'	L	635	25,620	51,250	5.32	3.06	2.66	2.30	1.83
	M	773	41,570	51,250	6.44	3.71	3.22	2.79	2.22
	H	915	57,635	51,250	7.69	4.40	3.81	3.30	2.64
52'	L	659	26,650	53,300	5.53	3.18	2.76	2.39	1.89
	M	802	43,230	53,300	6.69	3.85	3.34	2.89	2.29
	H	951	59,960	53,300	7.99	4.57	3.96	3.43	2.74

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

# Styllus Linear® LED Wall Direct/Indirect Architectural Grade Luminaire

Delivered Lumens & Electrical Data*									
Length	Direct Lumen Package	Indirect Lumen Package							
		High Lumen Package							
		System Watts	Initial Delivered Lumens**		Total Current (A)				
		120-347V	Downlight 80 CRI	Uplight 80 CRI	120V	208V	240V	277V	347V
54'	L	683	27,670	55,350	5.73	3.30	2.86	2.48	1.97
	M	832	44,890	55,350	6.94	4.00	3.46	3.00	2.38
	H	986	62,250	55,350	8.28	4.73	4.10	3.55	2.84
56'	L	707	28,700	57,400	5.93	3.41	2.96	2.56	2.03
	M	861	46,550	57,400	7.18	4.14	3.58	3.11	2.45
	H	1022	64,575	57,400	8.58	4.90	4.25	3.68	2.94
58'	L	736	29,720	59,450	6.17	3.55	3.08	2.67	2.12
	M	896	48,220	59,450	7.47	4.30	3.73	3.23	2.57
	H	1061	66,860	59,450	8.91	5.10	4.42	3.83	3.06
60'	L	760	30,750	61,500	6.37	3.67	3.18	2.75	2.18
	M	925	49,880	61,500	7.71	4.44	3.85	3.34	2.64
	H	1097	69,185	61,500	9.21	5.27	4.56	3.95	3.16
62'	L	784	31,770	63,550	6.58	3.78	3.28	2.84	2.26
	M	955	51,540	63,550	7.96	4.59	3.97	3.44	2.73
	H	1132	71,475	63,550	9.51	5.43	4.71	4.08	3.26
64'	L	808	32,800	65,600	6.78	3.90	3.38	2.93	2.32
	M	984	53,200	65,600	8.21	4.73	4.10	3.55	2.80
	H	1168	73,800	65,600	9.81	5.60	4.86	4.21	3.36
66'	L	837	33,820	67,650	7.02	4.04	3.50	3.03	2.41
	M	1019	54,870	67,650	8.49	4.89	4.24	3.68	2.92
	H	1207	76,085	67,650	10.14	5.80	5.02	4.35	3.48
68'	L	861	34,850	69,700	7.22	4.15	3.60	3.12	2.47
	M	1048	56,530	69,700	8.74	5.04	4.36	3.78	2.99
	H	1243	78,410	69,700	10.44	5.97	5.17	4.48	3.58
70'	L	885	35,870	71,750	7.42	4.27	3.70	3.21	2.55
	M	1078	58,190	71,750	8.99	5.18	4.49	3.89	3.08
	H	1278	80,700	71,750	10.73	6.14	5.32	4.61	3.68
72'	L	909	36,900	73,800	7.63	4.39	3.80	3.29	2.61
	M	1107	59,850	73,800	9.23	5.32	4.61	3.99	3.15
	H	1314	83,025	73,800	11.03	6.30	5.46	4.73	3.78

\* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347V +/- 10%.

\*\* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens.

© 2025 Cree Lighting USA LLC. All rights reserved. For informational purposes only. Content is subject to change. Patent [www.creelighting.com/patents](http://www.creelighting.com/patents). SmartCast®, Styllus Linear®, and the Styllus linear logo are registered trademarks, and OneButton™ is a trademark of Cree Lighting USA LLC. Cree Lighting® and the Cree Lighting logo are registered trademarks of CLNA Holdings LLC. The UL logo is a registered trademark of UL LLC. Lutron, the Lutron logo, EcoSystem, the Lutron EcoSystem Enabled logo and Vive are trademarks or registered trademarks of Lutron Electronics Co., Inc. The DLC QPL, DLC QPL Premium and the DLC LUNA Logos are the registered and unregistered trademarks of Efficiency Forward, Inc.

Website: [creelighting.com](http://creelighting.com)

US: (800) 236-6800 Canada: (800) 473-1234

