

CPU-Scheduling

The Illusion of Multitasking

Mark Krutzler

Kantonschule Im Lee — 2024/25

Contents

I	Forewords?	2
	Introduction	3
	Metrics	4
II	The ABCs of CPU Scheduling	5
1	Basic Algorithms	7
1.1	First In, First Out (FIFO)	7
1.2	Shortest Job First (SJF)	8
1.3	Shortest Time-to-Completion First(STCF)	8
1.4	Round Robin (RR)	9
III	Advanced Policies	10
2	Multi-Level Feedback Queue	11
3	Lottery and Stride Scheduling	12
IV	Implementations	13
4	My Implementation?	14
5	Solaris Scheduling	15
6	Linux 2.6 Fair Scheduler	16
V	Conclusion	17
	Sources	18

Part I

Forewords?

Introduction

We all use computers. The modern person couldn't do half of the things that is expected from him without an instance of Windows, MacOS or any other Operating System. We surf the web, write emails, documents and have a video call at the same time. The question is: "How does CPU achieve all of this?" The things listed are only the parts of the OS that we come in contact with on a daily basis. What about all the other things hidden under the hood of a graphics environment? If it comes down to doing one thing than it's fine. The problem arises then we have multiple tasks: The CPU can only do one thing at a time and yet we all multitask on our machines. This Black Box effect of taking multiple jobs and working on them in a proper order is what I will dissect in this "Maturarbeit".

The art of scheduling tasks could seem easy for us humans. We ?instinctively? estimate the many aspects of the task:

- Job: Convince our boss to give us a pay rise
Priority: High
Time Required: Medium (With a lot of Waiting Time)
Effort: High (Said "No Way" last week)
- Job: Walk the Dog
Priority: High
Time Required: Low
Effort: Low
- Job: Go to the Hairdresser
Priority: Low (Went last week as well)
Time Required: High
Effort: Low

These prediction are often highly complex and are based on previous experiences. We also include factors like: When was the last time I did it? In addition to all that every human plans differently based on what's important to him/her. Still from just the priority, time required and effort, we would roughly know how to order these things. For example I would walk the dog first, because it is a "request" made by someone else and therefore the response time should be as low as possible. The Hairdresser can fade into the background, due to its low priority. Maybe making an appointment is a good idea though.

A computer does nothing like that. How could it? What he sees is:

- Job: Process 1
Priority: Needs to be Set
Time Required: ??? (Waiting Time: ???)
Effort: ???

What he knows is when the task arrived and how much time he worked on it. With this in mind the let's get to a quick introduction of the metrics, so that we know how to rate the policies that we'll look at.

Metrics

MAYBE JUST LEAVING THIS OUT AND LOOKING AT THIS DURING A LATER TIME (WHEN THE METRICS ARE MENTIONNED OR LINK AS A FOOTNOTE?) ALSO THIS FOLLOWS THE OSTEP WAY TOO MUCH: We can measure different aspects of a Scheduler Policy. There is however a differentiation between fairness and performance. It is often a tradeoff between the two. For example the concept of everybody getting a same sized piece of cake is fair. However, it would be faster to give more to the fast eaters than to those who like to talk during eating. In this scenario we can't have both fairness and performance. In reality it is really difficult to predict, who'll eat faster.

Definition 0.1: Turnaround Time

The turnaround time is a performance metric. It measures how long a task took to be completed from the time it arrived. It is calculated as follows:

$$T_{Turnaround} = T_{Completion} - T_{Arrival}$$

We'll often look at the Average Turnaround time for a predetermined set of jobs. This helps us to quantify how "efficient" a single task is handled. In the best case scenario a single jobs turnaround time is equivalent to the runtime of that job. Another really important thing for us is Response Time. We want to move our mouse around. If we type we want the letter to appear in an instant and the Microsoft suite should start without much delay. Of course the startup time of a program depends on many other factors, however if we never even start to work on it, it'll take a good while.

Definition 0.2: Response Time

The response time is a performance metric. It measures the responsiveness of our computer. How much time does it take until the job is run? It is calculated as follows:

$$T_{Response} = T_{First_Run} - T_{Arrival}$$

Part II

The ABCs of CPU Scheduling

MAYBE HERE THE METRICS PART?

Chapter 1

Basic Algorithms

This chapter mainly focuses on simple policies that can be used to order processes. Usually there are multiple simplifications added to the scenario so that it makes sense. The policies are generally either an abstraction for though experiments or a part of a larger system. Therefore there will be an absense of answers to common questions like: "How do we know how long a process takes until completion?" (Actually we actually never really know how long something will take)

1.1 First In, First Out (FIFO)

Probably the most basic of them all. The "First In, First Our" is just as the name suggests it. Usually we humans know it as first come, first served. This policies runs into problems really quickly if the discard the possibility of all tasks requiring the same amount of run time. A so called "Convoy Effect" takes place. Just imagen how annoying it is, when you're at a store and a family of five cuts into the line in front of you. They have two full carts loaded. You have to wait until they finish. In addition to that they also send back their kid to get an extra bottle of ketchup. Wouldn't it be overall much faster if they let you in front, before the cashier starts scanning the items?

```
1  # Simple implementation of FIFO in Python
2  list = []
3
4  # Adding a new process
5  def add_client(client):
6      list.append(client)
7
8  # Decide which process is next
9  def allocate():
10     next = list.pop(0)
11     use_resource(next) # function that will allow "next" to use the CPU
```

As you can see the implementation is itself pretty easy.

1.2 Shortest Job First (SJF)

Now the situation changes a bit. The infamous family of five wants to go first, however the cashier picks you first after seeing, that you only have a few items. This is the "Shortest Job First" (SJF).

```
1  # Simple implementation of SJF in Python
2
3  # Define client class and list
4  class Client:
5      def __init__(self, ttc): # ttc as time to completion
6          self.ttc = ttc
7          # other stuff that is relevant for the client class
8
9  list = []
10
11 # Adding a new process
12 client = Client(ttc)
13 def add_client(client):
14     list.append(client)
15
16 # Decide which process is next
17 def allocate():
18     list.sort(key=lambda a: a.ttc) # sort according to ttc
19     next = list.pop(0)
20     use_resource(next) # function that will allow "next" to use the CPU
```

There are two notable changes in this code snippet, when compared to FIFO. One of them is relevant. First, the less exiting part is that I actually took my time to write out some of the client class definition. Second and the real difference to FIFO is that we sort the according to the time to completion. This means that we will choose the task with the shortest time to completion. AT THIS PART THE KNOWLEDGE OF PROPER SORTING ALGORITHMS IS MISSING: MAYBE A REVERSE BUBBLE SORT? THE LIST SHOULD BE ALREADY SOMEWHAT ORDERED AND THE LAST MEMBER HAS TO BE SORTED. The only problem is when you arrive late. The scanning of products already started and you'll have to wait. This policy is a so called non-preemptive policy. "Non-preemptive" just means that once a task will run until it finishes.

1.3 Shortest Time-to-Completion First(STCF)

If SJF and FIFO are cousins that STCF is the brother. Here we will make SJF "preemptive", meaning that our cashier can now "save" the state of the previously scanned items. Therefore STCF is also called "Preemptive Shortest Job First (PSJF)". Although the switching costs some time, you'd have to wait anyways until our little boy returns with the ketchup¹ The option of saving a state comes in handy, especially if a program has to wait for I/O. Preemptiveness also makes the computer much more response, because now you can really do certain things "at the same time". The best part is that we don't even have to change much of the previous code.

¹If you don't know what I am talking about read Chapter 1.1 (FIFO)

```

1  # Simple implementation of STCF in Python
2
3  # definition of client class and list go here
4  current = Client(ttc)
5  current_runtime = 0
6
7  # Adding a new process
8  def add_client(client):
9      list.append(client)
10     allocate()
11
12  # Decide which process is next
13  def allocate():
14      save_state() # saves of the current process
15
16      current.ttc -= current_runtime # first update ttc
17      current_runtime = 0
18
19      list.sort(key=lambda a: a.ttc) # sort according to ttc
20      current = list.pop(0)
21
22  use_resource(current) # function that will allow "next" to use the CPU
                          (also tracks runtime)

```

IDK ABOUT THE CODE; IT IS JUST KINDA HACKED TOGETHER; IT IS DEFINITELY NOT SECURE WHATSOEVER! Whenever a new client "joins", the "allocation" function gets run. In addition to that, whenever the process finishes, or it voluntarily gives up the CPU, the same "allocation" function can be run.

1.4 Round Robin (RR)

Part III

Advanced Policies

Chapter 2

Multi-Level Feedback Queue

Chapter 3

Lottery and Stride Scheduling

Part IV

Implementations

Chapter 4

My Implementation?

Chapter 5

Solaris Scheduling

Chapter 6

Linux 2.6 Fair Scheduler

Part V

Conclusion

Sources

- <https://texblog.org/2015/09/30/fancy-boxes-for-theorem-lemma-and-proof-with-mdframed/>

TODOS: - PROPERLY LABEL IMAGES AND CODE BLOCKS