Design of the frontend for LEN5, a RISC-V Out-of-Order processor

Candidate:
Marco Andorno

Supervisor:
prof. Maurizio Martina

POLITECNICO
DI TORINO

Master's thesis in Electronic Engineering

Academic year 2018-2019

LEN5 overview

RISC-V

- **Open source** ISA, which allows for open source hardware.

RISC-V

- **Open source** ISA, which allows for open source hardware.
- **Modular** ISA, that provides extensions to tailor the architecture to the design needs.

Speculative out-of-order core

Used in every modern high-performance processor, because it allows the best **exploitation of ILP**.

Speculative out-of-order core

Used in every modern high-performance processor, because it allows the best **exploitation of ILP**.

Based on three pillars:

1. Dynamic pipeline scheduling

Speculative out-of-order core

Used in every modern high-performance processor, because it allows the best **exploitation of ILP**.

Based on three pillars:

1. Dynamic pipeline scheduling
2. Branch prediction

Speculative out-of-order core

Used in every modern high-performance processor, because it allows the best **exploitation of ILP**.

Based on three pillars:

1. Dynamic pipeline scheduling
2. Branch prediction
3. Speculative execution

Speculative out-of-order core

Used in every modern high-performance processor, because it allows the best **exploitation of ILP**.

Based on three pillars:

1. Dynamic pipeline scheduling
2. Branch prediction
3. Speculative execution

LEN5 uses **Tomasulo's algorithm**, with its distributed control approach.

Frontend design

Frontend overview



PC gen stage


res_i.pc
1
0
4
+
res_i.mispredict
res_i.valid
except_i
res_i.taken
pred_i.taken
fetch_ready_i
enable
pred_i.target
res_i.target
except_pc_i
pc_priority_enc
pc_reg
pc_o

Instruction Fetch Unit (IFU)



Branch management

Branch Prediction Unit (BPU)



Gshare branch predictor



Branch Target Buffer (BTB)



Branch unit


rs1_i
rs2_i
imm_i
<<
pred_i.pc
>=<
+
type_i
pred_i.taken
pred_i.target
!=
!=
ops_valid_i
branch_unit_cu
pred_i.pc
enable
out_reg
ops_ready_o
res_o.mispredict
res_o.taken
res_o.valid
res_o.pc
res_o.target

BPU update actions

Prediction	Resolution	Target	Action
Taken	Taken	✔	Increment 2-bit counter
		✖	Increment 2-bit counter Update BTB entry Flush, go to right target
	Not taken	–	Decrement 2-bit counter Remove BTB entry Flush, go to branch PC+4
Not taken	Not taken	–	Decrement 2-bit counter
	Taken	–	Increment 2-bit counter Add BTB entry Flush, go to right target

Results

Gshare accuracy vs. History bits



Misprediction penalty vs. BTB size



Synthesis area results

Total cell area grows **exponentially** with the length of the **global history** and of the **BTB index** (z axis in log scale).



Synthesis frequency results



- Frequency depends only on the size of the BTB
- The BTB address **decoding network is the critical path** of the whole design

Wrap-up

Concluding remarks

Frontend design:

- Address generation

Concluding remarks

Frontend design:

- Address generation
- Instruction fetch unit

Concluding remarks

Frontend design:

- Address generation
- Instruction fetch unit
- Branch prediction unit

Concluding remarks

Frontend design:

- Address generation
- Instruction fetch unit
- Branch prediction unit

Insightful **exploratory work**, with several applications:

Concluding remarks

Frontend design:

- Address generation
- Instruction fetch unit
- Branch prediction unit

Insightful **exploratory work**, with several applications:

- Teaching and research

Concluding remarks

Frontend design:

- Address generation
- Instruction fetch unit
- Branch prediction unit

Insightful **exploratory work**, with several applications:

- Teaching and research
- High-performance computing

Future work

Possible improvements:

- More advanced branch prediction

Future work

Possible improvements:

- More advanced branch prediction
- SRAM data structures

Future work

Possible improvements:

- More advanced branch prediction
- SRAM data structures
- ISA extensions

Thank you for your attention!