

# Debugging of GDB debugger

## Goal

Compile debug version of GDB (`-g` option) and use system `gdb` to debug compiled one. In case system `gdb` isn't present, either compile release version (without `-g` option) of `gdb` or simply install it from software center. Debug version should run *test* program whose source code is:

```
#include <stdio.h>

int main()
{
    int a = 5;
    int *pa = &a;
    printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);

    return 0;
}
```

Compile *test* using:

```
gcc -g test.c -o test
```

## Compilation of GDB

Let's suppose you want to build `gdb` in `$HOME/builds` folder.

```
cd "$HOME"
# The following two lines should be uncommented just in case you haven't already downloaded gdb repo
git clone 'git://sourceware.org/git/binutils-gdb.git'
cp -r binutils-gdb binutils-gdb-backup
cd binutils-gdb
mkdir build && cd build
../configure --enable-tui --enable-source-highlight --with-python=python3 --prefix="$HOME/builds"
make -j$(nproc) >build.log
echo $?
```

If build succeeds, 0 should be printed as the last line in terminal. If it fails, you should find error in *build.log* file, which can be identified using:

```
grep -C4 -i 'error' build.log
```

The most common error is missing dependencies in system. After you install them, retry build process:

```
cd $HOME
rm -rf binutils-gdb
cp -r binutils-gdb-backup binutils-gdb
cd binutils-gdb
mkdir build && cd build
../configure --enable-tui --enable-source-highlight --with-python=python3 --prefix="$HOME/builds"
make -j$(nproc) >build.log
echo $?
```

Repeat above procedure until you get 0 exit status. After you succeed, in *build/gdb* will be present *gdb* executable. Now, before you install it inside aforementioned *\$HOME/builds* directory, check whether you got *debug* or *release* version of *gdb*.

## Debug / Release

Difference between *debug* and *release* version of executable is that *debug* version retains useful information for debugger, but *release* executable is optimized by compiler and much of these information is stripped. That being said, if you want to debug your program by some debugger, you should always compile it as *debug* version. To find out if executable is *debug* or *release* version, you may use one of the following commands:

```
file <executable file> | grep 'with .debug_info'
echo $?
```

```
objdump -Wi <executable file> | grep '.debug_info' -m 1
echo $?
```

Output is 0 if it's *debug* version, and some other number if it's *release*. In case you compiled *release* version, you should include *-g* option in *Makefile* or *configure* script and repeat build process. For more info, call *./configure --help* or consult official [gdb documentation](#).

## Install GDB

After build process completes, *gdb* can be installed:

```
cd "$HOME/binutils-gdb/build" # set current working dir to build folder
make install                  # install compiled gdb to specified --prefix folder
```

Note that we didn't use *sudomakeinstall* because we don't need admin privileges to access subdirs of *\$HOME* folder. Another two reasons to use *--prefix* option are to prevent conflict with system *gdb* in folders like */usr/bin*, */usr/local/bin*, */bin...* and conflicts with other users on the same computer.

## Running GDB by another GDB instance

Let */usr/bin/gdb* be path to system *gdb* - we will call it *gdb-release*. Let *\$HOME/builds/gdb/bin/gdb* be path to just built *gdb* - we will call it *gdb-debug*. On my system, version of *gdb-release* is 9.2 and version of *gdb-debug* is 13.0.50. Let's open *gdb-debug* using *gdb-release*:

```
/usr/bin/gdb $HOME/builds/gdb/bin/gdb
```

By using *show version* we can find out whether we are in *gdb-release* or *gdb-debug* debugger:

```
(gdb) show version
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2
Copyright (C) 2020 Free Software Foundation...
```

which means we are in *gdb-release*. Put breakpoint on function *value\_as\_address(struct value \*value)* which can be found in source code of *gdb-debug*.

```
(gdb) b value_as_address
Breakpoint 1 at 0x5646c0: file ../../gdb/value.c, line 2757
```

Make sure we are still in *gdb-release* debugger:

```
(gdb) show version
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2 ...
```

Load symbols from *test* executable:

```
(gdb) run ~/gdb-test/test # Load symbols from 'test' executable
Starting program: /home/syrmia/bin/gdb/bin/gdb ~/gdb-test/test
[Thread debugging using libthread_db enabled]
[Detaching after vfork from child process 6043]
[New Thread 0x7ffff49fd700 (LWP 6044)] ...
GNU gdb (GDB) 13.0.50.20220815-git
```

Note that *gdb 13.0.50* i.e. *gdb-debug* took control of the terminal. That's because *run* command 'starts debugged program'. Here, since *gdb-release* opened *gdb-debug*, *gdb-debug* is *debugged program*. When we say *run [args]*, *gdb-debug* is being run. Let's find out where are breakpoints placed:

```
(gdb) info b
No breakpoints or watchpoints.
```

We don't see any breakpoints because *gdb-release* is aware of breakpoints set on *gdb-debug* (on function *value\_as\_address*) and *gdb-debug* is aware of breakpoints set on *test* (no breakpoints yet). Let us see *test* source code:

```
(gdb) list
1  #include <stdio.h>
2
3  int main()
4  {
5      int a = 5;
6      int *pa = &a;
7      printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
8
9      return 0;
10 }
```

and let's put one breakpoint on the very start of our main function and run the *test*:

```
(gdb) b 3
Breakpoint 1 at 0x1175: file test.c, line 4
(gdb) run
Starting program: /home/syrmia/gdb-test/test
[Detaching after vfork from child process 15624]
[Detaching after fork from child process 15625]
...
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x55555622e3b0) at ../../gdb/value.c:2757
(gdb) show version
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2 ...
```

This means we are now in *gdb-release* on line *value\_as\_address* which is set on *gdb-debug* executable. Before *test* arrived to its breakpoint, *value\_as\_address* has been called. Let's inspect stack trace of *gdb-debug* process:

```
(gdb) bt
#0  value_as_address (val=0x55555622e3b0) at ../../gdb/value.c:2757
#1  0x00005555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
#2  0x00005555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
#3  0x000055555556f4865 in bpstat_stop_status (aspace=<optimized out>,
    bp_addr=bp_addr@entry=140737353955253, thread=thread@entry=0x555556174570, ws=...,
    stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:5558
#4  0x000055555587faac in handle_signal_stop (ecs=0x7fffffffdd30) at ../../gdb/regcache.h:344
#5  0x000055555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#6  0x00005555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#7  0x00005555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc:569
#8  0x00005555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#9  gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#10 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
```

```
#11 captured_command_loop () at ../../gdb/main.c:471
#12 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#13 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#14 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
```

What we knew until now is that content of pointer is address. But, do we need to perform some operations (e.g. shift) on these bytes in order to get usable address for specific architecture? Answer is **yes**, as can be read in 'Pointers Are Not Always Addresses' chapter of [this](#) document. That is purpose of *value\_as\_address* function. Continuing program execution:

```
(gdb) continue
Continuing.
```

```
Breakpoint 1, main () at test.c:4
4      {
```

Only now *test*'s breakpoint is being hit. If we continue one more time, *test* program will regularly finish it's execution. Also, we see that *gdb-debug* instance stays active:

```
(gdb) c
Continuing.
'a' is at address '0x7fffffffdf3c'.
'a' has value '5'
[Inferior 1 (process 16797) exited normally]
(gdb) show version
GNU gdb (GDB) 13.0.50.20220815-git
```

We found out that even if we don't access any pointer explicitly in *test* code, *value\_as\_address* is being called. The same function is invoked when we want to *print* some variable from interactive debugger, as the following example describes:

```
# Run gdb-debug using gdb-release
(bash) /usr/bin/gdb $HOME/builds/gdb/bin/gdb

# Make sure we are in gdb-release
(gdb) show version
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2

# Put breakpoint in 'gdb-debug' exe on 'value_as_address' function
(gdb) b value_as_address
Breakpoint 1 at 0x5646c0: file ../../gdb/value.c, line 2757

# Make sure we are still in gdb-release
(gdb) show version
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2 ...

# Load symbols from 'test' executable in 'gdb-debug'
(gdb) run ~/gdb-test/test
Starting program: /home/syrmia/bin/gdb/bin/gdb ~/gdb-vezba/test
[Thread debugging using libthread_db enabled]
[Detaching after vfork from child process 6043]
[New Thread 0x7ffff49fd700 (LWP 6044)] ...
GNU gdb (GDB) 13.0.50.20220815-git

# Display code that is about to be run
(gdb) list
1      #include <stdio.h>
2
3      int main()
4      {
5          int a = 5;
```

```

6             int *pa = &a;
7             printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
8
9             return 0;
10        }

```

*# Put 3 breakpoints in 'test' executable*

```

(gdb) b 3
Breakpoint 1 at 0x1175: file test.c, line 4.
(gdb) b 7
Breakpoint 2 at 0x1193: file test.c, line 7.
(gdb) b 9
Breakpoint 3 at 0x11b1: file test.c, line 9.

```

*# Make sure breakpoints are set*

```

(gdb) info b

```

Num	Type	Disp	Enb	Address	What
1	breakpoint	keep	y	0x0000000000001175	in main at test.c:4
2	breakpoint	keep	y	0x0000000000001193	in main at test.c:7
3	breakpoint	keep	y	0x00000000000011b1	in main at test.c:9

*# Start 'test'*

```

(gdb) run
Starting program: /home/syrmia/gdb-test/test
[Detaching after vfork from child process 17597]
[Detaching after fork from child process 17598]
[Detaching after fork from child process 17599]

```

```

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556225a00) at ../../gdb/value.c:2757
2757      {

```

*# Finish value\_as\_address function and continue execution until next breakpoint*

```

(gdb) c
Continuing.

```

```

Breakpoint 1, main () at test.c:4
4      {

```

*# Continue to next breakpoint*

```

(gdb) c
Continuing.

```

```

Breakpoint 2, main () at test.c:7
7

```

```

printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);

```

*# Recall 'test' source code to see if 'pa' pointer is initialized*

```

(gdb) list -5
1      #include <stdio.h>
2
3      int main()
4      {
5          int a = 5;
6          int *pa = &a;
7          printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
8
9          return 0;
10     }

```

```

# Print pointer 'pa'. Note that 'value_as_address' will be hit 3 times
(gdb) print pa

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556225a00) at ../../gdb/value.c:2757
2757      {
(gdb) c
Continuing.

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556225a00) at ../../gdb/value.c:2757
2757      {
(gdb) c
Continuing.

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x5555561f6c10) at ../../gdb/value.c:2757
2757      {
(gdb) c
Continuing.

# Now 'pa' prints its content which is address of variable a
$1 = (int *) 0x7fffffffdf3c

# Continue 'test' execution
(gdb) c
Continuing.
'a' is at address '0x7fffffffdf3c'.
'a' has value '5'

Breakpoint 3, main () at test.c:9
9          return 0;

# Finish 'test'
(gdb) c
Continuing.
[Inferior 1 (process 17597) exited normally]

```

## Function `value_as_address(struct value *value)`

The following examples examine `value_as_address` function. After each example is some conclusion.

### Example 1

```

(gdb) run
Starting program: /home/syrmia/gdb-test/test
[Detaching after vfork from child process 21164]
[Detaching after fork from child process 21165]
[Detaching after fork from child process 21166]

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556228300) at ../../gdb/value.c:2757
2757      {

# Inspect lval address
(gdb) x 0x555556228300
0x555556228300:      0x00000000

# Proceed until 'value_as_address' returns
(gdb) finish
Run till exit from #0  value_as_address (val=0x555556228300) at ../../gdb/value.c:2757

```

```
0x0000555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
1838         debug_base = value_as_address (val);
Value returned is $1 = 140737354129760
```

*# Inspect return value from 'value\_as\_address' call*

```
(gdb) x $1
```

```
0x7ffff7ffe160 <_r_debug>:      0x00000001    # So return value is address of '_r_debug' function
```

*# Print backtrace*

```
(gdb) bt
```

```
#0 0x0000555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
```

```
#1 0x0000555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
```

```
#2 0x0000555556f4865 in bpstat_stop_status (aspace=<optimized out>, bp_addr=bp_addr@entry=140737354129760,
thread=thread@entry=0x5555561745e0, ws=..., stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:100
```

```
#3 0x00005555587faac in handle_signal_stop (ecs=0x7ffff7ffdd30) at ../../gdb/regcache.h:344
```

```
#4 0x00005555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
```

```
#5 0x0000555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
```

```
#6 0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdb/support/event-loop.cc:569
```

```
#7 0x0000555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdb/support/event-loop.cc:569
```

```
#8 gdb_do_one_event () at ../../gdb/support/event-loop.cc:210
```

```
#9 0x0000555558c8b55 in start_event_loop () at ../../gdb/main.c:411
```

```
#10 captured_command_loop () at ../../gdb/main.c:471
```

```
#11 0x0000555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
```

```
#12 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
```

```
#13 0x00005555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
```

*# Continue execution until next breakpoint*

```
(gdb) c
```

Continuing.

Address of main is 0x55555555169

Breakpoint 1, main () at test.c:8

```
8         printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
```

*# 'a' and 'pa' are initialized. Let's check content of 'a' variable*

*# Note that 'value\_as\_address' will be hit 3 times with the same*

*# Eval parameter 2 times and getting different return value each time*

```
(gdb) print a
```

```
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x55555622d630) at ../../gdb/value.c:2757
2757     {
```

```
(gdb) x 0x55555622d630
```

```
0x55555622d630:      0x00000002
```

```
(gdb) fin
```

Run till exit from #0 value\_as\_address (val=0x55555622d630) at ../../gdb/value.c:2757

```
0x000055555826320 in address_from_register (regnum=<optimized out>, frame=frame@entry=0x55555600eb50)
at ../../gdb/findvar.c:979
```

```
979         result = value_as_address (value);
```

Value returned is \$2 = 140737488346928

```
(gdb) x $2
```

```
0x7ffff7ffdf30:      0x00000000
```

```
(gdb) c
```

Continuing.

Thread 1 "gdb" hit Breakpoint 1, value\_as\_address (val=0x55555622d630) at ../../gdb/value.c:2757

```
2757     {
```

```
(gdb) x 0x55555622d630
```

```
0x55555622d630:      0x00000002
```

```
(gdb) fin
```

```

Run till exit from #0 value_as_address (val=0x55555622d630) at ../../gdb/value.c:2757
0x000055555826320 in address_from_register (regnum=<optimized out>, frame=frame@entry=0x5555564221b
    at ../../gdb/findvar.c:979
979         result = value_as_address (value);
Value returned is $3 = 140737488346944
(gdb) x $3
0x7fffffffdf40:      0x55fa72a8
(gdb) c
Continuing.

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556231570) at ../../gdb/value.c:2757
2757     {
(gdb) x 0x555556231570
0x555556231570:      0x00000000
(gdb) fin
Run till exit from #0 value_as_address (val=0x555556231570) at ../../gdb/value.c:2757
dwarf_expr_context::fetch_result (this=this@entry=0x7fffffffdf860, type=<optimized out>, type@entry=0
    subobj_type=subobj_type@entry=0x5555561ee8c0, subobj_offset=subobj_offset@entry=0, as_lval=<opti
    at ../../gdb/dwarf2/expr.c:1004
1004         retval = value_at_lazy (subobj_type,
Value returned is $4 = 140737488346908
(gdb) x $4
0x7fffffffdf1c:      0x8d900db2
(gdb) c
Continuing.

# Finally, value of 'a' is being shown
$1 = 5

# Recall 'test' source code
(gdb) list
3      int main()
4      {
5          printf("Address of main is %p\n", main);
6          int a = 5;
7          int *pa = &a;
8          printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
9
10         return 0;
11     }

# Print 'pa' pointer
(gdb) print pa
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x55555622d630) at ../../gdb/value.c:2757
2757     {
(gdb) fin
Run till exit from #0 value_as_address (val=0x55555622d630) at ../../gdb/value.c:2757
dwarf_expr_context::fetch_result (this=this@entry=0x7fffffffdf860, type=<optimized out>, type@entry=0
    subobj_type=subobj_type@entry=0x5555561f0880, subobj_offset=subobj_offset@entry=0, as_lval=<opti
    at ../../gdb/dwarf2/expr.c:1004
1004         retval = value_at_lazy (subobj_type,
Value returned is $5 = 140737488346912
(gdb) x $5
0x7fffffffdf20:      0x55c0c290
(gdb) c
Continuing.

# 'pa' pointer

```



```

$2 = (int *) 0x7fffffffdf1c

# Print 'pa' one more time
(gdb) print pa
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x5555562141a0) at ../../gdb/value.c:2757
2757      {
(gdb) fin
Run till exit from #0  value_as_address (val=0x5555562141a0) at ../../gdb/value.c:2757
dwarf_expr_context::fetch_result (this=this@entry=0x7fffffffdf860, type=<optimized out>, type@entry=0
    subobj_type=subobj_type@entry=0x5555561f0880, subobj_offset=subobj_offset@entry=0, as_lval=<opti
    at ../../gdb/dwarf2/expr.c:1004
1004      retval = value_at_lazy (subobj_type,
Value returned is $6 = 140737488346912
(gdb) x $6
0x7fffffffdf20:      0x55c0c290
(gdb) c
Continuing.
$3 = (int *) 0x7fffffffdf1c

# Inspect address on which 'pa' points to
(gdb) x $3
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556215260) at ../../gdb/value.c:2757
2757      {
(gdb) c
Continuing.

# 5, which is exactly value of 'a' while 'pa' points to it
0x7fffffffdf1c:      0x00000005
(gdb) c
Continuing.
'a' is at address '0x7fffffffdf1c'.
'a' has value '5'
[Inferior 1 (process 21164) exited normally]

```

We saw that:

- *value\_as\_address* breakpoint was hit before entering *main* function of *test* program.
- The same breakpoint is hit whenever we *print \$some\_variable*

## Example 2

Run program one more time with focus on *backtrace*:

```

GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2
Reading symbols from /home/syrmia/builds/gdb/bin/gdb...
r(gdb) b value_as_address
Breakpoint 1 at 0x5646c0: file ../../gdb/value.c, line 2757.
(gdb) r gdb-test/test
Starting program: /home/syrmia/builds/gdb/bin/gdb gdb-test/test
GNU gdb (GDB) 13.0.50.20220815-git
Reading symbols from gdb-test/test...
(gdb) list
1      #include <stdio.h>
2
3      int main()
4      {
5          printf("Address of main is %p\n", main);
6          int a = 5;

```

```

7         int *pa = &a;
8         printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
9
10        return 0;

```

*# Put breakpoints on 'main' and 'printf()' lines and then run program*

```

(gdb) b main
Breakpoint 1 at 0x1175: file test.c, line 4.
(gdb) b 8
Breakpoint 2 at 0x11ab: file test.c, line 8.
(gdb) r
Starting program: /home/syrmia/gdb-test/test
[Detaching after vfork from child process 26556]...

```

```

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556228750) at ../../gdb/value.c:2757
2757      {

```

*# We hit 'value\_as\_address' breakpoint before entering main function of 'test'*  
*# Display stack trace before reaching main function of 'test' then continue execution*

```

(gdb) bt
#0  value_as_address (val=0x555556228750) at ../../gdb/value.c:2757
#1  0x00005555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
#2  0x00005555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
#3  0x000055555556f4865 in bpstat_stop_status (aspace=<optimized out>, bp_addr=bp_addr@entry=14073735
thread=thread@entry=0x555556174570, ws=..., stop_chain=stop_chain@entry=0x0) at ../../gdb/breakp
#4  0x0000555555587faac in handle_signal_stop (ecs=0x7fffffffdd40) at ../../gdb/regcache.h:344
#5  0x0000555555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#6  0x000055555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#7  0x00005555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc
#8  0x00005555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#9  gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#10 0x000055555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#11 captured_command_loop () at ../../gdb/main.c:471
#12 0x000055555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#13 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#14 0x0000555555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
(gdb) c
Continuing.

```

```

Breakpoint 1, main () at test.c:4
4      {

```

```

(gdb) c
Continuing.
Address of main is 0x55555555169

```

```

Breakpoint 2, main () at test.c:8

```

```

8         printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);

```

*# 'a' and 'pa' have been initialized.*

```

(gdb) print a

```

```

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556226c50) at ../../gdb/value.c:2757
2757      {

```

```

(gdb) bt
#0  value_as_address (val=0x555556226c50) at ../../gdb/value.c:2757
#1  0x00005555555826320 in address_from_register (regnum=<optimized out>, frame=frame@entry=0x5555560
at ../../gdb/findvar.c:979

```

```

#2 0x0000555557a229f in read_addr_from_reg (frame=frame@entry=0x55555600eb30, reg=<optimized out>)
   at ../../gdb/dwarf2/expr.c:86
#3 0x0000555557ab35e in dwarf2_frame_cache (this_frame=0x55555600eb30, this_cache=<optimized out>)
   at ../../gdb/dwarf2/frame.c:962
#4 0x0000555557ab5d7 in dwarf2_frame_this_id (this_frame=0x55555600eb30, this_cache=<optimized out>,
   this_id=0x55555600eb90) at ../../gdb/dwarf2/frame.c:1117
#5 0x000055555582b6e4 in compute_frame_id (fi=0x55555600eb30) at ../../gdb/frame.c:583
#6 0x000055555582b898 in get_frame_id (fi=fi@entry=0x55555600eb30) at ../../gdb/frame.c:626
#7 0x000055555582c4ff in get_prev_frame_always_1 (this_frame=0x55555600eb30) at ../../gdb/frame.c:231
#8 0x000055555582c8c0 in get_prev_frame_always (this_frame=0x55555600eb30) at ../../gdb/frame.c:231
#9 0x000055555582d04d in get_frame_unwind_stop_reason (frame=frame@entry=0x55555600eb30) at ../../gdb/frame.c:231
#10 0x0000555557a76b5 in dwarf2_frame_cfa (this_frame=0x55555600eb30) at ../../gdb/dwarf2/frame.c:1117
#11 0x0000555557a4b20 in dwarf_expr_context::execute_stack_op (this=0x7fffffffdd870, op_ptr=<optimized out>,
   op_end=0x5555561c8c60 "\003") at ../../gdb/dwarf2/expr.c:2110
#12 0x0000555557a5c98 in dwarf_expr_context::eval (this=0x7fffffffdd870, addr=<optimized out>, len=<optimized out>)
   at ../../gdb/dwarf2/expr.c:1238
#13 0x0000555557a51cd in dwarf_expr_context::execute_stack_op (this=0x7fffffffdd870, op_ptr=0x5555561c8c71 "\021pa")
   at ../../gdb/dwarf2/expr.c:1810
#14 0x0000555557a5c98 in dwarf_expr_context::eval (this=0x7fffffffdd870, addr=<optimized out>, len=<optimized out>)
   at ../../gdb/dwarf2/expr.c:1238
#15 0x0000555557a5f46 in dwarf_expr_context::evaluate (this=this@entry=0x7fffffffdd870,
   addr=addr@entry=0x5555561c8c6f "\221\\\021pa", len=len@entry=2, as_lval=as_lval@entry=true,
   per_cu=per_cu@entry=0x5555561b7230, frame=frame@entry=0x55555600eb30, addr_info=0x0, type=0x5555561b7230,
   subobj_type=0x5555561ee850, subobj_offset=0) at ../../gdb/dwarf2/expr.c:1077
#16 0x0000555557b8716 in dwarf2_evaluate_loc_desc_full (type=0x5555561ee850, frame=0x55555600eb30,
   data=0x5555561c8c6f "\221\\\021pa", size=2, per_cu=0x5555561b7230, per_objfile=<optimized out>,
   subobj_type=0x5555561ee850, subobj_byte_offset=0, as_lval=true) at ../../gdb/dwarf2/loc.c:1519
#17 0x0000555557b8aaa in dwarf2_evaluate_loc_desc (as_lval=true, per_objfile=<optimized out>,
   per_cu=<optimized out>, size=<optimized out>, data=<optimized out>, frame=<optimized out>, type=<optimized out>)
   at ../../gdb/dwarf2/loc.c:1563
--Type <RET> for more, q to quit, c to continue without paging--
#18 locexpr_read_variable (symbol=<optimized out>, frame=<optimized out>) at ../../gdb/dwarf2/loc.c:1563
#19 0x000055555582593f in language_defn::read_var_value (this=<optimized out>, var=0x5555561f0740,
   var_block=0x5555561f08e0, frame=0x55555600eb30) at ../../gdb/symtab.h:1232
#20 0x0000555555806b47 in evaluate_var_value (noside=EVAL_NORMAL, blk=<optimized out>, var=0x5555561f08e0)
   at ../../gdb/eval.c:559
#21 0x0000555555805e92 in expression::evaluate (this=0x55555621d6b0, expect_type=0x0, noside=EVAL_NORMAL)
   at /usr/include/c++/9/bits/unique_ptr.h:360
#22 0x0000555555927fc0 in process_print_command_args (args=<optimized out>, print_opts=0x7fffffffddac,
   voidprint=<optimized out>) at /usr/include/c++/9/bits/unique_ptr.h:360
#23 0x00005555559287eb in print_command_1 (args=<optimized out>, voidprint=1) at ../../gdb/printcmd.c:1232
#24 0x000055555733f45 in cmd_func (cmd=<optimized out>, args=<optimized out>, from_tty=<optimized out>)
   at ../../gdb/cli/cli-decode.c:2516
#25 0x0000555555a3c257 in execute_command (p=<optimized out>, p@entry=0x555555fae210 "print a", from_tty=<optimized out>)
   at ../../gdb/top.c:699
#26 0x000055555580c965 in command_handler (command=0x555555fae210 "print a") at ../../gdb/event-top.c:1232
#27 0x000055555580cd51 in command_line_handler (rl=...) at ../../gdb/event-top.c:842
#28 0x000055555580d4ec in gdb_rl_callback_handler (rl=0x55555621d690 "print a")
   at /usr/include/c++/9/bits/unique_ptr.h:153
#29 0x0000555555ae1e78 in rl_callback_read_char () at ../../gdb/readline/readline/callback.c:290
#30 0x000055555580bd86 in gdb_rl_callback_read_char_wrapper_noexcept () at ../../gdb/event-top.c:188
#31 0x000055555580d3a5 in gdb_rl_callback_read_char_wrapper (client_data=<optimized out>) at ../../gdb/event-top.c:188
#32 0x000055555580bc98 in stdin_event_handler (error=<optimized out>, client_data=0x555555fafa80)
   at ../../gdb/event-top.c:525
#33 0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=1) at ../../gdbsupport/event-loop.cc:569
#34 0x0000555555bc1c3b in gdb_wait_for_event (block=1) at ../../gdbsupport/event-loop.cc:569
#35 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:235
#36 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411

```

```

#37 captured_command_loop () at ../../gdb/main.c:471
#38 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
--Type <RET> for more, q to quit, c to continue without paging--
#39 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#40 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32

(gdb) c
Continuing.

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556226c50) at ../../gdb/value.c:2757
2757      {
(gdb) bt
#0  value_as_address (val=0x555556226c50) at ../../gdb/value.c:2757
#1  0x0000555555826320 in address_from_register (regnum=<optimized out>, frame=frame@entry=0x55555642c0b0,
at ../../gdb/findvar.c:979
#2  0x00005555557a229f in read_addr_from_reg (frame=frame@entry=0x55555642c0b0, reg=<optimized out>)
at ../../gdb/dwarf2/expr.c:86
#3  0x00005555557ab35e in dwarf2_frame_cache (this_frame=0x55555642c0b0, this_cache=<optimized out>)
at ../../gdb/dwarf2/frame.c:962
#4  0x00005555557ab5d7 in dwarf2_frame_this_id (this_frame=0x55555642c0b0, this_cache=<optimized out>,
this_id=0x55555642c110) at ../../gdb/dwarf2/frame.c:1117
#5  0x000055555582b6e4 in compute_frame_id (fi=0x55555642c0b0) at ../../gdb/frame.c:583
#6  0x000055555582bcaf in get_prev_frame_maybe_check_cycle (this_frame=0x55555600eb30) at ../../gdb/
#7  0x000055555582c480 in get_prev_frame_always_1 (this_frame=0x55555600eb30) at ../../gdb/frame.c:231
#8  0x000055555582c8c0 in get_prev_frame_always (this_frame=0x55555600eb30) at ../../gdb/frame.c:231
#9  0x000055555582d04d in get_frame_unwind_stop_reason (frame=frame@entry=0x55555600eb30) at ../../g
#10 0x00005555557a76b5 in dwarf2_frame_cfa (this_frame=0x55555600eb30) at ../../gdb/dwarf2/frame.c:1
#11 0x00005555557a4b20 in dwarf_expr_context::execute_stack_op (this=0x7fffffff870, op_ptr=<optimiz
op_end=0x5555561c8c60 "\003") at ../../gdb/dwarf2/expr.c:2110
#12 0x00005555557a5c98 in dwarf_expr_context::eval (this=0x7fffffff870, addr=<optimized out>, len=<
at ../../gdb/dwarf2/expr.c:1238
#13 0x00005555557a51cd in dwarf_expr_context::execute_stack_op (this=0x7fffffff870, op_ptr=0x555556
op_end=0x5555561c8c71 "\021pa") at ../../gdb/dwarf2/expr.c:1810
#14 0x00005555557a5c98 in dwarf_expr_context::eval (this=0x7fffffff870, addr=<optimized out>, len=<
at ../../gdb/dwarf2/expr.c:1238
#15 0x00005555557a5f46 in dwarf_expr_context::evaluate (this=this@entry=0x7fffffff870,
addr=addr@entry=0x5555561c8c6f "\221\\\021pa", len=len@entry=2, as_lval=as_lval@entry=true,
per_cu=per_cu@entry=0x5555561b7230, frame=frame@entry=0x55555600eb30, addr_info=0x0, type=0x5555
subobj_type=0x5555561ee850, subobj_offset=0) at ../../gdb/dwarf2/expr.c:1077
#16 0x00005555557b8716 in dwarf2_evaluate_loc_desc_full (type=0x5555561ee850, frame=0x55555600eb30,
data=0x5555561c8c6f "\221\\\021pa", size=2, per_cu=0x5555561b7230, per_objfile=<optimized out>,
subobj_type=0x5555561ee850, subobj_byte_offset=0, as_lval=true) at ../../gdb/dwarf2/loc.c:1519
#17 0x00005555557b8aaa in dwarf2_evaluate_loc_desc (as_lval=true, per_objfile=<optimized out>,
--Type <RET> for more, q to quit, c to continue without paging--
per_cu=<optimized out>, size=<optimized out>, data=<optimized out>, frame=<optimized out>, type=
at ../../gdb/dwarf2/loc.c:1563
#18 locexpr_read_variable (symbol=<optimized out>, frame=<optimized out>) at ../../gdb/dwarf2/loc.c:
#19 0x000055555582593f in language_defn::read_var_value (this=<optimized out>, var=0x5555561f0740,
var_block=0x5555561f08e0, frame=0x55555600eb30) at ../../gdb/symtab.h:1232
#20 0x0000555555806b47 in evaluate_var_value (noside=EVAL_NORMAL, blk=<optimized out>, var=0x5555561
at ../../gdb/eval.c:559
#21 0x0000555555805e92 in expression::evaluate (this=0x55555621d6b0, expect_type=0x0, noside=EVAL_NO
at /usr/include/c++/9/bits/unique_ptr.h:360
#22 0x0000555555927fc0 in process_print_command_args (args=<optimized out>, print_opts=0x7fffffff870,
voidprint=<optimized out>) at /usr/include/c++/9/bits/unique_ptr.h:360
#23 0x00005555559287eb in print_command_1 (args=<optimized out>, voidprint=1) at ../../gdb/printcmd.
#24 0x0000555555733f45 in cmd_func (cmd=<optimized out>, args=<optimized out>, from_tty=<optimized o
at ../../gdb/cli/cli-decode.c:2516

```

```

#25 0x0000555555a3c257 in execute_command (p=<optimized out>, p@entry=0x555555fae210 "print a", from
    at ../../gdb/top.c:699
#26 0x000055555580c965 in command_handler (command=0x555555fae210 "print a") at ../../gdb/event-top.
#27 0x000055555580cd51 in command_line_handler (rl=...) at ../../gdb/event-top.c:842
#28 0x000055555580d4ec in gdb_rl_callback_handler (rl=0x55555621d690 "print a")
    at /usr/include/c++/9/bits/unique_ptr.h:153
#29 0x0000555555ae1e78 in rl_callback_read_char () at ../../readline/readline/callback.c:290
#30 0x000055555580bd86 in gdb_rl_callback_read_char_wrapper_noexcept () at ../../gdb/event-top.c:188
#31 0x000055555580d3a5 in gdb_rl_callback_read_char_wrapper (client_data=<optimized out>) at ../../g
#32 0x000055555580bc98 in stdin_event_handler (error=<optimized out>, client_data=0x555555fafa80)
    at ../../gdb/event-top.c:525
#33 0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=1) at ../../gdbsupport/event-loop.cc
#34 0x0000555555bc1c3b in gdb_wait_for_event (block=1) at ../../gdbsupport/event-loop.cc:569
#35 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:235
#36 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#37 captured_command_loop () at ../../gdb/main.c:471
#38 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
--Type <RET> for more, q to quit, c to continue without paging--
#39 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#40 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
(gdb) c
Continuing.

```

```

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556247320) at ../../gdb/value.c:2757
2757      {
(gdb) bt
#0  value_as_address (val=0x555556247320) at ../../gdb/value.c:2757
#1  0x00005555557a2bd2 in dwarf_expr_context::fetch_result (this=this@entry=0x7fffffff870, type=<op
    type@entry=0x5555561ee850, subobj_type=subobj_type@entry=0x5555561ee850, subobj_offset=subobj_of
    as_lval=<optimized out>) at ../../gdb/dwarf2/expr.c:1002
#2  0x00005555557a5f63 in dwarf_expr_context::evaluate (this=this@entry=0x7fffffff870,
    addr=addr@entry=0x5555561c8c6f "\221\\\021pa", len=len@entry=2, as_lval=as_lval@entry=true,
    per_cu=per_cu@entry=0x5555561b7230, frame=frame@entry=0x55555600eb30, addr_info=0x0, type=0x5555
    subobj_type=0x5555561ee850, subobj_offset=0) at ../../gdb/dwarf2/expr.c:1078
#3  0x00005555557b8716 in dwarf2_evaluate_loc_desc_full (type=0x5555561ee850, frame=0x55555600eb30,
    data=0x5555561c8c6f "\221\\\021pa", size=2, per_cu=0x5555561b7230, per_objfile=<optimized out>,
    subobj_type=0x5555561ee850, subobj_byte_offset=0, as_lval=true) at ../../gdb/dwarf2/loc.c:1519
#4  0x00005555557b8aaa in dwarf2_evaluate_loc_desc (as_lval=true, per_objfile=<optimized out>,
    per_cu=<optimized out>, size=<optimized out>, data=<optimized out>, frame=<optimized out>, type=
    at ../../gdb/dwarf2/loc.c:1563
#5  locexpr_read_variable (symbol=<optimized out>, frame=<optimized out>) at ../../gdb/dwarf2/loc.c:
#6  0x000055555582593f in language_defn::read_var_value (this=<optimized out>, var=0x5555561f0740,
    var_block=0x5555561f08e0, frame=0x55555600eb30) at ../../gdb/symtab.h:1232
#7  0x0000555555806b47 in evaluate_var_value (noside=EVAL_NORMAL, blk=<optimized out>, var=0x5555561
    at ../../gdb/eval.c:559
#8  0x0000555555805e92 in expression::evaluate (this=0x55555621d6b0, expect_type=0x0, noside=EVAL_NO
    at /usr/include/c++/9/bits/unique_ptr.h:360
#9  0x0000555555927fc0 in process_print_command_args (args=<optimized out>, print_opts=0x7fffffff870,
    voidprint=<optimized out>) at /usr/include/c++/9/bits/unique_ptr.h:360
#10 0x00005555559287eb in print_command_1 (args=<optimized out>, voidprint=1) at ../../gdb/printcmd.
#11 0x0000555555733f45 in cmd_func (cmd=<optimized out>, args=<optimized out>, from_tty=<optimized o
    at ../../gdb/cli/cli-decode.c:2516
#12 0x0000555555a3c257 in execute_command (p=<optimized out>, p@entry=0x555555fae210 "print a", from
    at ../../gdb/top.c:699
#13 0x000055555580c965 in command_handler (command=0x555555fae210 "print a") at ../../gdb/event-top.
#14 0x000055555580cd51 in command_line_handler (rl=...) at ../../gdb/event-top.c:842
#15 0x000055555580d4ec in gdb_rl_callback_handler (rl=0x55555621d690 "print a")
--Type <RET> for more, q to quit, c to continue without paging--

```



```

    at /usr/include/c++/9/bits/unique_ptr.h:153
#16 0x0000555555ae1e78 in rl_callback_read_char () at ../.././readline/readline/callback.c:290
#17 0x0000555555580bd86 in gdb_rl_callback_read_char_wrapper_noexcept () at ../../gdb/event-top.c:188
#18 0x0000555555580d3a5 in gdb_rl_callback_read_char_wrapper (client_data=<optimized out>) at ../../gdb/event-top.c:188
#19 0x0000555555580bc98 in stdin_event_handler (error=<optimized out>, client_data=0x555555fafa80)
    at ../../gdb/event-top.c:525
#20 0x00005555555b19c6 in gdb_wait_for_event (block=block@entry=1) at ../../gdbsupport/event-loop.cc:569
#21 0x00005555555b1c3b in gdb_wait_for_event (block=1) at ../../gdbsupport/event-loop.cc:569
#22 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:235
#23 0x000055555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#24 captured_command_loop () at ../../gdb/main.c:471
#25 0x000055555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#26 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#27 0x0000555555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
(gdb) c
Continuing.

# Finally, content of 'a'
$1 = 5

# Let's check 'pa'
(gdb) print pa

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556227f80) at ../../gdb/value.c:2757
2757      {
(gdb) bt
#0  value_as_address (val=0x555556227f80) at ../../gdb/value.c:2757
#1  0x00005555557a2bd2 in dwarf_expr_context::fetch_result (this=this@entry=0x7fffffff870, type=<optimized out>,
    type@entry=0x5555561f0810, subobj_type=subobj_type@entry=0x5555561f0810, subobj_offset=subobj_offset@entry=0,
    as_lval=<optimized out>) at ../../gdb/dwarf2/expr.c:1002
#2  0x00005555557a5f63 in dwarf_expr_context::evaluate (this=this@entry=0x7fffffff870, addr=addr@entry=0x5555561c8c7d "\221",
    len=len@entry=2, as_lval=as_lval@entry=true, per_cu=per_cu@entry=0x5555561b7230, frame=frame@entry=0x55555600eb30,
    addr_info=0x0, type=0x5555561f0810, subobj_type=0x5555561f0810, subobj_offset=0) at ../../gdb/dwarf2/expr.c:1078
#3  0x00005555557b8716 in dwarf2_evaluate_loc_desc_full (type=0x5555561f0810, frame=0x55555600eb30, data=0x5555561c8c7d "\221",
    size=2, per_cu=0x5555561b7230, per_objfile=<optimized out>, subobj_type=0x5555561f0810, subobj_byte_offset=0,
    as_lval=true) at ../../gdb/dwarf2/loc.c:1519
#4  0x00005555557b8aaa in dwarf2_evaluate_loc_desc (as_lval=true, per_objfile=<optimized out>, per_cu=<optimized out>,
    size=<optimized out>, data=<optimized out>, frame=<optimized out>, type=<optimized out>) at ../../gdb/dwarf2/loc.c:1563
#5  locexpr_read_variable (symbol=<optimized out>, frame=<optimized out>) at ../../gdb/dwarf2/loc.c:1563
#6  0x0000555555582593f in language_defn::read_var_value (this=<optimized out>, var=0x5555561f07c0, var_block=0x5555561f08e0,
    frame=0x55555600eb30) at ../../gdb/symtab.h:1232
#7  0x00005555555806b47 in evaluate_var_value (noside=EVAL_NORMAL, blk=<optimized out>, var=0x5555561f07c0)
    at ../../gdb/eval.c:559
#8  0x00005555555805e92 in expression::evaluate (this=0x55555622c5c0, expect_type=0x0, noside=EVAL_NORMAL)
    at /usr/include/c++/9/bits/unique_ptr.h:360
#9  0x00005555555927fc0 in process_print_command_args (args=<optimized out>, print_opts=0x7fffffff870, voidprint=<optimized out>)
    at /usr/include/c++/9/bits/unique_ptr.h:360
#10 0x000055555559287eb in print_command_1 (args=<optimized out>, voidprint=1) at ../../gdb/printcmd.c:1232
#11 0x00005555555733f45 in cmd_func (cmd=<optimized out>, args=<optimized out>, from_tty=<optimized out>)
    at ../../gdb/cli/cli-decode.c:2516
#12 0x00005555555a3c257 in execute_command (p=<optimized out>, p@entry=0x555555fae230 "print pa", from_tty=<optimized out>)
    at ../../gdb/top.c:699
#13 0x0000555555580c965 in command_handler (command=0x555555fae230 "print pa") at ../../gdb/event-top.c:842
#14 0x0000555555580cd51 in command_line_handler (rl=...) at ../../gdb/event-top.c:842
#15 0x0000555555580d4ec in gdb_rl_callback_handler (rl=0x55555621d690 "print pa")
--Type <RET> for more, q to quit, c to continue without paging--

```

```

    at /usr/include/c++/9/bits/unique_ptr.h:153
#16 0x0000555555ae1e78 in rl_callback_read_char () at ../../../readline/readline/callback.c:290
#17 0x0000555555580bd86 in gdb_rl_callback_read_char_wrapper_noexcept () at ../../gdb/event-top.c:188
#18 0x0000555555580d3a5 in gdb_rl_callback_read_char_wrapper (client_data=<optimized out>) at ../../g
#19 0x0000555555580bc98 in stdin_event_handler (error=<optimized out>, client_data=0x555555fafa80)
    at ../../gdb/event-top.c:525
#20 0x00005555555bc19c6 in gdb_wait_for_event (block=block@entry=1) at ../../gdbsupport/event-loop.cc
#21 0x00005555555bc1c3b in gdb_wait_for_event (block=1) at ../../gdbsupport/event-loop.cc:569
#22 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:235
#23 0x000055555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#24 captured_command_loop () at ../../gdb/main.c:471
#25 0x000055555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#26 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#27 0x0000555555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
(gdb)
(gdb) c
Continuing.

# 'pa' content
$2 = (int *) 0x7fffffffdf3c
(gdb) c
Continuing.
'a' is at address '0x7fffffffdf3c'.
'a' has value '5'
[Inferior 1 (process 26556) exited normally]

```

Note that:

- Before reaching *value\_as\_address*, a certain set of event handlers are being called (*fetch\_inferior\_event*, *handle\_inferior\_event*, *handle\_solib\_event*, *svr4\_handle\_solib\_event* etc).
- Command *print \$some\_var* causes *dwarf\_\**, *dwarf2\_\** (and eventually *read\_addr\_from\_reg* and *address\_from\_register* if *print* is being called for the first time) function calls.
- First *print \$some\_var* (*print a* in the example) call caused three *value\_as\_address* breakpoint hits. There were *read\_addr\_from\_reg* and *address\_from\_register* stack frames present only in the first two backtraces, but not in the third, when *value* parameter for *value\_as\_address* function changed from *0x5555556226c50* to *0x5555556247320*. Every latter call of *print \$some\_var* command doesn't produce *read\_addr\_from\_reg* and *address\_from\_register* stack frames and doesn't hit *value\_as\_address* breakpoint three but just one time.

## Example 3

In this example, we use *next* command in order to find out which functions are being called after stack frame of *value\_as\_address* spawns:

```

GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2
For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from /home/syrmia/builds/gdb/bin/gdb...

```

```

(gdb) b value_as_address
Breakpoint 1 at 0x5646c0: file ../../gdb/value.c, line 2757.

```

```

(gdb) run gdb-test/test
Starting program: /home/syrmia/builds/gdb/bin/gdb gdb-test/test
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
[Detaching after vfork from child process 8771]
[New Thread 0x7ffff49fc700 (LWP 8772)] ...

```

GNU gdb (GDB) 13.0.50.20220815-git  
Copyright (C) 2022 Free Software Foundation, Inc ...  
Reading symbols from gdb-test/test...

```
(gdb) list
1      #include <stdio.h>
2
3      int main()
4      {
5          printf("Address of main is %p\n", main);
6          int a = 5;
7          int *pa = &a;
8          printf("'a' is at address '%p'.\n'a' has value '%d'\n", pa, *pa);
9
10         return 0;
```

```
(gdb) b main
Breakpoint 1 at 0x1175: file test.c, line 4.
```

```
(gdb) b 8
Breakpoint 2 at 0x11ab: file test.c, line 8.
```

```
(gdb) r
Starting program: /home/syrmia/gdb-test/test
[Detaching after vfork from child process 8782]
[Detaching after fork from child process 8783]
[Detaching after fork from child process 8784]
```

```
Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x555556228770) at ../../gdb/value.c:2757
2757      {
```

```
(gdb) bt
#0  value_as_address (val=0x555556228770) at ../../gdb/value.c:2757
#1  0x00005555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
#2  0x00005555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
#3  0x000055555556f4865 in bpstat_stop_status (aspace=<optimized out>,
      bp_addr=bp_addr@entry=140737353955253, thread=thread@entry=0x555556174590, ws=...,
      stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:5558
#4  0x000055555587faac in handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/regcache.h:344
#5  0x000055555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#6  0x00005555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#7  0x00005555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc:569
#8  0x00005555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#9  gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#10 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#11 captured_command_loop () at ../../gdb/main.c:471
#12 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#13 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#14 0x0000555555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
```

```
(gdb) next
2758      struct gdbarch *gdbarch = value_type (val)->arch ();
(gdb)
1027      return this->main_type->code;
(gdb)
2810      val = coerce_array (val);
(gdb)
2849      if (!value_type (val)->is_pointer_or_reference ()
```



```

(gdb)
2854         return unpack_long (value_type (val), value_contents (val).data ());
(gdb)
1100         return value->type;
(gdb)
unpack_long (type=0x555556372aa0, valaddr=0x555556231820 "\341\377\367\377\177") at ../../gdb/value
2874     {

(gdb) bt
#0  unpack_long (type=0x555556372aa0, valaddr=0x555556231820 "\341\377\367\377\177")
    at ../../gdb/value.c:2874
#1  0x0000555559c7cc6 in svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1838
#2  0x0000555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
#3  0x0000555556f4865 in bpstat_stop_status (aspace=<optimized out>,
    bp_addr=bp_addr@entry=140737353955253, thread=thread@entry=0x555556174590, ws=...,
    stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:5558
#4  0x00005555587faac in handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/regcache.h:344
#5  0x00005555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#6  0x0000555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#7  0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc:
#8  0x0000555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#9  gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#10 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#11 captured_command_loop () at ../../gdb/main.c:471
#12 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#13 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#14 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32

(gdb) next
2875         if (is_fixed_point_type (type))
(gdb)
2878         enum bfd_endian byte_order = type_byte_order (type);
(gdb)
2881         int nosign = type->is_unsigned ();
(gdb)
2883         switch (code)
(gdb)
2897             if (type->bit_size_differs_p ())
(gdb)
2912                 if (nosign)
(gdb)
2913                     result = extract_unsigned_integer (valaddr, len, byte_order);
(gdb)
2917             if (code == TYPE_CODE_RANGE)
(gdb)
svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1839
1839         if (debug_base == 0)

(gdb) bt
#0  svr4_handle_solib_event () at ../../gdb/solib-svr4.c:1839
#1  0x0000555559cd7f0 in handle_solib_event () at ../../gdb/solib.c:1338
#2  0x0000555556f4865 in bpstat_stop_status (aspace=<optimized out>,
    bp_addr=bp_addr@entry=140737353955253, thread=thread@entry=0x555556174590, ws=...,
    stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:5558
#3  0x00005555587faac in handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/regcache.h:344
#4  0x00005555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#5  0x0000555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#6  0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc:

```

```

#7 0x0000555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#8 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#9 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#10 captured_command_loop () at ../../gdb/main.c:471
#11 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#12 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#13 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32

```

```

(gdb) next
1843         info->debug_base = 0;
(gdb)
1844         if (locate_base (info) == 0)
(gdb)
1823             = inhibit_section_map_updates (current_program_space);
(gdb)
1874         if (action == UPDATE_OR_RELOAD)
(gdb)
1823             = inhibit_section_map_updates (current_program_space);
(gdb)
1903         if (action == FULL_RELOAD)
(gdb)
1905             if (!solist_update_full (info))
(gdb)
1695         return 1;
(gdb)
handle_solib_event () at ../../gdb/solib.c:1340
1340         current_inferior ()->pspace->clear_solib_cache ();

```

```

(gdb) bt
#0 handle_solib_event () at ../../gdb/solib.c:1340
#1 0x00005555556f4865 in bpstat_stop_status (aspace=<optimized out>,
    bp_addr=bp_addr@entry=140737353955253, thread=thread@entry=0x555556174590, ws=...,
    stop_chain=stop_chain@entry=0x0) at ../../gdb/breakpoint.c:5558
#2 0x000055555587faac in handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/regcache.h:344
#3 0x000055555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#4 0x00005555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#5 0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc:569
#6 0x0000555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#7 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#8 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#9 captured_command_loop () at ../../gdb/main.c:471
#10 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#11 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#12 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32

```

```

(gdb) next
1345         target_terminal::ours_for_output ();
(gdb)
1346         solib_add (NULL, 0, auto_solib_add);
(gdb)
1347         target_terminal::inferior ();
(gdb)
target_terminal::inferior () at ../../gdb/target.c:940
940     {
(gdb)
941         struct ui *ui = current_ui;
(gdb)
945         if (ui->prompt_state != PROMPT_BLOCKED)

```

```

(gdb)
952         if (ui != main_ui)
(gdb)
958         struct inferior *inf = current_inferior ();
(gdb)
960         if (inf->terminal_state != target_terminal_state::is_inferior)
(gdb)
962             current_inferior ()->top_target ()->terminal_inferior ();
(gdb)
963             inf->terminal_state = target_terminal_state::is_inferior;
(gdb)
966             m_terminal_state = target_terminal_state::is_inferior;
(gdb)
970         if (check_quit_flag ())
(gdb)
bpstat_stop_status (aspace=<optimized out>, bp_addr=bp_addr@entry=140737353955253,
thread=thread@entry=0x555556174590, ws=..., stop_chain=stop_chain@entry=0x0)
at ../../gdb/breakpoint.c:5559
5559             break;
(gdb)
5569         for (bs = bs_head; bs != NULL; bs = bs->next)
(gdb)
5571             if (!bs->stop)
(gdb)
5574                 b = bs->breakpoint_at;
(gdb)
5575                 b->check_status (bs);
(gdb)
5576                 if (bs->stop)
(gdb)
5608                     bs->print_it = print_it_noop;
(gdb)
5569         for (bs = bs_head; bs != NULL; bs = bs->next)
(gdb)
5616         if (! bpstat_causes_stop (bs_head))
(gdb)
5618             if (!bs->stop
(gdb)
5620                 && is_hardware_watchpoint (bs->breakpoint_at))
(gdb)
5617             for (bs = bs_head; bs != NULL; bs = bs->next)
(gdb)
5628                 if (need_remove_insert)
(gdb)
5630                 else if (removed_any)
(gdb)
5633                 return bs_head;
(gdb)
handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/infrun.c:6406
6406         if (ecs->event_thread->stop_signal () == GDB_SIGNAL_TRAP
(gdb)
423         return m_suspend.stop_signal;

(gdb) bt
#0  handle_signal_stop (ecs=0x7fffffffdd20) at ../../gdb/gdbthread.h:423
#1  0x000055555588209c in handle_inferior_event (ecs=<optimized out>) at ../../gdb/infrun.c:5869
#2  0x00005555558831fb in fetch_inferior_event () at ../../gdb/infrun.c:4233
#3  0x0000555555bc19c6 in gdb_wait_for_event (block=block@entry=0) at ../../gdbsupport/event-loop.cc

```

```
#4 0x0000555555bc1c86 in gdb_wait_for_event (block=0) at ../../gdbsupport/event-loop.cc:569
#5 gdb_do_one_event () at ../../gdbsupport/event-loop.cc:210
#6 0x00005555558c8b55 in start_event_loop () at ../../gdb/main.c:411
#7 captured_command_loop () at ../../gdb/main.c:471
#8 0x00005555558ca725 in captured_main (data=<optimized out>) at ../../gdb/main.c:1329
#9 gdb_main (args=<optimized out>) at ../../gdb/main.c:1344
#10 0x000055555565ccd0 in main (argc=<optimized out>, argv=<optimized out>) at ../../gdb/gdb.c:32
```

We saw that *value\_as\_address* calls *unpack\_long* which enters *if(code == TYPE\_CODE\_RANGE)* block and returns. *TYPE\_CODE\_RANGE* is 'integer within specified bounds' as specified in *gdbtypes.h* header file. After *value\_as\_address* i.e. *unpack\_long* finishes, stack frame shrinks (*svr4\_handle\_solib\_event* → *handle\_solib\_event* etc).

## Example 4

We know that *value\_as\_address* gets *value* parameter. But, we also know that the same function is invoked even before reaching *main*. There are certain preparations before *main* function can execute its instructions and by default, entry point for executable is *\_start* function. This example proves that *value* parameter isn't address of *\_start* function.

Source code of executable is saved to *no-main.c* file:

```
#include <stdio.h>
#include <stdlib.h>

int my_fun()
{
    printf("Hello from my_fun!\n");
    return 0;
}

int _start()
{
    printf("Address of _start is %p\n", _start);
    printf("Address of my_fun is %p\n", my_fun);
    int retcode = my_fun();
    exit(retcode);
}
```

and is compiled with:

```
gcc -g -nostartfiles -o no-main no-main.c
```

Here is debugger output:

```
GNU gdb (Ubuntu 9.2-0ubuntu1~20.04.1) 9.2
Reading symbols from /home/syrmia/builds/gdb/bin/gdb...
(gdb) b value_as_address
Breakpoint 1 at 0x5646c0: file ../../gdb/value.c, line 2757.
(gdb) r no-main
Starting program: /home/syrmia/builds/gdb/bin/gdb no-main
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
[Detaching after vfork from child process 13156]
[New Thread 0x7ffff49fc700 (LWP 13157)] ...
GNU gdb (GDB) 13.0.50.20220815-git
Reading symbols from no-main...
(gdb) list 14
9
10     int _start()
```

```

11      {
12          printf("Address of _start is %p\n", _start);
13          printf("Address of my_fun is %p\n", my_fun);
14          int retcode = my_fun();
15          exit(retcode);
16      }
17
(gdb) b _start
Breakpoint 1 at 0x1097: file no-main.c, line 12.
(gdb) r
Starting program: /home/syrmia/gdb-test-no-main/no-main
[Detaching after vfork from child process 13166] ...

Thread 1 "gdb" hit Breakpoint 1, value_as_address (val=0x55555622d1a0) at ../../gdb/value.c:2757
2757      {
(gdb) x 0x55555622d1a0
0x55555622d1a0:      0x00000000
(gdb) c
Continuing.

Breakpoint 1, _start () at no-main.c:12
12          printf("Address of _start is %p\n", _start);
(gdb) c
Continuing.
Address of _start is 0x55555555508b
Address of my_fun is 0x555555555070
Hello from my_fun!
[Inferior 1 (process 13166) exited normally]

```

Since *value\_as\_address* breakpoint was hit even before *no-main* executable started (*\_start* breakpoint), we can conclude that *gdb* performs some preparations before debugged program commences its execution. As we already said, parameter *value* passed to *value\_as\_address* isn't address of *\_start* nor *my\_fun* function.

# DWARF Functions in GDB

## Technical terms

- **Location Description.** Debugging information must provide consumers a way to find the location of program variables, determine the bounds of dynamic arrays and strings, and possibly to find the base address of a subroutine's stack frame or the return address of a subroutine. Furthermore, to meet the needs of recent computer architectures and optimization techniques, debugging information must be able to describe the location of an object whose location changes over the object's lifetime. Information about the location of program objects is provided by location descriptions.
- **CFA (Canonical Frame Address)** is address of caller function's stack frame just before the callee has been called.

## Common data types

- `struct frame_info` is a structure which describes stack frame.
- `struct value` defines the type of a value.
- `gdb_byte` unsigned char.

## Functions

```
/* Fetch the result of the expression evaluation in a form of
   a struct value, where TYPE, SUBOBJ_TYPE and SUBOBJ_OFFSET
   describe the source level representation of that result.
   AS_LVAL defines if the fetched struct value is expected to
   be a value or a location description. */
value *fetch_result (struct type *type, struct type *subobj_type,
                    LONGEST subobj_offset, bool as_lval);

/* The exported interface to dwarf2_evaluate_loc_desc_full; it always
   passes 0 as the byte_offset. */

struct value *
dwarf2_evaluate_loc_desc (struct type *type, struct frame_info *frame,
                        const gdb_byte *data, size_t size,
                        dwarf2_per_cu_data *per_cu,
                        dwarf2_per_objfile *per_objfile, bool as_lval)

/* Evaluate a location description, starting at DATA and with length
   SIZE, to find the current location of variable of TYPE in the
   context of FRAME. If SUBOBJ_TYPE is non-NULL, return instead the
   location of the subobject of type SUBOBJ_TYPE at byte offset
   SUBOBJ_BYTE_OFFSET within the variable of type TYPE. */
```

```

static struct value *
dwarf2_evaluate_loc_desc_full (struct type *type, struct frame_info *frame,
                               const gdb_byte *data, size_t size,
                               dwarf2_per_cu_data *per_cu,
                               dwarf2_per_objfile *per_objfile,
                               struct type *subobj_type,
                               LONGEST subobj_byte_offset,
                               bool as_lval)

/* Evaluate the expression at ADDR (LEN bytes long) in a given PER_CU
   and FRAME context.

   AS_LVAL defines if the returned struct value is expected to be a
   value (false) or a location description (true).

   TYPE, SUBOBJ_TYPE and SUBOBJ_OFFSET describe the expected struct
   value representation of the evaluation result.

   The ADDR_INFO property can be specified to override the range of
   memory addresses with the passed in buffer. */
value *evaluate (const gdb_byte *addr, size_t len, bool as_lval,
                 dwarf2_per_cu_data *per_cu, frame_info *frame,
                 const struct property_addr_info *addr_info = nullptr,
                 struct type *type = nullptr,
                 struct type *subobj_type = nullptr,
                 LONGEST subobj_offset = 0);

/* Evaluate the expression at ADDR (LEN bytes long). */

void
dwarf_expr_context::eval (const gdb_byte *addr, size_t len)

/* The engine for the expression evaluator. Using the context in this
   object, evaluate the expression between OP_PTR and OP_END. */
900 LINES OF CODE !!

void
dwarf_expr_context::execute_stack_op (const gdb_byte *op_ptr,
                                       const gdb_byte *op_end)

/* Compute the DWARF CFA for a frame. */
CORE_ADDR dwarf2_frame_cfa (struct frame_info *this_frame);

// CFA - Canonical Frame Address

/* Return the reason why we can't unwind past this frame. */

enum unwind_stop_reason get_frame_unwind_stop_reason (struct frame_info *);

/* Return a "struct frame_info" corresponding to the frame that called
   THIS_FRAME. Returns NULL if there is no such frame.

   Unlike get_prev_frame, this function always tries to unwind the

```

```

    frame. */
extern struct frame_info *get_prev_frame_always (struct frame_info *);

/* Return the per-frame unique identifier. Can be used to relocate a
   frame after a frame cache flush (and other similar operations). If
   FI is NULL, return the null_frame_id.

   NOTE: kettenis/20040508: These functions return a structure. On
   platforms where structures are returned in static storage (vax,
   m68k), this may trigger compiler bugs in code like:

   if (frame_id_eq (get_frame_id (l), get_frame_id (r)))

   where the return value from the first get_frame_id (l) gets
   overwritten by the second get_frame_id (r). Please avoid writing
   code like this. Use code like:

   struct frame_id id = get_frame_id (l);
   if (frame_id_eq (id, get_frame_id (r)))

   instead, since that avoids the bug. */
extern struct frame_id get_frame_id (struct frame_info *fi);

/* Compute the frame's unique ID that can be used to, later, re-find the
   frame. */

static void
compute_frame_id (struct frame_info *fi)

```