

Booking Manager XML API and Availability Service Description

Booking Manager XML API is a standard SOAP Web service that enables clients to connect their data with external systems and services and to extend the automation benefits of the Booking Manager System.

- It is used by charter agencies to publish availabilities of Charter Operators and automate booking processes by connecting Booking Manager to their own web sites to allow for seamless online booking experience for end users or integrating it with their CRM solutions in order to automate office procedures.
- Charter operators use the web service to connect Booking Manager with their book keeping softwares and save time and effort in accounting department.
- Third Party Software tools also use Booking Manager API to display richer information, for example boat tracking systems are able to visualise client contact information directly on the map showing the boat location in real time.

Description of the individual Web service methods in this manual is separated into three distinct chapters/categories depending on the particular use case:

- For Charter Agencies and entities wanting to synchronise yacht information and availability, Chapter 1 is relevant. It describes how to retrieve the basic details about Companies in the system, yachts (resources) and connected data about destinations. It also describes a way to create and manipulate reservations in the system directly via Web service calls.
- Chapter 2 describes methods for exporting the invoices produced in Booking Manager System and methods for manipulating and exporting payments. It is used primarily to automate export of accounting data to external Book keeping software.
- Chapter 3 describes all other data manipulation methods such as detailed reservation manipulation, crew list entry, address book access and todo notes manipulation. These methods are useful for plugin applications that communicate with Booking Manager, such as Check-in software or yacht position tracking software tools.

Web service description definition is located at:

http://www.booking-manager.com/cbm_web_service2/services/CBM?wsdl

Table of Contents

1. Availability Retrieval and Manipulation Methods.....	5
1.1. getCompanies.....	5
1.2. getResources.....	6
1.3. getResourceDetails.....	6
1.4. getAvailabilityInfo.....	6
1.5. getShortAvailabilityInfo.....	7
1.6. getSearchResults (DEPRECATED, use getSearchResultsFilter).....	9
1.7. getSearchResultsFilter.....	10
1.8. getSpecialOffers.....	12
1.9. isResourceAvailable.....	13
1.10. getResourceDiscount.....	13
1.11. getResourcesDiscount.....	14
1.12. createReservation.....	14
1.13. confirmReservation.....	15
1.14. cancelReservation.....	15
1.15. getReservationDetails.....	15
1.16. getBases.....	15
1.17. getRegions.....	16
1.18. getCountries.....	16
1.19. getEquipmentCategories.....	17
2. Invoice Retrieval Methods.....	19
2.1. getInvoices.....	19
2.2. getPayment.....	21
2.3. insertPayment.....	21
2.4. updatePayment.....	22
2.5. deletePayment.....	22
2.6. getCashRegister.....	23
3. Advanced Data Manipulation.....	24
3.1. getStatusTypes.....	24
3.2. getUsers.....	25
3.3. getUsers (2).....	25
3.4. getUserDetails.....	25
3.5. insertUser.....	25

3.6. updateUser.....	26
3.7. insertCrewMember.....	26
3.8. updateCrewMember.....	27
3.9. deleteCrewMember.....	27
3.10. getAllOptionItems.....	28
3.11. getAllDiscountItems.....	28
3.12. insertOptionItem.....	29
3.13. insertDiscountItem.....	29
3.14. getReservations.....	29
3.15. getReservations (2).....	29
3.16. getActiveReservation.....	30
3.17. getReservationGuest.....	31
3.18. updateReservation.....	31
3.19. getToDoNotes.....	32
3.20. insertToDoNote.....	32
3.21. updateToDoNote.....	33
3.22. deleteToDoNote.....	34
3.23. getTranslations.....	34
4. Discount calculation.....	35
4.1. Different discount types.....	36
4.2. Discount application policy.....	36
4.3. Examples.....	36
5. Code lists	36
6. APPENDIX.....	37
6.1. Date formats.....	37
6.2. Resource details.....	37
6.3. Reservation details.....	41
6.4. Payment details.....	43
6.5. User details.....	43
6.6. Crew member details.....	44
6.7. To do note details.....	44
6.8. Changeable user properties.....	44
6.9. Changeable reservation properties.....	46
6.10. Changeable payment properties.....	47
6.11. Changeable crewmember properties.....	47

6.12. Changeable to do note properties.....	48
6.13. Available translation languages.....	48
7. Code examples.....	49
7.1. PHP.....	49
7.2. PHP with Curl.....	50
8. Document Changes.....	52
8.1. Version 1.16 (27.04.2016.).....	52
8.2. Version 1.15 (17.03.2016.).....	52
8.3. Version 1.14 (08.12.2015.).....	52
8.4. Version 1.13 (18.11.2015.).....	53
8.5. Version 1.12 (15.06.2015.).....	53
8.6. Version 1.11 (18.03.2015.).....	53
8.7. Version 1.10 (28.03.2014.).....	54
8.8. Version 1.9 (01.10.2013.).....	54
8.9. Version 1.8 (27.05.2013.).....	54

1. Availability Retrieval and Manipulation Methods

1.1. *getCompanies*

```
public String getCompanies(long _userId,String _username,String _password) throws  
RemoteException;
```

This function retrieves the list of all the Charter operators in the Booking Manager System who manage their resources (yachts) availability in real time. This list provides the id's of the companies that are available for synchronisation. The method returns a single String with xml response in the following format:

```
<root>  
<company id="" name="" address="" city="" zip="" country="" telephone1=""  
telephone2="" fax1="" fax2="" mobile1="" mobile2="" vatcode="" email="" web=""  
availability="" ></company>  
</root>
```

Each *company* section holds a record of a single realtime charter fleet with relevant details of the company:

1. *id* - the company id in the system – this information is important for subsequent retrieval of fleet and availability using other methods
2. *name* – the legal name of the company
3. *address* – the street name and number
4. *city* – the city
5. *zip* – the zip code of the city
6. *country* - the country name
7. *telephone1* – primary contact telephone number
8. *telephone2* – secondary contact telephone number
9. *fax1* – primary fax
10. *fax2* – secondary fax
11. *mobile1* – primary mobile phone
12. *mobile2* – secondary mobile phone
13. *vatcode* – VAT code of the company
14. *email* – the e-mail address of the company
15. *web* – the web url of the company
16. *availability* – company availability: 0-realtime, 1-periodic, 2-rare

1.2. getResources

```
public String getResources(long _userId,String _username,String _password,long  
_companyId) throws RemoteException;
```

Retrieves all of the yachts available for booking with current characteristics, prices, extras and discounts. The result string returns a list of resource details (Resource details).

1.3. getResourceDetails

```
public String getResources(long _userId,String _username,String _password,long  
_resourceId) throws RemoteException;
```

The result string returns resource details (Resource details) for a single resource.

1.4. getAvailabilityInfo

```
public String getAvailabilityInfo(long _userId,String _username,String _password,  
long _companyId , int _year, boolean _onlyBusy, Date _lastModified) throws  
RemoteException;
```

For the retrieval of the booking sheet, a service call to getAvailabilityInfo method is placed. This is the only relevant method that needs to be used for availability retrieval

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *companyId* – the id of the requested company
5. int *year* – the year for which the booking sheet is being retrieved
6. boolean *onlyBusy* – set this to true if you only wish to retrieve the active terms, if set to false it will also pull all of the canceled reservations. If you are using this service for availability retrieval only you will always want to set this field to true .
7. Date *lastModified* – the last retrieval date (or 1.1.1970 for all reservations) – you can use this field to retrieve only changed reservations after last retrieval. This produces faster synchs but is more complex to implement on the connecting party's side. If you don't wish to use this feature and always want to pull all of the bookings, always set this parameter to "1.1.1970"

The method returns a single String with xml response in the following format:

```
<root company_id="" checktime="">  
  <reservation id="n" resourceid="n" status="s" blocksavailability="n" datefrom="d"  
  dateto="d" basefrom="n" baseto="n" optionexpirydate="d" created="d" lastmodified="d"  
  mybooking="" />  
</root>
```

Root section contains these information:

1. *company_id* – id of the charter company
2. *checktime* – time when request was made

Each “<reservation />” section contains the information about a specific term. All reservations are returned including canceled reservations and current offers that don't block availability field explanation:

1. *id* - unique reservation id
2. *resourceid* - the unique id of the individual yacht
3. *status* – status of the term (Option/Reservation/Owner week/Service/Canceled/Option expired)
4. *blocksavailability* (1/0) – if set to 1 then reservation blocks availability and is written in the booking sheet. For availability synchronizations only the terms with blocksavailability set to “1” are significant
5. *datefrom* – date of the checkin in format “yyyy-dd-mm”
6. *dateto* – date of the checkout in format “yyyy-dd-mm”
7. *basefrom* – the unique id of the check in base
8. *baseto* – the unique id of the checkout base
9. *optionexpirydate* – the unix timestamp of the expiration date for the option created – the unix timestamp of the creation date of the reservation
10. *lastmodified* – the unix timestamp of the last reservation change time
11. *mybooking* – true if reservation belongs to the company which made the request

1.5. *getShortAvailabilityInfo*

```
public String getShortAvailabilityInfo(long _userId,String _username,String
_password,long _companyId,int _year,int _resultTypeId) throws RemoteException;
```

Retrieves availability information in short format:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *companyId* – the id of the requested company. Can be set to “-1” to retrieve availability from all companies but it will take longer and response will be larger in size.
5. int *year* – the year for which the booking sheet is being retrieved
6. int *resultTypeId* – type of result that will be returned
 1. 1 – Binary
 2. 2 – Hex
 3. 3 - Status

Result types

Binary – use “1” to get results in binary format

```
<root year="" resulttypeid="" companyid="">
<![CDATA[
resourceId:availabilityInfo;resourceId:availabilityInfo; ...
]]>
</root>
```

Response contains availability information for yachts. Availabilities for multiple yachts are separated by “,”. Availability information for each yacht contains resourceId and availabilityInfo separated by “.”.

resourceId – id of the resource

availabilityInfo – availability information for the resource in binary format. Each availabilityInfo is 365 characters long (or 366 in case of the leap year) and it represents the whole year (single character is one day of the year). First character is January 1st, second character is January 2nd, and so on. If character is equal to “0” it means that yacht is available on that day, otherwise character is equal to “1”.

Hex – use “2” to get results in hexadecimal format

```
<root year="" resulttypeid="">
<![CDATA[
resourceId:availabilityInfo;resourceId:availabilityInfo; ...
]]>
</root>
```

Response contains availability information for yachts. Availabilities for multiple yachts are separated by “,”. Availability information for each yacht contains resourceId and availabilityInfo separated by “.”.

resourceId – id of the resource

availabilityInfo – availability information for the resource in hexadecimal format. Each availabilityInfo is 92 characters long and it represents the whole year. First character is January 1, January 2, January 3 and January 4, second character is January 5, January 6, January 7 and January 8, and so on. Last characters should be discarded depending on how long the requested year is.

For example, if availabilityInfo is “fe03f0...” in binary it is “0000 0001 1111 1100 0000 1111...” and it means that yacht is available from January 1 until January 8, but it is not available from January 8 until January 15, and so on.

Statuses – use “3” to get results in binary format

```
<root year="" resulttypeid="" companyid="">
<![CDATA[
resourceId:availabilityInfo;resourceId:availabilityInfo; ...
]]>
</root>
```

Response is the same as the Binary response with one difference – booked days are not represented with character “1” for all types of reservations but instead reservation status id is used. For example, if availabilityInfo is “2222 2220 0000...” it means that boat is under status Option from January 1 until January 8, and it is free from January 8 etc.

Status codes are:

- 0 – Available
- 1 – Reservation
- 2 – Option
- 3 – Option in expiration
- 4 – Service

1.6. *getSearchResults (DEPRECATED, use getSearchResultsFilter)*

This method is deprecated and will not be supported in a future versions. Use `getSearchResultsFilter` method which has more functionality and will be extended in the future.

```
getSearchResults(long _userId, String _username, String _password, long  
_companyId, Date _dateFrom, Date _dateTo, String _resourceTypes, String  
_countryCode, String _baseId)
```

Performs the availability search on the database. It is possible to retrieve all resources that meet the set parameters with their availability status, price and discount data.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *companyId* – the id of the requested company
5. Date *dateFrom* – start date of the requested period
6. Date *dateTo* – end date of the requested period
7. String *resourceTypes* – The list of gids separated by comma to filter out only certain yacht models. If left empty, it searches all models
8. String *countryCode* – the short two letter country code to search for resources only in certain country
9. String *baseId* – the id of the base if we want to search only resources available in one base

If *dateFrom* is set to January 1 and *dateTo* is set to December 31 it will return search results for the whole year.

```
<root>  
  
<resource resourceid="n" companyId="" reservationstatus="" baseprice=""  
discountvalue="" price="" baseid="" datefrom="" dateto=""></resource>  
...  
</root>
```

The results are returned as list of `<resource></resource>` elements. Attributes are:

1. *resourceid* – the id of the retrieved resource / yacht
2. *companyId* – the id of the company that rents the yacht

3. *reservationstatus* – the status of availability for this yacht. This can be:
 1. 0 – Free – yacht is available
 2. 1 – Fixed reservation – the term is booked
 3. 2 – Option – the term is under option
 4. 3 – Option Expired – the term is under option that is about to expire
 5. 4 – Service – The yacht is under service or not available for some other reason
4. *baseprice* – the price for the term in EUR (without the discount)
5. *discountvalue* – the discount value for the term (in %)
6. *price* – the price with the discount applied
7. *baseid* – the id of the base where resource is available
8. *basetoid* – the id of the base where resource will end up
9. *datefrom* – start date of the requested period
10. *dateto* – end date of the requested period

1.7. *getSearchResultsFilter*

```
getSearchResultsFilter(long _userId, String _username, String _password, String
_xmlValues)
```

Performs the availability search on the database. It is possible to retrieve all resources that meet the set parameters with their availability status, price and discount data.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. String *xmlValues* – xml string with filter parameters

All filter parameters, if used, are contained in *_xmlValues* string.

```
<filter>
  <element id="datefrom"></element>
  <element id="dateto"></element>
  <element id="flexibility"></element>
  <element id="companyids"></element>
  <element id="countrycodes"></element>
  <element id="baseids"></element>
  <element id="resourceids"></element>
  <element id="resourcetypeids"></element>
</filter>
```

1. Date *datefrom* – start of request period in SOAP format (see Date formats). This parameter is obligatory.

2. Date *dateto* – end of request period in SOAP format (see Date formats). This parameter is obligatory.
3. long flexibility – expand search outside of the request period
 1. 1 – on day (default)
 2. 2 – in week
 3. 3 – one week before or after
 4. 4 – two weeks before or after
 5. 5 – in month
 6. 6 – in year

If flexibility is used only *datefrom* is relevant (leave *dateto* at *datefrom*+7 days)

4. String *companyids* – filter one or multiple companies separated by comma (e.g. 123,456)
5. String *countrycodes* – filter one or multiple countries separated by comma (e.g. HR,IT)
6. String *baseids* – filter one or multiple bases separated by comma
7. String *resourceids* – filter one or multiple yachts separated by comma
8. String *resourcetypeids* – filter one or multiple yacht models separated by comma

```
<root>
<resource resourceid="" companyid="" reservationstatus="" baseprice=""
discountvalue="" price="" baseid="" datefrom="" dateto=""></resource>
...
</root>
```

The results are returned as list of `<resource></resource>` elements. Attributes are:

1. *resourceid* – the id of the retrieved resource / yacht
2. *companyid* – the id of the company that rents the yacht
3. *reservationstatus* – the status of availability for this yacht. This can be:
 1. 0 – Free – yacht is available
 2. 1 – Fixed reservation – the term is booked
 3. 2 – Option – the term is under option
 4. 3 – Option Expired – the term is under option that is about to expire
 5. 4 – Service – The yacht is under service or not available for some other reason
4. *baseprice* – the price for the term in EUR (without the discount)
5. *discountvalue* – the discount value for the term (in %)
6. *price* – the price with the discount applied
7. *baseid* – the id of the base where resource is available
8. *basetoid* – the id of the base where resource will end up
9. *datefrom* – start date of the requested period
10. *dateto* – end date of the requested period

1.8. *getSpecialOffers*

```
getSpecialOffers(long _userId, String _username, String _password, String _type, Date  
_dateFrom, Date _date, String _xmlValues)
```

Retrieves special offers from the database.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. String *type* – type of the requested special offer:
 1. 1 – short term offers
 2. 2 – one way offers
5. Date *date* – retrieve special offers for this date. System will return all the special offers around this date +/- two weeks.
6. String *xmlValues* – additional filtering parameters:
 1. *companyId* – filter results by company id

Example of the *xmlValues* parameter:

```
<values>  
  <element id="companyId">123</element>  
  ...  
</values>
```

Response format:

```
<root>  
<resource resourceid="n" companyId="" reservationstatus="" baseprice=""  
discountvalue="" price="" baseid="" datefrom="" dateto=""></resource>  
...  
</root>
```

The results are returned as list of `<resource></resource>` elements. Attributes are:

1. *resourceid* – the id of the retrieved resource / yacht
2. *companyId* – the id of the company that rents the yacht
3. *reservationstatus* – the status of availability for this yacht. This can be:
 1. 0 – Free – yacht is available
 2. 1 – Fixed reservation – the term is booked
 3. 2 – Option – the term is under option
 4. 3 – Option Expired – the term is under option that is about to expire
 5. 4 – Service – The yacht is under service or not available for some other reason
4. *baseprice* – the price for the term in EUR (without the discount)

5. *discountvalue* – the discount value for the term (in %)
6. *price* – the price with the discount applied
7. *baseid* – the id of the base where resource is available
8. *datefrom* – start date of the requested period
9. *dateto* – end date of the requested period

1.9. *isResourceAvailable*

```
public String isResourceAvailable(long _userId,String _username,String  
_password,long _resourceId,Date _dateFrom,Date _dateTo) throws RemoteException;
```

Checks if yacht is available in selected period.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *resourceId* – id of the resource
5. Date *dateFrom* – start date of the requested period
6. Date *dateTo* – end date of the requested period

```
<resource id="" isavailable="" status="" />
```

Result contains id of the resource and its availability.

1. *id* – id of the resource
2. *isavailable* – availability of the resource, 1 if available and 0 otherwise
3. *status* – status of the booking if yacht is reserved, 0 if it is free

1.10. *getResourceDiscount*

```
public String getResourceDiscount(long _userId,String _username,String  
_password,long _resourceId,Date _dateFrom,Date _dateTo) throws RemoteException;
```

Calculates total discount percentage for a particular resource in given date period.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *resourceId* – id of the resource
5. Date *dateFrom* – start date of the requested period
6. Date *dateTo* – end date of the requested period

```
<resource id="" discount="" price="" />
```

Result contains id of the resource and discount percentage.

1. *id* – id of the resource
2. *discount* – current discount on the base price in percentages on the base price
3. *price* – final price

1.11. *getResourcesDiscount*

```
public String getResourcesDiscount(long _userId,String _username,String
_password,String _xmlValues) throws RemoteException;
```

Calculates total discount percentage for requested resources in given date period.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. String *xmlValues* – xml string with filter parameters

All filter parameters, if used, are contained in *_xmlValues* string.

```
<filter>
    <element id="resourceids"></element>
    <element id="datefrom"></element>
    <element id="dateto"></element>
</filter>
```

1. String *resourceids* – get discounts for these boats, if it is left empty it will return discounts for all boats
2. Date *datefrom* – start of request period in SOAP format (see Date formats). This parameter is obligatory.
3. Date *dateto* – end of request period in SOAP format (see Date formats). This parameter is obligatory.

```
<root>
<resource id="" discount="" price="" />
...
</root>
```

Result contains all requested resources with their discount and price.

1. *id* – id of the resource
2. *discount* – current discount on the base price in percentages on the base price
3. *price* – final price

1.12. *createReservation*

```
public String createReservation(long _userId,String _username,String _password, long
_companyId , Date _dateFrom,Date _dateTo,long _resourceId, String _clientName)
throws RemoteException;
```

createReservation is used to place a new option in the Booking Manager system. The system creates an

option with standard discounts and obligatory options applied.

The result string returns a reservation details (Reservation details).

1.13. *confirmReservation*

```
public String confirmReservation(long _userId,String _username,String _password,  
long _reservationId) throws RemoteException;
```

Converts an option into finalized reservation.

The result string returns a reservation details (Reservation details).

1.14. *cancelReservation*

```
public String cancelReservation(long _userId,String _username,String _password, long  
_reservationId) throws RemoteException;
```

Cancels a option. An already confirmed booking is not possible to cancel automatically.

The result string returns a reservation details (Reservation details).

1.15. *getReservationDetails*

```
public String getReservationDetails(long _userId,String _username,String _password,  
long _reservationId) throws RemoteException;
```

The result string returns a reservation details (Reservation details).

1.16. *getBases*

```
public String getBases(long _userId,String _username,String _password) throws  
RemoteException;
```

This method retrieves the available home ports/bases of the resources, with some basic information.

The method receives standard authorization fields:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```
<root>  
<base id="" name="" city="" country="" address="" regionids="" longitude=""  
latitude="" countryid="" ></base>  
</root>
```

Results are in a form of a <base></base> list with following attributes:

1. *id* – the system id of the base. This is useful to correctly identify the bases of yachts in *getResources*, *getSearchResult* and *getAvailabilityInfo* methods
2. *name* – the name of the base
3. *city* – the city of the base

4. *country* – the country name of the base
5. *address* – the address information for the base
6. *regionids* – identifiers of the regions to which this base belongs to
7. *longitude* – geographical longitude of the destination
8. *latitude* – geographical latitude of the destination
9. *countryid* – the country id

1.17. *getRegions*

```
public String getRegions(long _userId,String _username,String _password) throws  
RemoteException;
```

This method retrieves the available subregions/sailing areas names and id's

The method receives standard authorization fields:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```
<root>  
  <region id="" name="" ></region>  
</root>
```

Results are in a form of a <region></region> list with following attributes:

1. *id* – the system id of the region
2. *name* – the name of the region

1.18. *getCountries*

```
public String getCountries(long _userId,String _username,String _password) throws  
RemoteException;
```

This method retrieves the available countries with some basic information.

The method receives standard authorization fields:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```
<countries>  
  <country id="" name="" shortname="" longshortname="" regionid="">  
    <translations>  
      <translation lang="" value="" />  
    </translations>  
  </country>  
</countries>
```



```

    </translations>
  </country>
</countries>

```

Results are in a form of a <country></country> list with following attributes:

1. *id* – the system id of the country
2. *name* – the name of the country
3. *shortname* – representation of the country name with 2 characters
4. *longshortname* – representation of the country name with 3 characters
5. *regionid* – id of the region to which this country belongs

<translations> contains country name translations in all available languages:

1. *lang* – language
2. *value* – country name in language

1.19. *getEquipmentCategories*

```

public String getEquipmentCategories(long _userId,String _username,String _password)
throws RemoteException;

```

Returns a list of all generic equipment.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```

<root>
  <equipmentcategory id="" name="" />
  ...
</root>

```

The results are returned as list of <equipmentcategory></equipmentcategory> elements. Attributes are:

1. *id* – id of the equipment category
2. *name* – name of the equipment category

getShipyards

```

public String getShipyards(long _userId,String _username,String _password) throws
RemoteException;

```

Returns a list of all shipyards.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```
<root>
  <shipyard id="" name="" shortname="" />
  ...
</root>
```

The results are returned as list of <shipyard></shipyard> elements. Attributes are:

1. *id* – id of the shipyard
2. *name* – name of the shipyard
3. *shortname* – short name of the shipyard

2. Invoice Retrieval Methods

2.1. *getInvoices*

```
public String getInvoices(long userId,String username,String password,int
filterInvoiceType,Date _dateFrom,Date _dateTo)
```

This method is used to fetch a list of all issued invoices in some period. It is possible to filter by date periods, and types of invoice.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. int *filterInvoiceType* – the type of invoice that is being fetched
 1. 0 – all invoices
 2. 1 – final invoices
 3. 2 – invoices for advance payments
 4. 3 – storno invoices
1. *datefrom* – start date of the invoicing period
2. *dateto* – end date of the invoicing period

The method returns a single String with xml response in the following format:

```
<root>
  <invoice type="" number="" reservationnumber="" date="" client="" clientcode=""
  clientvatcode="" clientid="" guestname="" currency="" exchangerate="" altcurrency=""
  altexchangerate="" resource="" resourcetype="" resourcecode="" totalprice=""
  totalpricewithouttax="" rate="" totalaltprice="" totalaltpricewithouttax=""
  basefrom="" baseto="" alreadytransferred="" servicedatefrom="" servicedateto=""
  paymentmethodname="" paymentmethodtype="" agencyid="" agencyname="" agencycode=""
  agencyvatcode="" relatedreservationid="" reservationid="">

  <vat><item base="" rate="" total="" basealt="" totalalt="" /></vat>
  <services><service name="" total="" rate="" /></services>
  <bi><item name="" value="" /></bi>

</invoice>
</root>
```

Each “<invoice />” section contains the following information about a specific invoice:

3. *type* – the type of the invoice
4. *number* – the number of the invoice
5. *reservationnumber* – the number of the reservation
6. *date* – date of the invoice in format “yyyy-dd-mm”

7. *client* – the name of the client
8. *clientcode* – the code of the client in the addressbook
9. *clientvatcode* – the VAT code of the client
10. *clientid* – the unique id of the client in the Booking Manager database
11. *guestname* – the name of the guest that is traveling
12. *currency* – the currency that the invoice is being issued in
13. *exchangerate* – the exchange rate of the currency on the invoice compared to EUR
14. *altcurrency* – the alternative currency (usually used to show also the value in domestic currency if different from invoice currency)
15. *altexchangerate* – exchange rate of the alternative currency
16. *resource* – the name of the resource (boat) that is invoiced
17. *resourcetype* – the name of the model
18. *resourcecode* – the code of the boat in the yacht editor
19. *totalprice* – the total price of the invoice
20. *totalaltpricewithouttax* – the base price without tax
21. *rate* – tax rate
22. *totalaltprice* – total price in alternative currency
23. *totalaltpricewithouttax* – total price in alternative currency without tax
24. *basefrom* – base where boat is boarding (check in base)
25. *baseto* – base where boat is disembarking (checkout base)
26. *alreadytransferred* – Flag to mark if this particular invoice was already pulled.
27. *servicedatefrom* – checkin date for the reservations
28. *servicedateto* – checkout date for the reservation
29. *paymentmethodname* – name of the payment method used on the invoice
30. *paymentmethodtype* – type of the transaction (Other, Cash, Card, Check, Transaction account)
31. *agencyid* – id of the agent attached to the reservation
32. *agencyname* – full name of the agent attached to the reservation
33. *agencycode* – code id of the agent
34. *agencyvatcode* – vat code of the agent
35. *relatedreservationid* – id of the related reservation, this parameter does not exist if there is no related reservation
36. *reservationid* – invoice is issued on the reservation identified by this id

Each <invoice /> section also may contain a <vat /> section where all the items in the invoice are separated by tax rate, which is important for bookkeeping purposes, items are as follows:

1. *base* – the base price without tax
2. *rate* – the tax rate

3. *total* – total price with tax
4. *basealt* – base price in alternative currency
5. *totalalt* – total price in alternative currency

Each <invoice/> section may contain a <services/> section which contains all services regarding the invoice. Each <service/> item has these attributes:

1. *name* – name of the service
2. *total* – service price
3. *rate* – service tax rate

Each <invoice/> contains a <bi/> section with <item/> which contains all useful information for business intelligence calculations. Each <item/> has these attributes:

6. *name* – name of the item
7. *value* – value of the item

Items with these names are sent in the <bi/> section:

1. *commission* – agency commission and corresponding amount
2. *profit* – charter profit based on charged amount and agency commission

2.2. *getPayment*

```
public String getPayment(long userId,String username,String password,long  
_paymentId) throws RemoteException;
```

This method is used to retrieve a details for certain payment.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *paymentId* – id of the payment that is being retrieved

The method returns a single String with xml response containing payment details (Payment details).

2.3. *insertPayment*

```
public String insertPayment(long userId,String username,String password,long  
_reservationId,String _xmlValues) throws RemoteException;
```

This method is used to insert payment to certain reservation.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation on which the payment will be added

5. String *xmlValues* - xml string with payment properties

All properties for the payment are contained in *_xmlValues* string:

```
<payment>
    <element id="value">1000.0</element>
    <element id="currency">1</element>
    <element id="exchangerate">7.405</element>
    ...
</payment>
```

For all available properties please read Changeable payment properties in Appendix.

The method returns a single String with xml response containing payment details (Payment details).

2.4. *updatePayment*

```
public String updatePayment(long userId,String username,String password,long
_paymentId,String _xmlValues) throws RemoteException;
```

This method is used to update payment.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *paymentId* – id of the payment that will be updated
5. String *xmlValues* - xml string with payment properties

All properties for the payment are contained in *_xmlValues* string:

```
<payment>
    <element id="value">1000.0</element>
    <element id="currency">1</element>
    <element id="exchangerate">7.405</element>
    ...
</payment>
```

For all available properties please read Changeable payment properties in Appendix.

The method returns a single String with xml response containing payment details (Payment details).

2.5. *deletePayment*

```
public String deletePayment(long userId,String username,String password,long
_paymentId) throws RemoteException;
```

This method is used to delete payment.

The parameters for the method are:

1. long *userId* – the userId of the connecting party

2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *paymentId* – id of the payment that will be deleted

The method returns a single String with xml response containing payment details (Payment details).

2.6. *getCashRegister*

```
public String getCashRegister(long userId,String username,String password,Date
_dateFrom,Date _dateTo,String _xmlValues) throws RemoteException;
```

This method is used to get cash register view.

The parameters for the method are:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. Date *dateFrom* – get cash register from this date
5. Date *dateTo* – get cash register until this date
6. String *xmlValues* – xml string with filter parameters

All filter parameters, if used, are contained in *_xmlValues* string. All of these filters are optional:

```
<filter>
  <element id="showincurrency">EUR</element>
  <element id="currency">HRK</element>
  <element id="methodofpayment">Cash,Card</element>
  <element id="paymentmethodid">123456789</element>
  <element id="operator">123/John Doe</element>
  <element id="officeid">123456789</element>
  <element id="deviceid">1999</element>
</filter>
```

1. String *showincurrency* – all values will be recalculated in this currency (use ISO 4217 currency code)
2. String *currency* – filter invoices that are issued in requested currency (use ISO 4217 currency code)
3. String *methodofpayment* – one of: Other, Cash, Card, Check, Transaction account. You can use multiple methods by concatenating them with comma.
4. long *paymentmethodid* – id of the payment method
5. String *operator* – invoice operator identifier that issued the invoice
6. long *officeid* – id of the office that issued the invoice
7. long *deviceid* – id of the device that issued the invoice

The method returns info about the cash register in requested period:

```
<root lastreceiptnumber="" lastexpensenumber="">
  <item id="" slipid="" paymentmethodtype="" date="" name="BALANCE TRANSFER"
amount="" currencycode="" />
  <item id="" slipid="" paymentmethodtype="" date="" name="" amount=""
currencycode="" />
  ...
</root>
```

1. long lastreceiptnumber – last receipt number after requested period
2. long lastexpensenumber – last expense number after requested period

<item> is a single cash register entry. In this case, first item is the balance transfer from the previous period.

1. long id – numerical number of the item in current listing
2. String slipid – slip number of the item in current year. If it starts with "U" it is receipt, if it starts with "I" it is an expense.
3. String paymentmethodtype – one of: Other, Cash, Card, Check, Transaction account
4. Date date – invoice date
5. String name – name or invoice number
6. float amount – amount in currency
7. String currencycode – ISO 4217 currency code

3. Advanced Data Manipulation

3.1. getStatusTypes

```
public String getStatusTypes(long _userId,String _username,String _password) throws
RemoteException;
```

This method retrieves the available reservation statuses.

The method receives standard authorization fields:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

```
<statustypes>
  <statustype id="" name=""></statustype>
</statustypes>
```

Results are in a form of a <statustype></statustype> list with following attributes:

1. *id* – the system id of the reservation status
2. *name* – the name of reservation status

3.2. getUsers

```
public String getUsers(long _userId,String _username,String _password,long  
_lastSyncPoint) throws RemoteException;
```

Returns a list of all users with details. Completely the same as the second getUsers method described below but with no decryption of the data.

3.3. getUsers (2)

```
public String getUsers(long _userId,String _username,String _password,long  
_lastSyncPoint,String _encryptionCode) throws RemoteException;
```

Returns users that were changed since _lastSyncPoint and decrypts the data if it is encrypted and if encryption code is provided.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *lastSyncPoint* – point when last synchronization was performed. Use 0 to get all users (this can be a little slow if there is more than 5000 users in your addressbook)
5. String *encryptionCode* – if your data is encrypted system will use this password to decrypt it and return them in response. If encryptionCode is null then it will return encrypted data and you should decrypt it on your side.

```
<users syncpoint="">  
<user ... >  
</user>  
...  
</users>
```

The results are returned as list of <users></users> elements. Attributes are:

1. *syncpoint* – point when synchronization was performed

The result string returns a list of user details (User details).

3.4. getUserDetails

```
public String getUserDetails(long _userId,String _username,String _password,long  
_id,String _encryptionCode) throws RemoteException;
```

The result string returns user details (User details) for a single user.

3.5. insertUser

```
public String insertUser(long _userId,String _username,String _password,String  
_xmlValues) throws RemoteException;
```

Inserts new user to your addressbook.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. String *xmlValues* – xml string with user properties

All properties for the user are contained in *_xmlValues* string:

```
<user>
  <element id="codeid">123</element>
  <element id="301">John</element>
  <element id="302">Johnson</element>
  ...
</user>
```

For all available properties please read Changeable user properties in Appendix.

3.6. *updateUser*

```
public String updateUser(long _userId,String _username,String _password,long
_addressBookUserId,String _xmlValues) throws RemoteException;
```

Updates user from the addressbook.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *addressBookUserId* – id of the user to update
5. String *xmlValues* – xml string with user properties

All properties for the user are contained in *_xmlValues* string:

```
<user>
  <element id="codeid">123</element>
  <element id="301">John</element>
  <element id="302">Johnson</element>
  ...
</user>
```

For all available properties please read Changeable user properties in Appendix.

3.7. *insertCrewMember*

```
public String insertCrewMember(long _userId,String _username,String _password,long
_reservationId,long _addressBookUserId,boolean _isSkipper) throws RemoteException;
```

Inserts user from the addressbook to the crew list on specified reservation.

1. long *userId* – the userId of the connecting party

2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation to which the crew member will be added
5. long *addressBookUserId* – id of the user that will be added as a crew member
6. boolean *isSkipper* – 1 if it is a skipper and 0 if it is a crew member (guest)

The method returns details for newly inserted crew member (Crew member details).

3.8. *updateCrewMember*

```
public String updateCrewMember(long _userId,String _username,String _password,long  
_reservationId,long _crewMemberId,String _xmlValues) throws RemoteException;
```

Updates crew member details on certain reservation.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation on which the crew member will be updated
5. long *crewMemberId* – id of the crew member to update
6. String *xmlValues* – xml string with crew member properties

All properties for the crew member are contained in *_xmlValues* string:

```
<crewmember>  
  <element id="1303">John</element>  
  <element id="1304">Johnson</element>  
  ...  
</crewmember>
```

For all available properties please read Changeable crewmember properties in Appendix.

The method returns details for updated crew member (Crew member details).

3.9. *deleteCrewMember*

```
public String deleteCrewMember(long _userId,String _username,String _password,long  
_reservationId,long _crewMemberId) throws RemoteException;
```

Deletes crew member from certain reservation.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation from which the crew member will be deleted
5. long *crewMemberId* – id of the crew member to delete

3.10. *getAllOptionItems*

```
public String getAllOptionItems(long _userId,String _username,String _password,long  
_companyId) throws RemoteException;
```

Retrieves all available option items for certain company.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *companyId* – id of the company whose option items you would like to retrieve

```
<optionitems>  
    <optionitem id="" name="" price="" />  
    ...  
</optionitems>
```

The results are returned as list of <optionitem></optionitem> elements. Attributes are:

1. *id* – id of the option item
2. *name* – name of the option item
3. *price* – price of the option item

3.11. *getAllDiscountItems*

```
public String getAllDiscountItems(long _userId,String _username,String  
_password,long _companyId) throws RemoteException;
```

Retrieves all available discount items for certain company.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *companyId* – id of the company whose option items you would like to retrieve

```
<discountitems>  
    <discountitem id="" name="" value="" />  
    ...  
</discountitems>
```

The results are returned as list of <discountitem></discountitem> elements. Attributes are:

1. *id* – id of the discount item
2. *name* – name of the discount item
3. *value* – value of the discount item

3.12. insertOptionItem

```
public String insertOptionItem(long _userId,String _username,String _password,long  
_reservationId,long _optionItemId,float _amount) throws RemoteException;
```

Inserts option item with the arbitrary amount to certain reservation.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation to which option item will be added
5. long *optionItemId* – id of the option item to add
6. float *amount* – amount for the option item

The result string returns a reservation details (Reservation details).

3.13. insertDiscountItem

```
public String insertDiscountItem(long _userId,String _username,String _password,long  
_reservationId,long _discountItemId,float _amount) throws RemoteException;
```

Inserts discount item with the arbitrary amount to certain reservation.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation to which discount item will be added
5. long *discountItemId* – id of the discount item to add
6. float *amount* – amount for the discount item

The result string returns a reservation details (Reservation details).

3.14. getReservations

```
public String getReservations(long _userId,String _username,String _password) throws  
RemoteException;
```

Returns a list of all reservations with details. Completely the same as the second getReservations method described below with the difference of returning all reservations.

3.15. getReservations (2)

```
public String getReservations(long _userId,String _username,String _password,long  
_lastSyncPoint) throws RemoteException;
```

Returns reservations that were changed since *_lastSyncPoint*.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

4. long *lastSyncPoint* – point from which you would like to retrieve only newly changed reservations. Use 0 if you want to retrieve all the reservations.

```
<root company_id="" checktime="" syncpoint="">
<reservation id="" charterreservationid="" charterstatus="" resourceid="" status=""
blocksavailability="" datefrom="" dateto="" basefrom="" baseto=""
optionexpirydate="" created="" lastmodified="" companyid="" userid=""
code=""></reservation>
...
</root>
```

The results are returned as list of `<resource></resource>` elements. Attributes are:

1. *company_id* – provided *userId* in the request
2. *checktime* – time in milliseconds when request has been performed
3. *syncpoint* – point when synchronization occurred. Can be used to retrieve reservations that were changed since last syncpoint
4. *id* – id of the reservation
5. *charterreservationid* – id of the corresponding charter reservation
6. *charterstatus* – status of the corresponding charter reservation
7. *resourceid* – id of the yacht
8. *status* – status of the reservation
9. *blocksavailability* – 1 if this reservation blocks availability
10. *datefrom* – checkin date
11. *dateto* – checkout date
12. *basefrom* – checkin base
13. *baseto* – checkout base
14. *optionexpirydate* – date when option will expire
15. *created* – date when reservation was created
16. *lastmodified* – time in milliseconds when this reservation was last modified
17. *companyid* – id of the charter company
18. *userid* – id of the client
19. *code* – reservation code

3.16. *getActiveReservation*

```
public String getActiveReservation(long _userId,String _username,String
_password,long _resourceId,Date _onDate) throws RemoteException;
```

Returns reservation id that is active at requested date.

1. long *userId* – the *userId* of the connecting party
2. String *username* – the user name of the connecting party

3. String *password* – the password of the connecting party
4. long *resourceId* – id of the boat
5. Date *onDate* – date for which active reservation is retrieved

```
<root>
  <reservation id="">
  </reservation>
  ...
</root>
```

Result is the id of the reservation that is active on requested date:

1. *id* – id of the active reservation

Multiple reservation nodes can exist if reservations overlap by accident.

3.17. *getReservationGuest*

```
public String getReservationGuest(long _userId,String _username,String
 _password,long _reservationId,String _encryptionCode) throws RemoteException;
```

Returns guest for the reservation.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *reservationId* – id of the reservation
5. String *encryptionCode* – encryption code if data is encrypted

```
<user id="" codeid="">
  <property id="" name=""> </property>
  ...
</user>
```

For all available properties please read Changeable user properties in Appendix.

3.18. *updateReservation*

```
public String updateReservation(long _userId,String _username,String _password,long
 _reservationId,String _xmlValues) throws RemoteException;
```

Updates reservation with provided id.

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party

4. long *reservationId* – id of the reservation to update
5. String *xmlValues* – xml string with reservation properties

All properties for the reservation are contained in *_xmlValues* string:

```
<reservation>
    <element id="codeid">123</element>
    <element id="301">John</element>
    <element id="302">Johnson</element>
    ...
</reservation>
```

For all available properties please read Changeable reservation properties in Appendix.

3.19. *getToDoNotes*

```
public String getToDoNotes(long _userId,String _username,String _password,int
_objectType,long _objectId) throws RemoteException;
```

Returns existing to do notes on requested object:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. int *objectType* – type of the object:
 1. 1-reservation
 2. 2-user
 3. 3-resource
5. long *objectId* – id of the object

```
<root>
    <todonote id="" ...>
    </todonote>
    ...
</root>
```

Result is details of all available to do notes on requested objects. Please read To do note details in Appendix.

3.20. *insertToDoNote*

```
public String insertToDoNote(long _userId,String _username,String _password,int
_objectType,long _objectId,String _xmlValues) throws RemoteException;
```

Inserts new to do note on the object:

1. long *userId* – the userId of the connecting party

2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. int *objectType* – type of the object:
 1. 1-reservation
 2. 2-user
 3. 3-resource
5. long *objectId* – id of the object
6. String *xmlValues* – xml string with to do note properties

All properties for the to do note are contained in *_xmlValues* string:

```
<todonote>
  <element id="description">Test description</element>
  <element id="iscompleted">1</element>
  ...
</todonote>
```

For all available properties please read Changeable to do note properties in Appendix.

Result is details of new to do note. Please read To do note details for more information.

3.21. *updateToDoNote*

```
public String updateToDoNote(long _userId,String _username,String _password,long
_noteId,String _xmlValues) throws RemoteException;
```

Updates the existing to do note:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *noteId* – id of the to do note
5. String *xmlValues* – xml string with to do note properties

All properties for the to do note are contained in *_xmlValues* string:

```
<todonote>
  <element id="description">Test description</element>
  <element id="iscompleted">1</element>
  ...
</todonote>
```

For all available properties please read Changeable to do note properties in Appendix.

Result is details of the updated to do note. Please read To do note details for more information.

3.22. *deleteToDoNote*

```
public String deleteToDoNote(long _userId,String _username,String _password,long _noteId) throws RemoteException;
```

Deletes the existing to do note:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. long *noteId* – id of the to do note

```
<root>
  <todonote id="">
</todonote>
</root>
```

Returns id of deleted to do note.

3.23. *getTranslations*

```
public String getTranslations(long _userId,String _username,String _password,String _xmlValues) throws RemoteException;
```

Returns translations for requested objects:

1. long *userId* – the userId of the connecting party
2. String *username* – the user name of the connecting party
3. String *password* – the password of the connecting party
4. String *xmlValues* – xml string with list of objects and languages

All parameters are contained in xmlValues string:

```
<root>
  <element id="items">object1,object2,object3</element>
  <element id="languages">de,hr,it</element>
</root>
```

Items element should contain ids of objects (their translationids, to be more precise) for which translations should be returned. Any object in the system that has an "translationid" attribute can be used in this method. "translationid" attribute should be used when calling getTranslations (e.g. if translationid=12:3456789 then <element id="items">12:3456789</element>).

Languages element can be omitted and in that case system will return translations for all available languages. All available languages can be found at Available translation languages. If translation does not exist in requested language response will not contain element for that language.

Result is in the format:

```
<root>
  <item id="">
```

```
<translation lang="" value="" />
...
</item>
...
</root>
```

This is an example of one request and corresponding response:

```
<!--REQUEST-->
<root>
  <element id="items">24:123456789,24:987654321</element>
  <element id="languages">de,hr</element>
</root>

<!--RESPONSE -->
<root>
  <item id="24:123456789">
    <translation lang="de" value="12V Kühlschrank" />
    <translation lang="hr" value="12V kuhalo" />
  </item>
  <item id="24:987654321">
    <translation lang="hr" value="Pomoćni čamac" />
  </item>
</root>
```

4. Discount calculation

4.1. Different discount types

Duration discount

Service period

Reservation period

4.2. Discount application policy

4.3. Examples

5. Code lists

For a successful synchronisation of the availability a receiving party must either change their own ids of the resources and bases to the system ones or create a translation table to match them to their internal lists. The list of bases and yacht codes are downloadable directly from the web service with `getBases` and `getResources` functions.

6. APPENDIX

6.1. Date formats

If you are accessing the web service thru PHP or any other language that does not have a automatic translation of the DateTime data into a SOAP envelope, you need to provide a proper format for the date field, which should also include time and a timezone information.

Example of the correct date time:

Date: 1st of January 2012, 11:35 AM

SOAP format: 2012-01-01T11:35:00

6.2. Resource details

```
<root>
  <resource id="" gid="" name="" base="" model="" berths="" berthsex="" year=""
length="" cabins="" cabinsex="" heads="" watercapacity="" fuelcapacity="" engine=""
deposit="EUR" commissionpercentage="" kind="" draught="" beam=""
lengthatwaterline="" maximumdiscount="" servicetype="" discountshavesubtotals=""
defaultcheckintime="" defaultcheckouttime="" calculateagencydiscountwithoutvat=""
taxableamount="" taxrate="" genericresourcetyname="" defaultcheckinday=""
codeid="" cgid="" companyid="" transitlog="" defaultcleaningcost="" shipyardid=""
saleprice="" requiredskipperlicense="" ownerid="">
  <prices>
    <price datefrom="d" dateto="d" price="nn" currency="xxx" ></price>
    .
    .
  </prices>
  <images>
    <image href="URL" comment="" ></image>
    .
    .
  </images>
  <equipment>
    <equipmentitem id="" parentid="" name="" value="" categoryname=""
translationid=""></equipmentitem>
    .
    .
  </equipment>
  <extras>
    <extra id="" name="" price="" timeunit="" customquantity="1/0" validdatefrom=""
validdateto="" sailingdatefrom="" sailingdateto="" obligatory="1/0" perperson=""
includedinbaseprice="" payableoninvoice="1/0" availableinbase=""
includesdepositwaiver="" includedoptions=""></extra>
  </extras>
  <discounts>
    <discount id="" name="" percentage="" validdatefrom="" validdateto=""
```

```
sailingdatefrom="" sailingdateto="" validdaysfrom="" validdaysto="" discounttype=""
includedinbaseprice="" excludesotherdiscounts="1/0" affectedbymaximum="1/0"
availableinbase=""></discount>
.
.
</discounts>
</resource>
</root>
```

Each <resource /> element contains attributes describing the basic characteristics of the boat as well as sub-elements for prices, equipment, extras and discounts.

<resource /> element attributes are:

1. *id* – unique resource id
2. *gid* – generic id of the yacht model, used to uniquely identify the model type of the yacht
3. *name* – the name of the individual yacht
4. *base* – the unique id of the home base
5. *model* – the name of the model
6. *berths* – number of berths
7. *berthsext* – number of berths with the comment included
8. *year* – the build year of the boat
9. *length* – overall length (m)
10. *cabins* – the number of cabins
11. *cabinsext* – number of cabins with the comment included
12. *heads* – number of bathrooms / toilets
13. *watercapacity* – capacity of the water tank (l)
14. *fuelcapacity* – capacity of the fuel tank (l)
15. *engine* – engine type
16. *deposit* – security deposit for the yacht on check-in.
17. *commissionpercentage* – agency commission percentage for the yacht. Usually this number is same for all boats of the same provider.
18. *kind* – The kind of a vessel. This can be:
 1. Sail boat
 2. Motor boat
 3. Catamaran
 4. Gulet
 5. Motorsailer
 6. Motoryacht
 7. Other
19. *draught* – draught (m)

20. *beam* – beam (m)
21. *lengthatwaterline* – length at waterline (m)
22. *maximumdiscount* – maximum discount allowed for this yacht
23. *servicetype* – type of service. This can be:
 1. Bareboat
 2. Crewed
 3. Cabin
24. *discountshavesubtotals* – 1 if discounts have subtotals, 0 otherwise
25. *defaultcheckintime* – checkin hours time
26. *defaultcheckouttime* – checkout hours time
27. *calculateagencydiscountwithoutvat* – 1 if agency discount is calculated without VAT, 0 otherwise
28. *taxableamount* – taxable amount
29. *taxrate* – tax rate
30. *genericresourcetype* – name of the generic model assigned to the yacht
31. *defaultcheckinday* – default checkin day for this yachts: Sunday=1, Monday=2, Tuesday=3, Wednesday=4, Thursday=5, Friday=6, Saturday=7
32. *codeid* – user defined code for the yacht
33. *cgid* – concatenated generic yacht id containing generic id and number of cabins (generic id + number of cabins)
34. *companyid* – company owner of the yacht
35. *transitlog* – default end cleaning/transit log value for the boat
36. *defaultcleaningcost* – default cleaning cost for the boat
37. *shipyardid* – id of the shipyard (boat manufacturer)
38. *saleprice* – price if resource is on sale, empty if resource is not on sale
39. *requiredskipperlicense* – 1 if skipper license is required for this resource, 0 if not
40. *ownerid* – id of the yacht owner, -1 if yacht doesn't have an owner

<prices /><price /> sub-element attributes are:

1. *datefrom* – date when the price becomes valid (at 0:00h)
2. *dateto* – date until price is valid (at 0:00h)
3. *price* – the weekly price of the boat in the given period
4. *currency* – the currency of the price (EUR)

<images /><image /> sub-element attributes are:

1. *href* – direct URL of the boat image on the Booking Manager server
2. *comment* – description of the image

<equipment /><equipmentitem /> sub-element attributes are:

1. *id* – the unique id of the equipment item
2. *parentid* – id of the generic equipment item
3. *name* – the name of the equipment item
4. *categoryname* – the name of the equipment item category
5. *value* – the additional information about the equipment item (number of items, horse power, etc..)
6. *translationid* – key that should be used when requesting translation for this item

<extras /><extra /> sub-element attributes are:

1. *id* – unique id of the extra item
2. *name* – name of the extra item
3. *price* – price of the extra
4. *timeunit* – the timeunit in milliseconds for the extra item:
 - 0 - per booking
 - 86400000 – per day
 - 604800000 – per week
4. *customquantity* – flag to mark if the extra is charged per person (1 if it is per person, 0 if it is per booking)
5. *validdatefrom* – which the offer is valid
6. *validdateto* – date until the offer is valid
7. *sailingdatefrom* – the beginning of the sailing period for which the offer is valid
8. *sailingdateto* – the end of the sailing period for which the offer is valid
9. *obligatory* – 1 if the extra item is an obligatory item, 0 if it is an optional item
10. *perperson (DEPRECATED)* – 1 if the extra is counted per person, 0 if counted per booking
11. *includedinbaseprice* – 1 if this extra is already included in the base price of the yacht
12. *payableoninvoice* – 1 if this extra is payable on invoice and 0 if it is payable at the base
13. *availableinbase* – id of the base where this extra is available or -1 if it is available in all bases
14. *includesdepositwaiver* – 1 if this extra includes security deposit waiver

<discounts /><discount /> sub-element attributes are:

1. *id* – the unique id of the discount item
2. *name* – the name of the discount item
3. *percentage* – the percentage value of the discount item
4. *validdatefrom* – date from which the offer is valid
5. *validdateto* – date until the offer is valid
6. *sailingdatefrom* – the beginning of the sailing period for which the offer is valid

7. *sailingdateto* – the end of the sailing period for which the offer is valid
8. *validdaysfrom* – days before a charter when the offer starts being valid (for example 0 for 14 days last minute) . In case of the “service duration” discount type it marks minimum days for duration discount, (for example 14 for two week discount)
9. *validdaysto* – days before a charter when the offer ends being valid (for example 14 for 14 days last minute). In case of the “service duration” discount type it marks maximum days for duration discount, (for example 20 for two week discount)
10. *discounttype* – the type of the discount item which marks how the discount behaves:
 - 0 – Duration discount (two weeks, three weeks)
 - 1 – Reservation period (date of request)
 - 2 – Service period (date of sailing)
 - 3 – Last minute/early booking discount
11. *includedinbaseprice* – 1 if this discount is included in base price
12. *excludesotherdiscounts* – 1 if this discount excludes other discounts
13. *affectedbymaximum* – 1 if this discount is affected by maximum defined discount value
14. *availableinbase* – id of the base where this extra is available or -1 if it is available in all bases

6.3. Reservation details

```
<root>
  <reservation id="" resourceid="" baseprice="" comission="" totalprice=""
datefrom="" dateto="" status="" statusid="" userid="" code="" formattedcode=""
firstpaymentpercentage="" firstpaymentdays="" secondpaymentpercentage=""
secondpaymentdays="" termsofpayment="" bankingdetails="" optionexpirydate=""
remarks="">
    <extras>
        <extra id="" parentid="" name="" price="" />
        ...
    </extras>
    <discounts>
        <discount id="" parentid="" name="" value="" price="" />
        ...
    </discounts>
    <payments>
        <payment id="" />
        ...
    </payments>
    <crewmembers>
        <crewmember />
        ...
    </crewmembers>
</root>
```

Results are in form of one `<reservation />` element which contains basic reservation attributes as well as sub-elements for extras, discounts and payments:

`<reservation />` element attributes are:

1. *id* – the id of the reservation in the system
2. *resourceid* – the id of the boat
3. *baseprice* – the price of the boat from the pricelist
4. *comission* – the comission applied (in EUR)
5. *totalprice* – the final price after comission and discounts
6. *datefrom* – sailing start date
7. *dateto* – sailing end date
8. *status* – status of a booking (Option/Reservation/Owner week/Service/Canceled/Option expired) - DEPRECATED (use *statusid* field instead)
9. *statusid* – booking status id
10. *userid* – the id of the provider company
11. *code* – reservation code
12. *formattedcode* – formatted reservation code
13. *firstpaymentpercentage* – percentage for the first payment
14. *firstpaymentdays* – how many days after the confirmation should the first payment be made
15. *secondpaymentpercentage* – percentage for the second payment
16. *secondpaymentdays* – how many days before the charter should the second payment be made
17. *termsofpayment* – string containing terms of payment text
18. *bankingdetails* – string containing banking details text
19. *optionexpirydate* – date when option expires
20. *remarks* – reservation remarks

`<extras />``<extra />` sub-element attributes are:

1. *id* – the id of the reservation extra
2. *parentid* – parent id of the extra
3. *name* – name of the extra
4. *price* – defined price

`<discounts />``<discount />` sub-element attributes are:

1. *id* – the id of the reservation discount
2. *parentid* – parent id of the discount
3. *name* – name of the discount
4. *value* – percentage value of the discount
5. *price* – price after the discount

`<payments />``<payment />` sub-element attributes are:

1. *id* – the id of the payment

<crewmembers /> contains details for each crew member (Crew member details).

6.4. Payment details

```
<payment id="" value="" invoiceid="" paymentmethodid="" date="" currency=""
exchangerate="" comment="" bankcostvalue="" invoicedate="" stornodate=""
altcurrency="" altexchangerate="">
</payment>
```

Each “<payment />” section contains the following information about a specific payment:

1. *id* – id of the payment
2. *value* – payment amount
3. *invoiceid* – id of this advanced invoice
4. *paymentmethodid* – id of the payment method assigned to the payment
5. *date* – date when payment was created
6. *currency* – currency assigned to the payment
7. *exchangerate* – exchange rate of the currency
8. *comment* – additional comment
9. *bankcostvalue* – amount of transaction cost
10. *invoicedate* – date when invoice issued
11. *stornodate* – date when storno invoice issued
12. *altcurrency* – the alternative currency
13. *altexchangerate* – exchange rate of the alternative currency

6.5. User details

```
<user id="" codeid="">
  <property id="" name=""> </property>
  ...
</user>
```

Each “<user />” section contains the following information about a specific user:

1. *id* – id of the user
2. *codeid* – user code

Each user contains one or more properties which are described with id, name and a value.

<user /><property /> sub-element attributes are:

1. *id* – id of the property
2. *name* – name of the property

For changeable user properties please read Changeable user properties in Appendix.

6.6. Crew member details

```
<crewmember id="" isskipper="" statusid="" userid="">
  <property id="" name="" />
  ...
</crewmember>
```

Each “<crewmember />” section contains the following information about a specific crew member:

1. *id* – id of the crew member
2. *isskipper* – 1 if it is a skipper, 0 otherwise (DEPRECATED, use statusid instead)
3. *statusid* – status of the crew member: 1=skipper, 2=crew member, 3=passenger
4. *userid* – id of the user in the addressbook

For all available properties please read Changeable crewmember properties in Appendix.

6.7. To do note details

```
<todonote id="" description="" createddate="" iscompleted="" completeddate=""
  typeid="" scheduleddate="" >
</todonote>
```

Each “< todonote />” section contains the following information about a specific to do note:

1. *id* – id of the to do note
2. *description* – description of the to do note
3. *createddate* – date of creation
4. *iscompleted* – 1 if to do note is completed, 0 otherwise
5. *completeddate* – date of completion
6. *typeid* – type of to do note
 1. 0-todo
 2. 1-event
 3. 2-note
7. *scheduleddate* – date

For all available properties please read Changeable to do note properties in Appendix.

6.8. Changeable user properties

Here is the list of all available user properties that can be used to insert or update user in the address book.

Id	Name	Type	Id	Name	Type
codeid	Code id	Long	329	Remarks	String
301	First name	String	331	State/Country/Province	String

302	Last name	String	361	Option expire	Integer
303	Company name	String	363	Login disabled	Boolean
305	Address	String	364	Invoice to Guest	Boolean
306	Country	Long	365	Only from Saturday	Boolean
307	City	String	366	Charge tax	Boolean
308	Zip code	String	367	Tax office	String
309	E-mail	String	368	Skipper License number	String
310	Telephone 1	String	369	Skipper license issued by	String
311	Telephone 2	String	370	Title	String
312	Mobile 1	String	373	Skype Name	String
313	Mobile 2	String	374	Contacted by	String
314	Fax 1	String	375	Loyalty card number	String
315	Fax 2	String	376	Loyalty card year	String
316	VAT Code	String	377	Loyalty card date issued	Date
317	Language	String	378	Loyalty card date of expiration	Date
318	Birthday	Date	379	Date of creation	Date
319	Address 2	String	380	E-mail 2	String
320	User Discount	Float	381	Maximum number of concurrent options	Integer
321	Webiste	String	450	Affiliate enabled	Boolean
322	Birth Place	String	451	Cookie duration	String
323	Country of birth	Long	453	Commission on base price	Boolean
324	Citizenship	Long	454	Commission fixed amount	Float
325	Passwport Number	String	455	Commission percentage	Float
326	Visa Id	Long	456	Notification email	Boolean
328	Password	String	457	Separate commission invoice	Boolean

Examples how you should use these properties to set some user values:

```
<element id="codeid">12345</element>
<element id="301">John</element>
<element id="306">12</element>
<element id="455">10.0</element>
```

6.9. Changeable reservation properties

Here is the list of all available reservation properties that can be used to update reservation.

Id	Name	Type	Id	Name	Type
resourceid	Yacht id	Long	653	Exchange rate	Float
datefrom	Checkin date	Date	656	Invoice to guest	Boolean
dateto	Checkout date	Date	657	Internal remarks	String
optionexpirydate	Option expiry date	Date	660	Dont invoice options	Boolean
userid	Client id	Long	663	Free entry reservation	Boolean
basefrom	Checkin base	Long	665	Alternative exchange rate	Float
baseto	Checkout base	Long	666	Master invocie note	String
code	Code	Long	670	Default cleaning cost	Float
confirmationdate	Confirmation date	Date	671	Actual cleaning cost	Float
90	Remark	String	674	Checkout remarks	String
579	Default checkin time	String	679	Separate commission invoice	Boolean
580	Default checkout time	String	680	Commission invoice received	Boolean
622	Base booking price	Float	681	Owner bank cost	Float
636	Tax percentage	Float	1605	First payment percentage	Long
646	Terms of payment	String	1606	First payment days	Integer
648	Note	String	1607	Second payment percentage	Long
651	Invoice code	String	1608	Second payment days	Integer
652	Date value	Date	1613	Reservation number suffix	String

Examples how you should use these properties to set some reservation values:

```
<element id="code">1202</element>
<element id="579">17:00</element>
<element id="653">7.407</element>
<element id="1606">7</element>
```

6.10. Changeable payment properties

Here is the list of all available payment properties that can be used to update payment.

Id	Name	Type	Id	Name	Type
paymentmethodid	Payment method id	Long	comment	Comment	String
invoiceid	Invoice id	String	bankcostvalue	Bank cost value	Float
value	Value (amount)	Float	invoicedate	Invoice date	Date
date	Date	Date	stornodate	Storno date	Date
currency	Currency	Long	altcurrency	Alternative currency	Long
exchangerate	Exchange rate	Float	altexchangerate	Alternative exchange rate	Float

Examples how you should use these properties to set some reservation values:

```
<element id="invoiceid">132/2012</element>
<element id="value">580.0</element>
<element id="exchangerate">7.407</element>
<element id="bankcostvalue">12.5</element>
```

6.11. Changeable crewmember properties

Here is the list of all available crew member properties that can be used to update crew member.

Id	Name	Type	Id	Name	Type
329	Remarks	String	1313	Date of entry	Long
1302	Border crossing ID	String	1314	Visa expiry date	Date
1303	First name	String	1315	Residence	String
1304	Last name	String	1316	Former residence	String
1305	Date of birth	Date	1317	Date of application	Date
1306	City of birth	String	1318	Date of departure	Date
1307	Country of birth	Long	1319	Guest type	String
1309	Citizenship	Long	1320	Guest status	String

1310	Type of travel document	String	1322	Point of entry	String
1311	Travel document ID	String	1323	Skipper license	String
1312	Visa	Long			

Examples how you should use these properties to set some crew member values:

```
<element id="329">Requested satellite phone</element>
<element id="1303">John</element>
<element id="1304">Johnson</element>
<element id="1306">New York</element>
```

6.12. Changeable to do note properties

Here is the list of all available to do note properties that can be used to update to do note.

Id	Name	Type	Id	Name	Type
description	Description	String	completeddate	Completed date	Date
createddate	Created date	Date	typeid	Type id	int
iscompleted	Is completed	Boolean	scheduleddate	Scheduled date	Date

Examples how you should use these properties to set some to do note values:

```
<element id="description">Repair yacht</element>
<element id="typeid">0</element>
```

6.13. Available translation languages

Chinese (zh), Croatian (hr), Czech (cs), Dutch (nl), English (en), French (fr), German (de), Greek (el), Hungarian (hu), Italian (it), Lithuanian (lt), Norwegian (no), Polish (pl), Russian (ru), Serbian (sh), Slovak (sk), Slovenian (sl), Spanish (es), Swedish (sv), Turkish (tr).

7. Code examples

7.1. PHP

```
<?php

/**
 * MMKStruct - object with MMK call parameters, simple Array to in0,in1 etc. object
 properties as of definitions
 */
class MMKStruct {
    /**
     * constructor
     *
     * @param $a array of parameters
     * @ret void
     */
    public function __construct($a) {
        $i=0;
        foreach($a as $var=>$val) {
            $varName = 'in'.$i;
            $this->$varName = $val;
            $i++;
        }
    }
}

// specify url
$wsdl = 'http://www.booking-manager.com/cbm_web_service2/services/CBM?wsdl';

// load client with definitions
$soapClient = new SoapClient($wsdl, Array('trace'=>1));

try {
    $struct = new MMKStruct(Array(YOUR_COMPANY_ID,'YOUR_EMAIL_ADDRESS','YOUR_PASSWORD',
    '635', '2010', 'true', 0));

    $result = $soapClient->getAvailabilityInfo($struct);

    if (isset($result->out)) {
        $xml = $result->out;
        echo $xml;
    }
}

// catch exceptions
catch (Exception $e) {
    print_r($soapClient->__getLastRequest());
    print_r($soapClient->__getLastResponse());
    print_r($e->getTrace());
    var_dump($e);
}

?>
```

7.2. PHP with Curl

Users with 32bit PHP can have issues with long ID values which will overflow if number is too big. In case that you can't switch to 64bit PHP you can use Curl to create the request instead of using SoapClient object.

```
<?php
//use this to test iv curl is enabled, if it is not then you should enable it
//echo 'Curl: ', function_exists('curl_version') ? 'Enabled' : 'Disabled';

$soap_request = "<soapenv:Envelope
xmlns:soapenv=\"http://schemas.xmlsoap.org/soap/envelope/\"
xmlns:cbm=\"http://cbm.mmk.com\">\n";

$soap_request .= "<soapenv:Header/>\n";
$soap_request .= "<soapenv:Body>\n";
$soap_request .= "    <cbm:getBases>\n";
$soap_request .= "        <cbm:in0>YOUR_COMPANY_ID</cbm:in0>\n";
$soap_request .= "        <cbm:in1>YOUR_EMAIL_ADDRESS</cbm:in1>\n";
$soap_request .= "        <cbm:in2>YOUR_PASSWORD</cbm:in2>\n";
$soap_request .= "    </cbm:getBases>\n";
$soap_request .= "</soapenv:Body>\n";
$soap_request .= "</soapenv:Envelope>\n";

$header = array(
    "Content-type: text/xml;charset=\"utf-8\"",
    "Accept: text/xml",
    "Cache-Control: no-cache",
    "Pragma: no-cache",
    "SOAPAction: \"run\"",
    "Content-length: ".strlen($soap_request),
);

$soap_do = curl_init();
curl_setopt($soap_do, CURLOPT_URL, "http://www.booking-
manager.com/cbm_web_service2/services/CBM" );
curl_setopt($soap_do, CURLOPT_CONNECTTIMEOUT, 60);
curl_setopt($soap_do, CURLOPT_TIMEOUT, 60);
curl_setopt($soap_do, CURLOPT_RETURNTRANSFER, true );
curl_setopt($soap_do, CURLOPT_SSL_VERIFYPEER, false);
curl_setopt($soap_do, CURLOPT_SSL_VERIFYHOST, false);
curl_setopt($soap_do, CURLOPT_POST, true );
curl_setopt($soap_do, CURLOPT_POSTFIELDS, $soap_request);
```

```
curl_setopt($soap_do, CURLOPT_HTTPHEADER, $header);

$result = curl_exec($soap_do);
if($result === false) {
    $err = 'Curl error: ' . curl_error($soap_do);
    curl_close($soap_do);
    print $err;
} else {
    curl_close($soap_do);
    print $result;
}
?>
```

8. Document Changes

8.1. Version 1.16 (27.04.2016.)

New methods

- getResourcesDiscount (1.11)
- getSearchResultsFilter (1.7)

New parameters on existing methods

- getCountries (1.18)
 - <translations>

8.2. Version 1.15 (17.03.2016.)

New methods

- getTranslations (3.23)
- getCashRegister (2.6)

New parameters on existing methods

- getInvoices (2.1) - added parameters
 - reservationid=""

8.3. Version 1.14 (08.12.2015.)

New parameters on existing methods

- createReservation (1.12) - added parameters
 - statusid=""
- getResourceDiscount (1.10) - added parameters
 - price=""
- isResourceAvailable(1.9) -added parameters
 - status=""

8.4. Version 1.13 (18.11.2015.)

New methods

- getUserDetails (3.4)

New parameters on existing methods

- Resource details (6.2) - added parameters
 - ownerid=""
- Crew member details (6.6) - added parameters
 - statusid="", userid=""

New elements on existing methods

- Reservation details (6.3) - added element
 - <crewmembers>

8.5. Version 1.12 (15.06.2015.)

New parameters on existing methods

- getInvoices (2.1) - added parameters
 - relatedreservationid=""

8.6. Version 1.11 (18.03.2015.)

New methods

- getSpecialOffers (1.8)
- getResourceDiscount (1.10)
- getResourceDetails (1.3)
- Resource details (6.2) - extracted list of resource details to single place because it will be used as a return string for both getResourceDetails and getResources methods
- getShipyards (1.19)

New parameters on existing methods

- getSearchResults (1.6) - added parameters

- datefrom="" dateto=""
- basetoid=""
- Resource details (6.2) - added parameters
 - shipyardid="", saleprice="", requiredskipperlicense="", extras.includedoptions=""
- getBases (1.16) - added parameters
 - countryid=""

8.7. Version 1.10 (28.03.2014.)

New methods

- getShortAvailabilityInfo (1.5)

New parameters on existing methods

- getResources (1.2) - added parameters
 - cgid="" companyid=""

8.8. Version 1.9 (01.10.2013.)

New Parameters on existing methods

- getBases (1.16)
 - inside <base> tag new attributes "longitude" , "latitude"

8.9. Version 1.8 (27.05.2013.)

New methods

- isResourceAvailable(1.9)
- getEquipmentCategories (1.19)
- getActiveReservation(3.16)
- getReservationGuest (3.17)
- getToDoNotes (3.19)
- insertToDoNote (3.20)

- updateToDoNote (3.21)
- deleteToDoNote (3.22)
- Duration discount (6.7)
- Changeable to do note properties (6.12)

New parameters on existing methods

- getResources (1.2) - added parameters
 - berthsex="" discountshavesubtotals="" defaultcheckintime="" defaultcheckouttime="" calculateagencydiscountwithoutvat="" taxableamount="" taxrate="" genericresourcetypename=""
 - inside <equipment> tag new attributes "parentid" "categoryname"
 - inside <extras> tag new attribute "availableinbase"
 - inside <discount> tag new attribute availableinbase=""
- getCompanies (1.1) - new attribute: "availability=""
- getReservations (2) (Error: Reference source not found) - new attribute: code=""
- getInvoices (Error: Reference source not found)
 - inside <invoice>tag new attribute rate=""
 - added services tags <services><service name="" total="" rate="" /></services>