

# From PFL to DFL

---

Eyes on the prize



# Prediction and Optimization in the Wild

Real world problems typically rely on **estimated parameters**

E.g. travel times, demands, item weights/costs...



However, sometimes we have access to **a bit more information**



# Prediction and Optimization in the Wild

Take **traffic-dependent travel times** as an example

If we know the **time of the day** we can probably estimate them better



Let's see how these problems are often addressed



# Predict...

First, we train **an estimator for the problem parameters**:

$$\theta^* = \operatorname{argmin}_{\theta} \{ \mathbb{E}_{(x,y) \sim P(X,Y)} [L(y, \hat{y})] \mid \hat{y} = h(x, \theta) \}$$

- $L$  is the single-example loss (typically a likelihood)
- $h$  is the estimator, with parameter vector  $\theta$
- $P(X, Y)$  is the data distribution
- ...Which will typically be approximated via a sample (training set)

**In our example:**

- $x$  would be the time of the day
- $y$  would be a vector of travel times



## ...Then Optimize

Then, we **solve the optimization problem** with the estimated parameters

$$z^*(y) = \operatorname{argmin}_z \{ f(z, y) \mid z \in F \}$$

- $z$  is the vector of variables of the optimization problem
- $f$  is the cost function
- $F$  is the feasible space
- In general, both  $y$  and  $F$  may depend on the estimated parameters

### In our example


- $z$  may represent routing decisions
- $f$  may be the total travel time
- $F$  may encode a deadline constraint





# Inference

This setup involves using the estimator and the optimizer in sequence



At inference time:

- We observe  $x$
- We evaluate our estimator  $h(x; \theta)$  to obtain  $\hat{y}$
- We solve the problem to obtain  $z^*(\hat{y})$

**Overall, the process consists in evaluating:**

$$z^*(h(x; \theta))$$



# Prediction Focused Learning

**This two-stage approach used to have no name at all**

These days, it is referred to as:

- Predict, then Optimization
- ...Or Prediction Focused Learning

**PFL has several favorable properties:**

- It's easy to implement
- ...It has good scalability
- ...And it's asymptotically correct (perfect predictions result in minimum cost)

Application fields include logistics, planning, finance, etc.



However, the method has also a significant flaw  
One that was only recently emphasized





# A Toy Problem

Let's see this in action on a toy problem

Consider this two-variable optimization problem:

$$\operatorname{argmin}_z \{ y_0 z_0 + y_1 z_1 \mid z_0 + z_1 = 1, z \in \{0, 1\}^2 \}$$

Let's assume that the true relation between  $\mathbf{x}$  (a scalar) and  $\mathbf{y}$  is:

$$y_0 = 2.5x^2$$

$$y_1 = 0.3 + 0.8x$$

...But that we can only learn the following ML model with a scalar weight  $\theta$ :

$$\hat{y}_0 = \theta^2 x$$

$$\hat{y}_1 = 0.5\theta$$


 Our model cannot represent the true relation exactly

# Spotting Trouble

This is what we get from supervised learning with uniformly distributed data:

```
In [21]: util.draw(w=None, figsize=figsize, model=1)
```

Optimized theta: 1.375



- The crossing point of the grey lines is where we should pick item 0 instead of 1
- The orange lines (trained model) miss it by a wide margin




Hence, if we optimize based on our best predictions,  
we make mistakes!  
...But why is this happening?



# Misaligned Objectives

We trained for **maximum accuracy** regardless of the decision cost!

```
In [22]: util.draw(w=0.91, figsize=figsize, model=1)
```



- However, if we focus on choosing  $\theta$  to **match the crossing point**
- ...The same model can lead the optimizer consistently to the correct choice



We just need to train for minimal decision cost,  
which is key idea in Decision Focused Learning



# Getting Started

We'll start with the setup considered in one of the DFL seminal papers

We consider an optimization problem in the form:

$$z^*(y) = \operatorname{argmin}_z \{y^T z \mid z \in F\}$$

- $z$  is the set of decisions
- $F$  is the feasible space
- $y$  is a cost vector

The  $y$  parameters **cannot be measured**

...But they depend on some observable  $x$

- And both can be represented as random variables with a joint distribution:

$$X, Y \sim P(X, Y)$$



# Getting Started

So, in practice we can estimate  $y$  via a ML model

$$\hat{y} = h(x; \theta)$$

...And at inference time we get our decisions by computing:

$$z^*(h(x; \theta))$$

I.e. exactly as in Prediction Focused Learning

**The key assumption is the use of a linear cost function**

...And the lack of dependence of the constraints on  $y$

- The constraint can otherwise be anything (including integrality)
- ...And they could also depend on the observable, i.e.  $F \equiv F(x)$





# The Main DFL Idea

The key difference between PFL and DFL is **the training process**

...Which in DFL is done by minimizing a **decision cost**, i.e. by solving:

$$\theta^* = \operatorname{argmin}_{\theta} \{ \mathbb{E}_{(x,y) \sim P(X,Y)} [\operatorname{regret}(y, \hat{y})] \mid \hat{y} = h(x, \theta) \}$$

Where in our setting we have:

$$\operatorname{regret}(y, \hat{y}) = y^T z^*(\hat{y}) - y^T z^*(y)$$

- $z^*(\hat{y})$  is the best solution with the **estimated** costs
- $z^*(y)$  is the best solution with the **true** costs

Intuitively, we want to **loose as little as possible** w.r.t. the best we could do




**One of the main challenges in DFL is dealing with  
this loss**



# Knowing Regret

To see this, let's push our example a little further

```
In [23]: x = util.normal_sample_(mean=0.54, std=0.2, size=1000)  
util.plot_histogram(x, figsize=figsize, label='x')
```




- Say we have access to a normally distributed collection of  $x$  values
- ...And to the corresponding true values  $y$



# Knowing Regret

This is how the regret looks like for a single example

```
In [24]: util.draw_loss_landscape(losses=[util.RegretLoss()], model=1, seed=42, batch_size=1, figsize=(10, 5))
```




- If  $f(x, \theta)$  leads to the correct decision, the regret is 0
- Otherwise we have some non-null value



# Knowing Regret

...And this is the same for a larger sample

```
In [25]: util.draw_loss_landscape(losses=[util.RegretLoss()], model=1, seed=42, batch_size=64, figsi
```



This function breaks havoc with gradient descent, for **two main reasons**



# What's Wrong with Regret (1)

As a first issue, the loss is **not inherently differentiable**

Given:

$$\text{regret}(y, \hat{y}) = y^T z^*(\hat{y}) - y^T z^*(y) \quad \text{with: } \hat{y} = h(x; \theta)$$

The derivative chain:

$$\frac{\partial \text{regret}}{\partial \theta} = \frac{\partial \text{regret}}{\partial z^*} \frac{\partial z^*}{\partial \hat{y}} \frac{\partial \hat{y}}{\partial \theta}$$

...Contains a term that is based on an **argmin** operator

- For this reason, computing the derivative might be tricky
- ...And for some  $\hat{y}$  values a derivative might not be defined at all




# What's Wrong with Regret (2)

Second, when the derivative exists, it might be **useless**

E.g. for combinatorial and linear problems, regret will be **piecewise constant**

```
In [26]: util.draw_loss_landscape(losses=[util.RegretLoss()], model=1, seed=42, batch_size=1, figsize=(10, 5))
```



When the derivative is defined, **its value is 0**





# Self-Contrastive Loss

These issues have been addressed in multiple ways

Here we'll start with the idea of **changing perspective**

- In particular, any prediction vector  $\hat{y}$  defines a cost function:

$$\hat{y}^T z$$

- ...Which will lead the solver toward the optimal solution:

$$z^*(\hat{y})$$



# Self-Contrastive Loss

These issues have been addressed in multiple ways

Here we'll start with the idea of **changing perspective**

- In particular, any prediction vector  $\hat{y}$  defines a cost function:

$$\hat{y}^T z$$

- ...Which will lead the solver toward the optimal solution:

$$z^*(\hat{y})$$

**Given an example  $(x, y)$ , for a **good** prediction vector  $\hat{y}$**

- The cost of the **true** optimal solution  $z^*(y)$
- ...Should not be worse than the cost of the **"estimated"** optimal solution  $z^*(\hat{y})$



## Self-Contrastive Loss

Hence we can think of using as a **surrogate loss** the difference:

$$\hat{y}^T z^*(y) - \hat{y}^T z^*(\hat{y})$$

It represents "how wrong" the estimated cost function is w.r.t. the true one

- It contains a naturally differentiable term (i.e.  $\hat{y}$ )
- It is not constant, even when  $z^*$  is piecewise constant

**The gradient represents the difference between the optimal solutions:**

$$\nabla \left( \hat{y}^T z^*(y) - \hat{y}^T z^*(\hat{y}) \right) = z^*(y) - z^*(\hat{y})$$

In the DFL literature, this is known as **self-contrastive loss**




# Limitations of the Self-Contrastive Loss

**However, the self-contrastive loss has some significant limitations**

Here's how it looks for one example in our toy problem:


```
In [27]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SelfContrastiveLoss()], model=1, se
```



# Limitations of the Self-Contrastive Loss

Here's the plot for multiple examples

```
In [28]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SelfContrastiveLoss()], model=1, se
```




There's a problem here! **Can you see which one?**



# Limitations of the Self-Contrastive Loss

There's **a spurious minimum!**

```
In [29]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SelfContrastiveLoss()], model=1, se
```



At training time, there's a chance of reaching **the wrong minimum!**



## SPO+ Loss

**A well-known DFL approach can be seen as solution for this issue**

I.e. the SPO+ loss from [1], which can be defined as:

$$\text{spo}^+(y, \hat{y}) = \hat{y}_{spo}^T z^*(y) - \hat{y}_{spo}^T z^*(\hat{y}_{spo}) \quad \text{with:} \quad \hat{y}_{spo} = 2\hat{y} - y$$

- The structure is the same as the self-contrastive loss
- ...But **at training time** we compute it w.r.t. a modified prediction vector

**At inference time we behave as usual, i.e. we solve:**

$$z^*(\hat{y}) \quad \text{with:} \quad \hat{y} = h(x; \theta)$$

[1] Elmachoub, Adam N., and Paul Grigas. "Smart "predict, then optimize"." *Management Science* 68.1 (2022): 9-26.






# SPO+ Loss

This is the SPO+ loss for a single example on our toy problem

```
In [30]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SPOPlusLoss()], model=1, seed=42, l
```




- Like in the self-contrastive case, there are two local minima



# SPO+ Loss

This is the SPO+ loss for a **two examples**

```
In [31]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SPOPlusLoss()], model=1, seed=42, l
```




- The "good" local minima for both examples are roughly in the same place
- The "spurious" local minima fall in different position



# SPO+ Loss

Over many examples, the spurious local minima tend to cancel out

```
In [32]: util.draw_loss_landscape(losses=[util.RegretLoss(), util.SPOPlusLoss()], model=1, seed=42, l
```



- This effect is *invaluable* when training with gradient descent



**Let's see the approach in action on a single problem**



## A (Slightly) More Complex Example

We will consider an optimization problem in this form:

$$z^*(y) = \operatorname{argmin}\{y^T z \mid v^T z \geq r, z \in \{0, 1\}^n\}$$

- We need to decide which of a set of jobs to accept
- Accepting a job ( $z_j = 1$ ) provides immediate value  $v_j$
- The cost  $y_j$  of the job is not known
- ...But it can be estimated based on available data

```
In [33]: nitems, rel_req, seed = 20, 0.5, 42
prb = util.generate_problem(nitems=nitems, rel_req=rel_req, seed=seed)
display(prb)


ProductionProblem(values=[1.14981605 1.38028572 1.29279758 1.23946339 1.06240746 1.0623978
1
1.02323344 1.34647046 1.240446 1.28322903 1.0082338 1.38796394
1.33297706 1.08493564 1.07272999 1.0733618 1.1216969 1.20990257
1.17277801 1.11649166], requirement=11.830809153591138)
```



# A (Slightly) More Complex Example

Next, we generate some training (and test) data

```
In [34]: data_tr = util.generate_costs(nsamples=350, nitems=nitems, seed=seed, noise_scale=0, noise_
data_ts = util.generate_costs(nsamples=150, nitems=nitems, seed=seed, sampling_seed=seed+1,
util.plot_df_cols(data_tr, figsize=figsize, title='Training Set')
```




- We assume that costs can be estimated based on an scalar observable  $x$
- The set of least expensive jobs changes considerably with  $x$



# Prediction Focused Approach

As a baseline, we'll consider a basic prediction-focused approach

```
In [35]: pfl = util.build_ml_model(input_size=1, output_size=nitems, hidden=[], name='pfl_det', output_size=nitems)
history = util.train_ml_model(pfl, data_tr.index.values, data_tr.values, epochs=1000, loss='mse')
util.plot_training_history(history, figsize=figsize_narrow, print_scores=False, print_time=True)
util.print_ml_metrics(pfl, data_tr.index.values, data_tr.values, label='training')
util.print_ml_metrics(pfl, data_ts.index.values, data_ts.values, label='test')
```



Training time: 7.0220 sec  
R2: 0.86, MAE: 0.086, RMSE: 0.10 (training)  
R2: 0.86, MAE: 0.087, RMSE: 0.10 (test)

- The ML model is just a linear regressor, but it is decently accurate






# Prediction Focused Approach

...But our true evaluation should be in terms of regret

```
In [36]: r_tr = util.compute_regret(prb, pfl, data_tr.index.values, data_tr.values)
r_ts = util.compute_regret(prb, pfl, data_ts.index.values, data_ts.values)
util.plot_histogram(r_tr, figsize=figsize, label='training', data2=r_ts, label2='test', pri
```



Mean: 0.052 (training), 0.052 (test)


- In this case, the average **relative** regret is ~5%



# A Decision Focused Learning Approach

Next, we train a DFL approach

```
In [37]: spo = util.build_dfl_ml_model(input_size=1, output_size=nitems, problem=prb, hidden=[], name='spo')
history = util.train_dfl_model(spo, data_tr.index.values, data_tr.values, epochs=200, verbose=True)
util.plot_training_history(history, figsize=figsize_narrow, print_scores=False, print_time=True)
util.print_ml_metrics(spo, data_tr.index.values, data_tr.values, label='training')
util.print_ml_metrics(spo, data_ts.index.values, data_ts.values, label='test')
```



Training time: 94.6590 sec  
R2: -0.24, MAE: 0.23, RMSE: 0.28 (training)  
R2: -0.23, MAE: 0.23, RMSE: 0.27 (test)


In terms of accuracy, this is considerably worse



# Comparing Regrets

But the regret is so much better!

```
In [38]: r_ts_spo = util.compute_regret(prb, spo, data_ts.index.values, data_ts.values)
util.plot_histogram(r_ts_spo, figsize=figsize, label='spo', data2=r_ts, label2='pfl', print_
```



Mean: 0.005 (spo), 0.052 (pfl)

This is the kind of result that attracted so much attention since [2]

[2] Donti, Priya, Brandon Amos, and J. Zico Kolter. "Task-based end-to-end model learning in stochastic optimization." *Advances in neural information processing systems* 30 (2017).

