

Homework 5: Deep Learning

Due June 16, beginning of exercise session

Kristian Kersting, Alejandro Molina
{kersting, molina}@cs.tu-darmstadt.de

upload link: <https://www.dropbox.com/request/OEyNaA11EGyiexfyadSa>

In this homework, you will use a neural network to classify MNIST!. Probably the most famous dataset in the deep learning community¹.

MNIST is a collection of images of handwritten digits. The task here is to classify an image into the correct digits.

You are to train a neural network on the train datasets (X_{train}, Y_{train}) and then use the test datasets (X_{test}, Y_{test}) to make predictions.

X datasets contain the image data, the Y s are the labels.

1. Implement an NN with 2-hidden layers (you get to decide on the size) and a 1-output layer of size 10 (each output represents a class). Feel free to use any DL framework.

To train this network, you have to use one-hot-encoding. That is, you convert your numerical label into a vector of 10 dimensions that is all zeros, except for one value that contains a one in the position of the value of the label.

$0 \rightarrow [1, 0, 0, 0, 0, 0, 0, 0, 0, 0]$

$1 \rightarrow [0, 1, 0, 0, 0, 0, 0, 0, 0, 0]$

\vdots

$8 \rightarrow [0, 0, 0, 0, 0, 0, 0, 0, 1, 0]$

$9 \rightarrow [0, 0, 0, 0, 0, 0, 0, 0, 0, 1]$

Use sigmoid activation functions and square error loss function 1.

$$\mathcal{L}(\theta; \mathbf{x}, \mathbf{y}) = \frac{1}{M} \sum_{n=1}^M \frac{1}{2} \|f_{NN}(\mathbf{x}_n) - \mathbf{y}_n\|^2 \quad (1)$$

2. Obtain the predicted class by finding the output neuron with the highest value.

¹<http://yann.lecun.com/exdb/mnist/>

Use the following code to obtain the training and test datasets as well as to compute the classification reports:

```
from sklearn.metrics import classification_report , confusion_matrix
from sklearn.model_selection import train_test_split
from sklearn.datasets import fetch_mldata
from sklearn.preprocessing import StandardScaler
from sklearn.utils import check_random_state

mnist = fetch_mldata( 'MNIST_original' )
X = mnist.data.astype( 'float64' )
y = mnist.target
random_state = check_random_state(0)

X_train , X_test , y_train , y_test = train_test_split(X, y,
    train_size=1000, test_size=300, random_state=random_state)

scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)

expected = y_test
predicted = y_test # here, use a NN to make predictions

print( " Classification_report:" )
print( classification_report( expected , predicted ) )
print( " Confusion_matrix:" )
print( confusion_matrix( expected , predicted ) )
```