Machine Learning For Design

Lecture 3 - Machine Learning for Images

Alessandro Bozzon

16/02/2022

mlfd-io@tudelft.nl
www.ml4design.com

Admin

Week 2 Tasks

Previously, on ML4D….



Credits: B. Timmermans, Z. Szlavik

Classification / Regression

Classification

- Learn to output a **category** label
  - Binary (e.g. Spam / not Spam, Cat / not cat)
  - Multi-class (e.g. cat, dog, bird)

Regression

- Learn to guess one or more numbers
  - e.g. value of a share, number of stars in a review



Images

- Visual content acquired through cameras, scanners, etc.
- Each pixel in an image is a feature
  - But spatially and geometrically organised
  - e.g. edges, corners
- Feature values are numerical values across channels
  - e.g. R,G,B
- Dimensionality —> n x m



Image →

P(1,1)	P(2,1)	P(3,1)	...	P(n,m)	Class
255, 0, 0	255, 1, 1	255, 0, 0		R,G,B	Cat
255, 213, 0	255, 213, 1	255, 213, 4		R,G,B	Dog
					Cat
					Duck

More in Module 1

A bit more on regression and classification

And your very first contact with (deep) neural networks

Linear Regression /1



Linear Regression /2



Linear Regression

Intercept (parameter, or **weight**)

Slope (parameter, or **weight**)

Dependent Variable → **Cost = *a* + *b* Size** ← Independent Variable



Cost = *b* Size



Cost = *b* Size

predicted value - actual value

Fit$_1$:



b **= 0.05**

Error$_1$:

Cost = *b* Size

***b* = 0.2**



Error1:

Error2:

Data Item

$$Error = \frac{1}{2d}\sum_{i=1}^{d}(Prediction_i - Value_i)^2$$

Mean Squared Error (MSE)

Current data item

Finding the best parameter values (training the model)

- **Gradient descent**





- **Hyperparameters**
  - **Learning Rate**: “speed” of descent
  - **Epochs**: max number of steps

Polynomial Regression

N^{th} degree polynomial → **Cost = *a* + *b* Size + c Size^2 + …. + *w* Size^n**



Classification



Classification



Classification



Logistic Regression






Error: 2


Error: 2


Error: 1


Error: 0


Math
10
9
8
7
6
5
4
3
2
1
Test
1
2
3
4
5
6
7
8
9
10


Math
10
9
8
7
6
5
4
3
2
1
Test
1
2
3
4
5
6
7
8
9
10


Math
10
9
8
7
6
5
4
3
2
1
Test
1
2
3
4
5
6
7
8
9
10


Math
10
9
8
7
6
5
4
3
2
1
Test
1
2
3
4
5
6
7
8
9
10

Neural Network





Neural Network



Neuron



Perceptron

Perceptron


Inputs
Weights
Activation function
Output
x_1
x_2
x_3
1
3
−2
4
2
Bias
$\hat{y} = \sigma(3x_1 - 2x_2 + 4x_3 + 2)$

Perceptron

Cost = *a* + *b* Size

Remember our linear regression function?
It can be represented with a perceptron having a single input and a bias



Perceptron

Cost = *a* + *b* Size

Remember our linear regression function? It can be represented with a perceptron having a single input and a bias







Neural Network



Neural Network



Neural Network



Neural Network





Neural Network





Fully Conected Neural Network



- **Hyperparameters**
  - Learning rate
  - Number of epochs
  - Architecture
    - # layers, #nodes, activation functions
  - Batch vs. mini-batch vs. stochastic gradient descent
  - Regularization parameters:
  - Dropout probability p

Advanced, not covered

Classifying into multiple classes - softmax function

- Return a probability for **each class**
  - Imagine example C_1= *ADMITTED*, C_2 = *NOT ADMITTED*, C_3 = *NEW TEST*
  - $p(C_1) = 0.37$, $p(C_2) = 0,21$, $p(C_3) = 0,42$
- We use the Softmax activation function for the output layer



$$\text{Softmax}(x_i) = \frac{e^{(x_i)}}{\sum_j^K e^{(x_j)}}$$

Value of class *i*

Normalisation term on K classes



https://playground.tensorflow.org/

Machine Learning and Images


What do you see?
TRUMP
TRUMP


This is what a computer “sees”

Images



- Each pixel in an image is a feature
- Dimensionality
  - n x m
- Feature (pixel) values are numerical
  - 0 or 1 for Black and White
  - Between 0 and 255 for greyscale
  - 16M values for RGB

Computer Vision

- Building algorithms that can “understand” the content of images and use it for other applications
- It is a “Strong AI” problem
  - signal-to-symbol conversion
  - The **semantic gap**

- A general-purpose vision system requires
  - Flexible, robust visual representatation
    - Updated and maintaned
  - Reasoning
  - Interfacing with attention goals, and plans

- What specific tasks can we train a CV system to perform?






Is this a flag?
(Recognition / Classification)
TRUMP
TRUMP


Where are the people?
(Recognition/Classification)


truck
person
person
person
car
person
person
motorbike
car
motorbike




World's Largest Selfie ©
Powered by Lumia 730


https://demo.morphcast.com/sdk-features/index.html?video=https%3A%2F%2Fdemo.morphc
MORPHCAST
AFFECT
EMOTION
LIKELY AGE
100
90
80
70
60
50
40
30
20
10
0
Get now AI HTML5 SDK
Choose your camera:
Camera 1
Camera 2
Camera 3
19.1 fps
GDPR COMPLIANT
Fully protects your privacy
No recording
No storing of biometric data
All images overwritten in 100 MS
FEATURES
Obstructive
Contemptuous
Disgusted
Frustrated
ACTIVATION
Active / Aroused
Passive / Calm
DEACTIVATION
Negative
UNPLEASANT
Positive
PLEASANT
Low power / Control
High Power / Control
Obstructive
Conductive
bellicose
hostile
ALARMED
TENSE
hateful
envious
AFRAID
ANGRY
defiant
enraged
contemptuous
ANNOYED
DISTRESSED
jealous
disgusted
indignant
loathing
FRUSTRATED
discontented
bitter
suspicious
impatient
insulted
distrustful
startled
disappointed
MISERABLE
dissatisfied
apathetic
taken aback
worried
uncomfortable
SAD
despondent
feel guilt
GLOOMY
DEPRESSED
desperate
ashamed
languid
embarrassed
melancholic
wavering
hesitant
BORED
anxious
dejected
DROOPY
doubtful
TIRED
SLEEPY
AROUSED
ASTONISHED
adventurous
lusting
triumphant
EXCITED
conceited
ambitious
self confident
courageous
feeling superior
convinced
DELIGHTED
enthusiastic
light hearted
determined
amused
passionate
HAPPY
joyous
expectant
interested
impressed
feel well
PLEASED
amorous
GLAD
confident
hopeful
longing
attentive
solemn
SERENE
CONTENT
pensive
contemplative
friendly
AT EASE
SATISFIED
serious
polite
RELAXED
CALM
conscientious
peaceful
compassionate
reverent
nervous
alert
excited
stressed
elated
sad
happy
contented
depressed
serene
bored
relaxed
fatigued
calm


Is this Jeff?
(Identification)
TRUMP
TRUMP




WA
USA
WASHINGTON
DRIVER LICENSE
FEDERAL LIMITS APPLY
4d LIC# WDLABCD456DG
9 CLASS
DONOR
1 TALBOT
2 LIAM R.
3 DOB 01/06/1958
4a ISS 01/06/2015
8 123 STREET ADDRESS
YOUR CITY WA 99999-1234
15 SEX M
16 HGT 5'-08"
12 RESTRICTIONS B
18 EYES BLU
17 WGT 165 lb
9a END L
4b EXP 08/12/2020
5 DDWDLABCD456DG1234567XX1101
Veteran
REV 07/01/2018


撮影画像
登録済画像
対象人物
撮影画像
登録済画像
対象人物
撮影画像
登録済画像
対象人物
撮影画像
登録済画像
対象人物


Is this the Wollman Rink?
(Identification)
TRUMP
TRUMP


8:00
Google Lens
Coit Tower
Text selection
Coit Tower
4.4 2287 Reviews


23:19
App Store
Google Lens
DELFT
DESIGN
GUIDE
PERSPECTIVES - MODELS - APPROACHES
BISPUBLISHERS
Translate
Text
Search
Homework
Shoppin
Delft Design Guide: Design Strategies and Methods
Book
Search



What is in the scene?
(Semantic Segmentation)



https://github.com/matterport/Mask_RCNN

Project Sunroof

https://www.google.com/get/sunroof


What type of scene is it?
(Scene Categorisation)
Outdoor, City, Park
TRUMP
TRUMP



darkest forest path | wintering forest path | greener forest path



rocky coast | misty coast | sunny coast

Predictions:

- **Type of environment:** outdoor
- **Scene categories:** skyscraper (0.704), downtown (0.211)
- **Scene attributes:** man-made, vertical components, open area, natural light, clouds, no horizon, metal, glass, sunny
- **Informative region for predicting the category *skyscraper* is:**

Hugging Face | Search models, datasets, users... | Models | Datasets | Spaces | Docs | Solutions | Pricing

Spaces: OFA-Sys / OFA-Image_Caption | like 12 | Running

App | Files and versions

OFA-Image_Caption

Gradio Demo for OFA-Image_Caption. Upload your own image or click any one of the examples, and click "Submit" and then wait for the generated caption.

Image

Caption 8.28s

people skating on a rink in a city park with skyscrapers

Clear | Submit


What are these people doing?
(Activity / event recognition)
Skating
TRUMP
TRUMP


TRUMP
TRUMP


How are people moving?
(Pose estimation)



Ethical task tracking of operators in agile manufacturing

http://resolver.tudelft.nl/uuid:3408e8c3-809b-436d-94eb-efb4f0532b17

Stereolabs ZED Camera

- 3D Object Detection
- Body tracking
- Positional tracking



https://www.stereolabs.com/docs/object-detection/

https://www.stereolabs.com/docs/body-tracking/


Are these images of the same person?
(Image / Face Similarity)
Bonus if you guess the movie!





Image search results







Machine Learning For Design

Lecture 3 - Machine Learning for Images

Alessandro Bozzon

16/02/2022

mlfd-io@tudelft.nl
www.ml4design.com

Credits

- CMU Computer Vision course - Matthew O’Toole. http://16385.courses.cs.cmu.edu/spring2022/