

pairadigm: A Python Library for Concept-Guided Chain-of-Thought Pairwise Measurement of Scalar Constructs Using Large Language Models

Michael Leon Chrzan
Center for Educational Data Science and Innovation
University of Maryland
College Park MD USA
ORCID: 0009-0004-0957-3857

17 December 2025

Summary

Measurement in the social sciences and Natural Language Processing (NLP) often relies on converting unstructured text into quantitative scales. While Large Language Models (LLMs) have demonstrated a possible ability to annotate text, they frequently struggle with reliably and consistently doing so, especially when providing direct scalar ratings (e.g., “Rate this text 1-5 for incivility”), due to calibration issues and lack of consistency. Pairwise comparison—determining which of two items exhibits more of a specific trait—is a robust psychometric alternative that has been shown to reduce cognitive load and improves reliability in humans (Thurstone 1927) and now has shown promise in helping improve LLM annotations as well.

pairadigm is a Python library designed to streamline the creation of high-quality, continuous measurement scales from text using LLMs. It implements a **Concept-Guided Chain-of-Thought (CGCoT)** methodology to generate reasoned pairwise comparisons using state-of-the-art LLMs (e.g., Google Gemini, OpenAI GPTs, Anthropic Claude, and open source models) (Wu et al. 2024). It then converts these comparisons into continuous scores using the Bradley-Terry model (Bradley and Terry 1952) and provides a pipeline both evaluate LLM score using human annotations and to fine-tune efficient encoder models (e.g., ModernBERT) as reward models for scaling measurement to larger datasets.

Statement of Need

Researchers in computational social science, psychology, education, and NLP frequently need to measure abstract constructs (e.g., “politeness,” “toxicity,” “creativity,” “reasoning”) in large corpora. Existing workflows often require stitching together disparate tools for: 1. Interfacing with LLM APIs. 2. Managing pairwise comparison logistics. 3. Calculating psychometric scores. 4. Validating results against human labels. 5. Training downstream classifiers.

pairadigm unifies these steps into a single, object-oriented workflow. It fills a gap between general-purpose LLM libraries and specialized psychometric tools (like **choix**). Specifically, it allows researchers to:

- **Generate High-Fidelity Data:** Use the **LLMClient** to drive diverse backends (Google, OpenAI, Anthropic, Ollama, HuggingFace) with a unified interface for chain-of-thought reasoning.
- **Validate Rigorously:** The library includes built-in methods for assessing transitivity violations, calculating reliabilities, and performing sensitivity analysis to detect model brittleness. These methods will continue to be updated as new validation techniques emerge in the literature.

- **Align with Humans:** It provides methods to include or append human gold-standard labels into the workflow to compute LLM-Human alignment and Inter-Rater Reliability (IRR) (Cohen 1960).
- **Scale Efficiently:** The `RewardModel` class implements a complete training loop to distill the LLM's pairwise preferences into a localized BERT-based model (following the InstructGPT reward modeling approach (Ouyang et al. 2022)), allowing for the cost-effective scoring of millions of documents without further API calls.

Functionality and Architecture

The package is structured around two primary modules: `core` and `model`.

The Core Paradigm

The `Pairadigm` class manages the measurement lifecycle. It handles data ingestion and executes pairwise comparisons using LLM clients and scores those annotations using a Bradley-Terry model. A key innovation is the integration of Concept-Guided Chain-of-Thought prompting, where the LLM must articulate its reasoning based on a researcher-designed prompts to critically evaluate the text before making the binary choice.

Installation

```
# For development version
pip install git+https://github.com/mlchrzan/pairadigm.git
```

```
# For latest stable release
pip install pairadigm
```

Here is an example workflow for measuring emotional valence in text using EMOBANK scores (Buechel and Hahn 2022) using GPT-5.1 in `pairadigm`:

```
import pairadigm as pdm
import pandas as pd
import os
import dotenv
dotenv.load_dotenv()

# NOTE: This example uses the EMOBANK dataset for measuring emotional valence
# and requires an API key for OpenAI to be set in your environment.

# Download EmoBank dataset if not already present
def download_emobank():
    """Download the EmoBank dataset from the official source."""
    url = "https://github.com/JULIELab/EmoBank/raw/master/corpus/emobank.csv"

    # Save to current working directory
    file_path = Path("data/emobank.csv")

    if not file_path.exists():
        print("Downloading EmoBank dataset...")
        response = requests.get(url)
        response.raise_for_status()

        with open(file_path, 'w', encoding='utf-8') as f:
            f.write(response.text)
        print(f"Downloaded EmoBank dataset to {file_path}")
    else:
```

```

    print(f"EmoBank dataset already exists at {file_path}")

    return file_path

# Download the dataset
emobank_path = download_emobank()

# Load sample data
data = pd.read_csv(emobank_path)

# Craft CGCoT prompts for valence measurement
cgcot_prompts = [
    "Summarize the text in one clear sentence: {text}",
    "Who or what is the primary target or focus of the following text (person, group,
    ↪ idea, object, or no clear target)? Answer with a short label. Text: {text}",
    "Describe the overall evaluative tone toward the target in the following text using
    ↪ concrete words (examples: praising, appreciative, approving, congratulatory;
    ↪ neutral, descriptive, matter-of-fact; critical, hostile, insulting, disparaging).
    ↪ Text: {text}",
    "Based on your previous analysis, provide a single categorical judgment: does the
    ↪ following text express Positive, Neutral, or Negative valence toward the
    ↪ identified target? Answer with only one of those three words. Text: {text}"
]

# Initialize measurement for a specific construct
p_valence = pdm.Pairadigm(
    data = data,
    item_id_name = 'id',
    text_name = 'text',
    cgcot_prompts = cgcot_prompts, # Used to generate breakdowns for comparison
    model_name = 'gpt-5.1',
    api_key = os.getenv('OPENAI_API_KEY'),
    target_concept = 'valence' # This is used in the internal comparison prompt
)

# Run pairwise annotation
build_pairadigm(p_valence)

# Evaluate and score items
p_valence.check_transitivity()
p_valence.score_items(normalization_scale='negative-one-to-one')

```

The core module utilizes `choix` (Maystre and Grossglauser 2015) for the underlying spectral ranking and Bradley-Terry optimization, while adding layers for error handling, retry logic, and concurrent API execution. This example demonstrates how `pairadigm` abstracts away the complexities of prompt engineering, API management, and psychometric scoring into a streamlined interface. It can further be extended to incorporate paired human annotations for model validation.

Reward Modeling for Scale

Once a reliable scale is constructed via the `Pairadigm` class, the model module allows users to train a dedicated reward model. The `RewardModel` class leverages the Hugging Face transformers library to fine-tune architectures like ModernBERT (Answer.AI 2024) using a pairwise loss function.

```

from pairadigm.model import RewardModel

```

```

model = RewardModel(model_name="answerdotai/ModernBERT-large",
                    Pairadigm=p_valence)
model.model.to(model.device)

# Use the pairadigm object's internal data and decisions to prepare data loaders
dataloaders = model.prepare_data(test_size=0.15, eval_size=0.15, batch_size=4)

# Access the loaders
train_loader = dataloaders['train']
eval_loader = dataloaders['eval']
test_loader = dataloaders['test']

# Train and evaluate a scalar measurement model
model.train(train_loader, eval_loader, epochs=10, learning_rate=2e-5)
model.test_model(test_loader)
model.save_model("valence_reward_model")

```

This functionality democratizes the “Reward Modeling” phase of RLHF (Reinforcement Learning from Human Feedback), repurposing it for social science measurement as described in recent literature (Licht et al. 2025).

Quality Control and Visualization

pairadigm places a heavy emphasis on validation. It includes automated generation of:

- Transitivity Analysis: To measure logical consistency in annotator choices.
- Inter-Rater Reliability (IRR): Using Cohen’s Kappa, Fleiss’ Kappa, or Krippendorff’s Alpha to assess agreement between LLMs and humans.
- Alternative Annotator Test (AltTest): To compare LLM-derived scores against human annotations (Calderon et al. 2025).
- More to come!

Acknowledgements

We acknowledge the contributions of the open-source community, particularly the maintainers of `choix`, `transformers`, and `pandas`. We also thank the co-learning community at the Center for Educational Data Science and Innovation at the University of Maryland for their support and feedback during development.

References

- Answer.AI. 2024. *ModernBERT: A Modern BERT Model*. <https://huggingface.co/answerdotai/ModernBERT-large>.
- Bradley, Ralph Allan, and Milton E Terry. 1952. “Rank Analysis of Incomplete Block Designs: I. The Method of Paired Comparisons.” *Biometrika* 39 (3/4): 324–45.
- Buechel, Sven, and Udo Hahn. 2022. *EmoBank: Studying the Impact of Annotation Perspective and Representation Format on Dimensional Emotion Analysis*. <https://arxiv.org/abs/2205.01996>.
- Calderon, Nitay, Roi Reichart, and Rotem Dror. 2025. “The Alternative Annotator Test for LLM-as-a-Judge: How to Statistically Justify Replacing Human Annotators with LLMs.” In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, edited by Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar. Association for Computational Linguistics. <https://doi.org/10.18653/v1/2025.acl-long.782>.

- Cohen, Jacob. 1960. “A Coefficient of Agreement for Nominal Scales.” *Educational and Psychological Measurement* 20 (1): 37–46.
- Licht, Hauke, Rupak Sarkar, Patrick Y. Wu, et al. 2025. “Measuring Scalar Constructs in Social Science with LLMs.” In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, edited by Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng. Association for Computational Linguistics. <https://doi.org/10.18653/v1/2025.emnlp-main.1635>.
- Maystre, Lucas, and Matthias Grossglauser. 2015. “Fast and Accurate Inference of Plackett-Luce Models.” *Advances in Neural Information Processing Systems* 28.
- Ouyang, Long, Jeff Wu, Xu Jiang, et al. 2022. *Training Language Models to Follow Instructions with Human Feedback*. <https://arxiv.org/abs/2203.02155>.
- Thurstone, Louis L. 1927. “A Law of Comparative Judgment.” *Psychological Review* 34 (4): 273.
- Wu, Patrick Y., Jonathan Nagler, Joshua A. Tucker, and Solomon Messing. 2024. “Concept-Guided Chain-of-Thought Prompting for Pairwise Comparison Scoring of Texts with Large Language Models.” *2024 IEEE International Conference on Big Data (BigData)*, 7232–41. <https://doi.org/10.1109/BigData62323.2024.10825235>.