Multimodal Autonomous AI Agents

Russ Salakhutdinov

Machine Learning Department
Carnegie Mellon University

Carnegie Mellon University

MACHINE LEARNING DEPARTMENT

Large Language Models



Autonomous AI Agents

- Many productive tasks we perform today are done on the computer
  - And many of these are on the web
- Many opportunities to automate menial tasks
- Augment human capabilities



Generated with DALLE

Autonomous Agents



Autonomous Agents



Task: “Create a set of PowerPoint slides to present the content in this paper.”

Autonomous Agents



Employee	Department	Score
Bob Jones	HR	89
Sarah Smith	Marketing	93
Julia Kane	F	
Christina Graham	H	
Mike Beck	F	
Alison Adams	C	
Josh White	M	
Zoey Clark	C	
Robert Jackson	F	
Sam Johnson	M	
Mary Brown	C	
Chris Williams	F	
Emily Anderson	C	
John Lee	H	
Tina Thompson	M	
Katie Allen	C	

Web Agents

Web Grounding

Visual Encoder



LLM

HTML Understanding

Web Agents

Web



Shunyu Yao, REACT Synergizing Reasoning and Acting in Language Models, 2023

Jason Wei et al, Chain of Thought Prompting Elicits Reasoning in Large Language Models, 2022

Reiichiro Nakano et al, WebGPT: Browser-assisted Question-Answering with Human Feedback, 2021.

Xiang Deng et al, MIND2WEB: Towards a Generalist Agent for the Web, 2023

Timo Schick et al, Toolformer: Language Models can Teach Themselves to Use Tools, 2023

Shibo Hao et al, ToolkenGPT: Augmenting Frozen Language Models with Massive Tools via Tool Embeddings, 2023

Yang et al., SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering, 2024

Task: Navigate to a page of a good Thai restaurant in Pittsburgh. It should have at least 200 reviews and 4.3 stars. Pick the one with the highest rating

ellon University

Task: Navigate to the page of a good Thai restaurant in Pittsburgh. It should have at least 200 reviews and 4.3 stars. Pick the one with the highest rating.



visualwebarena — Python run_demo.py --instruction_path agent/prompts/jsons...

```
(venv) jingyuk@GS22433 visualwebarena %
python run_demo.py \
  --instruction_path agent/prompts/jsons
/p_som_cot_id_actree_3s.json \
  --start_url "https://www.yelp.com/" \
  --intent "Navigate to the page of a go
od Thai restaurant in Pittsburgh. It sho
uld have at least 200 reviews and 4.3 st
ars. Pick the one with the highest ratin
g." \
  --result_dir demo_test_yelp \
  --model gpt-4-vision-preview \
  --action_set_tag som  --observation_ty
pe image_som \
  --render
```

ellon University

Task: Make a reservation at Pusadee's Garden for 2 people on the earliest date for dinner. Use my name JY Koh and phone number 650-555-5555.



visualwebarena — Python run_demo.py --instruction_path agent/prompts/jsons...

```
(venv) jingyuk@GS22433 visualwebarena %
python run_demo.py \
  --instruction_path agent/prompts/jsons
/p_som_cot_id_actree_3s.json \
  --start_url "https://www.google.com/"
\
  --intent "Make a reservation at Pusade
e's Garden for 2 people on the earliest
date at any time. Use my name JY Koh and
 phone number 650-555-5555." \
  --result_dir demo_test_yelp \
  --model gpt-4-vision-preview \
  --action_set_tag som  --observation_ty
pe image_som \
  --render
```

Task: Help me navigate to a shirt that has this on it.

ellon University

visualwebarena — Python run_demo.py --instruction_path agent/prompts/jsons...

```
(venv) jingyuk@GS22433 visualwebarena %
python run_demo.py \
  --instruction_path agent/prompts/jsons
/p_som_cot_id_actree_3s.json \
  --start_url "https://www.amazon.com/"
\
  --image "https://media.npr.org/assets/
img/2023/01/14/this-is-fine_wide-0077dc0
607062e15b476fb7f3bd99c5f340af356-s1400-
c100.jpg" \
  --intent "Help me navigate to a shirt
that has this on it." \
  --result_dir demo_test_amazon \
  --model gpt-4-vision-preview \
  --action_set_tag som  --observation_ty
pe image_som \
  --render
```

Talk Outline

- VisualWebArena -- Evaluating Multimodal Agents on Realistic Visual Web Tasks (Koh et al., ACL 2024)
- Tree Search for Language Model Agents (Koh, McAleer, Fried, Salakhutdinov, arXiv 2024)
- Towards Internet-Scale Training For Agents (Trabucco, Sigurdsson, Piramuthu, Salakhutdinov, arXiv 2025)

WebArena



Shuyan Zhou Frank Xu

- Most realistic web environment at the moment
- Websites from popular categories (shopping, Reddit, GitLab)
  - Self-hosted open source re-implementations
  - Data from real websites (Amazon, Reddit, GitHub)
- Tasks are easy for humans (78% success rate) but difficult for language model agents (14%)
- **But:** Tasks are designed to use just text and HTML source code
- Messy HTML, JavaScript: usually minified or compressed for efficiency
- Interactive elements don't display correctly in HTML
  - e.g., JavaScript/CSS code that moves objects after the page is loaded
- Context length: HTML pages are complex, easily filling up > 100k tokens

Zhou*, Xu*, et al., 2023. "WebArena: A Realistic Web Environment for Building Autonomous Agents"

HTML is insufficient



- Messy HTML, JavaScript: usually minified or compressed for efficiency
- Interactive elements don't display correctly in HTML
  - e.g., JavaScript/CSS code that moves objects after the page is loaded
  - Spatial layout is also usually not conveyed well
- Context length: HTML pages are complex, easily filling up > 100k tokens

VisualWebArena


Jing Yu Koh


Shuyan Zhou


Frank Xu

- Build and track the progress of **multimodal agents**
- We design visually grounded tasks to test these abilities
- Visual inputs (and outputs) allow for unique, interesting, and realistic tasks



JY Koh, V. Duvvur, P. Huang, L. Jang, MC Lim, R. Lo, G. Neubig, S. Zhou, R. Salakhutdinov, D. Fried

VisualWebArena: Classifields

Task: Find this exact bike that's listed for $300-500 and post a comment offering $10 less than their asking price.



VisualWebArena: Shopping

Task: Buy the cheapest color photo printer and send it to Emily's place (as shown in the image).



VisualWebArena: Reddit



Task: What is the 2022 total nominal GDP of the area that produces most sugarcane in the year of 2021? (in billion)?



VisualWebArena

POMDP environment: $\mathcal{E} = \langle \mathcal{S}, \mathcal{A}, \mathcal{O}, \mathcal{T} \rangle$

- Observations $\mathcal{O}$



- Actions $\mathcal{A}$

Action Type a	Description
`click [elem]`	Click on element `elem`.
`hover [elem]`	Hover on element `elem`.
`type [elem] [text]`	Type `text` on element `elem`.
`press [key_comb]`	Press a key combination.
`new_tab`	Open a new tab.
`tab_focus [index]`	Focus on the i-th tab.
`tab_close`	Close current tab.
`goto [url]`	Open `url`.
`go_back`	Click the back button.
`go_forward`	Click the forward button.
`scroll [up|down]`	Scroll up or down the page.
`stop [answer]`	End the task with an optional output.

- Deterministic transition function

$$\mathcal{T} : \mathcal{S} \times \mathcal{A} \longrightarrow \mathcal{S}$$

- Reward function: $r(\mathbf{a}, \mathbf{s})$

Image Inputs:



Task: "Buy the cheapest color photo printer and send it to Emily's place (as shown in the image)."

Shopping

Task: “Buy the cheapest color photo printer and send it to Emily's place (as shown in the image).”



Step 0: Start on the homepage of OneStopMarket.



Step 1: Navigate to the printers category.

Task: “Buy the cheapest color photo printer and send it to Emily's place (as shown in the image).”



Step 2: Sort by descending price.



Step 3: Click on the cheapest color photo printer.

Task: “Buy the cheapest color photo printer and send it to Emily's place (as shown in the image).”



Step 4: Add it to the shopping cart.



Step 5: Proceed to checkout

Task: “Buy the cheapest color photo printer and send it to Emily's place (as shown in the image).”



Step 6: Edit address to that of Emily’s place.



Step 7: Place the order

VisualWebArena





Execution Based Evaluation

Webpage / Input Image(s)	Example Intent	Reward Function $r(s, a)$ Implementation
	What is the ISIN of the company that occupies the largest portion in Warren Buffet's portfolio? Answer using the information from the Wikipedia site in the second tab.	`exact_match(â, "US0378331005")`

	Add something like what the man is wearing to my wish list.	`url="/wishlist"`
		`locator(".wishlist .product-image-photo")`
		`eval_vqa(s, "Is this a polo shirt? (yes/no)", "yes")`
		`eval_vqa(s, "Is this shirt green? (yes/no)", "yes")`

	Create a post for each of the following images in the most related forums.	`eval_fuzzy_image_match(s, a*)`

	Navigate to my listing of the white car and change the price to $25000. Update the price in the description as well.	`url="/index.php?page=item&id=84144"`
		`must_include(â, "$25000 |OR| $25,000")`
		`must_exclude(â, "$30000 |OR| $30,000")`

LLM and VLM Agents

Visual Language Models as Agents

```
Tab 0 (current): Search results for: 'hp inkjet'

[1] RootWebArea "Search results for: 'hp inkjet'" focused: True
        [81] link 'My Account'
        [82] link 'My Wish List'
        [83] link 'Sign Out'
        [4086] StaticText 'Welcome to One Stop Market'
        [37] link 'Skip to Content'
        [23] link 'store logo'
                [39] img 'one_stop_market_logo'
        [40] link '\ue611 My Cart'
        [278] StaticText 'Search'
        [163] combobox '\ue615 Search' autocomplete: both hasPopup: listbox required: False expanded: False
                [426] StaticText 'hp inkjet'
        [281] link 'Advanced Search'
        [120] button 'Search' disabled: True
        [4080] tablist '' multiselectable: False orientation: horizontal
                [4082] tabpanel ''
                        [2326] menu '' orientation: vertical
                                [3077] menuitem '\ue622 Beauty & Personal Care' hasPopup: menu
                                [3142] menuitem '\ue622 Sports & Outdoors' hasPopup: menu
                                [3152] menuitem '\ue622 Clothing, Shoes & Jewelry' hasPopup: menu
                                [3166] menuitem '\ue622 Home & Kitchen' hasPopup: menu
                                [3203] menuitem '\ue622 Office Products' hasPopup: menu
                                [3211] menuitem '\ue622 Tools & Home Improvement' hasPopup: menu
                                [3216] menuitem '\ue622 Health & Household' hasPopup: menu
                                [3222] menuitem '\ue622 Patio, Lawn & Garden' hasPopup: menu
                                [3227] menuitem '\ue622 Electronics' hasPopup: menu
                                [3288] menuitem '\ue622 Cell Phones & Accessories' hasPopup: menu
                                [3303] menuitem '\ue622 Video Games' hasPopup: menu
                                [3316] menuitem '\ue622 Grocery & Gourmet Food' hasPopup: menu
        [47] link 'Home '
        [12] main ''
                [32] heading "Search results for: 'hp inkjet'"
                [264] StaticText 'View as'
                [146] strong 'Grid'
                [147] link 'View as \ue60b List'
                [148] StaticText 'Items '
                [151] StaticText '-'
                [153] StaticText '12'
                [154] StaticText ' of '
                [156] StaticText '687'
                [269] StaticText 'Sort By'
                [158] combobox 'Sort By' hasPopup: menu expanded: False
                [159] link '\ue614 Set Ascending Direction'
                [424] link 'Image'
                        [1010] img 'Image'
                [1011] link 'HP Business Inkjet 2800 Wide Format Printer (C8174A#A2L)'
                [720] LayoutTable ''
                        [1451] StaticText 'Rating:'
                        [1232] generic '47%'
                        [1869] link '12 \xa0Reviews'
                [1871] StaticText '$37.64'
                [1600] link 'Image'
```



Accessibility tree / HTML representations: Cluttered with unnecessary information, long and confusing context.

VLM + SoM: Simplified representation with Set-of-Marks (SoM) prompting over interactable elements.

Visual Language Models as Agents



Original Webpage



Webpage with SoM of Interactable Elements

SoM Elements and Text Content

"I'm trying to find this post. Navigate to the comment section for it."

LLM / VLM Agent

click [31]

Visual Language Models as Agents

User goal:

I'm trying to find this post. Navigate to the comment section for it.

Observations o_t:




```
...
[7] [A] [Comments]
[8] [BUTTON] [Hot]
[9] [IMG] [description: picture of a pumpkin]
[10] [A] [kneechalice]
...
```

Multimodal LLM

Let's think step-by-step... The objective is to navigate to the find the post and navigate to the comment section for it. From the observation, I can see... To navigate to this listing, I need to click on the comment link associated with the sushi. In summary, the next action I will perform is ```click [34]```

Action a_t: click [34]

VLM + SoM: Simplified representation with Set-of-Marks (SoM) prompting over interactable elements.

Baseline Agents



Baseline Agents: Text-based LLMs

Model Type	LLM Backbone	Visual Backbone	Inputs	Success Rate (↑)
Text-only	LLaMA-2-70B	-	Accessibility Tree	1.10%
	Mixtral-8x7B			1.76%
	Gemini-Pro			2.20%
	GPT-3.5			2.20%
	GPT-4			7.25%
Caption-augmented	LLaMA-2-70B	BLIP-2-T5XL	Accessibility Tree + Captions	0.66%
	Mixtral-8x7B	BLIP-2-T5XL		1.87%
	GPT-3.5	LLaVA-7B		2.75%
	GPT-3.5	BLIP-2-T5XL		2.97%
	Gemini-Pro	BLIP-2-T5XL		3.85%
	GPT-4	BLIP-2-T5XL		12.75%

Baseline Agents: Multimodal LLMs

Model Type	Multimodal Model	Inputs	Success Rate (↑)
Multimodal	IDEFICS-80B-Instruct	Image + Captions + Accessibility Tree	0.77%
	CogVLM		0.33%
	Gemini-Pro		6.04%
	GPT-4V		15.05%
Multimodal (SoM)	IDEFICS-80B-Instruct	Image + Captions + SoM	0.99%
	CogVLM		0.33%
	Gemini-Pro		5.71%
	GPT-4V		**16.37%**
Human Performance	-	Webpage	88.70%

Task: "I don't like the author of this image from one of the hot posts in /f/memes. Can you help me block them?"



Step 0: Start on the homepage of Reddit



Step 1: Search "/f/memes"



Step 2: Navigate to the list of all forums



Step 3: Navigate to the /f/memes forum



Step 4: Go to the profile page of the user who posted the target image



Step 5: Click the block button



Step 6: Confirm blocking the user

Successful execution trajectory of the GPT-4V + SoM agent on the task for blocking a user that posted a certain picture

Web Agent Architecture

- Model architecture of our interactive agent:
  - High-level Planning and Reasoning
  - Observation Parsing
  - Low-level Action Generation



Planning

High-level plans are important for long-sequence and complex objectives.

Task: Buy the highest rated product from the Beauty & Personal Care category within a budget under 20.

Step 1: Navigate to the Beauty & Personal Care Category (1 low-level action)



Step 2: Sort based on rating for that category (2 low-level actions)



Step 3: Select one item under 20 dollars (1 low-level action)

Step 4: Buy the selected item (3 low-level actions)



Measuring Productive Tasks

VisualWebArena is a step towards building general purpose agents. But:

- Tasks are not very ***consequential***: do not represent significant economic value
- Tasks are simpler, as current LLM agents do not even do well on these problems

Long term: Automate productive, economically valuable tasks





Examples from Collabora Online / LibreOffice.

Common Failure Modes

- Long horizon reasoning and planning:
  - Models oscillate between two webpages, or get stuck in a loop
  - Correctly performing tasks but undoing them
  - Agents tend to stop exploration / execution too early

What is Missing?

- We need to do a lot more to close the gap:
  - **Reasoning** and **Planning** over long horizons
  - Allow agent to **Search**, execute and coordinate multiple instances in parallel and ask for clarifications/confirmations
  - Strong vision-language-code models
  - Identifying the appropriate level of abstraction for agents (HTML/screenshots/APIs)

- **Multimodal models:** Many real-world tasks require visual grounding to effectively solve (e.g., every task involving PowerPoint, Excel, Photoshop). To develop strong general agents, we will need to train and build strong vision-language models.

Talk Outline

- VisualWebArena -- Evaluating Multimodal Agents on Realistic Visual Web Tasks (Koh et al., ACL 2024)
- Tree Search for Language Model Agents (Koh, McAleer, Fried, Salakhutdinov, arXiv 2024)
- Towards Internet-Scale Training For Agents (Trabucco, Sigurdsson, Piramuthu, Salakhutdinov, arXiv 2025)

Exponential Error Compounding in Agents

Accuracy @ k steps:				
1 (single step)	**5**	**10**	**30**	**50**
90%	59.05%	34.87%	4.24%	0.52%
95%	77.38%	59.87%	21.46%	7.69%
99%	95.10%	90.44%	73.97%	60.50%
99.9%	99.50%	99.00%	97.04%	95.12%
99.99%	99.95%	99.90%	99.70%	99.50%

Local Decisions; Global Consequences

"Add coconut milk to my cart"



Local Decisions; Global Consequences

"Add coconut milk to my cart"



Search By Repeated Sampling

1. Sample actions from the language model until [STOP].



Pan et al. 2024,
Autonomous Evaluation and Refinement of Digital Agents

Search By Repeated Sampling

1. Sample actions from the language model until [STOP].
2. Evaluate the resulting trajectory
3. Repeat?

Pan et al. 2024,
Autonomous Evaluation and Refinement of Digital Agents

Search By Repeated Sampling

1. Sample actions from the language model until [STOP].
2. Evaluate the resulting trajectory
3. Repeat?



Pan et al. 2024,
Autonomous Evaluation and Refinement of Digital Agents

Search By Repeated Sampling

1. Sample actions from the language model until [STOP].
2. Evaluate the resulting trajectory
3. Repeat?



Pan et al. 2024,
Autonomous Evaluation and Refinement of Digital Agents

Search By Repeated Sampling



Repeated sampling helps!

- But the space is exponentially large. Can we guide exploration?
- Key idea: apply value function to intermediate nodes.

Jing Yu Koh

Our Method: Tree Search

- Best-first search algorithm
- Ingredients:
  - Baseline agent to propose actions.
  - Way to backtrack in the environment.
  - A **value function** $v_p = f_v(I, \{o_1, \ldots, o_p\})$ to score and rerank candidate states.



In this work, we prompt a multimodal LLM (GPT-4o) to act as an evaluator.

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

GPT-4o Agent + Search

Starting State

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

1

GPT-4o Agent + Search

1

v = 0.5

Starting State

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search



Starting State

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent

GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search



Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Task Instruction (I): "Can you add this and the other canned fruit (of the same brand) that looks like this, but red instead of brown to the comparison page?"

Legend

1 Step sequence

v = 1.0 State values

Backtracking

GPT-4o Agent



GPT-4o Agent + Search

Results


WebArena
40%
20%
0%
8%
10%
15%
19%
Llama-3-70B
GPT-4o
Baseline
w/ Search


VisualWebArena
40%
20%
0%
8%
17%
19%
26%
Llama-3-70B
GPT-4o
Baseline
w/ Search

Ablations



Success rate on a subset of 200 VWA tasks with search budget c. $c = 0$ indicates no search is performed. Success rate generally increases as c increases.

Depth d	**Branch** b	**SR** (↑)	Δ
0	1	24.5%	0%
1	3	26.0%	+6%
	5	32.0%	+31%
2	3	31.5%	+29%
	5	35.0%	+43%
3	5	35.5%	+45%
5	5	**37.0%**	+51%

Success rate (SR) and relative change over the baseline (Δ) on a subset of 200 VWA tasks with varying search depth (d) and branching factor (b). $d = 0$ indicates no search is performed. All methods use a max search budget $c = 20$.

Ablations

- Having a good value function is essential.
- There is still a lot of headroom for improving both the base agent policy, and the value function.

Value Function	SR (↑)
None (no search)	24.5%
LLaVA (w/ SC, $n = 20$)	30.0%
GPT-4o (no SC)	28.5%
GPT-4o (w/ SC, $n = 5$)	32.5%
GPT-4o (w/ SC, $n = 20$)	37.0%

Table 3: Success rate of the GPT-4o agent with different value functions.

Qualitative Results

Task Instruction (I): "I recall seeing this exact item on the site, help me find the most recent post of it. I recall seeing it in either the Collectibles or Antiques section."



Qualitative Results

Task Instruction (I): "I need something like this for my apartment. Can you add one to my wishlist?"

GPT-4o Agent + Search



Legend: 1 Search sequence → Backtracking v = 1.0 State values

Limitations

- Search is slow
  - We implemented backtracking in a relatively naive way (store actions in a queue, take them again to get to the original state)

- Dealing with destructive actions
  - Some things on the web are very difficult to undo, e.g., ordering an item

Current Work

- Search as a policy improvement function
- Improving Value Function by fine-tuning instead of prompting
- Explore compute tradeoff between improving baseline agent vs. doing **more search at inference time**
- What if we don't have a perfect simulator – **how can we collect data at scale**?

Talk Outline

- VisualWebArena -- Evaluating Multimodal Agents on Realistic Visual Web Tasks (Koh et al., ACL 2024)
- Tree Search for Language Model Agents (Koh, McAleer, Fried, Salakhutdinov, arXiv 2024)
- Towards Internet-Scale Training For Agents (Trabucco, Sigurdsson, Piramuthu, Salakhutdinov, arXiv 2025)

Agents Suffer From A **Data Problem**

- Top LLMs fall short of humans by 68.92% on Visual Web Arena
- LLMs are often **trained offline**, then **deployed zero-shot** as agents

Training Data



Test Environment



Agents Suffer From A **Data Problem**

- Top LLMs fall short of humans by 68.92% on Visual Web Arena
- Can **synthetic tasks** unlock internet-scale training for agents?

.





Towards Internet-Scale Training For Agents (InSTA)

- Can synthetic tasks unlock internet-scale training for agents?
- **Key Idea:** use Llama to **generate and verify** synthetic agentic tasks

Stage 1: Task Generation

`www.github.com`

LLM Find a codebase for generating images with Flux.1 [dev].

Stage 2: Task Evaluation



LLM Codebase found: ✅
Flux supported: ✅
Task solved: ✅

Stage 3: Data Collection

```
www.github.com
www.stackoverflow.com
www.uefi.org
www.javatpoint.com
manuals.playstation.net
calculator.bcis.co.uk
research.vu.nl
...
(150k sites)
```

Use Llama To Generate Agentic Tasks

- Given a web domain as text (i.e. merseyferries.co.uk)
- Propose a realistic task that an average user could complete in one session.

Use Llama To Generate Agentic Tasks

- Given a web domain as text (i.e. merseyferries.co.uk)
- Propose a realistic task that an average user could complete in one session.

Llama-3.1-70B-Instruct: describe the “merseyferries.co.uk” site

Mersey Ferries (merseyferries.co.uk) is the **official website for the famous Mersey Ferry service** in Liverpool, England. This website serves as a one-stop platform for users to access various services and information related to the ferry operation. Here are some things a user can do on this site:

1. **Plan a Journey**: Users can plan their journey by checking the ferry timetable, which includes departure and arrival times for both commuter and cruise services.
2. **Book Tickets**: Users can book tickets online for both commuter and cruise services, including the popular Manchester Ship Canal Cruise and the Liverpool Bay Cruise.

Use Llama To Generate Agentic Tasks



- Heavy-tailed distribution, most tasks involve information retrieval
- Crucially, **tasks do not modify the state of the internet**

Generated Tasks

- Tasks are diverse, and many require multiple steps of reasoning (i.e., what makes a font suitable for a children's book)

Web Domain	Generated Task
wordpress.org	Find a free and popular theme for a personal blog.
policies.google.com	Read Google's terms of service for using YouTube.
ec.europa.eu	Retrieve a report on the EU's climate change policy.
vimeo.com	Find a short film on environmental conservation.
fonts.adobe.com	Browse fonts suitable for a children's book.
apps.apple.com	Find the top-rated free productivity app for iPhone.

Generated Tasks

- Llama can identify facts that a site is likely to contain, such as the meaning of the Om symbol

Web Domain	Generated Task
ancient-symbols.com	Look up the meaning of the Om symbol in ancient cultures.
petsforhomes.com.au	Find a list of available dogs for adoption in New South Wales.
timorousbeasties.com	View the latest fabric designs by the Timorous Beasties studio.
shop.nikon-image.com	Compare prices of the Nikon D850 and D500 cameras.
blueridgecountry.com	Find a scenic hiking trail in the Blue Ridge Mountains.
awg-fittings.com	Find the dimensions of a 1/2\" NPT fitting.

Generated Tasks

- Llama has broad knowledge of sites, such as for timorousbeasties.com, an independent Scottish design studio (fairly obscure)

Web Domain	Generated Task
ancient-symbols.com	Look up the meaning of the Om symbol in ancient cultures.
petsforhomes.com.au	Find a list of available dogs for adoption in New South Wales.
timorousbeasties.com	View the latest fabric designs by the Timorous Beasties studio.
shop.nikon-image.com	Compare prices of the Nikon D850 and D500 cameras.
blueridgecountry.com	Find a scenic hiking trail in the Blue Ridge Mountains.
awg-fittings.com	Find the dimensions of a 1/2\" NPT fitting.

Generated Tasks

View the latest fabric designs by the Timorous Beasties studio

- Tasks are grounded, even for sites in the tail of the data distribution



The Data Pipeline

- **Key Idea:** use Llama to **generate and verify** synthetic agentic tasks.

Stage 1: Task Generation

`www.github.com`

LLM Find a codebase for generating images with Flux.1 [dev].

Stage 2: Task Evaluation



LLM

Codebase found: ✅
Flux supported: ✅
Task solved: ✅

Stage 3: Data Collection

```
www.github.com
www.stackoverflow.com
www.uefi.org
www.javatpoint.com
manuals.playstation.net
calculator.bcis.co.uk
research.vu.nl
...
(150k sites)
```

88

The Data Pipeline

- **Key Idea:** use Llama to **generate and verify** synthetic agentic tasks
- How do we know **when tasks are solved**? Build on Llama models



Automatic Task Verification

- How do we know when tasks are solved?
  - Observe a sequence of actions, and the last observation
  - Estimate the **probability the task is a success** at the final step

$$V_{\text{LLM}}(s_T, a_{1:T}) = P(\text{success} | s_T, a_{1:T})$$

Automatic Task Verification

- How do we know when tasks are solved?
  - Observe a sequence of actions, and the last observation
  - Estimate the **probability the task is a success** at the final step

$$V_{\text{LLM}}(s_T, a_{1:T}) = P(\text{success} | s_T, a_{1:T})$$

- Prompt Llama to rate its confidence the task is solved on a scale from **0.0 (not possible)** → **1.0 (certain)**

- Of 150,000 tasks, 14.6% are rated as a success with a **confidence of 1.0** by the Llama verifier**,** roughly 22,000 tasks

Exploring The Data: InvasivePlantAtlas.org

Proposed Task: find invasive plant species native to North America

Agent Response:

To find invasive plant species native to North America, I will first click on the link "All Species" to view the list of all species.

Here is the action in JSON format:

```json
{
    "action_key": "click",
    "action_kwargs": {},
    "target_element_id": 12
}
```

Exploring The Data: InvasivePlantAtlas.org

Agent Response:

To find invasive plant species native to North America, I will first click on the link "Home" to go back to the main page and then click on the link "Sources" to view the list of sources that provide information on invasive plant species native to North America.

However, since the link "Sources" is not on the current page, I will first click on the link "Home" to go back to the main page.

Here is the action in JSON format:

```json
{
    "action_key": "click",
    "action_kwargs": {},
    "target_element_id": 1
}
```

Misread Page



Exploring The Data: InvasivePlantAtlas.org

Agent Response:

To find invasive plant species native to North America, I will first click on the link "Sources" to view the list of sources that provide information on invasive plant species native to North America.

Here is the action in JSON format:

```json
{
    "action_key": "click",
    "action_kwargs": {},
    "target_element_id": 15
}
```

Exploring The Data: InvasivePlantAtlas.org

Agent Response:

To find invasive plant species native to North America, I will first click on the link "FONA" under the "Native Range and Taxonomic References" section, which stands for "Flora of North America". This will take me to the Flora of North America website, where I can search for invasive plant species native to North America.

Here is the action in JSON format:

```json
{
    "action_key": "click",
    "action_kwargs": {},
    "target_element_id": 25
}
```



Exploring The Data: InvasivePlantAtlas.org

Agent Response:

To find invasive plant species native to North America, I will first click on the link "Sort on “U.S. Nativity”" to sort the list by the nativity of the plant species in the United States.

Here is the action in JSON format:

```json
{
    "action_key": "click",
    "action_kwargs": {},
    "target_element_id": 20
}
```



Subject Name	Scientific Name ↓	Family	U.S. Nativity
hairy Indian mallow	*Abutilon grandifolium* (Willd.) Sweet	Malvaceae	Exotic
black wattle	*Acacia mearnsii* de Wildeman.	Fabaceae	Exotic
black acacia	*Acacia melanoxylon* R. Br. ex Ait. f.	Fabaceae	Exotic
Japanese maple	*Acer palmatum* Thunb.	Sapindaceae	Exotic
Norway maple	*Acer platanoides* L.	Sapindaceae	Exotic
rough maidenhair fern	*Adiantum hispidulum* Sw.	Pteridaceae	Exotic
delta maidenhair	*Adiantum raddianum* K. Presl	Pteridaceae	Exotic
jointed goatgrass	*Aegilops cylindrica* Host	Poaceae	Exotic
sisal	*Agave sisalana* Perrine	Asparagaceae	Exotic
croftonweed	*Ageratina adenophora* (Spreng.) King & H.E. Robins.	Asteraceae	Exotic
creeping croftonweed	*Ageratina riparia* (Regel) King & H.E. Robins.	Asteraceae	Native
tropic ageratum	*Ageratum conyzoides* L.	Asteraceae	Native
colonial bentgrass	*Agrostis capillaris* L.	Poaceae	Exotic
redtop	*Agrostis gigantea* Roth	Poaceae	Exotic
creeping bentgrass	*Agrostis stolonifera* L.	Poaceae	Exotic

Exploring The Data: InvasivePlantAtlas.org

Agent Response:

To find invasive plant species native to North America, I will first scroll down the page to view the list of invasive plant species that are native to North America.

However, since the list is already sorted by "U.S. Nativity" in ascending order, I can see that the first 165 plant species are native to North America.

Here is the action in JSON format:

```json
{
    "action_key": "stop",
    "action_kwargs": {
        "answer": "The first 165 plant species on the list are invasive plant species native to North America."
    },
    "target_element_id": null
}
```



Subject Name	Scientific Name	Family	U.S. Nativity
water speedwell	*Veronica anagallis-aquatica* L.	Plantaginaceae	Native
crownbeard	*Verbesina encelioides* (Cav.) Benth. & Hook. f. ex Gray	Asteraceae	Native
Sacramento burrbark	*Triumfetta semitriloba* Jacq.	Tiliaceae	Native
St. Augustinegrass	*Stenotaphrum secundatum* (Walt.) Kuntze	Poaceae	Native
Jamaica vervain	*Stachytarpheta jamaicensis* (L.) Vahl	Verbenaceae	Native
smutgrass	*Sporobolus indicus* (L.) R. Br.	Poaceae	Native
cutleaf nightshade	*Solanum triflorum* Nutt.	Solanaceae	Native
American black nightshade	*Solanum americanum* P. Mill.	Solanaceae	Native
knotroot foxtail	*Setaria parviflora* (Poir.) Kerguélen	Poaceae	Native
highbush blackberry	*Rubus argutus* Link	Rosaceae	Native
anglestem beaksedge	*Rhynchospora caduca* Ell.	Cyperaceae	Native
Douglas-fir	*Pseudotsuga menziesii* (Mirbel) Franco	Pinaceae	Native
balsam poplar	*Populus balsamifera* L.	Salicaceae	Native
cure for all	*Pluchea carolinensis* (Jacq.) G. Don	Asteraceae	Native
Mexican plantain	*Plantago australis* Lam.	Plantaginaceae	Native
eastern white pine	*Pinus strobus* L.	Pinaceae	Native
Monterey pine	*Pinus radiata* D. Don	Pinaceae	Native
ponderosa pine	*Pinus ponderosa* P.& C. Lawson	Pinaceae	Native
Jeffrey pine	*Pinus jeffreyi* Grev. & Balf.	Pinaceae	Native

Exploring The Data: InvasivePlantAtlas.org

Proposed Task: find invasive plant species native to North America

- Despite reasoning failures, the agent **self-corrected**, and found the target information
- The Llama verifier evaluates this trajectory as **successful** with confidence = 1.0



Invasive Plant Atlas of the United States

Home | About

ENHANCED BY Google

Home | Aquatics | Grasses | Herbs/Forbs | Shrubs/Subshrubs | Trees | Vines | All Species | Images | Parks | Sources

Plant Species Reported to be Invasive in Natural Areas List

Source: Jil M. Swearingen, Survey of invasive plants occurring on National Park Service lands, 2000-2007

Source URL: http://www.invasiveplantatlas.org/surveynps.pdf

590 Species

Subject Name	Scientific Name	Family	U.S. Nativity
water speedwell	*Veronica anagallis-aquatica* L.	Plantaginaceae	Native
crownbeard	*Verbesina encelioides* (Cav.) Benth. & Hook. f. ex Gray	Asteraceae	Native
Sacramento burrbark	*Triumfetta semitriloba* Jacq.	Tiliaceae	Native
St. Augustinegrass	*Stenotaphrum secundatum* (Walt.) Kuntze	Poaceae	Native
Jamaica vervain	*Stachytarpheta jamaicensis* (L.) Vahl	Verbenaceae	Native
smutgrass	*Sporobolus indicus* (L.) R. Br.	Poaceae	Native
cutleaf nightshade	*Solanum triflorum* Nutt.	Solanaceae	Native
American black nightshade	*Solanum americanum* P. Mill.	Solanaceae	Native
knotroot foxtail	*Setaria parviflora* (Poir.) Kerguélen	Poaceae	Native
highbush blackberry	*Rubus argutus* Link	Rosaceae	Native
anglestem beaksedge	*Rhynchospora caduca* Ell.	Cyperaceae	Native
Douglas-fir	*Pseudotsuga menziesii* (Mirbel) Franco	Pinaceae	Native
balsam poplar	*Populus balsamifera* L.	Salicaceae	Native
cure for all	*Pluchea carolinensis* (Jacq.) G. Don	Asteraceae	Native
Mexican plantain	*Plantago australis* Lam.	Plantaginaceae	Native
eastern white pine	*Pinus strobus* L.	Pinaceae	Native
Monterey pine	*Pinus radiata* D. Don	Pinaceae	Native
ponderosa pine	*Pinus ponderosa* P.& C. Lawson	Pinaceae	Native
Jeffrey pine	*Pinus jeffreyi* Grev. & Balf.	Pinaceae	Native

Find the opening hours for La Sagrada Familia.

Find information on the European Union's climate action policies.

The Data Pipeline

- We've covered **generation and verification** of synthetic agentic tasks



The Data Pipeline

- We've covered **generation and verification** of synthetic agentic tasks
- Now we can **scale up** data collection



Scaling Up To 150k Live Websites

- We can use the **Common Crawl PageRank** to find important sites
  - **97% accuracy** in detecting and filtering harmful content
  - **89% success rate** in generating feasible tasks
  - **82% accuracy** in judging successful task completions



[4] CommonCrawl, The Common Crawl Foundation, 2024.

Results: Improving Efficiency



- Training on synthetic and human demonstrations scale faster than training on human data
- Adding synthetic data improves Step Accuracy by
  - +89.5% relative to human data for Mind2Web
  - +122.1% relative to human data for WebLINX

Results: Improving Generalization



- Training with only human demonstrations struggle with generalization
- Adding synthetic data improves generalization by
  - +149.0% for WebLINX
  - +156.3% for Mind2Web

Next Steps

- There are 385M unique domains in the Common Crawl PageRank, suggesting another 1000x more data could be available by scaling further
- Moving towards **online RL**

Physical Agent: Long-horizon Robotic Manipulation Task

- Model architecture of our interactive agent:
  - High-level Planning
  - Observation Parsing
  - Low-level Action Generation



Plan-Sequence-Learn

Murtaza Dalal



Plan-Seq-Learn (PSL): Language Model Guided RL for Solving Long Horizon Robotics, M Dalal, T Chiruvolu, D Chaplot, R Salakhutdinov, ICLR 2024

Planning Module

- Structured language plans: (object, condition)
- Prompt: Task description, conditions, objects, formatting

Stage termination conditions: (grasp, place).
Task description: The silver nut goes on the silver peg and the gold nut goes on the gold peg. Give me a simple plan to solve the task using only the stage termination conditions. Make sure the plan follows the formatting specified below and make sure to take into account object geometry.
Formatting of output: a list in which each element looks like: (<object/region>, <stage termination condition>). Don't output anything else.

Output:

[(“silver nut”, “grasp”), (“silver peg”, “place”), (“gold nut”, “grasp”), (“gold peg”, “place”)]

Sequencing/Parsing Module: Grounding Language Plans in the Scene



Learning Low-level Actions Module: Learning Local Control

- Learned RL policies for interaction
- Trained with task reward
- Single RL model instead of separate per stage
- Local instead of global observations



Learning Low-level Actions Module: Learning Local Control

- Learned RL policies for interaction
- Trained with task reward
- Single RL model instead of separate per stage
- Local instead of global observations



Full Pipeline Example



Full Pipeline Example



Full Pipeline Example



Full Pipeline Example





PSL solves 25+ long-horizon robotics tasks across four benchmark environment suites with greater than 85% success rates


Task: put the mouse in the drawer and close it
Environment: CabinetStore, Success Rate: 90%, #Stages: 4
16x

Generalizes to Novel Object Geometries/Categories



Manipulate novel objects with unseen receptacles

8x

Manipulate Deformable Objects (not observed in sim!)



8x

Summary

- VisualWebArena: a benchmark of realistic tasks designed to rigorously evaluate and advance the capabilities of autonomous multimodal web agents
- Inference-time search algorithm designed to enhance the capabilities of language model agents on realistic web tasks
- Data pipeline for large-scale generation and verification of synthetic web tasks, powered by Llama models

Summary

- VisualWebArena: a benchmark of realistic tasks designed to rigorously evaluate and advance the capabilities of autonomous multimodal web agents
- Inference-time search algorithm designed to enhance the capabilities of language model agents on realistic web tasks
- Data pipeline for large-scale generation and verification of synthetic web tasks, powered by Llama models
- **AI Safety and robustness, especially in the age of autonomous systems.**

Adversarial Attacks on Multimodal Agents

Chen Henry Wu, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, Aditi Raghunathan
Carnegie Mellon University
{chenwu2,jingyuk,rsalakhu,dfried,aditirag}@cs.cmu.edu



Thank you