

Switch Configuration — Guided Notes

Unit 2.1.3 | CompTIA Network+ N10-009 Obj. 2.1 | N10-008 2.1

Name: _____ Date: _____ Period: _____

Complete each question using the lesson reading. Write in the blank or answer in the space provided.

Question 1

The first access method used on a new unconfigured switch is a _____ cable connected to the _____ port. Terminal settings are: _____ baud, _____ data bits, _____ parity, _____ stop bit.

Question 2

You should always use _____ instead of _____ to protect the privileged EXEC password, because the latter stores it in _____. The command _____ applies weak encryption to all plaintext passwords in the config.

Question 3

To configure SSH, three prerequisites are required: (1) _____, (2) _____, and (3) _____. The VTY lines must be set to _____ to prevent Telnet access.

Question 4

Write the commands to create VLAN 10 named CLASSROOM and assign GigabitEthernet0/1 to it as an access port:

Question 5

Write the commands to configure GigabitEthernet0/48 as a trunk carrying VLANs 10, 20, and 30 with native VLAN 99:

Question 6

The running-config lives in _____ and is lost on reboot. The startup-config is loaded at boot. The command to save is _____. If you skip this step after making changes and the switch reboots, the result is _____.

Question 7

Match each show command to what it verifies:

show vlan brief → _____

show interfaces trunk → _____

show mac address-table → _____

show interfaces Gi0/1 → _____

Question 8 — Real World Application

REAL WORLD: After configuring VLANs and trunks on two switches, devices on VLAN 20 can't communicate between switches but VLAN 10 works fine. What commands do you run and what are you looking for?

Download the answer key from the class server:

```
wget http://[SERVER]/resources/network-engineer/2-1-3-switch-configuration/2-1-3-switch-configuration-answer-key.pdf
```