



Degree Project in Decision and Control Systems

Second cycle, 30 credits

Patient-Specific Parameter Estimation in Mechanistic Insulin-Glucose Models

Degree Project 2026

MARKUS MULVIHILL

Patient-Specific Parameter Estimation in Mechanistic Insulin-Glucose Models

Degree Project 2026

MARKUS MULVIHILL

Master's Programme, Information and Network Engineering, 120 credits
Date: May 15, 2026

Supervisor: Martin Lindström
Examiner: Ragnar Thobaben

School of Electrical Engineering and Computer Science
Swedish title: Detta är den svenska översättningen av titeln
Swedish subtitle: Detta är den svenska översättningen av undertiteln

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Keywords

Canvas Learning Management System, Docker containers, Performance tuning

Sammanfattning

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nyckelord

Canvas Lärplattform, Dockerbehållare, Prestandajustering

Acknowledgments

Stockholm, May 2026

Markus Mulvihill

Contents

1	Introduction	1
1.1	Background	2
1.2	Problem	2
1.2.1	Original problem and definition	2
1.2.2	Scientific and engineering issues	2
1.3	Purpose	3
1.4	Goals	3
1.5	Research Methodology	3
1.6	Delimitations	4
1.7	Structure of the thesis	4
2	Background	5
2.1	Observability and Identifiability	6
2.2	State Estimation	9
2.2.1	Extended Kalman filter	10
2.2.2	Bootstrap particle filter	11
2.3	Parameter Estimation	13
2.3.1	State Augmentation	13
2.3.2	Markov Chain Monte Carlo Sampling	14
2.3.2.1	Extended Kalman Filter-based Energy Func- tion	14
2.3.3	Metropolis-Hastings Algorithm	15
2.4	Related Work	16
2.5	Summary	17
3	Research Methods	19
3.1	Research Process	19
3.2	Research Paradigm	20
3.3	Data Collection	20

3.4	Assessing reliability and validity of the data collected	21
3.4.1	Validity of method	21
3.4.2	Reliability of method	22
3.5	Planned Data Analysis	22
3.6	Evaluation framework	22
4	Research Methodology	23
4.1	Observability and Identifiability in Patient Insulin-Glucose Models	23
4.2	Nonlinear State Estimation	24
4.2.1	Extended Kalman Filter	24
4.2.2	Bootstrap Particle Filter	24
4.3	Parameter Estimation	24
4.3.1	Parameters of Interest	24
4.3.2	Computational Methods	24
4.3.2.1	Integral-Based Fitting	24
4.3.2.2	State-Augmentation	24
4.3.2.3	Markov Chain Monte Carlo	24
5	Results and Analysis	25
5.1	Major results	25
5.2	Reliability Analysis	27
5.3	Validity Analysis	27
6	Discussion	29
7	Conclusions and Future work	31
7.1	Conclusions	31
7.2	Limitations	32
7.3	Future work	32
7.3.1	What has been left undone?	32
7.3.1.1	Cost analysis	32
7.3.1.2	Security	33
7.3.2	Next obvious things to be done	33
7.4	Reflections	33
	References	35
A	Something Extra	41
A.1	Just for testing KTH colors	41

B	Main equations	43
B.1	A simple example	43
B.2	An even simpler example	43

List of Figures

2.1	Blood Glucose Dynamic Example	17
5.1	Analysis of the integral-based parameter identification method	26

List of Tables

2.1	Constant parameters in the Intensive Control Insulin-Nutrition-Glucose model.	7
5.1	Comparing different estimators based on their respective time complexity and predictive performance regarding blood glucose.	27

Chapter 1

Introduction

Patients in the intensive care unit suffering from critical illnesses (e.g. acute myocardial infarction, sepsis, stroke) have been widely documented to undergo hyperglycaemia, even those without a prior diagnosis of diabetes [1]. Acute stress observed in critical illnesses often induces physiological changes, as the secretion of cortisol and catecholamines results in an inflammatory response associated with insulin-resistance [2] [3] [4] [5] [6] [7]. While there is inconclusive evidence pertaining to the causality of stress hyperglycaemia and adverse outcomes, the onset of mortality is far greater in patients with no reported history of hyperglycaemia, in contrast to patients with diabetes [1] [3]. Sustaining glucose concentration under 6.106 mmol/L through insulin infusion has demonstrated a reduction of mortality and morbidity, compared to less-intensive methods of glycaemic control [8], at the subsequent cost of an increase of reported incidences of hypoglycaemia [9]. Further review of intensive insulin therapy and tight glucose control has identified discrepancies in the administration of glycaemic control, mostly corresponding to the risk of moderate to severe hypoglycaemia and glycaemic variability in a critically ill patient is equally detrimental as stress hyperglycaemia, with an increase of mortality and health complications observed [9] [10] [11]. Clinicians aim to maintain blood glucose in a range of 6 mmol/L to 10 mmol/L to account for adverse outcomes in hyperglycaemia and hypoglycaemia. Traditional intensive insulin therapy struggles to fully capture the dynamic fluctuations of blood glucose in critically ill patients. Thus, more personalized model-based methods are required to achieve tight glycaemic control.

1.1 Background

The implementation of state feedback in model-based tight glucose control methods relies on the formulation of derived state estimators of insulin-glucose dynamics. Mechanistic insulin-glucose models have been developed with an extensive physiological foundation, and have been validated for gluco-regulation in clinical settings [12] [13] [14] [15] [16]. The insulin-glucose models derived are nonlinear, which requires more advanced state estimation methods to properly estimate the insulin-glucose dynamics in patients, as well as prediction into the future. The patient parameters used in such estimators must reflect glucose-insulin dynamics observed physiologically to accurately model gluco-regulation. Mechanistic insulin-glucose models published have traditionally assigned patient parameters as population constants, backed by parameter sensitivity analysis studies. There are data-driven methods to approximate some patient parameters as shown in [14] [16], but a lack of estimators for a subset of patient-specific parameters has been implemented along with the nonlinear state estimation of insulin-glucose dynamics. As a result, this current methodology of estimating insulin-glucose dynamics is not designed to be patient-specific.

1.2 Problem

1.2.1 Original problem and definition

There currently exists a gap in research for further fine-tuning of mechanistic insulin-glucose models. While there is evidence shown in sensitivity studies that certain patient-specific parameters do not have much influence in the insulin-glucose dynamics [12] [15] [16], inadequate assigning of the remaining parameters can lead to inadequate glycaemic control in critically ill patients.

1.2.2 Scientific and engineering issues

System identification can be employed to model the behavior of dynamical systems. Experience of statistical modeling within system identification is often required to construct the assumptions of the system parameters. In the case of insulin-glucose dynamics, there are several unknown patient-specific parameters, and each has its respective role in modeling gluco-regulation. As

a result, identifying key patient-specific parameters and the methods to model them are not intuitive, and poses an ongoing challenge.

1.3 Purpose

Mechanistic insulin-glucose models are of great benefit to critically ill patients and clinicians, as modeling gluco-regulation allows for necessary glycaemic adjustments to avoid the onset of adverse outcomes. In practice, clinicians only have the ability to base insulin sensitivity on blood glucose measurements, and thus, state estimators models fill in the gap as a tool for insulin-glucose dynamics estimation. Improvements in the estimation of insulin-glucose dynamics can better capture the evolution of the health of the patient in the intensive care unit to prevent mortality and morbidity.

1.4 Goals

The overall goal of this project is the estimation of patient-specific parameters in mechanistic insulin-glucose models to compare to current methods. This has been divided into the following sub-goals:

1. Estimate insulin-glucose dynamics using a nonlinear state estimator
2. Determine the subset of patient-specific parameters of interest to model
3. Formulate and evaluate estimators for chosen patient-specific parameters

1.5 Research Methodology

The modeling of the insulin-glucose dynamics found in critically ill patients will be implemented on a virtual patient cohort. Using virtual patients allows the researcher to manually control the patient-specific parameters. The control of the experiment will be insulin-glucose state estimators without any parameter estimation (i.e. assigning parameters as population constants), while the treatment group incorporates parameter estimation with the state estimators. To evaluate the performance of the study, the control group and the treatment group will estimate the insulin-glucose dynamics of unseen virtual patients, and fitting metrics of the state estimators are utilized to draw inferences about the performance of the parameter estimation.

1.6 Delimitations

This study will not consist of any real patient data from the intensive care unit. Using virtual patients is important for maintaining internal validity in the experimental process, as it verifies the observed outcome of the experiment is due to the manipulation of patient-specific parameters and not from uncontrolled variables. This study will build the foundation of the modeling of insulin-glucose dynamics, and future work can replicate the study with observed clinical patient data.

1.7 Structure of the thesis

Chapter 2 will introduce the existing modeling of insulin-glucose dynamics used, followed by an overview of state estimation and parameter estimation techniques. In Chapter 3, the research method will be motivated along with the data collection. The research methodology will be presented in Chapter 4 such that the steps to answer the research questions are clearly documented. The results will be shown in Chapter 5, and the analysis of the results will proceed in Chapter 5. Finally, the overall conclusion, key findings, and future work of the experiment will be summarized in Chapter 7.

Chapter 2

Background

The Intensive Control Insulin-Nutrition-Glucose model presented by Lin et al. [14] characterizes the insulin-glucose dynamics in critically ill patients. The model is constructed as a fusion of two existing models validated for patients in the intensive care unit [12] [13], containing the following ensemble of ordinary differential equations

$$\dot{G} = -p_G G(t) - S_I(t) G(t) \frac{Q(t)}{1 + \alpha_G Q(t)} + \frac{P(t) + E_G - C_G}{V_G} \quad (2.1)$$

$$\dot{Q} = n_I(I(t) - Q(t)) - n_C \frac{Q(t)}{1 + \alpha_G Q(t)} \quad (2.2)$$

$$\begin{aligned} \dot{I} = & -n_K I(t) - n_L \frac{I(t)}{1 + \alpha_I I(t)} - n_I(I(t) - Q(t)) + \frac{u_{ex}(t)}{V_I} \\ & + \frac{(1 - x_L)u_{en}(t)}{V_I} \end{aligned} \quad (2.3)$$

$$\dot{P1} = -d_1 P1 + D(t) \quad (2.4)$$

$$\dot{P2} = -\min(d_2 P2, P_{max}) + d_1 P1 \quad (2.5)$$

$$P(t) = -\min(d_2 P2, P_{max}) + P_N(t) \quad (2.6)$$

$$u_{en}(t) = k_1 e^{-\frac{k_2}{k_3} I(t)}, \quad \text{when C-peptide data is not available.} \quad (2.7)$$

Equation (2.1) is the independent insulin glucose removal, with G being the total blood glucose concentration (mmol/L). The whole-body insulin sensitivity $S_I(t)$ gives insight into the metabolic condition of the patient and is a time-varying dynamic. The insulin pharmacodynamics are shown in Equations (2.2) and (2.3), with Q and I being the interstitial insulin concentration (mU/L) and the plasma insulin concentration (mU/L)

respectively. The exogenous insulin input is $u_{ex}(t)$ (mU/min), and the endogenous insulin production $u_{en}(t)$ (mU/min) can be measured from C-Peptide, but if measurements are not feasible, the kinetics can model as such in Equation (2.7). The gastric absorption of glucose is defined in Equations (2.4) to (2.6). The dynamics $P1$ and $P2$ describe the glucose in the stomach and the gut (mmol), with $P(t)$ representing the glucose appearance in the blood (mmol/min). Any enteral food intake given to the patient is accounted for by $D(t)$ (mmol/min), and additional parenteral dextrose is described by $P_N(t)$ (mmol/min).

The Intensive Control Insulin-Nutrition-Glucose model consists of several fixed parameters detailed in Table 2.1. The majority of the patient model parameters are assigned as general population constants observed from clinical trials, and are validated in relevant insulin-glucose control parameter sensitivity studies [15] [16] [17]. The identification of the remaining constant parameters was estimated with a data-driven approach (i.e. model identifiability) by fitting the patient parameters to the observed dynamics in 173 patients, and by assessing the impact of prediction errors. Estimating the endogenous glucose removal p_G and the suppression of endogenous glucose produce E_G constants involved assigning all other patient parameters and the insulin sensitivity to constants, then starting a grid search that covers $p_G = 0.001, 0.002, \dots, 0.1(\text{min}^{-1})$ and $E_G = 0.0, 0.1, \dots, 3.5$ (mmol/min). The joint p_G and E_G value that achieved the lowest fitting and prediction error for blood glucose in Equation (2.1) was chosen. Ultimately, that was $p_G = 0.006(\text{min}^{-1})$ and $E_G = 1.16$, while both falling in the ranges observed physiologically. The glucose distribution rate between the stomach and the gut n_I , and cellular insulin clearance rate in the interstitium were estimated similarly by fitting to Q in the Equation (2.2), a grid search covers a range of $n_I = n_C = 0.0001, \dots, 0.02(\text{min}^{-1})$, with a value of $n_I = 0.003$ resulting in the best predictive performance.

While the proposed clinically-validated model for patients in the intensive care unit has shown to capture long-term insulin-glucose dynamics, in practice, typically it is only possible for clinicians to take blood glucose measurements, consequently, excluding measurements for the dynamics seen in Equations (2.2) to (2.7).

2.1 Observability and Identifiability

Analyzing observability and identifiability in linear and nonlinear systems assesses how well the dynamics of the model can be inferred from the

Table 2.1: Constant parameters in the Intensive Control Insulin-Nutrition-Glucose model.

Constant Parameter	Notation	Value
Patient endogenous glucose removal	p_G (min^{-1})	0.006
Saturation of insulin-stimulated glucose removal	α_G (L/mU)	0.0154
Suppression of endogenous glucose production	E_G (mmol/min)	1.16
Central nervous system uptake	C_G (mmol/L)	0.3
Glucose distribution volume	V_G (L)	13.3
Glucose distribution rate between the stomach and the gut	n_I (min^{-1})	0.003
Cellular insulin clearance rate in the interstitium	n_C (min^{-1})	$= n_I$
Kidney clearance rate of insulin from plasma	n_K (min^{-1})	0.0542
Liver clearance rate of insulin from plasma	n_L (min^{-1})	0.01578
Saturation of plasma insulin disappearance	α_I (L/mU)	0.0017
Insulin distribution volume	V_I (L)	3.15
Fraction of endogenous insulin hepatic extraction	x_L	0.67
Maximal glucose out flux from the gut	P_{max} (mmol/min)	6.11
Base endogenous insulin production rate	k_1 (mU/min)	45.7
Transport rates between the stomach and the gut	d_1 (min^{-1})	0.0347
	d_2 (min^{-1})	0.0069
Exponential suppression constants	k_2	1.5
	k_3	1000

Parameters shaded in gray are derived from fitting methods, as the rest are assigned as population constants.

observations. The observability gramian W_O has traditionally been used in model reduction of linear dynamic systems, but empirical methods have been adapted to accommodate nonlinear systems [18]. The observability gramian provides insight into which states or parameters have the most influence on the output of the system by analyzing the rank condition of the observability gramian matrix, which in return allows for analytically evaluating observability and identifiability.

We can define the following generic discrete system with a nonlinear dynamic function $f(\cdot)$ and a nonlinear measurement function $h(\cdot)$

$$\begin{aligned} \dot{x}_k &= f(x_{k-1}, u_k) \\ y_k &= h(x_k). \end{aligned} \tag{2.8}$$

To empirically calculate the observability gramian, we first generate 2^n unique

combinations of the initial state $x_0 \in \mathcal{R}^n$, with n denoting the numbers of states and parameters. The initial condition x_0 will be assigned as perturbations $\delta_i \in \mathcal{R}^n$ around a nominal value $x_{nom} \in \mathcal{R}^n$

$$\begin{aligned} x_{0,i} &= x_{nom} + \delta_i \\ \delta_i &= c \cdot S \cdot t_i \end{aligned} \quad \text{with } S = \text{diag}(x_{\max}). \quad (2.9)$$

The scalar constant c corresponds to the magnitude of deviation, $S \in \mathcal{R}^{n,n}$ is the diagonal matrix of the maximum of each state and parameter. The row vector $t_i \in \mathcal{R}^n$ is the specified perturbation i from the orthonormal matrix $T = [t_1 \ t_2 \ \dots \ t_{2^n}] \in \mathcal{R}^{n,2^n}$

$$\begin{aligned} t_1^T &= \frac{1}{\sqrt{2^n}} [-1 \ -1 \ \dots \ -1] \\ t_2^T &= \frac{1}{\sqrt{2^n}} [-1 \ -1 \ \dots \ 1] \\ &\vdots \\ t_{2^n}^T &= \frac{1}{\sqrt{2^n}} [1 \ 1 \ \dots \ 1]. \end{aligned} \quad (2.10)$$

After calculating the 2^n perturbations of the initial state, the output can be derived iteratively with Equations (2.8) from time step $k = 1, \dots, K$ beginning with $x_{0,i}$ to generate $y_i [1 : K]$. Then, the empirical observability with discrete time steps $t = k\Delta T$ can be expressed as such

$$W_O = (cS)^{-1} \sum_{k=1}^K T \Psi[k] T^T \Delta T (cS)^{-1}, \quad (2.11)$$

with the positive definite matrix $\Psi[k]$ being assigned as the following

$$\Psi_{i,j}[k] = |y_i[k] - y_0[k]| |y_j[k] - y_0[k]|. \quad (2.12)$$

To make inferences about the observability and identifiability of the observability gramian, one can check the rank condition of the matrix by analyzing the nonzero singular values of W_0 . The singular values close to zero can be classified as not observable. If the states have varying magnitudes of scale, it is recommended [19] to rerun the observability gramian algorithm

again with the following transformations

$$x_s = \sqrt{\text{diag}(W_O)} \quad T_s = \text{diag}^{-1}(x_s). \quad (2.13)$$

The new state perturbations and perturbation matrix are now assigned as the transformation such as $\bar{x} = T_s x$ and $\bar{T} = T_s T$. If the system is found to be weakly observable or not observable after calculating the singular values with the transformed parameters, consequently, a subset of the dynamics of the system can't be observed from the measurements. State estimators will be discussed in the following sections, which can account for the lack of intuition into the dynamics not observable through various probabilistic filtering mechanisms.

2.2 State Estimation

A probabilistic state estimator can be modeled in the following state space representation

$$\begin{aligned} x_k &\sim p(x_k | x_{k-1}, u_{k-1}) \\ y_k &\sim p(y_k | x_k), \end{aligned} \quad (2.14)$$

where $p(x_k | x_{k-1}, u_k)$ and $p(y_k | x_k)$ are the discrete-time dynamic and measurement models, with $x_k \in \mathbb{R}^n$ representing the states, $u_k \in \mathbb{R}^p$ are the inputs, and $y_k \in \mathbb{R}^m$ are the measurements. The objective is to ultimately derive the distribution of the state x_k , given all the measurements up to the current sample $p(x_k | y_{1:k})$. In the case of assuming the state estimator is linear and Gaussian,

$$\begin{aligned} x_k &= A_{k-1}x_{k-1} + B_{k-1}u_{k-1} + q_{k-1} \\ y_k &= Hx_k + r_k, \end{aligned} \quad (2.15)$$

where $q_{k-1} \sim N(0, Q_{k-1})$ is the process noise, $r_k \sim N(0, R_k)$ is the measurement noise, we can rewrite the Equation (2.14) as the following

$$\begin{aligned} p(x_k | x_{k-1}, u_{k-1}) &= N(x_k | A_{k-1}x_{k-1} + B_{k-1}u_{k-1}, Q_{k-1}) \\ p(y_k | x_k) &= N(y_k | H_k x_k, R_k). \end{aligned} \quad (2.16)$$

The closed-form solution of $p(x_k | y_{1:k})$ for linear and Gaussian dynamic and measurement functions is known as the Kalman filter, with a full derivation available from Sräkkä and Svensson [20]. The filter contains two key parts: the *prediction step* and the *update step*.

1. *Prediction step*

$$\begin{aligned} m_k^- &= A_{k-1}x_{k-1} + B_{k-1}u_{k-1} \\ P_k^- &= A_{k-1}P_{k-1}A_{k-1}^T + Q_{k-1}. \end{aligned} \quad (2.17)$$

2. *Update step*

$$\begin{aligned} v_k &= y_k - H_k m_k^- \\ S_k &= H_k P_k^- H_k^T + R_k \\ K_k &= P_k^- H_k^T S_k^{-1} \\ m_k &= m_k^- + K_k v_k \\ P_k &= P_k^- - K_k S_k K_k^T. \end{aligned} \quad (2.18)$$

The Kalman filter is recursive, as the filter starts with an estimate of the initial distribution of the state m_0^- and the covariance P_0^- , and iterates sequentially over discrete time steps k . While the Kalman filter is a great starting point for an estimator, as the assumptions of linearity and Gaussianity often hold in many contexts, it is clear when analyzing the Equations (2.1) to (2.5), the ordinary differential equations are not linear, hence, the estimators of choice must have the capability to properly handle nonlinearities in the dynamic function.

2.2.1 Extended Kalman filter

The extended Kalman filter expands upon the linearity condition to allow for nonlinear models. The structure of the extended Kalman filter remains the same as the Equations (2.19) and (2.20), but changes are seen in the matrices of the dynamic and measurement models $f(\cdot)$ and $h(\cdot)$. Assuming the same Gaussianity condition as the Kalman filter, the prediction and update steps [20] can be defined as

1. *Prediction step*

$$\begin{aligned} m_k^- &= f(m_{k-1}, u_{k-1}) \\ P_k^- &= F_x(m_{k-1})P_{k-1}F_x^T(m_{k-1}) + Q_{k-1} \end{aligned} \quad (2.19)$$

2. Update step

$$\begin{aligned}
v_k &= y_k - h(m_k^-) \\
S_k &= H_x(m_k^-)P_k^-H_x^T(m_k^-) + R_k \\
K_k &= P_k^-H_k^T(m_k^-)S_k^{-1} \\
m_k &= m_k^- + K_kv_K \\
P_k &= P_k^- - K_kS_kK_k^T,
\end{aligned} \tag{2.20}$$

the Jacobian matrices $F_x(m_k^-)$ and $H_x(m_k^-)$ are derived from $f(\cdot)$ and $h(\cdot)$, as F_x and H_x are inferred from the Taylor series Gaussian approximation of a linear transformation, and are written as

$$\begin{aligned}
[F_x(m)]_{j,j'} &= \left. \frac{\partial f_j(x)}{\partial x_{j'}} \right|_{x=m} \\
[H_x(m)]_{j,j'} &= \left. \frac{\partial h_j(x)}{\partial x_{j'}} \right|_{x=m}.
\end{aligned} \tag{2.21}$$

2.2.2 Bootstrap particle filter

When revisiting the probabilistic state estimators in section 2.2, to analytically compute the point estimate of the states $\hat{x}$, given all observations up to time step K , one must evaluate the expected value of the conditional probability

$$\hat{x} = E[g(x) \mid y_{1:K}] = \sum_x g(x)p(x \mid y_{1:K}), \tag{2.22}$$

with $g(\cdot)$ being an arbitrary function $\mathbb{R}^n \rightarrow \mathbb{R}^m$. Such an integral is often difficult to compute in closed-form due to the intractability of the posterior $p(x \mid y_{1:K})$ in many settings, but by formulating a Monte Carlo approximation by drawing N many random samples from the target distribution $x^{(i)} \sim p(x \mid y_{1:K})$ $i = 1, \dots, N$, the approximation of the point estimate of the states will converge to the true point estimate for a large N , according to the Law of Large Numbers and the Central Limit Theorem [21], and the approximation of the point estimate of the states can be rewritten as

$$\hat{x} \approx \frac{1}{N} \sum_{i=1}^N g(x^{(i)})p(x^{(i)} \mid y_{1:K}). \tag{2.23}$$

The conditional probability $p(x^{(i)} \mid y_{1:K})$ can be rewritten in terms of the likelihood $p(y_{1:K} \mid x^{(i)})$ and the prior $p(x^{(i)})$ according to Bayes' rule

$$p(x^{(i)} \mid y_{1:K}) = \frac{p(y_{1:K} \mid x^{(i)})p(x^{(i)})}{p(y_{1:K})}. \quad (2.24)$$

The normalization term is often not able to be computed numerically, but by introducing importance sampling, the term can be approximated. The importance mass $\pi(x^{(i)} \mid y_{1:K})$ is a Monte Carlo approximation of $p(y_{1:K})$, with the condition that the mass is non-zero whenever $p(x^{(i)} \mid y_{1:K})$ is non-zero, which results in a nonuniform distribution. Sampling from a nonuniform distribution will result in each particle having a corresponding weight $w^{*(i)}$, and a normalized weight w^i

$$\begin{aligned} w^{*(i)} &= \frac{p(y_{1:K} \mid x^{(i)})p(x^{(i)})}{\pi(x^{(i)} \mid y_{1:K})} \\ w^i &= \frac{w^{*(i)}}{\sum_{j=1}^N w^{*(j)}}, \end{aligned} \quad (2.25)$$

with the approximation of the point estimate being rewritten as

$$\hat{x} \approx \sum_{i=1}^N w^i g(x^{(i)}). \quad (2.26)$$

The bootstrap particle filter is formulated on the basis of Markov Chain Monte Carlo approximations, the filtering distributions are shown in Equation (2.14), and the filter is run sequentially like the Kalman filter, the importance mass is assigned as the dynamic model $p(x_k \mid x_{k-1}^{(i)})$ at the time step k for a given particle (i) , which results in the following algorithm [20] [21]

1. Sample N particles from the dynamic function

$$x_k^{(i)} = p(x_k \mid x_{k-1}^{(i)}, u_{k-1}) \quad i = 1, \dots, N \quad (2.27)$$

2. Update weights from the measurement

$$\begin{aligned} w_k^{*(i)} &\propto p(y_k \mid x_k^{(i)}) \quad i = 1, \dots, N \\ w_k^{(i)} &= \frac{w_k^{*(i)}}{\sum_{j=1}^N w_k^{*(j)}} \quad i = 1, \dots, N \end{aligned} \quad (2.28)$$

3. Resample particles from a distribution proportional to the weights.

2.3 Parameter Estimation

As previously mentioned, there exists patient-specific parameters. The whole-body insulin sensitivity S_I or the endogenous insulin u_{en} dynamically fluctuates over time depending on the patient's metabolic condition. As a result, naively assigning either a population constant can hinder the performance of the estimators. The unknown constant parameters of interest will be denoted as θ , with different proposed computational methods to estimate them will be elaborated on within this section.

2.3.1 State Augmentation

A practical method to handle unknown parameters is to augment them to the existing state variables x_k , such that Equation (2.14) can be redefined as

$$\begin{aligned}\theta_k &= \theta_{k-1} \\ x_k &\sim p(x_k \mid x_{k-1}, u_{k-1}, \theta_{k-1}) \\ y_k &\sim p(y_k \mid x_k).\end{aligned}\tag{2.29}$$

An important distinction in Equation (2.29) is that the unknown parameters are treated as stochastic variables with singularity in the process noise. This can be problematic as nonlinear models often have approximation errors, and this can drive the extended Kalman filter to ultimately diverge in the Gaussian approximation, as well as introduce sample impoverishment in particle filters [20].

One method to compensate for singularity is to add artificial process noise Q_k to allow the unknown parameters to randomly walk in the state space, thus, accounting for errors in the dynamic function

$$\theta_k = \theta_{k-1} + \epsilon_{k-1}, \quad \text{with } \epsilon_{k-1} \sim N(0, Q_{k-1}).\tag{2.30}$$

With this method, you inherently add another unknown parameter Q_k , but such a parameter can be tuned with prior knowledge of the parameters θ_k , or one can utilize the Rao-Blackwellized representation of the covariance Q_k in the state space.

2.3.2 Markov Chain Monte Carlo Sampling

The Markov Chain Monte Carlo methods are a class of parameter estimation approaches to estimate the posterior $p(\theta \mid y_{1:K})$ by drawing random samples of the unknown parameters θ from a desired stationary distribution formulated as a Markov Chain [20][22]. Only the unnormalized posterior is considered due to similar concerns regarding computing $p(y_{1:K})$ as previously discussed in Section 2.2.2

$$p(\theta \mid y_{1:K}) \propto p(y_{1:K} \mid \theta)p(\theta). \quad (2.31)$$

The marginal likelihood $p(y_{1:K} \mid \theta)$ can be represented recursively as the state space models are run sequentially

$$p(y_{1:K} \mid \theta) = \prod_{k=1}^K p(y_k \mid y_{k-1}, \theta). \quad (2.32)$$

The energy function $\varphi(\theta)$ will be introduced to maximize $p(y_{1:K} \mid \theta)$ in the negative log-domain

$$\varphi(\theta) = -\log p(y_{1:K} \mid \theta) = -\sum_{k=1}^K \log p(y_k \mid y_{k-1}, \theta), \quad (2.33)$$

which can additionally be expressed as in the recursive form

$$\varphi_k(\theta) = \varphi_{k-1}(\theta) - \log p(y_k \mid y_{k-1}, \theta). \quad (2.34)$$

2.3.2.1 Extended Kalman Filter-based Energy Function

If we return to Equations (2.19) and (2.20), the equations will be redefined such that the filter parameters are also dependent on the unknown parameters θ

1. Prediction step

$$\begin{aligned} m_k^-(\theta) &= f(m_{k-1}(\theta), u_{k-1}) \\ P_k^-(\theta) &= F_x(m_{k-1}(\theta))P_{k-1}(\theta)F_x^T(m_{k-1}(\theta)) + Q_{k-1}(\theta) \end{aligned} \quad (2.35)$$

2. Update step

$$\begin{aligned}
v_k(\theta) &= y_k - h(m_k^-(\theta)) \\
S_k(\theta) &= H_x(m_k^-(\theta))P_k^-(\theta)H_x^T(m_k^-(\theta)) + R_k(\theta) \\
K_k(\theta) &= P_k^-(\theta)H_k^T(m_k^-(\theta))S_k^{-1}(\theta) \\
m_k(\theta) &= m_k^-(\theta) + K_k(\theta)v_k(\theta) \\
P_k(\theta) &= P_k^-(\theta) - K_k(\theta)S_k(\theta)K_k^T(\theta).
\end{aligned} \tag{2.36}$$

The marginal log likelihood $\log p(y_k \mid y_{k-1}, \theta)$ in the extended Kalman filter can be simply derived as

$$\begin{aligned}
\log p(y_k \mid y_{k-1}, \theta) &= \log N(y_k \mid h(m_k^-(\theta)), S_k(\theta)) \\
&= \log \frac{1}{\sqrt{|2\pi S_k(\theta)|}} \exp \left(-\frac{1}{2} v_k^T(\theta) S_k(\theta) v_k(\theta) \right) \\
&= -\frac{1}{2} \log |2\pi S_k(\theta)| - \frac{1}{2} v_k^T(\theta) S_k(\theta) v_k(\theta).
\end{aligned} \tag{2.37}$$

Given the closed form formulation of the marginal log likelihood, the energy function in Equation (2.34) can be finalized as

$$\varphi_k(\theta) = \varphi_{k-1}(\theta) + \frac{1}{2} \log |2\pi S_k(\theta)| + \frac{1}{2} \log v_k^T(\theta) S_k(\theta) v_k(\theta). \tag{2.38}$$

2.3.3 Metropolis-Hastings Algorithm

The Metropolis-Hastings algorithm is one of the most common Markov Chain Monte Carlo samplers, and provides a sequential process of estimating the potential candidates of θ by drawing them from a symmetric proposal distribution $\theta^* \sim q(\theta^* \mid \theta_{(k-1)})$, given the previous candidate $\theta_{(k-1)}$ [20] [22]. The algorithm will be laid out in the preceding block

- $k = 0$
 1. assign an initial candidate θ_0 and the initial energy function value $\varphi_0(\theta_0) = -\log p(\theta)$
- for $k = 1 : K$
 1. sample a proposal candidate $\theta^* \sim q(\theta^* \mid \theta_{k-1})$
 2. calculate energy of proposed candidate $\varphi_k(\theta^*)$
 3. calculate acceptance probability $\alpha_k = \min(1, \exp(\varphi_k(\theta^*) - \varphi_k(\theta_{k-1})))$

$$4. \theta_k = \begin{cases} \theta^* & \text{if } z < \alpha_k \\ \theta_{k-1} & \text{otherwise} \end{cases} \quad \text{with } z \sim \mathcal{U}[0, 1]$$

2.4 Related Work

A nonlinear, and nonconvex integral-based parameter identification method has been introduced that can estimate patient-specific parameters through maximum likelihood estimation [15]. By linearly interpolating between the blood glucose measurements in times $[t_0, t_1]$,

$$\widetilde{G}(t) = \frac{G(t_1) - G(t_0)}{t_1 - t_0} t, \quad (2.39)$$

the Equation (2.1) can be rearranged as such for a piecewise constant S_I

$$\begin{aligned} \int_{t_0}^{t_1} \dot{G} dt &= -p_G \int_{t_0}^{t_1} \widetilde{G}(t) dt - S_I \int_{t_0}^{t_1} \widetilde{G}(t) \frac{Q(t)}{1 + \alpha_G Q(t)} dt \\ &\quad + \frac{1}{V_G} \int_{t_0}^{t_1} P(t) + E_G - C_G dt \\ G(t_1) - G(t_0) &= -p_G \int_{t_0}^{t_1} \widetilde{G}(t) dt - S_I \int_{t_0}^{t_1} \widetilde{G}(t) \frac{Q(t)}{1 + \alpha_G Q(t)} dt \\ &\quad + \frac{1}{V_G} \int_{t_0}^{t_1} P(t) + E_G - C_G dt, \end{aligned} \quad (2.40)$$

and S_I can be expressed as a linear equation

$$\underbrace{\int_{t_0}^{t_1} \widetilde{G}(t) \frac{Q(t)}{1 + \alpha_G Q(t)} dt}_{A(t_0, t_1)} S_I = \underbrace{\left(G(t_0) - G(t_1) - p_G \int_{t_0}^{t_1} \widetilde{G}(t) dt + \frac{1}{V_G} \int_{t_0}^{t_1} (P(t) + E_G - C_G) dt \right)}_{b(t_0, t_1)}. \quad (2.41)$$

It is often the case with longer measurement periods ($t_1 - t_0$), that identifying multiple S_I values within the time period may be necessary. For instance, if every 120 mins glucose measurements are taken from the patient, but every 60 mins a patient's insulin sensitivity should be identified $S_I \in \mathbb{R}^2$. Both insulin sensitivity parameters at 60 mins S_I^{60} and 120 mins S_I^{120} can be derived as the

least squares solution from the system of linear equations

$$\begin{bmatrix} A(t_0, t_0 + 30) & 0 \\ A(t_0 + 30, t_0 + 60) & 0 \\ 0 & A(t_0 + 60, t_0 + 90) \\ 0 & A(t_0 + 90, t_0 + 120) \end{bmatrix} \begin{bmatrix} S_I^{60} \\ S_I^{120} \end{bmatrix} = \begin{bmatrix} b(t_0, t_0 + 30) \\ b(t_0 + 30, t_0 + 60) \\ b(t_0 + 60, t_0 + 90) \\ b(t_0 + 90, t_0 + 120) \end{bmatrix}. \quad (2.42)$$

The fundamental flaw of the integral-based parameter identification method is the assumption of linear blood glucose dynamics between measurements of times $[t_0, t_1]$. If we closely analyze the Figure 2.1, linearly interpolating blood glucose introduces residuals, due to fitting errors. Consequently, the residuals will propagate into the integrals in the Equation (2.41), resulting in errors in the parameter calculation. Relying on data-driven methods can not account for physiological behavior in the parameters, and other methods must be explored to allow for realistic estimation of parameters, thus giving better insight of the patient's health status to clinicians.




Figure 2.1: Blood glucose and its' corresponding measurements from the patient*.

2.5 Summary

The Intensive Control Insulin-Nutrition-Glucose model provides a foundation to model glucose removal, insulin pharmacokinetics, and gastric absorption of glucose for tight glucose control in critically ill patients. Often, clinicians

*The initial conditions of the patient model are $BG = 5.0$ (mmol/L), $I = 15.0$ (mU/L), $Q = 15.0$ (mU/L), $P1 = P2 = 0.0$ (mmol). The inputs are $u_{ex}(t) = 75 \cdot e^{-\left(\frac{\log(2)}{300}\right) \cdot ((t+120) \bmod (300))}$ (mU/min), $P_N(t) = e^{-\left(\frac{\log(2)}{300}\right) \cdot (t \bmod (300))}$ (mmol/min), and no external nutrition is given. Measurements are sampled with additive Gaussian noise $r_k \sim N(0, 0.25^2)$.

solely rely on blood glucose measurements, which limits the knowledge of the insulin-glucose dynamics in real-time. Utilizing nonlinear state estimators, such as the extended Kalman filter and the bootstrap particle filter, allow for estimation of all dynamics over time. To evaluate patient-specific parameters, model identifiability is used to make inferences about the parameters of interest. The current method of integral-based parameter identification is formulated with strict assumptions of blood glucose measurements, which limits the ability for clinicians to infer the health of the patient from the approximated patient-specific parameters. More in-depth parameter estimation methods can improve model identifiability for glucoregulation in critically ill patients.

Chapter 3

Research Methods

This chapter will consist of presenting the scientific design of the experiment. Beginning with the overall goals of the study, and how the corresponding experimental process will be formulated to achieve answering the stated research questions. The inclusion and motivation of the data collected, models used, and analysis of the observations in the experiment will be laid out in the following sections.

3.1 Research Process

The main topics this study aim to address fall in line with the following research questions:

1. **Does the mathematical formulation of the Intensive Control Insulin-Nutrition-Glucose model permit patient-specific model-identifiability when approximating insulin-glucose dynamics for patients in the intensive care unit?**
2. **How do state estimation techniques compare against traditional parameter-identification methods in estimating patient-specific insulin-glucose dynamics in terms of accuracy and computational complexity?**

Given the overall experimental goals, the research process can therefore be outlined as such:

Step 1 create virtual patients,

Step 2 conduct experiments with patient data,

Step 3 analyze statistical metrics from the experiments, and

Step 4 discuss the results of the analysis.

3.2 Research Paradigm

The philosophical motivation in this study is founded on utilizing a set of quantitative methods that serve the purpose of ultimately answering the previously stated research questions. The use of statistical metrics will quantitatively express the relationships of variables tested in the experiment. Consequently, the research questions will effectively be addressed.

3.3 Data Collection

A virtual patient cohort will be simulated to model clinical insulin-glucose data observed in patients in the intensive care unit. A patient model consists of simulated insulin-glucose dynamics ($G, Q, I, P1, P2$) represented in Equations (2.1) to (2.5), known insulin sensitivity $S_I(t)$, exogenous insulin $u_{ex}(t)$, and enteral feed $D(t)$. The population constants listed in Table 2.1 are assigned to the constant parameters for all virtual patients. To simulate patient data, each virtual patient (100 total patients) is given an initial state for the dynamics x_0 . Blood glucose concentration (mmol/L) has been demonstrated to have an underlying log-normal distribution [23], thus, for the purpose of this experiment, we can define blood glucose as the following random variable $\ln G \sim N(2.02, 1.3^2)$, with each patient being assigned an unique initial state of

$$\begin{aligned} x_0 &= [G_0 \quad Q_0 \quad I_0 \quad P1_0 \quad P2_0] \\ &= [\exp(\ln G) \quad 15.0 \quad 15.0 \quad 0.0 \quad 0.0]. \end{aligned} \quad (3.1)$$

Q_0 and I_0 are both chosen as 15.0 (mU/L) as the initial interstitial and plasma insulin concentration are in line with measurements collected to model an insulin-glucose system [24]. The initial glucose concentration (mmol/L) in the stomach $P1_0$ and gut $P2_0$ are assumed to be zero at the beginning of insulin infusion and feeding. All patients are given continuous ($t = \text{mins}$) exogenous insulin input

$$u_{ex}(t) = 140 \exp\left(-\frac{\log 2}{300}(t \bmod 300)\right) \text{ (mU/min)}, \quad (3.2)$$

and a constant enternal intake of glucose

$$D(t) = 0.30 \text{ (mmol/min)}. \quad (3.3)$$

The units of insulin per hour (U/hr) can be derived as

$$\frac{1}{1000} \int_{t_1}^{t_1+60} u_{ex}(t) dt \approx 7.84 \text{ (U/hr)} \quad \text{for } t > 300, \quad (3.4)$$

as well as the total caloric intake of glucose per day

$$\frac{0.30 \text{ (mol/min)}}{1000} \times 180.156 \text{ (g/mol)} \times 1440 \text{ (min)} \times 4 \text{ (kcal/day)} \approx 304 \text{ (kcal/day)}, \quad (3.5)$$

with both aligning in typical ranges given to ICU patients in the Karolinska University Hospital.

Given all the initial states x_0 , known insulin sensitivity $S_I(t)$, and the patient inputs $u_{ex}(t)$, $D(t)$, the patient cohort can be generated by solving the Differential Equations (2.1) to (2.5) from times 0 mins to 3600 mins with a time step of $dt = 1$ min for each patient. The ODE solver `scipy.integrate.solve_ivp`* function in python will be applied with the Explicit Runge-Kutta of order 5(4) integration method [25] to solve for the necessary dynamics.

3.4 Assessing reliability and validity of the data collected

A virtual patient cohort is a simplified model to characterize the target population of patients in the intensive care unit, given certain assumptions of the patients. Each patient will have their unique insulin-glucose model that contains all the recorded dynamics and inputs in time.

3.4.1 Validity of method

The patient models, parameters, and initial states are all adopted and cross-validated from multiple clinically validated studies. This provides a physiologically accurate basis to the control variables of the experiment.

*https://docs.scipy.org/doc/scipy/reference/generated/scipy.integrate.solve_ivp.html

Interventions in the experiment can be assessed and compared knowing the manipulated variable is correlated with the change in the output and not due to poor model formulation.

3.4.2 Reliability of method

Simulating patient data gives the necessary control to assign all patient parameters. A clear benefit of virtual patients is the repeatability of experiments, given identical patient parameters. Often in clinical settings, the true patient dynamics and parameters are unknown. Thus, results from clinical data may not be repeatable under the same conditions as there could be unaccounted for variables in the methods.

3.5 Planned Data Analysis

3.6 Evaluation framework

Chapter 4

Research Methodology

In order to evaluate the estimation of patient-specific parameters, the methodology will follow a trajectory of investigating patient identifiability in insulin-glucose models, comparing state estimators in stochastic models, and then assessing computational parameter estimation methods. Each phase of the experiment will have their own respective patient cohort, and statistical metrics. As previously mentioned, measurements of the patient model y_k correspond on lone observations of blood glucose corrupted with zero-mean Gaussian noise, which will be used for all of the following sections.

4.1 Observability and Identifiability in Patient Insulin-Glucose Models

In Chapter 3, a patient model was created for each individual patients based on the Intensive Control Insulin-Glucose model, with the ensemble of patient models being labeled as a patient cohort. For a particular patient model to be identifiable, it must be possible to learn the underlying unique patient-specific parameters that define the model, given a sufficient number of observations. To establish if the formulation of the patient model is identifiable, a mathematical analysis can determine the relationship of the insulin-glucose dynamics and the observations.

4.2 Nonlinear State Estimation

4.2.1 Extended Kalman Filter

4.2.2 Bootstrap Particle Filter

4.3 Parameter Estimation

4.3.1 Parameters of Interest

4.3.2 Computational Methods

4.3.2.1 Integral-Based Fitting

4.3.2.2 State-Augmentation

4.3.2.3 Markov Chain Monte Carlo

Chapter 5

Results and Analysis

5.1 Major results

Theorem 1. *Given a blood glucose measurement, there exists a nonunique solution for the unknown insulin sensitivity S_I and the interstitial glucose concentration Q .*

Proof. Let y be a positive blood glucose measurement corrupted with zero-mean Gaussian measurement noise of variance σ^2 , and $f(S_I, Q)$ denotes the true blood glucose in terms of the corresponding insulin sensitivity and interstitial glucose concentration from the ODE in Equation (2.1). Under the Maximum Likelihood Expectation criterion for a Gaussian process, the most probable S_I and Q given the observation is the maximum of the log-likelihood

$$\begin{aligned}
 P(S_I, Q | y) &= \frac{P(y | S_I, Q)P(S_I, Q)}{P(y)} \\
 &= \frac{P(y | S_I, Q)P(S_I)P(Q)}{P(y)} \\
 S_I^*, Q^* &= \arg \max_{S_I, Q} \ln P(y | S_I, Q) \\
 &= \arg \max_{S_I, Q} \ln \left(\frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(y - f(S_I, Q))^2}{2\sigma^2}\right) \right) \\
 &= \arg \max_{S_I, Q} -\frac{1}{2} \ln(2\pi\sigma^2) - \frac{(y - f(S_I, Q))^2}{2\sigma^2},
 \end{aligned} \tag{5.1}$$

which yields the pair (S_I^*, Q^*) such that $f(S_I^*, Q^*) = y$.

Let H_0 and H_1 denote the null and alternative hypotheses, respectively.

- H_0 : Given the measurement y , the pair (S_I^*, Q^*) is the unique solution for S_I and Q of Equation (2.1)
- H_1 : Given the same measurement y , there exists nonzero perturbations (δ_S, δ_Q) such that $(S_I^* + \delta_S, Q^* + \delta_Q)$ satisfies Equation (2.1), so that the solution is nonunique.

For H_0 to be true, if δ_Q is nonzero, there should be no δ_S that satisfies the given equation

$$(S_I^* + \delta_S)y \frac{(Q^* + \delta_Q)}{1 + \alpha_G(Q^* + \delta_Q)} - S_I^*y \frac{Q^*}{1 + \alpha_G Q^*} = 0 \quad \text{for } \delta_Q \neq -\frac{1}{\alpha_G} - Q^*, \quad (5.2)$$

as that would imply S_I^* is dependent on Q^* . If one continues to solve for Equation (5.2), you would arrive at the following result

$$\delta_S = \frac{S_I^* Q^* (1 + \alpha_G(Q^* + \delta_Q))}{(Q^* + \delta_Q)(1 + \alpha_G Q^*)} - S_I^* \quad \text{for } \delta_Q \notin \left\{-\frac{1}{\alpha_G} - Q^*, -Q^*\right\}. \quad (5.3)$$

Thus, given a nonzero δ_Q , there exists a corresponding δ_S , which would result in rejecting the hypothesis H_0 . $\square$




Figure 5.1: The performance of approximating insulin sensitivity with the integral-based method across various measurement noise.

Table 5.1: Comparing different estimators based on their respective time complexity and prediction performance regarding blood glucose.

Estimator	Median (Run Time, s)	IQR (Run Time, s)	Median (MSE)	IQR (MSE)
EKF	0.3252	0.0092	0.3998	0.0356
PF ($N = 500$)	129.1	1.686	0.3991	0.0400
PF ($N = 750$)	193.6	1.870	0.3954	0.0364
PF ($N = 1000$)	257.8	2.067	0.3962	0.0384
PF ($N = 1250$)	323.1	2.895	0.3962	0.0363

The extended Kalman Filter is denoted as EKF, with PF representing the particle filter with N total particles.

5.2 Reliability Analysis

Analys av tillförlitlighet
Tillförlitlighet i metod och data

5.3 Validity Analysis

Analys av validitet
Validitet i metod och data

Chapter 6

Discussion

Chapter 7

Conclusions and Future work

Slutsats och framtida arbete

Add text to introduce the subsections of this chapter.

7.1 Conclusions

Slutsatser

Describe the conclusions (reflect on the whole introduction given in Chapter 1).

Discuss the positive effects and the drawbacks.

Describe the evaluation of the results of the degree project.

Did you meet your goals?

What insights have you gained?

What suggestions can you give to others working in this area?

If you had it to do again, what would you have done differently?

Uppfyllde du dina mål?

Vilka insikter har du fått?

Vilka förslag kan du ge till andra som arbetar inom detta område? Om du skulle göra detta igen, vad skulle du ha gjort annorlunda?

7.2 Limitations

Begränsande faktorer

Vad gjorde du som begränsade dina ansträngningar? Vilka är begränsningarna i dina resultat?

What did you find that limited your efforts? What are the limitations of your results?

7.3 Future work

Vad du har kvar ogjort?

Vad är nästa självklara saker som ska göras?

Vad tips kan du ge till nästa person som kommer att följa upp på ditt arbete?

Describe valid future work that you or someone else could or should do. Consider: What you have left undone? What are the next obvious things to be done? What hints can you give to the next person who is going to follow up on your work?

Due to the breadth of the problem, only some of the initial goals have been met. In these section we will focus on some of the remaining issues that should be addressed in future work. ...

7.3.1 What has been left undone?

The prototype does not address the third requirement, *i.e.*, a yearly unavailability of less than 3 minutes, this remains an open problem. ...

7.3.1.1 Cost analysis

Example of a missing component

The current prototype works, but the performance from a cost perspective makes this an impractical solution. Future work must reduce the cost of this solution, to do so a cost analysis needs to first be done. ...

7.3.1.2 Security

Example of a missing component

A future research effort is needed to address the security holes that results from using a self-signed certificate. Page filling text mass. Page filling text mass. ...

7.3.2 Next obvious things to be done

In particular, the author of this thesis wishes to point out xxxxxx remains as a problem to be solved. Solving this problem is the next thing that should be done. ...

7.4 Reflections

Reflektioner

Vilka är de relevanta ekonomiska, sociala, miljömässiga och etiska aspekter av ditt arbete?

What are the relevant economic, social, environmental, and ethical aspects of your work?

One of the most important results is the reduction in the amount of energy required to process each packet while at the same time reducing the time required to process each packet.

The thesis contributes to the **United Nations (UN) Sustainable Development Goals (SDGs)** numbers 1 and 9 by xxxx.

In the references, let Zotero or other tool fill this in for you. I suggest an extended version of the IEEE style, to include URLs, DOIs, ISBNs, etc., to make it easier for your reader to find them. This will make life easier for your opponents and examiner.
IEEE Editorial Style Manual: https://www.ieee.org/content/dam/ieee-org/ieee/web/org/conferences/style_references_manual.pdf

Låt Zotero eller annat verktyg fylla i det här för dig. Jag föreslår en utökad version av IEEE stil - att inkludera webbadresser, DOI, ISBN etc. - för att göra det lättare för läsaren att hitta dem. Detta kommer att göra livet lättare för dina opponenter och examinerator.

References

- [1] K. M. Dungan, S. S. Braithwaite, and J.-C. Preiser, “Stress hyperglycaemia,” *The Lancet*, vol. 373, no. 9677, pp. 1798–1807, May 2009. doi: 10.1016/S0140-6736(09)60553-5. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0140673609605535> [Page 1.]
- [2] P. Paolisso, A. Foà, L. Bergamaschi, F. Donati, M. Fabrizio, C. Chiti, F. Angeli, S. Toniolo, A. Stefanizzi, M. Armillotta, P. Rucci, G. Iannopollo, G. Casella, C. Marrozzini, N. Galiè, and C. Pizzi, “Hyperglycemia, inflammatory response and infarct size in obstructive acute myocardial infarction and MINOCA,” *Cardiovascular Diabetology*, vol. 20, no. 1, p. 33, Feb. 2021. doi: 10.1186/s12933-021-01222-9. [Online]. Available: <https://doi.org/10.1186/s12933-021-01222-9> [Page 1.]
- [3] G. Song, X. Liu, Z. Lu, J. Guan, X. Chen, Y. Li, G. Liu, G. Wang, and F. Ma, “Relationship between stress hyperglycaemic ratio (SHR) and critical illness: a systematic review,” *Cardiovascular Diabetology*, vol. 24, no. 1, p. 188, May 2025. doi: 10.1186/s12933-025-02751-3. [Online]. Available: <https://doi.org/10.1186/s12933-025-02751-3> [Page 1.]
- [4] C. H. Lang, C. Dobrescu, and K. Mészáros, “Insulin-mediated glucose uptake by individual tissues during sepsis,” *Metabolism*, vol. 39, no. 10, pp. 1096–1107, Oct. 1990. doi: 10.1016/0026-0495(90)90172-9. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/0026049590901729> [Page 1.]
- [5] R. C. ANDREWS and B. R. WALKER, “Glucocorticoids and insulin resistance: old hormones, new targets,” *Clinical Science*, vol. 96, no. 5, pp. 513–523, Apr. 1999. doi: 10.1042/cs0960513. [Online]. Available: <https://doi.org/10.1042/cs0960513> [Page 1.]

- [6] R. E. Shangraw, F. Jahoor, H. Miyoshi, W. A. Neff, C. A. Stuart, D. N. Herndon, and R. R. Wolfe, "Differentiation between septic and postburn insulin resistance," *Metabolism*, vol. 38, no. 10, pp. 983–989, Oct. 1989. doi: 10.1016/0026-0495(89)90010-3. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/0026049589900103> [Page 1.]
- [7] T. Heise, L. Heinemann, and A. A. R. Starke, "Simulated postaggression metabolism in healthy subjects: Metabolic changes and insulin resistance," *Metabolism*, vol. 47, no. 10, pp. 1263–1268, Oct. 1998. doi: 10.1016/S0026-0495(98)90334-1. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0026049598903341> [Page 1.]
- [8] G. V. d. Berghe, P. Wouters, F. Weekers, C. Verwaest, F. Bruyninckx, M. Schetz, D. Vlasselaers, P. Ferdinande, P. Lauwers, and R. Bouillon, "Intensive Insulin Therapy in Critically Ill Patients," *New England Journal of Medicine*, vol. 345, no. 19, pp. 1359–1367, Nov. 2001. doi: 10.1056/NEJMoa011300_eprint: <https://www.nejm.org/doi/pdf/10.1056/NEJMoa011300>. [Online]. Available: <https://www.nejm.org/doi/full/10.1056/NEJMoa011300> [Page 1.]
- [9] F. M. Brunkhorst, C. Engel, F. Bloos, A. Meier-Hellmann, M. Ragaller, N. Weiler, O. Moerer, M. Gruendling, M. Oppert, S. Grond, D. Olthoff, U. Jaschinski, S. John, R. Rossaint, T. Welte, M. Schaefer, P. Kern, E. Kuhnt, M. Kiehntopf, C. Hartog, C. Natanson, M. Loeffler, and K. Reinhart, "Intensive Insulin Therapy and Pentastarch Resuscitation in Severe Sepsis," *New England Journal of Medicine*, vol. 358, no. 2, pp. 125–139, Jan. 2008. doi: 10.1056/NEJMoa070716_eprint: <https://www.nejm.org/doi/pdf/10.1056/NEJMoa070716>. [Online]. Available: <https://www.nejm.org/doi/full/10.1056/NEJMoa070716> [Page 1.]
- [10] NICE-SUGAR Study Investigators, S. Finfer, B. Liu, D. R. Chittock, R. Norton, J. A. Myburgh, C. McArthur, I. Mitchell, D. Foster, V. Dhingra, W. R. Henderson, J. J. Ronco, R. Bellomo, D. Cook, E. McDonald, P. Dodek, P. C. Hébert, D. K. Heyland, and B. G. Robinson, "Hypoglycemia and risk of death in critically ill patients," *The New England Journal of Medicine*, vol. 367, no. 12, pp. 1108–1118, Sep. 2012. doi: 10.1056/NEJMoa1204942 [Page 1.]

- [11] L. Evans, A. Rhodes, W. Alhazzani, M. Antonelli, C. M. Coopersmith, C. French, F. R. Machado, L. McIntyre, M. Ostermann, H. C. Prescott, C. Schorr, S. Simpson, W. J. Wiersinga, F. Alshamsi, D. C. Angus, Y. Arabi, L. Azevedo, R. Beale, G. Beilman, E. Belley-Cote, L. Burry, M. Cecconi, J. Centofanti, A. Coz Yataco, J. De Waele, R. P. Dellinger, K. Doi, B. Du, E. Estenssoro, R. Ferrer, C. Gomersall, C. Hodgson, M. H. Møller, T. Iwashyna, S. Jacob, R. Kleinpell, M. Klompas, Y. Koh, A. Kumar, A. Kwizera, S. Lobo, H. Masur, S. McGloughlin, S. Mehta, Y. Mehta, M. Mer, M. Nunnally, S. Oczkowski, T. Osborn, E. Papathanassoglou, A. Perner, M. Puskarich, J. Roberts, W. Schweickert, M. Seckel, J. Sevransky, C. L. Sprung, T. Welte, J. Zimmerman, and M. Levy, “Surviving sepsis campaign: international guidelines for management of sepsis and septic shock 2021,” *Intensive Care Medicine*, vol. 47, no. 11, pp. 1181–1247, Nov. 2021. doi: 10.1007/s00134-021-06506-y. [Online]. Available: <https://doi.org/10.1007/s00134-021-06506-y> [Page 1.]
- [12] J. G. Chase, G. M. Shaw, T. Lotz, A. LeCompte, J. Wong, J. Lin, T. Lonergan, M. Willacy, and C. E. Hann, “Model-Based Insulin and Nutrition Administration for Tight Glycaemic Control in Critical Care,” *Current Drug Delivery*, vol. 4, no. 4, pp. 283–296. doi: 10.2174/156720107782151223. [Online]. Available: <https://www.eurekaselect.com/article/4990> [Pages 2 and 5.]
- [13] T. F. Lotz, J. G. Chase, K. A. McAuley, G. M. Shaw, X.-W. Wong, J. Lin, A. LeCompte, C. E. Hann, and J. I. Mann, “Monte Carlo analysis of a new model-based method for insulin sensitivity testing,” *Computer Methods and Programs in Biomedicine*, vol. 89, no. 3, pp. 215–225, Mar. 2008. doi: 10.1016/j.cmpb.2007.03.007. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0169260707000582> [Pages 2 and 5.]
- [14] J. Lin, N. N. Razak, C. G. Pretty, A. Le Compte, P. Docherty, J. D. Parente, G. M. Shaw, C. E. Hann, and J. Geoffrey Chase, “A physiological Intensive Control Insulin-Nutrition-Glucose (ICING) model validated in critically ill patients,” *Computer Methods and Programs in Biomedicine*, vol. 102, no. 2, pp. 192–205, May 2011. doi: 10.1016/j.cmpb.2010.12.008. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0169260710003007> [Pages 2 and 5.]

- [15] C. E. Hann, J. G. Chase, J. Lin, T. Lotz, C. V. Doran, and G. M. Shaw, “Integral-based parameter identification for long-term dynamic verification of a glucose–insulin system model,” *Computer Methods and Programs in Biomedicine*, vol. 77, no. 3, pp. 259–270, Mar. 2005. doi: 10.1016/j.cmpb.2004.10.006. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0169260704002123> [Pages 2, 6, and 16.]
- [16] A. L. Compte, J. G. Chase, A. Lynn, C. Hann, G. Shaw, X.-W. Wong, and J. Lin, “Blood Glucose Controller for Neonatal Intensive Care: Virtual Trials Development and First Clinical Trials,” *Journal of Diabetes Science and Technology*, vol. 3, no. 5, pp. 1066–1081, Sep. 2009. doi: 10.1177/193229680900300510. [Online]. Available: <https://journals.sagepub.com/doi/10.1177/193229680900300510> [Pages 2 and 6.]
- [17] J. G. Chase, G. M. Shaw, J. Lin, C. V. Doran, C. Hann, M. B. Robertson, P. M. Browne, T. Lotz, G. C. Wake, and B. Broughton, “Adaptive bolus-based targeted glucose regulation of hyperglycaemia in critical care,” *Medical Engineering & Physics*, vol. 27, no. 1, pp. 1–11, Jan. 2005. doi: 10.1016/j.medengphy.2004.08.006. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S1350453304001420> [Page 6.]
- [18] J. Hahn and T. F. Edgar, “An improved method for nonlinear model reduction using balancing of empirical gramians,” *Computers & Chemical Engineering*, vol. 26, no. 10, pp. 1379–1397, Oct. 2002. doi: 10.1016/S0098-1354(02)00120-5. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0098135402001205> [Page 7.]
- [19] C. Eberle and C. Ament, “Identifiability and online estimation of diagnostic parameters with in the glucose insulin homeostasis,” *Biosystems*, vol. 107, no. 3, pp. 135–141, Mar. 2012. doi: 10.1016/j.biosystems.2011.11.003. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0303264711001857> [Page 8.]
- [20] S. Särkkä and L. Svensson, “Bayesian Filtering and Smoothing.” [Pages 9, 10, 12, 13, 14, and 15.]

- [21] J. S. Liu, *Monte Carlo Strategies in Scientific Computing*, ser. Springer Series in Statistics. New York, NY: Springer, 2004. ISBN 978-0-387-76369-9 978-0-387-76371-2. [Online]. Available: <http://link.springer.com/10.1007/978-0-387-76371-2> [Pages 11 and 12.]
- [22] B. Ninness and S. Henriksen, “Bayesian system identification via Markov chain Monte Carlo techniques,” *Automatica*, vol. 46, no. 1, pp. 40–51, Jan. 2010. doi: 10.1016/j.automatica.2009.10.015. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0005109809004762> [Pages 14 and 15.]
- [23] S. Davidson, C. Pretty, V. Uyttendaele, J. Knopp, T. Desai, and J. G. Chase, “Multi-input stochastic prediction of insulin sensitivity for tight glycaemic control using insulin sensitivity and blood glucose data,” *Computer Methods and Programs in Biomedicine*, vol. 182, p. 105043, Dec. 2019. doi: 10.1016/j.cmpb.2019.105043. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0169260718314342> [Page 20.]
- [24] C. Dalla Man, R. A. Rizza, and C. Cobelli, “Meal Simulation Model of the Glucose-Insulin System,” *IEEE Transactions on Biomedical Engineering*, vol. 54, no. 10, pp. 1740–1749, Oct. 2007. doi: 10.1109/TBME.2007.893506. [Online]. Available: <https://ieeexplore.ieee.org/document/4303268> [Page 20.]
- [25] J. Dormand and P. Prince, “A family of embedded Runge-Kutta formulae,” *Journal of Computational and Applied Mathematics*, vol. 6, no. 1, pp. 19–26, Mar. 1980. doi: 10.1016/0771-050X(80)90013-3. [Online]. Available: <https://linkinghub.elsevier.com/retrieve/pii/0771050X80900133> [Page 21.]

Appendix A

Something Extra

svensk: Extra Material som Bilaga

A.1 Just for testing KTH colors

You have selected to optimize for print output

- Primary color

- kth-blue 

- kth-blue80 

- Secondary colors

- kth-lightblue 

- kth-lightred 

- kth-lightred80 

- kth-lightgreen 

- kth-coolgray 

- kth-coolgray80 

black 

Appendix B

Main equations

This appendix gives some examples of equations that are used throughout this thesis.

B.1 A simple example

The following example is adapted from Figure 1 of the documentation for the package `nomencl` (<https://ctan.org/pkg/nomencl>).

$$a = \frac{N}{A} \tag{B.1}$$

The equation $\sigma = ma$ follows easily from Equation (B.1).

B.2 An even simpler example

The formula for the diameter of a circle is shown in Equation (B.2) area of a circle is shown in eq. (B.3).

$$D_{circle} = 2\pi r \tag{B.2}$$

$$A_{circle} = \pi r^2 \tag{B.3}$$

Some more text that refers to (B.3).

€€€€ For DIVA €€€€

```
{
  "Author1": { "Last name": "Mulvihill",
    "First name": "Markus",
    "Local User Id": "u100001",
    "E-mail": "mulvkth.se",
    "organisation": { "L1": "School of Electrical Engineering and Computer Science",
      }
    },
  "Cycle": "2",
  "Course code": "EA260X",
  "Credits": "30.0",
  "Degree1": { "Educational program": "Master's Programme, Information and Network Engineering, 120 credits"
    , "programcode": "TINNM"
    , "Degree": "Master's"
    , "subjectArea": "Decision and Control Systems"
    },
  "Title": {
    "Main title": "Patient-Specific Parameter Estimation in Mechanistic Insulin-Glucose Models",
    "Subtitle": "Degree Project 2026",
    "Language": "eng" },
    "Alternative title": {
      "Main title": "Detta är den svenska översättnin gen av titeln",
      "Subtitle": "Detta är den svenska översättningen av undertiteln",
      "Language": "swe"
    },
    "Supervisor1": { "Last name": "Lindström",
      "First name": "Martin",
      "Local User Id": "u15dficv",
      "E-mail": "martin12@kth.se",
      "organisation": { "L1": "School of Electrical Engineering and Computer Science",
        "L2": "Teknisk informationsvetenskap" }
      },
      "Examiner1": { "Last name": "Thobaben",
        "First name": "Ragnar",
        "Local User Id": "u1rs7mp9",
        "E-mail": "ragnart@kth.se",
        "organisation": { "L1": "School of Electrical Engineering and Computer Science",
          "L2": "Teknisk informationsvetenskap" }
        },
        "National Subject Categories": "10201, 10206",
        "Other information": { "Year": "2026", "Number of pages": "1,45" },
        "Copyrightleft": "copyright",
        "Series": { "Title of series": "TRITA-EECS-EX" , "No. in series": "2022:00" },
        "Opponents": { "Name": "A. B. Normal & A. X. E. Normalè" },
        "Presentation": { "Date": "2022-03-15 13:00"
          , "Language": "eng"
          , "Room": "via Zoom https://kth-se.zoom.us/j/ddddddd"
          , "Address": "Isafjordsgatan 22 (Kistagången 16)"
          , "City": "Stockholm" },
          "Number of lang instances": "2",
          "Abstract[eng ]": €€€€
          Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. €€€€,
          "Keywords[eng ]": €€€€
          Canvas Learning Management System, Docker containers, Performance tuning €€€€,
          "Abstract[swe ]": €€€€
          Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. €€€€,
          "Keywords[swe ]": €€€€
          Canvas Lärplattform, Dockerbehållare, Prestandajustering €€€€,
```


acronyms.tex

```
%%% Local Variables:
%%% mode: latex
%%% TeX-master: t
%%% End:
% The following command is used with glossaries-extra
\setabbreviationstyle{acronym}{long-short}
% The form of the entries in this file is \newacronym{label}{acronym}{phrase}
%                                     or \newacronym[options]{label}{acronym}{phrase}
% see "User Manual for glossaries.sty" for the details about the options, one example is shown below
% note the specification of the long form plural in the line below
\newacronym[longplural={Debugging Information Entities}]{DIE}{DIE}{Debugging Information Entity}
%
% The following example also uses options
\newacronym[shortplural={OSes}, firstplural={operating systems (OSes)}]{OS}{OS}{operating system}

% note the use of a non-breaking dash in long text for the following acronym
\newacronym{IQL}{IQL}{Independent Q-Learning} % <-- regular dash

\newacronym{KTH}{KTH}{KTH Royal Institute of Technology}

\newacronym{LAN}{LAN}{Local Area Network}
\newacronym{VM}{VM}{virtual machine}
% note the use of a non-breaking dash in the following acronym
\newacronym{WiFi}{Wi-Fi}{Wireless Fidelity}

\newacronym{WLAN}{WLAN}{Wireless Local Area Network}
\newacronym{UN}{UN}{United Nations}
\newacronym{SDG}{SDG}{Sustainable Development Goal}
```