

THE PROBLEM

Three answers before you edit.

Where

The exact file and line.

Who

People who still change that file.

What breaks

The tests to run, and every importer.

DEMO · EXPRESS · 5.1s

lib/response.js:236

```
$ pnpm dev ask "where is the response json method implemented?" -d ../demo-repos/express
```

scanned 153 files · asking grok-4.6 via grok-cli...

→ lib/response.js:236

This is where Express implements `res.json()` on the response prototype.

 Ask: Sebastian Beltran (2 commits, 8 months ago), cui fliter (1 commit, 2 weeks ago)

 Run: test/res.json.js, test/res.jsonp.js, test/app.response.js

 Blast radius: low (1 importer: lib/express.js)

5.1s

HOW IT WORKS

Local files. Checked lines.

01

Scan the repo on disk.

02

Send excerpts, not the tree.

03

Resolve the line in the file.

04

Add owners, tests, blast radius.

FOR AGENTS TOO

Your agent asks first.

```
$ whereis ask "where is res.json implemented?" -d ../demo-repos/express --json
[{"file": "lib/response.js", "line": 236,
  "why": "Defines res.json on the response.",
  "owners": [{"name": "Sebastian Beltran", ... }],
  "tests": ["test/res.json.js", ...],
  "blast": { "label": "low", "count": 1,
             "paths": ["lib/express.js"] } }]
```

01

Edit the right line

verified file:line, not a guess

02

Run the right tests

before and after the change

03

Know the risk

blast radius decides "just do it" vs "ask a human"

Today: --json for any agent. Next: MCP server + Cursor rule.

BUILT IN CURSOR

Spec first.

19 min

Cursor Agent build time

9 / 9

tasks from the spec

6 / 6

acceptance tests pass

requirements → design → tasks, checked one task at a time.

WHEREIS

Cursor tells you
where the code is.

whereis tells you where it is,
who knows it, and what you'll break.



github.com/
mlomovskoy/whereis-cli