

---

# A Mathematical Exploration of Why Language Models Help Solve Downstream Tasks

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract

1 Autoregressive language models pretrained on large corpora have been successful  
2 at solving downstream tasks, even with zero-shot usage. However, there is little the-  
3 oretical justification for their success. This paper considers the following questions:  
4 (1) Why should learning the distribution of natural language help with downstream  
5 classification tasks? (2) Why do features learned using language modeling help  
6 solve downstream tasks with *linear classifiers*? For (1), we hypothesize, and verify  
7 empirically, that classification tasks of interest can be reformulated as next word  
8 prediction tasks, thus making language modeling a meaningful pretraining task.  
9 For (2), we analyze properties of the cross-entropy objective to show that  $\epsilon$ -optimal  
10 language models in cross-entropy (log-perplexity) learn features that are  $\mathcal{O}(\sqrt{\epsilon})$ -  
11 good on natural linear classification tasks, thus demonstrating mathematically that  
12 doing well on language modeling can be beneficial for downstream tasks. We  
13 perform experiments to verify assumptions and validate theoretical results. Our  
14 theoretical insights motivate a simple alternative to the cross-entropy objective that  
15 performs well on some linear classification tasks.

## 16 1 Introduction

17 The construction of increasingly powerful language models that use gigantic text corpora and a cross-  
18 entropy objective to predict a distribution over the next word after a given context, has revolutionized  
19 natural language processing (NLP). The learned representations are useful for many other tasks, either  
20 as initializations [Ramachandran et al., 2017, Howard and Ruder, 2018] or as a source of contextual  
21 word embeddings [McCann et al., 2017, Peters et al., 2018]. Although representations previously  
22 needed fine-tuning to solve downstream tasks, recent models [Radford et al., 2019, Brown et al.,  
23 2020] have demonstrated strong performance even without fine-tuning.

24 Next word prediction being a powerful test of language understanding, intuitively it is believable that  
25 language modeling can help with downstream tasks. It is still intriguing how even small decreases in  
26 test perplexity can lead to improved downstream performance. Though inductive biases of models and  
27 algorithms play a role in this success, it is very challenging to say anything mathematically precise  
28 about this, given the nascency of deep learning theory. Instead we take a stab at the mathematical  
29 study of why solving the next-word prediction should intrinsically learn representations useful for  
30 downstream tasks. As a first cut analysis, we restrict attention to *classification tasks* and the striking  
31 observation that they can be solved fairly well using linear classifiers on language model features  
32 without fine-tuning. Although we are forced to treat models as black boxes, just first-order optimality  
33 conditions reveal interesting properties of the learned features, leading to an understanding of their  
34 success on interesting linear classification tasks. We now summarize our contributions.

35 With the observation that classification tasks of interest can be phrased as sentence completion tasks,  
36 we define *natural classification tasks*, in Section 3, as those that can be solved as *linear functions*

of the conditional distribution over words that can follow a given context. Section 4 presents our main results, theorems 4.1 and 4.2, that mathematically quantify the benefit of language model features for solving natural tasks. We show that a  $\epsilon$ -optimal language model (in cross-entropy) will do  $\mathcal{O}(\sqrt{\epsilon})$ -well on natural tasks. Theorem 4.2 proves a stronger result for low dimensional softmax models using a new tool that we call *conditional mean features* (Definition C.1), which empirically (Section 5) does well. We construct a new mathematically motivated objective Quad with provable guarantees (Section 4); we report its good performance on linear classification tasks (Section 5).

## 2 Language modeling and optimal solutions

We use  $\mathcal{S}$  to denote the set of contexts (sentences and partial sentences),  $\mathcal{W}$  to denote the set of words, with  $V = |\mathcal{W}|$ .  $\Delta_A$  denotes the set of all distributions on  $A$ .  $p_{\cdot|s}, p_{\cdot|s}^* \in \Delta_{\mathcal{W}}$  denote distributions over next word given a context  $s$ ; we also use  $p_{\cdot|s}, p_{\cdot|s}^* \in \mathbb{R}^V$  also as vectors of probabilities.  $\phi_w \in \mathbb{R}^d$  is a  $d$ -dimensional embedding for word  $w \in \mathcal{W}$ . Embeddings are stacked into a matrix  $\Phi \in \mathbb{R}^{d \times V}$ .

**Unconstrained language modeling using cross-entropy:** The goal is to learn the true distribution of a text corpus by predicting  $p_{\cdot|s}$  for a context  $s \in \mathcal{S}$  (e.g.  $s = \text{“The food was ”}$ ,  $p_{\cdot|s}$  is supported on “delicious”, “expensive”, etc.). Let  $p_L$  be the distribution over  $\mathcal{S}$  in the corpus and  $p_{\cdot|s}^*$  be the true conditional distribution. It is standard to minimize the expected cross-entropy between  $p_{\cdot|s}^*$  and  $p_{\cdot|s}$ .

$$\ell_{\text{xent}}(\{p_{\cdot|s}\}) = \mathbb{E}_{s \sim p_L} [\ell_{\text{xent},s}(p_{\cdot|s})] = \mathbb{E}_{s \sim p_L} \mathbb{E}_{w \sim p_{\cdot|s}^*} [-\log(p_{\cdot|s}(w))] \quad (1)$$

Using  $\ell_{\text{xent},s}(p_{\cdot|s}) - \ell_{\text{xent},s}(p_{\cdot|s}^*) = D_{\text{KL}}(p_{\cdot|s}^* \| p_{\cdot|s})$ , it is easy to show that this recovers  $p_{\cdot|s}^*$  exactly.

**Proposition 2.1.** *The unique minimizer of  $\ell_{\text{xent}}(\{p_{\cdot|s}\})$  is  $p_{\cdot|s} = p_{\cdot|s}^*$  for every  $s \sim p_L$ .*

**Softmax parametrized language modeling:** Recent models parametrize  $p_{\cdot|s}$  as a softmax computed using *low dimensional* embeddings  $f(s) \in \mathbb{R}^d$ , where  $f$  is the output of a model architecture of choice. These embeddings then induce the softmax distribution  $p_{\cdot|s} = p_{f(s)}$  with  $p_{f(s)}(w) = e^{f(s)^\top \phi_w} / Z_{f(s)}$ , where  $Z_\theta = \sum_{w' \in \mathcal{W}} e^{\theta^\top \phi_{w'}}$ . We can now rewrite the cross-entropy for this setting

$$\ell_{\text{xent}}(f, \Phi) = \mathbb{E}_{s \sim p_L} [\ell_{\text{xent},s}(p_{f(s)})] = \mathbb{E}_{s \sim p_L} \left[ \mathbb{E}_{w \sim p_{\cdot|s}^*} [-f(s)^\top \phi_w] + \log(Z_{f(s)}) \right] \quad (2)$$

We define  $\ell_{\text{xent},s}(\theta, \Phi) = \ell_{\text{xent},s}(p_\theta)$ . Analogous to Proposition 2.1, we want to know the optimal  $d$ -dimensional feature map  $f^*$  and the induced conditional distribution  $p_{f^*(s)}$ .

**Proposition 2.2.** *For a fixed  $\Phi$ , if  $f^* \in \arg \min_{f: \mathcal{S} \rightarrow \mathbb{R}^d} \ell_{\text{xent}}(f, \Phi)$ , then  $\Phi p_{f^*(s)} = \Phi p_{\cdot|s}^*$  for every  $s \sim p_L$ .*

Unlike Proposition 2.1,  $p_{f^*(s)} \in \mathbb{R}^V$  is only equal to  $p_{\cdot|s}^* \in \mathbb{R}^V$  in the subspace of the rows of  $\Phi \in \mathbb{R}^{d \times V}$ . Thus smaller values of  $d$  will guarantee learning  $p_{\cdot|s}^*$  on smaller subspaces.

**Downstream classification tasks:** We focus on binary classification tasks. Task  $\mathcal{T}$  is a distribution  $p_{\mathcal{T}}$  over  $\mathcal{S} \times \{\pm 1\}$ , with input sentence  $s \in \mathcal{S}$  and the label  $y \in \{\pm 1\}$ . Given a feature map  $g: \mathcal{S} \rightarrow \mathbb{R}^D$  (for any  $D$ ), we solve task  $\mathcal{T}$  by fitting a linear classifier  $\mathbf{v} \in \mathbb{R}^D$  on top of  $g(s)$ . The classification loss is written as  $\ell_{\mathcal{T}}(g, \mathbf{v}) = \mathbb{E}_{(s,y) \sim p_{\mathcal{T}}} [\ell(\mathbf{v}^\top g(s), y)]$ , where  $\ell$  is a 1-Lipschitz surrogate to the 0-1 loss<sup>1</sup>. The loss incurred by a representation function  $g$  is defined as  $\ell_{\mathcal{T}}(g) = \inf_{\mathbf{v} \in \mathbb{R}^D} \ell_{\mathcal{T}}(g, \mathbf{v})$ . For embeddings  $\{\theta_s\}_{s \in \mathcal{S}}$ , classification loss is thus  $\ell_{\mathcal{T}}(\{\theta_s\}, \mathbf{v}) = \mathbb{E}_{(s,y) \sim p_{\mathcal{T}}} [\ell(\mathbf{v}^\top \theta_s, y)]$ .

## 3 Using language models for classification tasks

Section 2 shows that both unconstrained and softmax language models aim to learn  $p_{\cdot|s}^*$  or a projection  $\Phi p_{\cdot|s}^*$ . Thus we ask: why should  $p_{\cdot|s}^*$  help with downstream tasks? We argue that classification tasks can be reframed as sentence completion problems and  $p_{\cdot|s}^*$  can give completions to predict the label.

<sup>1</sup>hinge  $\ell(\hat{y}, y) = (1 - y\hat{y})_+$  or the logistic  $\ell(\hat{y}, y) = \log(1 + e^{-y\hat{y}})$ . Extending to  $k$ -way tasks is easy.

In particular, for a movie review sentiment analysis task, we can compare probabilities of “:”) and “:(” after an input and predict sentiment based on which is higher. We can view this as learning a linear classifier  $v$  over  $p_{\cdot|s}^* \in \mathbb{R}^V$  to solve the task, where  $v[“:]” = 1$  and  $v[“(”] = -1$ . Since  $p_{\cdot|s}^*$  will place higher probability on words like “The” that are not useful for sentiment, we can also add a prompt like “This movie is ” and query probabilities of useful adjectives like “good”, “bad”, etc. This is also a linear classifier with positive and negative weights assigned to respective adjectives. This approach also works for AG news dataset [Zhang et al., 2015] with a prompt like “This article is about ’. We verify experimentally that SST and AG news tasks can be solved by a linear function of probabilities of just a small subset of words in Section 5. We can further formalize this intuition.

**Definition 3.1.** A classification task  $\mathcal{T}$  is  $(\tau, B)$ -natural if  $\min_{v \in \mathbb{R}^V, \|v\|_\infty \leq B} \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, v) \leq \tau$ .

Thus a natural task  $\mathcal{T}$  is one that can achieve a small error  $\tau$  by learning an  $\ell_\infty$ -norm bounded<sup>2</sup> linear classifier on top of features  $p_{\cdot|s}^* \in \mathbb{R}^V$ . Low dimensional softmax models, however, only learn  $p_{\cdot|s}^*$  in the subspace of  $\Phi$  (see Proposition 2.2). Thus we are interested in tasks this subspace can solve.

**Definition 3.2.** Task  $\mathcal{T}$  is  $(\tau, B)$ -natural w.r.t.  $\Phi \in \mathbb{R}^{d \times V}$  if  $\min_{v \in \text{row-span}(\Phi), \|v\|_\infty \leq B} \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, v) \leq \tau$ .

This subset of tasks is not too restrictive if  $\Phi$  assigns similar embeddings to synonyms. Section 4 describes a carefully designed objective that can provably learn such embeddings.

## 4 Guarantees for language models on natural tasks (overview)

We present simplified versions our main results that show that  $\epsilon$ -optimal language models will have a loss of  $\tau + \mathcal{O}(B\sqrt{\epsilon})$  on  $(\tau, B)$ -natural classification tasks (see Section C for detailed results), formalizing the intuition that better language models are more useful for downstream tasks. We first define optimal cross entropies.

$$\ell_{\text{xent}}^* = \ell_{\text{xent}}(\{p_{\cdot|s}^*\}), \quad \ell_{\text{xent}}^*(\Phi) = \mathbb{E}_{s \sim p_L} \left[ \inf_{\theta \in \mathbb{R}^d} \ell_{\text{xent},s}(\theta, \Phi) \right] \quad (3)$$

where  $\ell_{\text{xent}}^*$  is the absolute minimum achievable cross entropy, while  $\ell_{\text{xent}}^*(\Phi)$  is the minimum achievable cross entropy by a  $d$ -dimensional softmax language model that uses  $\Phi$ ; clearly  $\ell_{\text{xent}}^* \leq \ell_{\text{xent}}^*(\Phi)$ . We first present the simplified result for unconstrained language models.

**Theorem 4.1.** [Simplified, unconstrained] Let  $\{p_{\cdot|s}\}$  be a language model that is  $\epsilon$ -optimal, i.e.  $\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^* \leq \epsilon$ , for some  $\epsilon > 0$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural, we have

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$$

This bound applies to all language models, ( $n$ -gram models, softmax models), and suggests that smaller test cross-entropy is desirable to guarantee good downstream. The suboptimality  $\epsilon$  propagates gracefully as  $\mathcal{O}(\sqrt{\epsilon})$  to the task  $\mathcal{T}$ . While  $\tau$  is some small constant like 0.01, the norm bound  $B$  captures the difficulty of task  $\mathcal{T}$  when solved linearly using  $\{p_{\cdot|s}^*\}$ . Intuitively, if the words in support of the classifier (Section 3), have total probability mass of  $\Omega(\alpha)$  in  $p_{\cdot|s}^*$ , then  $B \sim \mathcal{O}(1/\alpha)$ . It is thus desirable for a task  $\mathcal{T}$  to depend on a larger and more frequent set of words. Adding a prompt, as in Section 3, can increase the set of indicative words, thus decreasing  $B$ .

For  $d$ -dimensional softmax language models, inspired by Proposition 2.2, we show guarantees for conditional mean features  $g_{f,\Phi}(s) = \Phi p_{f(s)} \in \mathbb{R}^d$ . This gives a way to use softmax language model features for linear classification; we test the success of this mechanism experimentally in Section 5.

**Theorem 4.2.** [Simplified, softmax] Let  $f$  be an  $\epsilon$ -optimal  $d$ -dimensional softmax language model, i.e.  $\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi) \leq \epsilon$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have

$$\ell_{\mathcal{T}}(g_{f,\Phi}) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$$

The key differences from Theorem 4.1 are, (1)  $\epsilon$  captures the suboptimality of learned language model compared  $\ell_{\text{xent}}^*(\Phi)$  and not  $\ell_{\text{xent}}^*$ , (2) guarantees are only for natural tasks w.r.t.  $\Phi$ . Theorem 4.1 can also

<sup>2</sup>Makes sense since  $\|p_{\cdot|s}^*\|_1 = 1$  &  $\|\cdot\|_\infty$  is dual norm of  $\|\cdot\|_1$ . See Theorem 4.1 for an interpretation of  $B$

Table 1: Pretrained GPT-2 performance on linear classification tasks using features  $f(s)$ ,  $p_{f(s)}$  and  $g_{f,\Phi}(s)$ . An asterisk indicates that we added a task-specific prompt.

Task	Features $f(s)$	$g_{f,\Phi}(s) = \Phi p_{f(s)}$	$p_{f(s)}$ over subset	$p_{f(s)}$ over class words
SST	87.6%	82.6%	78.2%	76.4%
SST*	89.5%	87.0%	83.5%	79.4%
AG news	90.7%	84.5%	78.3%	68.4%
AG news*	91.1%	88.0%	83.0%	71.4%

be invoked to get an upper bound of  $\mathcal{O}(B\sqrt{\epsilon + \epsilon_\Phi^*})$  instead of  $\mathcal{O}(B\sqrt{\epsilon})$ , where  $\epsilon_\Phi^* = \ell_\Phi^*(\Phi) - \ell_{\text{xent}}^*$ . Thus Theorem 4.2 is stronger since models only need optimality w.r.t. the best  $d$ -dimensional model. This improvement to  $\mathcal{O}(B\sqrt{\epsilon})$  comes at the cost of only having guarantees for natural tasks w.r.t.  $\Phi$ .

**$g_{f,\Phi}(s)$  is a linear function of  $f(s)$ :** While Theorem 4.2 shows that  $g_{f,\Phi}$  is useful for linear classification, using  $f$  directly is more standard and performs well in practice (Section 5). We show a linear relation between  $f$  and  $g_{f,\Phi}$  if word embeddings  $\Phi$  satisfy the following property.

**Assumption 4.1.** *There exists a symmetric positive semidefinite matrix  $\mathbf{A} \in \mathbb{R}^{d \times d}$ , a vector  $\mathbf{b} \in \mathbb{R}^d$  and a constant  $c \in \mathbb{R}$  such that  $\log(Z_\theta) = \frac{1}{2}\theta^\top \mathbf{A} \theta + \theta^\top \mathbf{b} + c$  for any  $\theta \in \mathbb{R}^d$ .*

If word embeddings were distributed as Gaussians, i.e.  $\phi_w \sim \mathcal{N}(\mu, \Sigma)$  independently, it is not hard to show (Lemma F.5) that  $\log(Z_\theta) \approx \frac{1}{2}\theta^\top \Sigma \theta + \theta^\top \mu + \log(V)$ . Empirically we find the fit to be very good, as evident in Figure 1. Under the above assumption, we can show a linear relation between  $f$  and  $g_{f,\Phi}$  and thus good performance of  $f$  on natural tasks. See detailed discussion in Section C.3.

**Lemma 4.3.** *Under Assumption 4.1, feature map  $f$  satisfies  $g_{f,\Phi}(s) = \mathbf{A}f(s) + \mathbf{b}, \forall s \in \mathcal{S}$ .*

**Corollary 4.1.** *Under same setting as Lemma 4.3 and Theorem 4.2,  $\ell_{\mathcal{T}}(f) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$ .*

**Quad objective:** Word embeddings  $\Phi$  determine the tasks that softmax language model features can solve, but the cross-entropy objective does not lend a simple closed form expression for optimal  $\Phi$ . This motivates our Quad objective with two nice properties: (1) optimal feature map  $f^*$  can solve some natural tasks, (2) optimal  $\Phi^*$  has an intuitively meaningful closed-form solution.

$$\ell_{\text{quad}}(f, \Phi) = \mathbb{E}_{s \sim p_L} \left[ \mathbb{E}_{w \sim p_{\cdot|s}^*} [-f(s)^\top \phi_w] + \frac{1}{2} \|\Phi^\top f(s)\|^2 \right] \quad (4)$$

The Quad objective is very similar to the cross-entropy objective from Equation (2), with the log partition function  $\log(Z_{f(s)})$  replaced with a quadratic function  $\frac{1}{2} \|\Phi^\top f(s)\|^2$ , inspired in part by Assumption 4.1. The optimal solution  $\Phi^*$  depends on the eigendirections of a *substitutability matrix*.

**Definition 4.1.** *The substitutability matrix is defined to be  $\Omega^* := \mathbb{E}_{s \sim p_L} [p_{\cdot|s}^* p_{\cdot|s}^{*\top}] \in \mathbb{R}^{V \times V}$ . If  $\Omega^* = \mathbf{U} \mathbf{S} \mathbf{U}^\top$  is the eigendecomposition, then  $\mathbf{U}_d \in \mathbb{R}^{V \times d}$  is matrix of top  $d$  eigenvectors of  $\Omega^*$ .*

**Theorem 4.4.** *Let  $f^*, \Phi^* = \arg \min_{f, \Phi} \ell_{\text{quad}}(f, \Phi)$ . Then  $\Phi^* = \mathbf{B} \mathbf{U}_d^\top$ , for full rank  $\mathbf{B} \in \mathbb{R}^{d \times d}$ . Also, for a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi^*$ , we have  $\ell_{\mathcal{T}}(f^*) \leq \tau$ .*

Thus  $f^*$  excels on natural tasks w.r.t.  $\Phi^*$ , the best  $d$ -dimensional projection of  $\Omega^*$ . Please refer to Section E for an interpretation of  $\Phi^*$  relating it to synonyms. We train with Quad objective and compare to a similarly trained language model (Section G.2), finding Quad to be reasonably effective. The goal is not to obtain state-of-the-art results, but show the practical utility of theoretical insights.

## 5 Experiments

We validate our claims from Section 3 that classification tasks can be solved by linear functions of  $p_{\cdot|s}$ . Table 1 demonstrates that on SST [Socher et al., 2013] and AG News tasks we can use  $p_{\cdot|s} = p_{f(s)}$  from GPT-2 [Radford et al., 2019] of just 20 task-relevant tokens (Section G.1) to solve tasks. Even just one token per class yields non-trivial performance. We validate the complete-the-sentence intuition by observing improved performance after adding a task specific prompt. We validate Theorem 4.2 by verifying that the conditional mean features  $g_{f,\Phi}(s) = \Phi p_{f(s)}$  also linearly solve downstream tasks fairly well. Section G.1 has results for a wider range of classification tasks. Evidence for Assumption 4.1 is provided in Section G.3.

## References

- Sanjeev Arora, Yuanzhi Li, Yingyu Liang, Tengyu Ma, and Andrej Risteski. A latent variable model approach to pmi-based word embeddings. *Transactions of the Association for Computational Linguistics*, 2016.
- Sanjeev Arora, Yingyu Liang, and Tengyu Ma. A simple but tough-to-beat baseline for sentence embeddings. In *Proceedings of the International Conference on Learning Representations*, 2017.
- Sanjeev Arora, Mikhail Khodak, Nikunj Saunshi, and Kiran Vodrahalli. A compressed sensing view of unsupervised text embeddings, bag-of-n-grams, and LSTMs. In *Proceedings of the International Conference on Learning Representations*, 2018.
- Sanjeev Arora, Hrishikesh Khandeparkar, Mikhail Khodak, Orestis Plevrakis, and Nikunj Saunshi. A theoretical analysis of contrastive unsupervised representation learning. In *Proceedings of the 36th International Conference on Machine Learning*, 2019.
- Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. Dbpedia: A nucleus for a web of open data. In *Proceedings of the 6th International The Semantic Web and 2nd Asian Conference on Asian Semantic Web Conference*, 2007.
- Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Jauvin. A neural probabilistic language model. *Journal of machine learning research*, 2003.
- Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.
- Stanley F Chen and Joshua Goodman. An empirical study of smoothing techniques for language modeling. *Computer Speech & Language*, 13, 1999.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- Chris Dyer. Notes on noise contrastive estimation and negative sampling. *arXiv preprint arXiv:1410.8251*, 2014.
- John R Firth. A synopsis of linguistic theory, 1930-1955. *Studies in linguistic analysis*, 1957.
- Zellig Harris. Distributional structure. *Word*, 1954.
- Jeremy Howard and Sebastian Ruder. Universal language model fine-tuning for text classification. *arXiv preprint arXiv:1801.06146*, 2018.
- Minqing Hu and Bing Liu. Mining and summarizing customer reviews. In *Proceedings of the Tenth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2004.
- Mikhail Khodak, Nikunj Saunshi, Yingyu Liang, Tengyu Ma, Brandon Stewart, and Sanjeev Arora. A la carte embedding: Cheap but effective induction of semantic feature vectors. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2018.
- Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.
- Ryan Kiros, Yukun Zhu, Russ R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Skip-thought vectors. In *Advances in neural information processing systems*, 2015.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*, 2019.
- Jason D. Lee, Qi Lei, Nikunj Saunshi, and Jiacheng Zhuo. Predicting what you already know helps: provable self-supervised learning. *arXiv preprint arXiv:2008.01064*, 2020.

198 Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. In *Advances*  
199 *in neural information processing systems*, 2014.

200 Xin Li and Dan Roth. Learning question classifiers. In *Proceedings of the 19th international*  
201 *conference on Computational linguistics-Volume 1*, 2002.

202 Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike  
203 Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining  
204 approach. *arXiv preprint arXiv:1907.11692*, 2019.

205 Lajanugen Logeswaran and Honglak Lee. An efficient framework for learning sentence representa-  
206 tions. In *Proceedings of the International Conference on Learning Representations*, 2018.

207 Zhuang Ma and Michael Collins. Noise contrastive estimation and negative sampling for conditional  
208 models: Consistency and statistical efficiency. In *Proceedings of the Conference on Empirical*  
209 *Methods in Natural Language Processing*, 2018.

210 Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher  
211 Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of*  
212 *the ACL: Human Language Technologies*, 2011.

213 Julian J. McAuley, Rahul Pandey, and Jure Leskovec. Inferring networks of substitutable and  
214 complementary products. *CoRR*, 2015.

215 Bryan McCann, James Bradbury, Caiming Xiong, and Richard Socher. Learned in translation:  
216 Contextualized word vectors. In *Advances in Neural Information Processing Systems*, 2017.

217 Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. The natural language  
218 decathlon: Multitask learning as question answering. *arXiv preprint arXiv:1806.08730*, 2018.

219 Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture  
220 models. *arXiv preprint arXiv:1609.07843*, 2016.

221 Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representa-  
222 tions in vector space. *arXiv preprint arXiv:1301.3781*, 2013a.

223 Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations  
224 of words and phrases and their compositionality. In *Advances in neural information processing*  
225 *systems*, 2013b.

226 Jiaqi Mu and Pramod Viswanath. All-but-the-top: Simple and effective postprocessing for word  
227 representations. In *Proceedings of the International Conference on Learning Representations*,  
228 2018.

229 Matteo Pagliardini, Prakhar Gupta, and Martin Jaggi. Unsupervised learning of sentence embeddings  
230 using compositional n-gram features. *Proceedings of the North American Chapter of the ACL:*  
231 *Human Language Technologies*, 2018.

232 Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word  
233 representation. In *Proceedings of the 2014 conference on empirical methods in natural language*  
234 *processing (EMNLP)*, 2014.

235 Matthew E Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and  
236 Luke Zettlemoyer. Deep contextualized word representations. *arXiv preprint arXiv:1802.05365*,  
237 2018.

238 Raul Puri and Bryan Catanzaro. Zero-shot text classification with generative language models. *arXiv*  
239 *preprint arXiv:1912.10165*, 2019.

240 Alec Radford, Rafal Jozefowicz, and Ilya Sutskever. Learning to generate reviews and discovering  
241 sentiment. *arXiv preprint arXiv:1704.01444*, 2017.

242 Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving lan-  
243 guage understanding by generative pre-training. 2018. URL [https://s3-us-west-2.](https://s3-us-west-2.amazonaws.com/openai-assets/researchcovers/languageunsupervised/languageunderstandingpaper.pdf)  
244 [amazonaws.com/openai-assets/researchcovers/languageunsupervised/](https://s3-us-west-2.amazonaws.com/openai-assets/researchcovers/languageunsupervised/languageunderstandingpaper.pdf)  
245 [languageunderstandingpaper.pdf](https://s3-us-west-2.amazonaws.com/openai-assets/researchcovers/languageunsupervised/languageunderstandingpaper.pdf).

246 Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language  
247 models are unsupervised multitask learners. *OpenAI Blog*, 2019.

248 Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi  
249 Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text  
250 transformer. *arXiv preprint arXiv:1910.10683*, 2019.

251 Prajit Ramachandran, Peter Liu, and Quoc Le. Unsupervised pretraining for sequence to sequence  
252 learning. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language*  
253 *Processing*, 2017.

254 Timo Schick and Hinrich Schütze. It’s not just size that matters: Small language models are also  
255 few-shot learners. *arXiv preprint arXiv:2009.07118*, 2020.

256 Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and  
257 Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank.  
258 In *Proceedings of the 2013 conference on empirical methods in natural language processing*, 2013.

259 Alon Talmor, Yanai Elazar, Yoav Goldberg, and Jonathan Berant. olmpics—on what language model  
260 pre-training captures. *arXiv preprint arXiv:1912.13283*, 2019.

261 Christopher Tosh, Akshay Krishnamurthy, and Daniel Hsu. Contrastive learning, multi-view redun-  
262 dancy, and linear models. *arXiv preprint arXiv:2008.10150*, 2020a.

263 Christopher Tosh, Akshay Krishnamurthy, and Daniel Hsu. Contrastive estimation reveals topic  
264 posterior information to linear models. *arXiv preprint arXiv:2003.02234*, 2020b.

265 Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through align-  
266 ment and uniformity on the hypersphere. *arXiv preprint arXiv:2005.10242*, 2020.

267 Theresa Wilson and Janyce Wiebe. Annotating opinions in the world press. In *Proceedings of the*  
268 *Fourth SIGdial Workshop of Discourse and Dialogue*, 2003.

269 Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi,  
270 Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface’s  
271 transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*,  
272 2019.

273 Wei Xu and Alex Rudnicky. Can artificial neural networks learn language models? In *Sixth*  
274 *international conference on spoken language processing*, 2000.

275 Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le.  
276 Xlnet: Generalized autoregressive pretraining for language understanding. In *Advances in neural*  
277 *information processing systems*, 2019.

278 Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text  
279 classification. In *Advances in Neural Information Processing Systems* 28. 2015.

## 280 A Overview

281 Section B discusses related work. Section C is a detailed version of Section 4 with the full statements  
 282 of Theorems 4.1 and 4.2. Section D describes stronger versions of Theorems 4.1 and 4.2. Section E  
 283 is a detailed version of Section 4. Section F contains proofs for all results. Section G contains many  
 284 more experimental findings that consolidate many of our theoretical results. Section G.1 provides  
 285 the information about subsets of words used for results in Table 1 and also additional experiments  
 286 to test the performance of pretrained language model embeddings  $f$  on more downstream tasks and  
 287 also verifying that conditional mean embeddings  $\Phi p_f$  do well on these tasks. In Section G.2, we  
 288 present additional results for our Quad objective trained on a larger corpus and tested on SST. Finally  
 289 Section G.3 provides additional details on how  $\mathbf{A}$ ,  $\mathbf{b}$  and  $\mathbf{c}$  from Assumption 4.1 are learned and also  
 290 further verification of the assumption on more datasets.

## 291 B Related work

292 **Embedding methods:** Prior to language models, large text corpora like Wikipedia [Merity et al.,  
 293 2016] were used to learn low dimensional embeddings for words [Mikolov et al., 2013b,a, Pennington  
 294 et al., 2014] and subsequently for sentences [Kiros et al., 2015, Arora et al., 2017, Pagliardini et al.,  
 295 2018, Logeswaran and Lee, 2018] for downstream task usage. These methods were inspired by the  
 296 distributional hypothesis [Firth, 1957, Harris, 1954], which posits that meaning of text is determined  
 297 in part by the surrounding context. Recent methods like BERT [Devlin et al., 2018] and variants  
 298 [Lan et al., 2019, Yang et al., 2019, Liu et al., 2019] learn from auxiliary tasks, such as sentence  
 299 completion, and are among the top performers on downstream tasks.

300 **Language models for downstream tasks:** We are interested in language models, including  $n$ -gram  
 301 models [Chen and Goodman, 1999], and more recent models [Xu and Rudnicky, 2000, Bengio et al.,  
 302 2003] that use neural networks to compute low dimensional features for contexts and parametrize the  
 303 next word distribution using softmax. Language models have shown to be useful for downstream tasks  
 304 as initializations [Ramachandran et al., 2017, Howard and Ruder, 2018] or as learned feature maps  
 305 [Radford et al., 2017, McCann et al., 2017, Peters et al., 2018]. The idea of phrasing classification  
 306 tasks as sentence completion problems is motivated by recent works [Radford et al., 2019, Puri and  
 307 Catanzaro, 2019, Schick and Schütze, 2020] that show that many downstream tasks can be solved  
 308 by next word prediction for an appropriately conditioned language model. This idea also shares  
 309 similarities with work that phrase a suite of downstream tasks as question-answering tasks [McCann  
 310 et al., 2018] or text-to-text tasks [Raffel et al., 2019] and symbolic reasoning as fill-in-the-blank tasks  
 311 [Talmor et al., 2019]. Our work exploits this prevalent idea of task rephrasing to theoretically analyze  
 312 why language models succeed on downstream tasks.

313 **Theoretical analysis:** Since the success of early word embedding algorithms like word2vec [Mikolov  
 314 et al., 2013a] and GloVe [Pennington et al., 2014], there have been attempts to understand them  
 315 theoretically. Levy and Goldberg [2014] show that, in some regimes, the word2vec algorithm  
 316 implicitly factorizes the PMI matrix. The theory of Noise Contrastive Estimation (NCE) is used  
 317 by Dyer [2014] to understand word embedding methods and by Ma and Collins [2018] to prove  
 318 parameter recovery for negative sampling methods that learn conditional models. A latent variable  
 319 log-linear model is proposed in Arora et al. [2016] to explain and unify various word embedding  
 320 algorithms. Theoretical justification is provided for sentence embedding methods either by using a  
 321 latent variable model [Arora et al., 2017] or through the lens of compressed sensing [Arora et al.,  
 322 2018]. Also relevant is recent work on theory for contrastive learning [Arora et al., 2019, Tosh et al.,  
 323 2020b,a, Wang and Isola, 2020] and reconstruction-based methods [Lee et al., 2020], which analyze  
 324 the utility of representations learned in the self-supervised regime for downstream tasks. Our work is  
 325 the first to analyze the efficacy language model features on downstream tasks.

## 326 C Guarantees for language models on natural tasks

327 We now show guarantees for features from language models on natural tasks. For an unconstrained  
 328 model, we use the learned  $p_{\cdot|s} \in \mathbb{R}^V$  as features and for softmax model  $f$ , we show guarantees  
 329 for  $\Phi p_{f(s)} \in \mathbb{R}^d$ . Since we cannot practically hope to learn the optimal solutions described in  
 330 Propositions 2.1 and 2.2, we only assume that the language models are  $\epsilon$ -optimal in cross-entropy.



331 To define  $\epsilon$ -optimality in the two settings, we first define optimal cross-entropies.

$$\ell_{\text{xent}}^* = \ell_{\text{xent}}(\{p_{\cdot|s}^*\}), \quad \ell_{\text{xent}}^*(\Phi) = \mathbb{E}_{s \sim p_L} \left[ \inf_{\theta \in \mathbb{R}^d} \ell_{\text{xent},s}(\theta, \Phi) \right] \quad (5)$$

332 where  $\ell_{\text{xent}}^*$  is the absolute minimum achievable cross-entropy, while  $\ell_{\text{xent}}^*(\Phi)$  is the minimum achiev-  
 333 able cross-entropy by a  $d$ -dimensional softmax language model using  $\Phi$ ; clearly  $\ell_{\text{xent}}^* \leq \ell_{\text{xent}}^*(\Phi)$ .

### 334 C.1 Unconstrained language models

335 We show guarantees for a language model that satisfies  $\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^* \leq \epsilon$ . An important  
 336 consideration is that the language model distribution  $p_L$  of contexts is often a diverse superset of  
 337 the downstream distribution  $p_{\mathcal{T}}$  (defined in Section 2), thus requiring us to show how guarantees  
 338 of  $p_{\cdot|s} \approx p_{\cdot|s}^*$  on average over the distribution  $s \sim p_L$  transfer to guarantees on a subset  $p_{\mathcal{T}}$ . In the  
 339 worst case, all of the  $\epsilon$  error by  $\{p_{\cdot|s}\}$  occurs on sentences from the subset  $p_{\mathcal{T}}$ , leading to pessimistic  
 340 bounds<sup>3</sup>. In practice, however, the errors might be more evenly distributed across  $p_L$ , thus bypassing  
 341 this worst case bound. As a first step, we present the worst case bound here; stronger guarantees are  
 342 in Section D. The worst-case coefficient  $\gamma(p_{\mathcal{T}})$ , defined below, captures that  $p_{\mathcal{T}}$  is a  $\gamma(p_{\mathcal{T}})$ -fraction  
 343 of  $p_L$ .

$$\gamma(p_{\mathcal{T}}) = \max\{\gamma \in \mathbb{R} : p_L(s) \geq \gamma p_{\mathcal{T}}(s) \forall s \in \mathcal{S}\} \quad (6)$$

344 We now present our results that applies to any language model, regardless of the parametrization  
 345 (e.g.,  $n$ -gram models, softmax models). The result suggests that small test cross-entropy (hence test  
 346 perplexity) is desirable to guarantee good classification performance, thus formalizing the intuition  
 347 that better language models should do better on downstream tasks.

348 **Theorem 4.1.** *Let  $\{p_{\cdot|s}\}$  be a language model that is  $\epsilon$ -optimal, i.e.  $\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^* \leq \epsilon$ , for  
 349 some  $\epsilon > 0$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural, we have*

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}})}}$$

350 **Discussion:** The suboptimality  $\epsilon$  propagates gracefully as  $\mathcal{O}(\sqrt{\epsilon})$  to a downstream task. While  $\tau$   
 351 can be thought of as a small constant like 0.01, the norm bound  $B$  captures the margin of task  $\mathcal{T}$   
 352 when solved linearly using  $\{p_{\cdot|s}^*\}$ . Intuitively, for  $\ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v})$  to be smaller than  $\tau$ ,  $B$  needs to be  
 353 large enough so that  $\mathbf{v}^\top p_{\cdot|s}^* = \Omega(1)$ . Thus if the words of interest in the support of  $\mathbf{v}$ , described in  
 354 Section 3, have total probability mass of  $\Omega(\alpha)$  in  $p_{\cdot|s}^*$ , then  $B \sim \mathcal{O}(1/\alpha)$ . It is thus desirable for a  
 355 task  $\mathcal{T}$  to depend on a larger and more frequent set of words. A task that depends on probabilities of  
 356 rare words will have a high value of  $B$ . Adding a prompt, as described in Section 3, can broaden  
 357 the set of indicative words, thus potentially decreasing  $B$ . A key step in the proof is to bound  
 358 the difference in prediction on  $s$  for classifier  $\mathbf{v}$  as  $|\mathbf{v}^\top(p_{\cdot|s} - p_{\cdot|s}^*)| \leq \|\mathbf{v}\|_\infty \|p_{\cdot|s} - p_{\cdot|s}^*\|_1 \leq$   
 359  $\|\mathbf{v}\|_\infty \sqrt{2(\ell_{\text{xent},s}(p_{\cdot|s}) - \ell_{\text{xent},s}(p_{\cdot|s}^*))}$ , using Holder’s and Pinsker’s inequalities respectively.

### 360 C.2 Softmax language model with conditional mean features

361 We now describe guarantees for a softmax language model with feature map  $f$  that satisfies  
 362  $\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi) \leq \epsilon$ ; suboptimality is measured w.r.t. the best  $d$ -dimensional model, un-  
 363 like Theorem 4.1. Note that Theorem 4.1 can be applied here to give a bound of  $\ell_{\mathcal{T}}(\{p_{f(s)}\}) \leq$   
 364  $\tau + \mathcal{O}(B\sqrt{\epsilon + \epsilon_\Phi^*})$  on  $(\tau, B)$ -natural tasks, where  $\epsilon_\Phi^* = \ell_{\text{xent}}^*(\Phi) - \ell_{\text{xent}}^*$  is the suboptimality of the  
 365 best  $d$ -dimensional model. This fixed error of  $\mathcal{O}(B\sqrt{\epsilon_\Phi^*})$  (even when  $\epsilon = 0$ ), however, is undesir-  
 366 able. We improve on this by proving a stronger result specifically for softmax models. Inspired by  
 367 Proposition 2.2 that shows  $\Phi p_{f^*(s)} = \Phi p_{\cdot|s}^*$ , our guarantees are for features  $\Phi p_{f(s)} \in \mathbb{R}^d$  that we call  
 368 conditional mean features.

369 **Definition C.1** (Conditional Mean Features). *For a feature map  $f : \mathcal{S} \rightarrow \mathbb{R}^d$  and  $\Phi \in \mathbb{R}^{d \times V}$ , we  
 370 define conditional mean features  $g_{f,\Phi} : \mathcal{S} \rightarrow \mathbb{R}^d$ , where  $g_{f,\Phi}(s) = \Phi p_{f(s)}$ , where  $p_{f(s)} \in \mathbb{R}^V$ .*

<sup>3</sup>For instance if  $p_{\mathcal{T}}$  is 0.001 fraction of  $p_L$ ,  $\{p_{\cdot|s}\}$  could have  $1000\epsilon$  error on  $p_{\mathcal{T}}$  and 0 error on rest of  $p_L$ .

The result below will show that conditional mean features  $g_{f,\Phi}$  are guaranteed to do well on natural tasks w.r.t.  $\Phi$ , thereby suggesting a novel way to use softmax features  $f$  for downstream tasks. We also test  $g_{f,\Phi}$  on downstream tasks in Section G.1 and find that they perform comparably to  $f$ . We now present the result for softmax language models that has the similar implication as Theorem 4.1, but with above-mentioned subtle differences. The proof (Section F.2) is similar to that of Theorem 4.1, but crucially requires showing a  $d$ -dimensional version of Pinsker’s inequality.

**Theorem 4.2.** *For a fixed  $\Phi$ , let  $f$  be features from an  $\epsilon$ -optimal  $d$ -dimensional softmax language model, i.e.  $\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi) \leq \epsilon$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ ,*

$$\ell_{\mathcal{T}}(g_{f,\Phi}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}})}}$$

### C.3 $g_{f,\Phi}(s)$ is a linear function of $f(s)$

Theorem 4.2 shows that  $g_{f,\Phi}$  is useful for linear classification. However, using feature map  $f$  directly is more standard and performs well in practice (see Section G.1). Here we argue that there is a linear relation between  $f$  and  $g_{f,\Phi}$  if word embeddings  $\Phi$  satisfy a certain property, which we show implies that tasks solvable linearly with  $g_{f,\Phi}$  are also solvable linearly using  $f$ . Our main assumption about word embeddings  $\Phi$  is that the logarithm of the partition function  $Z_{f(s)}$  is quadratic in  $f(s)$ .

**Assumption 4.1.** *There exists a symmetric positive semidefinite matrix  $\mathbf{A} \in \mathbb{R}^{d \times d}$ , a vector  $\mathbf{b} \in \mathbb{R}^d$  and a constant  $c \in \mathbb{R}$  such that  $\log(Z_{\theta}) = \frac{1}{2}\theta^{\top}\mathbf{A}\theta + \theta^{\top}\mathbf{b} + c$  for any  $\theta \in \mathbb{R}^d$ .*

If word embeddings were distributed as Gaussians, i.e.  $V$  columns of  $\Phi$  are sampled from  $\mathcal{N}(\mu, \Sigma)$  independently, it is not hard to show (Lemma F.5) that  $\log(Z_{\theta}) \approx \frac{1}{2}\theta^{\top}\Sigma\theta + \theta^{\top}\mu + \log(V)$ . While some papers [Arora et al., 2016, Mu and Viswanath, 2018] have noted that word embeddings are fairly random-like in the bulk to argue that the log partition function is constant for all  $\|\theta\|_2 = 1$ , our quadratic assumption is a bit stronger. However, empirically we find the fit to be very good, as evident in Figure 1. Under the above assumption, we can show a linear relation between  $f$  and  $\Phi p_f$ .

**Lemma 4.3.** *Under Assumption 4.1, feature map  $f$  satisfies  $g_{f,\Phi}(s) = \mathbf{A}f(s) + \mathbf{b}, \forall s \in \mathcal{S}$ .*

**Corollary 4.1.** *Under same setting as Lemma 4.3 and Theorem 4.2,  $\ell_{\mathcal{T}}(f) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$ .*

Thus we get that  $f$  itself is good for natural linear classification tasks. However, in practice, the linearity between  $f$  and  $g_{f,\Phi}$  holds only approximately when tested on features from the pretrained GPT-2 language model Radford et al. [2018]. The ratio of the residual norm of the best linear map to the norm of  $f$ , i.e.  $r = \frac{\mathbb{E}_{s \sim p} \|g_{f,\Phi}(s) - \mathbf{A}f(s) - \mathbf{b}\|^2}{\mathbb{E}_{s \sim p} \|g_{f,\Phi}(s)\|^2}$ , is measured for different distributions  $p$  ( $r = 0$  means perfect fit). These ratios are 0.28 for SST, 0.39 for AG News, and 0.18 for IMDB contexts. This non-trivial linear relationship, although surprising, might not completely explain the success of  $f$ . In fact,  $f$  almost always performs better than  $g_{f,\Phi}$ ; we leave exploring this to future work.

## D Better handling of distributional shift

While the bounds above used  $\gamma(p_{\mathcal{T}})$  to transfer from the distribution  $p_L$  to  $p_{\mathcal{T}}$ , we define a more refined notion of transferability here. While  $\gamma(p_{\mathcal{T}})$  only depends on  $p_L$  and  $p_{\mathcal{T}}$ , the more refined notions depend also on the learned language model, thus potentially exploiting some inductive biases. We first define the notion of error made in the predicted probabilities by any predictor  $p_{\cdot|s}$  as  $\Delta_{\{p_{\cdot|s}\}}(s) = p_{\cdot|s} - p_{\cdot|s}^*$ . Thus for any softmax language model  $f$  we have  $\Delta_{\{p_{f(s)}\}}(s) = p_{f(s)} - p_{\cdot|s}^*$ . For any distribution  $p \in \Delta_{\mathcal{S}}$ , we define the covariance<sup>4</sup> of a function  $g : \mathcal{S} \rightarrow \mathbb{R}^D$  as  $\Sigma_p(g) = \mathbb{E}_{s \sim p} [g(s)g(s)^{\top}]$ . We define 3 coefficients for the results to follow

**Definition D.1.** *For any distribution  $p \in \Delta_{\mathcal{S}}$ , we define the following*

$$\gamma(p; \{p_{\cdot|s}\}) := \left( \left\| \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \Sigma_p(\Delta_{\{p_{\cdot|s}\}}) \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \right\|_2 \right)^{-1} \quad (7)$$

<sup>4</sup>This is not exactly the covariance since the mean is not subtracted, all results hold even for the usual covariance.

$$\gamma_{\Phi}(p; \{p_{\cdot|s}\}) := \left( \left\| \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \Sigma_p(\Phi \Delta_{\{p_{\cdot|s}\}}) \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \right\|_2 \right)^{-1} \quad (8)$$

$$\gamma(p; g_{f,\Phi}) := \gamma_{\Phi}(p; \{p_{f(s)}\}) \quad (9)$$

411 We notice that  $\Sigma_p(\Delta_{\{p_{\cdot|s}\}}) = \mathbb{E}_{s \sim p} [(p_{\cdot|s} - p_{\cdot|s}^*)(p_{\cdot|s} - p_{\cdot|s}^*)^\top]$ ,  $\Sigma_p(\Phi \Delta_{\{p_{\cdot|s}\}}) = \Phi \Sigma_p(\Delta_{\{p_{\cdot|s}\}}) \Phi^\top$ .

412 We are now ready to state the most general results.

413 **Theorem D.1** (Strengthened Theorem 4.1). *Let  $\{p_{\cdot|s}\}$  be a language model that is  $\epsilon$ -optimal, i.e.*  
 414  *$\ell_{xent}(\{p_{\cdot|s}\}) - \ell_{xent}^* \leq \epsilon$  for some  $\epsilon > 0$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural, we have*

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

415 For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

416 **Theorem D.2.** [Strengthened Theorem 4.2] *For a fixed  $\Phi$ , let  $f$  be features from an  $\epsilon$ -optimal  $d$ -*  
 417 *dimensional softmax language model, i.e.  $\ell_{xent}(f, \Phi) - \ell_{xent}^*(\Phi) \leq \epsilon$ , where  $\ell_{xent}^*(\Phi)$  is defined in*  
 418 *Equation (5). For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have*

$$\ell_{\mathcal{T}}(\{p_{f(s)}\}) \leq \ell_{\mathcal{T}}(g_{f,\Phi}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}}; g_{f,\Phi})}}$$

419 **Discussions:** It is not hard to show that the coefficients satisfy  $\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\}) \geq \gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\}) \geq$   
 420  $\gamma(p_{\mathcal{T}})$  and  $\gamma(p_{\mathcal{T}}; g_{f,\Phi}) \geq \gamma(p_{\mathcal{T}})$ , thus showing that these results are strictly stronger than the ones  
 421 from the previous section. The transferability coefficient is a measure of how guarantees on  $p_L$   
 422 using a language model can be transferred to another distribution of contexts and it only depends  
 423 on the distribution of contexts and not the labels. Unlike  $\gamma(p_{\mathcal{T}})$ , the coefficients in Definition D.1  
 424 depend on the learned models, either  $\{p_{\cdot|s}\}$  or  $\{p_{f(s)}\}$ , and can be potentially much smaller due to  
 425 the inductive bias of the learned models. For instance, if errors made by the model are random-like,  
 426 i.e.  $\Delta_{\{p_{f(s)}\}}(s) \sim \rho$ , independently of  $s$ , then  $\Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \approx \Sigma_p(\Delta_{\{p_{\cdot|s}\}}) \approx \mathbb{E}_{\eta \sim \rho}[\eta \eta^\top]$ , making  
 427  $\gamma(p; \{p_{\cdot|s}\}) \approx 1$ . The independence between  $\Delta_{\{p_{f(s)}\}}(s)$  and  $s$  prevents language modeling error  
 428 from accumulating on contexts from  $p_{\mathcal{T}}$ , bypassing the worst case transfer of  $\gamma(p_{\mathcal{T}})$ .

## 429 E Quad: A new objective function

430 In Definition 3.2 we discuss how low dimensional softmax language models learn a linear projection  
 431 of  $p_{\cdot|s}^*$ , only solving tasks that lie in the row span of word embeddings  $\Phi$ . Although  $\Phi$  defines tasks  
 432 that language model features can solve, the standard cross-entropy objective does not lend a simple  
 433 closed form expression for optimal  $\Phi$ . This motivates the construction of our Quad objective, that  
 434 has two nice properties: (1) the optimal feature map  $f^*$  is a linear function of  $p_{\cdot|s}^*$  and thus can solve  
 435 some natural tasks, and (2) the optimal  $\Phi^*$  has an intuitively meaningful closed-form solution.

$$\ell_{quad,s}(\theta, \Phi) = \mathbb{E}_{w \sim p_{\cdot|s}^*} [-\theta^\top \phi_w] + \frac{1}{2} \|\Phi^\top \theta\|^2 = -\theta^\top \Phi p_{\cdot|s}^* + \frac{1}{2} \|\Phi^\top \theta\|^2 \quad (10)$$

$$\ell_{quad}(f, \Phi) = \mathbb{E}_{s \sim p_L} [\ell_{quad,s}(f(s), \Phi)] \quad (11)$$

436 The Quad objective is very similar to the cross-entropy objective from Equation (2), with the log  
 437 partition function replaced by a quadratic function, inspired in part by Assumption 4.1. We can derive  
 438 the optimal solution  $\Phi^*$  that depends on the eigen-decomposition of a *substitutability matrix*.

439 **Definition 4.1.** *The substitutability matrix is defined to be  $\Omega^* := \mathbb{E}_{s \sim p^*} [p_{\cdot|s}^* p_{\cdot|s}^{*\top}] \in \mathbb{R}^{V \times V}$ . If*  
 440  *$\Omega^* = U S U^\top$  is the eigendecomposition, then  $U_d \in \mathbb{R}^{V \times d}$  is matrix of top  $d$  eigenvectors of  $\Omega^*$ .*

The matrix  $\Omega^*$  captures substitutability between pairs of words. Words  $w$  and  $w'$  are substitutable if they have identical conditional probabilities for every context  $s \in \mathcal{S}$  and thus can replace occurrences of each other while still providing meaningful completions. By definition, these words satisfy  $\Omega^*[w] = \Omega^*[w']$ . Such pairs of words were called “free variants” in the work on distributional semantics [Harris, 1954], and capture the notion of synonyms in the distributional hypothesis. We now derive expressions for the optimal solution of the Quad objective described in Equation (11).

**Theorem E.1.** *The optimal solution  $f^*, \Phi^* = \arg \min_{f, \Phi} \ell_{quad}(f, \Phi)$  satisfies*

$$\begin{aligned} \Phi^* &= \mathbf{B} \mathbf{U}_d^\top, \text{ for full rank } \mathbf{B} \in \mathbb{R}^{d \times d} \\ f^*(s) &= (\Phi^* \Phi^{*\top})^{-1/2} \Phi^* p_{\cdot|s}^* = \mathbf{C} \mathbf{U}_d^\top p_{\cdot|s}^*, \text{ for full rank } \mathbf{C} \in \mathbb{R}^{d \times d} \end{aligned}$$

If  $\Phi$  is fixed, then the optimal solution is  $f^*(s) = (\Phi \Phi^\top)^{-1/2} \Phi p_{\cdot|s}^*$ .

**Theorem 4.4.** *Let  $f^*, \Phi^* = \arg \min_{f, \Phi} \ell_{quad}(f, \Phi)$ . Then  $\Phi^* = \mathbf{B} \mathbf{U}_d^\top$ , for full rank  $\mathbf{B} \in \mathbb{R}^{d \times d}$ . Also, for a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi^*$ , we have  $\ell_{\mathcal{T}}(f^*) \leq \tau$ .*

Thus  $f^*$  excels on natural tasks w.r.t.  $\Phi^*$ , which in turn, is the best  $d$ -dimensional projection of  $\Omega^*$ . Thus words  $w, w' \in \mathcal{W}$  that are synonyms (hence substitutable) will satisfy  $\phi_w^* = \phi_{w'}^*$ , fulfilling the desired property for word embeddings discussed in Definition 3.2. We train using the Quad objective and compare its performance to a similarly trained language model in Section G.2, finding Quad to be reasonably effective. The goal of testing Quad is not to obtain state-of-the-art results, but to demonstrate that theoretical insights can aid the design of provably effective algorithms.

## F Proofs

### F.1 Proofs for unconstrained language models

**Theorem D.1** (Strengthened Theorem 4.1). *Let  $\{p_{\cdot|s}\}$  be a language model that is  $\epsilon$ -optimal, i.e.  $\ell_{xent}(\{p_{\cdot|s}\}) - \ell_{xent}^* \leq \epsilon$  for some  $\epsilon > 0$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural, we have*

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

*Proof.* The proof has two main steps that we summarize by the following two lemmas. The first one upper bounds the downstream performance on natural tasks with the covariance of errors.

**Lemma F.1.** *For a language model  $\{p_{\cdot|s}\}$ , if  $\mathcal{T}$  is  $(\tau, B)$ -natural,*

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_{\infty} \leq B} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

If  $\mathcal{T}$  is  $(\tau, B)$ -natural w.r.t.  $\Phi \in \mathbb{R}^{d \times V}$ ,

$$\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \sup_{\substack{\mathbf{v} = \Phi^\top \lambda \in \mathbb{R}^V \\ \|\mathbf{v}\|_{\infty} \leq B}} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

where  $\gamma(\cdot)$  and  $\gamma_{\Phi}(\cdot)$  are from Definition D.1.

The second lemma upper bounds the covariance of error with the suboptimality of the language model.

469 **Lemma F.2.** For a language model  $\{p_{\cdot|s}\}$  and classifier  $\mathbf{v} \in \mathbb{R}^V$ ,

$$\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} \leq 2\|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^*)$$

470 where  $\Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) = \mathbb{E}_{s \sim p_L} \left[ (p_{\cdot|s} - p_{\cdot|s}^*)(p_{\cdot|s} - p_{\cdot|s}^*)^\top \right]$  as defined in Section D.

471 Combining the two lemmas, we get the following inequality

$$\begin{aligned} \ell_{\mathcal{T}}(\{p_{\cdot|s}\}) &\stackrel{(a)}{\leq} \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_\infty \leq B} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \\ &\stackrel{(b)}{\leq} \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_\infty \leq B} \sqrt{\frac{2\|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^*)}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \\ &\stackrel{(c)}{\leq} \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \end{aligned}$$

472 where (a) uses first part of Lemma F.1, (b) uses Lemma F.2 and (c) uses the  $\epsilon$ -optimality of  $\{p_{\cdot|s}\}$ .  
473 This proves the first part of the result. The second part can also be proved similarly.

$$\begin{aligned} \ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) &\stackrel{(a)}{\leq} \tau + \sup_{\substack{\mathbf{v} = \Phi^\top \lambda \in \mathbb{R}^V, \\ \|\mathbf{v}\|_\infty \leq B}} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \\ &\stackrel{(b)}{\leq} \tau + \sup_{\substack{\mathbf{v} = \Phi^\top \lambda \in \mathbb{R}^V, \\ \|\mathbf{v}\|_\infty \leq B}} \sqrt{\frac{2\|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^*)}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \\ &\leq \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_\infty \leq B} \sqrt{\frac{2\|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^*)}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \stackrel{(c)}{\leq} \tau + \sqrt{\frac{2B^2\epsilon}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{\cdot|s}\})}} \end{aligned}$$

474 where (a) uses second part of Lemma F.1, (b) uses Lemma F.2 and (c) uses the  $\epsilon$ -optimality of  $\{p_{\cdot|s}\}$ .  
475 The proof of the lemmas can be found in Section F.5.  $\square$

476 **Theorem 4.1.** Let  $\{p_{\cdot|s}\}$  be a language model that is  $\epsilon$ -optimal, i.e.  $\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^* \leq \epsilon$ , for  
477 some  $\epsilon > 0$ . For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural, we have

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}})}}$$

478 *Proof.* This follows from the first part of Theorem D.1 if we can also show that  $\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})^{-1} \leq$   
479  $\gamma(p_{\mathcal{T}})^{-1}$ . For that we use the following lemma that we prove in Section F.5.

480 **Lemma F.3.** For any  $g : \mathcal{S} \rightarrow \mathbb{R}^D$  and  $p_{\mathcal{T}} \in \Delta_{\mathcal{S}}$ , we have  $\|\Sigma_{p_L}(g)^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(g) \Sigma_{p_L}(g)^{-\frac{1}{2}}\|_2 \leq$   
481  $\gamma(p_{\mathcal{T}})^{-1}$

482 Instantiating this for  $g = \Delta_{\{p_{\cdot|s}\}}$  and using Equation (7), we get  $\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})^{-1} \leq \gamma(p_{\mathcal{T}})^{-1}$ , which  
483 completes the proof.  $\square$

## 484 F.2 Proofs for softmax language models

485 **Theorem D.2** (Strengthened Theorem 4.2). For a fixed  $\Phi$ , let  $f$  be features from an  $\epsilon$ -optimal  $d$ -  
486 dimensional softmax language model, i.e.  $\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi) \leq \epsilon$ , where  $\ell_{\text{xent}}^*(\Phi)$  is defined in  
487 Equation (5). For a classification task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have

$$\ell_{\mathcal{T}}(\{p_{f(s)}\}) \leq \ell_{\mathcal{T}}(g_{f, \Phi}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}}; g_{f, \Phi})}}$$

488 *Proof.* Instantiating Lemma F.1 for  $p_{\cdot|s} = p_{f(s)}$ , we get

$$\begin{aligned}
\ell_{\mathcal{T}}(\{\Phi p_{f(s)}\}) &\leq \tau + \sup_{\substack{\mathbf{v} = \Phi^\top \lambda \in \mathbb{R}^V \\ \|\mathbf{v}\|_\infty \leq B}} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{f(s)}\}}) \mathbf{v}}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{f(s)}\})}} \\
&=^{(a)} \tau + \sqrt{\frac{\sup_{\|\Phi^\top \lambda\|_\infty \leq B} \lambda^\top \Phi \Sigma_{p_L}(\Delta_{\{p_{f(s)}\}}) \Phi^\top \lambda}{\gamma_\Phi(p_{\mathcal{T}}; g_{f,\Phi})}} \\
&= \tau + \sqrt{\frac{\sup_{\|\Phi^\top \lambda\|_\infty \leq B} \lambda^\top \Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) \lambda}{\gamma_\Phi(p_{\mathcal{T}}; g_{f,\Phi})}}
\end{aligned}$$

489 where (a) follows from Equation (9) that says  $\gamma_\Phi(p_{\mathcal{T}}; g_{f,\Phi}) = \gamma_\Phi(p_{\mathcal{T}}; \{p_{f(s)}\})$ . We now prove a  
490 similar result for the second term in the following lemma

491 **Lemma F.4.** For a fixed  $\Phi$  and a softmax language model with features  $f$  and  $\lambda \in \mathbb{R}^d$ ,

$$\lambda^\top \Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) \lambda \leq 2 \|\Phi^\top \lambda\|_\infty^2 (\ell_{xent}(f, \Phi) - \ell_{xent}^*(\Phi))$$

492 where  $\Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) = \mathbb{E}_{s \sim p_L} \left[ (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)(\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)^\top \right]$  as defined in Section D.

493 Using Lemma F.4 directly gives us  $\mathbf{W}(g_{f,\Phi}) = \ell_{\mathcal{T}}(\{\Phi p_{f(s)}\}) \leq \tau + \sqrt{\frac{B^2(\ell_{xent}(f, \Phi) - \ell_{xent}^*(\Phi))}{\gamma_\Phi(p_{\mathcal{T}}; g_{f,\Phi})}}$ , and  
494 the  $\epsilon$ -optimality almost completes the proof. The only thing remaining to show is that  $\ell_{\mathcal{T}}(\{p_{f(s)}\}) \leq$   
495  $\ell_{\mathcal{T}}(g_{f,\Phi})$  which follows from the following sequence.

$$\begin{aligned}
\ell_{\mathcal{T}}(\{p_{f(s)}\}) &= \inf_{\mathbf{v} \in \mathbb{R}^V, b \in \mathbb{R}} \ell_{\mathcal{T}}(\{p_{f(s)}\}, \mathbf{v}) \leq \inf_{\Phi^\top \lambda \in \mathbb{R}^V, b \in \mathbb{R}} \ell_{\mathcal{T}}(\{p_{f(s)}\}, (\Phi^\top \lambda, b)) \\
&= \inf_{\lambda \in \mathbb{R}^d, b \in \mathbb{R}} \ell_{\mathcal{T}}(\{\Phi p_{f(s)}\}, (\lambda, b)) = \ell_{\mathcal{T}}(g_{f,\Phi})
\end{aligned}$$

496 □

497 **Theorem 4.2.** For a fixed  $\Phi$ , let  $f$  be features from an  $\epsilon$ -optimal  $d$ -dimensional softmax language  
498 model, i.e.  $\ell_{xent}(f, \Phi) - \ell_{xent}^*(\Phi) \leq \epsilon$ , where  $\ell_{xent}^*(\Phi)$  is defined in Equation (5). For a classification  
499 task  $\mathcal{T}$  that is  $(\tau, B)$ -natural w.r.t.  $\Phi$ , we have

$$\ell_{\mathcal{T}}(\{p_{f(s)}\}) \leq \ell_{\mathcal{T}}(g_{f,\Phi}) \leq \tau + \sqrt{\frac{2B^2\epsilon}{\gamma(p_{\mathcal{T}})}}$$

500 *Proof.* This result follows directly from Theorem D.2, if we can also show that  $\gamma(p_{\mathcal{T}}; g_{f,\Phi})^{-1} \leq$   
501  $\gamma(p_{\mathcal{T}})^{-1}$  just like in the proof of Theorem 4.1. For that we again use Lemma F.3 with  $g = \Phi \Delta_{\{p_{f(s)}\}}$   
502 and Equation (9) and this completes the proof. □

### 503 F.3 Proofs for Section C.3

504 We first show why Assumption 4.1 is approximately true when word embeddings are gaussian like.

505 **Lemma F.5.** Suppose word embeddings  $\phi_w$  are independent samples from the distribution  $\mathcal{N}(\mu, \Sigma)$ .  
506 Then for any  $\theta \in \mathbb{R}^d$  such that  $\lambda^2 = \theta^\top \Sigma \theta = O(1)$  we have that  $|\log(Z_\theta) - \frac{1}{2} \theta^\top \Sigma \theta - \theta^\top \mu -$   
507  $\log(V)| \leq \epsilon$  with probability  $1 - \delta$  for  $\epsilon = \tilde{O}\left(\frac{e^{\lambda^2}}{\sqrt{V}}\right)$  and  $\delta = 1 - \exp(-\Omega(\log^2(V)))$ .

508 *Proof.* We first note that  $\log(Z_\theta) = \log\left(\sum_w e^{\theta^\top \phi_w}\right) = \theta^\top \mu + \log\left(\sum_w e^{\theta^\top (\phi_w - \mu)}\right)$ , thus we  
509 can simply deal with the case where  $\phi_w$  are sampled from  $\mathcal{N}(0, \Sigma)$ . Furthermore the only random  
510 variable of interest is  $X_w = \theta^\top \phi_w$  which is a gaussian variable  $\mathcal{N}(0, \theta^\top \Sigma \theta) = \mathcal{N}(0, \lambda^2)$ . Thus the  
511 problem reduces to showing that for  $V$  samples of  $X_w \sim \mathcal{N}(0, \lambda^2)$ ,  $\log(Z)$  is concentrated around

512  $\lambda^2 + \log(V)$  where  $Z = \sum_w \exp(X_w)$ . This can be proved similarly to the proof of Lemma 2.1  
 513 in Arora et al. [2016]. It is easy to see that  $\mathbb{E}_{X_w \sim \mathcal{N}(0, \lambda^2)}[\exp(X_w)] = e^{\lambda^2}$ . However the variable  
 514  $\exp(X_w)$  is neither sub-gaussian nor sub-exponential and thus standard inequalities cannot be used  
 515 directly. We use the same technique as Arora et al. [2016] to first observe that  $\mathbb{E}[Z] = Ve^{\frac{1}{2}\lambda^2}$   
 516 and  $\text{Var}[Z] \leq \mathbb{E}[\exp(2X_w)] = Ve^{2\lambda^2}$ . After conditioning on the event that  $X_w \leq \frac{1}{2}\lambda \log(V)$  and  
 517 applying Bernstein's inequality just like in Arora et al. [2016] completes the proof.  $\square$

518 **Lemma 4.3.** *Under Assumption 4.1, any feature map  $f : \mathcal{S} \rightarrow \mathbb{R}^d$  satisfies  $g_{f, \Phi}(s) = \mathbf{A}f(s) + \mathbf{b}$ ,  
 519 for all  $s \in \mathcal{S}$ .*

520 *Proof.* Assumption 4.1 gives us that  $\log(Z_\theta) = \frac{1}{2}\theta^\top \mathbf{A}\theta + \theta^\top \mathbf{b} + c$ . We prove this lemma by matching  
 521 the gradients of  $\log(Z_\theta)$  and the quadratic function on the R.H.S.

$$\nabla_\theta \log(Z_\theta) = \frac{\nabla_\theta Z_\theta}{Z_\theta} = \frac{\sum_{w \in \mathcal{W}} e^{\phi_w^\top \theta} \phi_w}{Z_\theta} = \sum_{w \in \mathcal{W}} p_\theta(w) \phi_w = \Phi p_\theta$$

522 Whereas the gradient of the quadratic part is  $\nabla_\theta [\frac{1}{2}\theta^\top \mathbf{A}\theta + \theta^\top \mathbf{b} + c] = \mathbf{A}\theta + \mathbf{b}$ . Matching the two  
 523 gives us  $g_{f, \Phi}(s) = \Phi p_{f(s)} = \mathbf{A}f(s) + \mathbf{b}$ .  $\square$

524 **Corollary 4.1.** *Using Lemma 4.3, for any  $\epsilon$ -optimal  $f$ , as defined in Theorem 4.2, for classification  
 525 tasks that are  $(\tau, B)$ -natural w.r.t.  $\Phi$  we have  $\ell_{\mathcal{T}}(f) \leq \tau + \mathcal{O}(\sqrt{\epsilon})$ .*

526 *Proof.* The main idea is that Lemma 4.3 gives us that  $g_{f, \Phi}(s) = \mathbf{A}f(s) + \mathbf{b}$  and thus any linear  
 527 function of  $g_{f, \Phi}$  will also be a linear function of  $f(s)$ . And from Theorem D.2 (or Theorem 4.2), we  
 528 know that  $g_{f, \Phi}$  will do well on  $\mathcal{T}$ , i.e.  $\ell_{\mathcal{T}}(g_{f, \Phi}) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$ . We formalize the intuition as

$$\begin{aligned} \ell_{\mathcal{T}}(g_{f, \Phi}) &= \inf_{\lambda \in \mathbb{R}^d} \ell_{\mathcal{T}}(g_{f, \Phi}, (\lambda, b)) = \inf_{\lambda \in \mathbb{R}^d} \ell_{\mathcal{T}}(\mathbf{A}f + \mathbf{b}, (\lambda, b)) = \inf_{\lambda \in \mathbb{R}^d} \ell_{\mathcal{T}}(f, (\mathbf{A}^\top \lambda, b + \lambda^\top \mathbf{b})) \\ &\geq \inf_{v \in \mathbb{R}^d} \ell_{\mathcal{T}}(f, v) = \ell_{\mathcal{T}}(f) \end{aligned}$$

529 This shows that  $\ell_{\mathcal{T}}(f) \leq \ell_{\mathcal{T}}(g_{f, \Phi}) \leq \tau + \mathcal{O}(B\sqrt{\epsilon})$  and completes the proof.  $\square$

## 530 F.4 Proofs for Section E

531 **Theorem E.1.** *The optimal solution  $f^*, \Phi^* = \arg \min_{f, \Phi} \ell_{quad}(f, \Phi)$  satisfies*

$$\begin{aligned} \Phi^* &= \mathbf{B} \mathbf{U}_d^\top, \text{ for full rank } \mathbf{B} \in \mathbb{R}^{d \times d} \\ f^*(s) &= (\Phi^* \Phi^{*\top})^{-1/2} \Phi^* p_{\cdot|s}^* = \mathbf{C} \mathbf{U}_d^\top p_{\cdot|s}^*, \text{ for full rank } \mathbf{C} \in \mathbb{R}^{d \times d} \end{aligned}$$

532 *If  $\Phi$  is fixed, then the optimal solution is  $f^*(s) = (\Phi \Phi^\top)^{-1/2} \Phi p_{\cdot|s}^*$ .*

533 *Proof.* Given that,  $\ell_{quad, s}(\theta, \Phi) = -\theta^\top \Phi p_{\cdot|s}^* + \frac{1}{2} \|\Phi^\top \theta\|^2$ , for a fixed  $\Phi$ , we define  $f_\Phi^*(s) =$   
 534  $\arg \min_{\theta \in \mathbb{R}^d} \ell_{quad, s}(\theta, \Phi)$ . We use the first order optimality condition to get  $f_\Phi^*(s)$ , by using the fact  
 535 that  $\nabla_\theta \ell_{quad, s}(\theta, \Phi) = -\Phi p_{\cdot|s}^* + \Phi \Phi^\top \theta$ . Setting the gradient to zero, we  $f_\Phi^*(s) = (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^*$ .  
 536 To get the optimal  $\Phi^*$  for this objective, we plug in this expression for  $f_\Phi^*(s)$  and observing that the  
 537 optimal solution also satisfies  $\Phi^* = \arg \min_\Phi \ell_{quad}(f_\Phi^*, \Phi)$ .

$$\begin{aligned} \ell_{quad}(f_\Phi^*, \Phi) &= \mathbb{E}_{s \sim p^*} [\ell_{quad, s}(f_\Phi^*(s), \Phi)] = \mathbb{E}_{s \sim p^*} \left[ -f_\Phi^*(s)^\top \Phi p_{\cdot|s}^* + \frac{1}{2} \|\Phi^\top f_\Phi^*(s)\|^2 \right] \\ &= \mathbb{E}_{s \sim p^*} \left[ -((\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^*)^\top \Phi p_{\cdot|s}^* + \frac{1}{2} \|\Phi^\top (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^*\|^2 \right] \\ &= \mathbb{E}_{s \sim p^*} \left[ -p_{\cdot|s}^{*\top} \Phi^\top (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^* + \frac{1}{2} p_{\cdot|s}^{*\top} \Phi^\top (\Phi \Phi^\top)^{-1} \Phi \Phi^\top (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^* \right] \\ &= \mathbb{E}_{s \sim p^*} \left[ -\frac{1}{2} p_{\cdot|s}^{*\top} \Phi^\top (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^* \right] = -\frac{1}{2} \mathbb{E}_{s \sim p^*} \left[ \text{tr} \left( p_{\cdot|s}^{*\top} \Phi^\top (\Phi \Phi^\top)^{-1} \Phi p_{\cdot|s}^* \right) \right] \end{aligned}$$

$$\begin{aligned}
&= -\frac{1}{2} \text{tr} \left( \Phi^\top (\Phi \Phi^\top)^{-1} \Phi \mathbb{E}_{s \sim p^*} \left[ p_{\cdot|s}^* p_{\cdot|s}^{*\top} \right] \right) \\
&= -\frac{1}{2} \left\langle \Phi^\top (\Phi \Phi^\top)^{-1} \Phi, \mathbb{E}_{s \sim p^*} \left[ p_{\cdot|s}^* p_{\cdot|s}^{*\top} \right] \right\rangle = -\frac{1}{2} \langle \Phi^\top (\Phi \Phi^\top)^{-1} \Phi, \Omega^* \rangle
\end{aligned}$$

538 Let  $\Phi = NTV^\top$  be the SVD. Then the above objective reduces to  $\ell_{quad}(f_\Phi^*, \Phi) = -\frac{1}{2} \langle \mathbf{V}\mathbf{V}^\top, \Omega^* \rangle$   
539 And hence learning the optimal  $\Phi^*$  reduces to learning an optimal  $\mathbf{V}^*$  such that

$$\mathbf{V}^* = \arg \min_{\mathbf{V} \in \mathbb{R}^{V \times d}, \mathbf{V}^\top \mathbf{V} = I_d} -\langle \mathbf{V}\mathbf{V}^\top, \Omega^* \rangle$$

540 We will now show that the best such matrix is the matrix of top  $d$  eigenvectors of  $\Omega^*$ , i.e.  $\mathbf{V}^* = U_d$ .  
541 Here we will assume that the eigenvalues of  $\Omega^*$  are all distinct for simplicity of presentation.

542 First we note that  $\langle \mathbf{V}\mathbf{V}^\top, \Omega^* \rangle = \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2$ , where  $\Omega^{*\frac{1}{2}} = U S^{\frac{1}{2}} U^\top$ , with  $U$ ,  $U_d$  and  $S$  define  
543 in Definition 4.1. This can be shown by the following sequence of steps

$$\begin{aligned}
\langle \mathbf{V}\mathbf{V}^\top, \Omega^* \rangle &= \text{tr}(\mathbf{V}\mathbf{V}^\top \Omega^*) = \text{tr}(\mathbf{V}\mathbf{V}^\top \mathbf{V}\mathbf{V}^\top \Omega^*) = \text{tr}(\mathbf{V}\mathbf{V}^\top \Omega^* \mathbf{V}\mathbf{V}^\top) \\
&= \text{tr}(\mathbf{V}\mathbf{V}^\top U S U^\top \mathbf{V}\mathbf{V}^\top) = \text{tr}(\mathbf{V}\mathbf{V}^\top U S^{\frac{1}{2}} U^\top U S^{\frac{1}{2}} U^\top \mathbf{V}\mathbf{V}^\top) \\
&= \text{tr}(\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}} \Omega^{*\frac{1}{2}} \mathbf{V}\mathbf{V}^\top) = \langle \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}, \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}} \rangle \\
&= \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2
\end{aligned}$$

544 Furthermore, we notice that  $\|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 = \|\Omega^{*\frac{1}{2}}\|_F^2 - \|\Omega^{*\frac{1}{2}} - \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2$  as shown below

$$\begin{aligned}
\|\Omega^{*\frac{1}{2}} - \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 &= \|\Omega^{*\frac{1}{2}}\|_F^2 + \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 - 2\text{tr}(\Omega^{*\frac{1}{2}} \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}) \\
&= \|\Omega^{*\frac{1}{2}}\|_F^2 + \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 - 2\text{tr}(\Omega^{*\frac{1}{2}} \mathbf{V}\mathbf{V}^\top \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}) \\
&= \|\Omega^{*\frac{1}{2}}\|_F^2 + \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 - 2\|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2 \\
&= \|\Omega^{*\frac{1}{2}}\|_F^2 - \|\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2
\end{aligned}$$

545 Thus we get  $\arg \min_{\mathbf{V} \in \mathbb{R}^{V \times d}, \mathbf{V}^\top \mathbf{V} = I_d} -\langle \mathbf{V}\mathbf{V}^\top, \Omega^* \rangle = \arg \min_{\mathbf{V} \in \mathbb{R}^{V \times d}, \mathbf{V}^\top \mathbf{V} = I_d} \|\Omega^{*\frac{1}{2}} - \mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}\|_F^2$ .

546 Note that  $\mathbf{V}\mathbf{V}^\top \Omega^{*\frac{1}{2}}$  has columns that are columns of  $\Omega^{*\frac{1}{2}}$  projected on the space spanned by columns  
547  $\mathbf{V}$ . It is folklore that the best such subspace  $\mathbf{V}^*$  is the subspace spanned by the top  $d$  eigenvectors of  
548  $\Omega^{*\frac{1}{2}}$ , which is the same as top  $d$  eigenvectors of  $\Omega^*$ , thus giving us  $\mathbf{V}^* \mathbf{V}^{*\top} = U_d U_d^\top$ . Thus we get  
549  $\mathbf{V}^* = U_d M$  for  $M = U_d^\top \mathbf{V}^*$ .

550 This tells us that the optimal solution  $\Phi^*$  will have SVD of the form  $\Phi^* = N^* T^* \mathbf{V}^{*\top}$ , thus  
551 giving us  $\Phi^* = B U_d^\top$  for matrix  $B = N^* T^* M^\top \in \mathbb{R}^{d \times d}$ . This directly gives  $f^* = f_{\Phi^*}^* =$   
552  $(\Phi^* \Phi^{*\top})^{-1} \Phi^* p_{\cdot|s}^* = N^* T^{*-1} \mathbf{V}^{*\top} p_{\cdot|s}^* = C U_d^\top p_{\cdot|s}^*$  for  $C = N^* T^{*-1} M^\top$ .

553 □

## 554 E.5 Proof for supporting lemmas

555 **Lemma F.1.** For a language model  $\{p_{\cdot|s}\}$ , if  $\mathcal{T}$  is  $(\tau, B)$ -natural,

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_\infty \leq B} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

556 If  $\mathcal{T}$  is  $(\tau, B)$ -natural w.r.t.  $\Phi \in \mathbb{R}^{d \times V}$ ,

$$\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \sup_{\substack{\mathbf{v} = \Phi^\top \lambda \in \mathbb{R}^V \\ \|\mathbf{v}\|_\infty \leq B}} \sqrt{\frac{\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma_\Phi(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

557 where  $\gamma(\cdot)$  and  $\gamma_\Phi(\cdot)$  are from Definition D.1.



558 *Proof.* We note the following upper bounds on  $\ell_{\mathcal{T}}(\{p_{\cdot|s}\})$  and  $\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\})$ .

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) = \inf_{\mathbf{v} \in \mathbb{R}^V} \{\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})\} \leq \inf_{\substack{\mathbf{v} \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \{\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})\} \quad (12)$$

$$\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) = \inf_{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V} \{\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})\} \leq \inf_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, b \in \mathbb{R}, \\ \|\mathbf{v}\|_{\infty} \leq B}} \{\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})\} \quad (13)$$

559 When  $\mathcal{T}$  is  $(\tau, B)$ -natural, by Definition 3.1 we know that  $\inf_{\substack{\mathbf{v} \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} [\ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v})] \leq \tau$ . We now

560 upper bound  $\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})$  using Lemma F.8. Taking infimum w.r.t.  $\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_{\infty} \leq B$  from the  
561 inequality in Lemma F.8.

$$\begin{aligned} \ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v}) &\leq \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) + \sqrt{\mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \\ \inf_{\substack{\mathbf{v} \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v}) &\leq \inf_{\substack{\mathbf{v} \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_{\infty} \leq B} \sqrt{\mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \end{aligned}$$

562 This, combined with Equation (12), gives us

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}) \leq \tau + \sup_{\mathbf{v} \in \mathbb{R}^V, \|\mathbf{v}\|_{\infty} \leq B} \sqrt{\mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \quad (14)$$

563 Using Lemma F.9 and the definition of  $\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})$  in Equation (7), we get that

$$\begin{aligned} \mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} &\leq \left\| \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \right\|_2 \left( \mathbf{v}^{\top} \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} \right) \\ &= \frac{\mathbf{v}^{\top} \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma(p_{\mathcal{T}}; \{p_{\cdot|s}\})} \end{aligned}$$

564 We have thus successfully transferred the bound from the distribution  $p_{\mathcal{T}}$  to  $p_L$ . Combining this with  
565 Equation (14) completes the proof of the first part of the lemma.

566 We now prove the second part of the lemma where we only assume that  $\mathcal{T}$  is  $(\tau, B)$ -natural w.r.t.  $\Phi$ .  
567 Here we instead take the infimum over classifiers in the span of  $\Phi$  in Lemma F.8 to get

$$\begin{aligned} \inf_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, b \in \mathbb{R}, \\ \|\mathbf{v}\|_{\infty} \leq B}} \{\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v})\} &\leq \inf_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, b \in \mathbb{R}, \\ \|\mathbf{v}\|_{\infty} \leq B}} \left\{ \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) \right\} + \\ &\quad \sup_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \sqrt{\mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \end{aligned} \quad (15)$$

568 This, combined with definition of  $(\tau, B)$ -natural task w.r.t.  $\Phi$  and Equation (13) gives us

$$\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \sup_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \sqrt{\mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \quad (16)$$

569 For the last term, for any  $\mathbf{v} = \Phi^{\top} \lambda, \lambda \in \mathbb{R}^d$  we notice that

$$\begin{aligned} \mathbf{v}^{\top} \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} &= \lambda^{\top} \Phi \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \Phi^{\top} \lambda = \lambda^{\top} \Sigma_{p_{\mathcal{T}}}(\Phi \Delta_{\{p_{\cdot|s}\}}) \lambda \\ &\stackrel{(a)}{\leq} \left\| \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(\Phi \Delta_{\{p_{\cdot|s}\}}) \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}})^{-\frac{1}{2}} \right\|_2 \left( \lambda^{\top} \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}}) \lambda \right) \\ &= \frac{\lambda^{\top} \Sigma_{p_L}(\Phi \Delta_{\{p_{\cdot|s}\}}) \lambda}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})} = \frac{\mathbf{v}^{\top} \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})} \end{aligned}$$

570 This combined with Equation (16), we get

$$\ell_{\mathcal{T}}(\{\Phi p_{\cdot|s}\}) \leq \tau + \inf_{\substack{\mathbf{v} = \Phi^{\top} \lambda \in \mathbb{R}^V, \\ \|\mathbf{v}\|_{\infty} \leq B}} \sqrt{\frac{\mathbf{v}^{\top} \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}{\gamma_{\Phi}(p_{\mathcal{T}}; \{p_{\cdot|s}\})}}$$

571

□

572 **Lemma F.2.** For a language model  $\{p_{\cdot|s}\}$  and classifier  $\mathbf{v} \in \mathbb{R}^V$ ,

$$\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} \leq 2 \|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}^*)$$

573 where  $\Sigma_{p_L}(g) = \mathbb{E}_{s \sim p_L} [g(s)g(s)^\top]$  and  $\Delta_{\{p_{\cdot|s}\}}(s) = p_{\cdot|s} - p_{\cdot|s}^*$  are defined in Section D

574 *Proof.* We first note that

$$\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}(\{p_{\cdot|s}^*\}) = \mathbb{E}_{s \sim p_L} \mathbb{E}_{w \sim p_{\cdot|s}^*} \left[ \log \left( \frac{p_{\cdot|s}^*(w)}{p_{\cdot|s}(w)} \right) \right] = \mathbb{E}_{s \sim p_L} [D_{\text{KL}}(p_{\cdot|s}^*, p_{\cdot|s})] \quad (17)$$

575 We bound  $\mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}$  below

$$\begin{aligned} \mathbf{v}^\top \Sigma_{p_L}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v} &= \mathbb{E}_{s \sim p_L} \left[ \left( \mathbf{v}^\top (p_{\cdot|s} - p_{\cdot|s}^*) \right)^2 \right] \stackrel{(a)}{\leq} \mathbb{E}_{s \sim p_L} [\|\mathbf{v}\|_\infty^2 \|p_{\cdot|s} - p_{\cdot|s}^*\|_1^2] \\ &\stackrel{(b)}{\leq} \|\mathbf{v}\|_\infty^2 \mathbb{E}_{s \sim p_L} [2D_{\text{KL}}(p_{\cdot|s}^*, p_{\cdot|s})] \\ &\stackrel{(c)}{=} 2 \|\mathbf{v}\|_\infty^2 (\ell_{\text{xent}}(\{p_{\cdot|s}\}) - \ell_{\text{xent}}(\{p_{\cdot|s}^*\})) \end{aligned}$$

576 where (a) uses Holder's inequality, (b) uses Pinsker's inequality, (c) uses Equation (17).  $\square$

577 **Lemma F.3.** For any  $g : \mathcal{S} \rightarrow \mathbb{R}^D$  and  $p_{\mathcal{T}} \in \Delta_{\mathcal{S}}$ , we have  $\|\Sigma_{p_L}(g)^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(g) \Sigma_{p_L}(g)^{-\frac{1}{2}}\|_2 \leq$   
578  $\gamma(p_{\mathcal{T}})^{-1}$

579 *Proof.* By definition of  $\gamma(p_{\mathcal{T}})$ , we have that

$$\begin{aligned} \Sigma_{p_L}(g) &= \mathbb{E}_{s \sim p_L} [g(s)g(s)^\top] = \sum_{s \in \mathcal{S}} p_L(s) g(s)g(s)^\top \\ &\succcurlyeq \gamma(p_{\mathcal{T}}) \sum_{s \in \mathcal{S}} p_{\mathcal{T}}(s) g(s)g(s)^\top = \gamma(p_{\mathcal{T}}) \mathbb{E}_{s \sim p_{\mathcal{T}}} [g(s)g(s)^\top] = \gamma(p_{\mathcal{T}}) \Sigma_{p_{\mathcal{T}}}(g) \end{aligned}$$

580 Thus  $\frac{1}{\gamma(p_{\mathcal{T}})} \Sigma_{p_L}(g) \succcurlyeq \Sigma_{p_{\mathcal{T}}}(g)$  and hence  $\frac{1}{\gamma(p_{\mathcal{T}})} \Sigma_{p_L}(g)^{-\frac{1}{2}} \Sigma_{p_L}(g) \Sigma_{p_L}(g)^{-\frac{1}{2}} \succcurlyeq$   
581  $\Sigma_{p_L}(g)^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(g) \Sigma_{p_L}(g)^{-\frac{1}{2}}$ , which is equivalent to  $\frac{1}{\gamma(p_{\mathcal{T}})} I_D \succcurlyeq \Sigma_{p_L}(g)^{-\frac{1}{2}} \Sigma_{p_{\mathcal{T}}}(g) \Sigma_{p_L}(g)^{-\frac{1}{2}}$ . This  
582 finishes the proof.  $\square$

583 **Lemma F.4.** For a fixed  $\Phi$ , a softmax language model with features  $f$  and  $\lambda \in \mathbb{R}^d$ ,

$$\lambda^\top \Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) \lambda \leq 2 \|\Phi^\top \lambda\|_\infty^2 (\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi))$$

584 where  $\Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) = \mathbb{E}_{s \sim p_L} [(\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)(\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)^\top]$  as defined in Section D.

585 *Proof.* We start by noting that  $\lambda^\top \Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) \lambda =$   
586  $\mathbb{E}_{s \sim p_L} [(\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)(\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)^\top] \lambda = \mathbb{E}_{s \sim p_L} [|\lambda^\top (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)|^2]$ . We will  
587 use Lemma F.6 to bound each term on the right hand side, which essentially bounds the  
588 norm of the gradient of  $\ell_{\text{xent},s}$  at  $f(s)$  when  $f(s)$  is an almost optimal for  $s \in \mathcal{S}$ . Notice that  
589  $\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi) = \mathbb{E}_{s \sim p_L} [\ell_{\text{xent},s}(f(s), \Phi) - \inf_{\theta \in \mathbb{R}^d} \ell_{\text{xent},s}(\theta, \Phi)]$ .

$$\begin{aligned} \lambda^\top \Sigma_{p_L}(\Phi \Delta_{\{p_{f(s)}\}}) \lambda &= \mathbb{E}_{s \sim p_L} [|\lambda^\top (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)|^2] \\ &\stackrel{(a)}{\leq} 2 \|\Phi^\top \lambda\|_\infty^2 \mathbb{E}_{s \sim p_L} \left[ \ell_{\text{xent},s}(f(s), \Phi) - \inf_{\theta \in \mathbb{R}^d} \ell_{\text{xent},s}(\theta, \Phi) \right] \\ &\leq 2 \|\Phi^\top \lambda\|_\infty^2 (\ell_{\text{xent}}(f, \Phi) - \ell_{\text{xent}}^*(\Phi)) \end{aligned}$$

590 where (a) follows from Lemma F.6. This completes the proof.  $\square$

591 **Lemma F.6.** For  $s \in \mathcal{S}$  and embedding  $f(s) \in \mathbb{R}^d$ , we have

$$|\lambda^\top (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)|^2 \leq 2\|\Phi^\top \lambda\|_\infty^2 \left( \ell_{\text{xent},s}(f(s), \Phi) - \inf_{\theta \in \mathbb{R}^d} \ell_{\text{xent},s}(\theta, \Phi) \right)$$

592 *Proof.* Since we are assuming  $\Phi$  to be fixed, we will abuse notation and say  $\ell_{\text{xent},s}(\theta) := \ell_{\text{xent},s}(\theta, \Phi)$ .  
 593 All gradients are w.r.t.  $\theta$ . Before we get to the main proof, we compute the gradient and hessian of  
 594  $\ell_{\text{xent},s}(\theta)$  w.r.t.  $\theta$ . The gradient is

$$\begin{aligned} \nabla \ell_{\text{xent},s}(\theta) &= \nabla \left[ -\theta^\top \Phi p_{\cdot|s}^* + \log(Z_\theta) \right] = -\Phi p_{\cdot|s}^* + \frac{\nabla Z_\theta}{Z_\theta} \\ &= -\Phi p_{\cdot|s}^* + \frac{\nabla \sum_w e^{\theta^\top \phi_w}}{Z_\theta} = -\Phi p_{\cdot|s}^* + \frac{\sum_w e^{\theta^\top \phi_w} \phi_w}{Z_\theta} \\ &= -\Phi p_{\cdot|s}^* + \Phi p_\theta \end{aligned}$$

595 Similarly the Hessian can be computed

$$\begin{aligned} \nabla^2 \ell_{\text{xent},s}(\theta) &= \nabla(\nabla \ell_{\text{xent},s}(\theta)) = \nabla[-\Phi p_{\cdot|s}^* + \Phi p_\theta] = \nabla \sum_{w \in \mathcal{W}} p_\theta(w) \phi_w = \sum_{w \in \mathcal{W}} \nabla \frac{e^{\theta^\top \phi_w}}{Z_\theta} \phi_w \\ &= \sum_{w \in \mathcal{W}} \frac{e^{\theta^\top \phi_w}}{Z_\theta} \phi_w \phi_w^\top - \frac{e^{\theta^\top \phi_w}}{Z_\theta^2} \phi_w \left( \sum_{w'} e^{\theta^\top \phi_{w'}} \phi_{w'} \right)^\top \\ &= \mathbb{E}_{w \sim p_\theta} [\phi_w \phi_w^\top] - \left( \mathbb{E}_{w \sim p_\theta} \phi_w \right) \left( \mathbb{E}_{w \sim p_\theta} \phi_w \right)^\top = \text{Cov}_{w \sim p_\theta}[\phi_w] \end{aligned}$$

596 Where  $\text{Cov}_{w \sim p_\theta}[\phi_w]$  denotes the covariance of the word embeddings  $\phi_w$  when measured w.r.t. the  
 597 distribution  $p_\theta$ . This directly gives us that  $\nabla^2 \ell_{\text{xent},s}(\theta) \succcurlyeq 0$ , since the covariance is always psd, and  
 598 thus  $\ell_{\text{xent},s}$  is convex in  $\theta$ .

599 Using the closed form expression for  $\nabla \ell_{\text{xent},s}$ , we note that the quantity we wish to upper bound can  
 600 be rewritten as  $|\lambda^\top (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)|^2 = |\lambda^\top \nabla \ell_{\text{xent},s}(f(s))|^2$ . Furthermore, using the definition of  
 601 the Hessian, it is not hard to see for some  $\lambda, \tilde{\theta} \in \mathbb{R}^d$  that  $\lambda^\top \nabla^2 \ell_{\text{xent},s}(\tilde{\theta}) \lambda = \text{Cov}_{w \sim p_{\tilde{\theta}}}[\lambda^\top \phi_w] \leq$   
 602  $\mathbb{E}_{w \sim p_{\tilde{\theta}}} [(\lambda^\top \phi_w)^2] \leq \|\Phi^\top \lambda\|_\infty^2$ . We use the following lemma that can exploit the above observations.

603 **Lemma F.7.** If a function  $\ell : \mathbb{R}^d \rightarrow \mathbb{R}$  and  $\lambda \in \mathbb{R}^d$  satisfy  $\lambda^\top \nabla^2 \ell(\tilde{\theta}) \lambda \leq L, \forall \tilde{\theta} \in \mathbb{R}^d$  ( $L$ -smoothness  
 604 in the direction of  $\lambda$ ) and if  $\ell^* = \inf_{\theta \in \mathbb{R}^d} \ell(\theta)$ , then  $|\lambda^\top \nabla \ell(\theta)|^2 \leq 2L(\ell(\theta) - \ell^*)$

605 We first use this lemma for  $\ell_{\text{xent},s}$  to complete the proof with  $L = \|\Phi^\top \lambda\|_\infty^2$ . The lemma gives us  
 606 that  $|\lambda^\top \nabla \ell_{\text{xent},s}(f(s))|^2 \leq 2\|\Phi^\top \lambda\|_\infty^2 (\ell_{\text{xent},s}(f(s)) - \ell_{\text{xent},s}^*) \leq 2\|\Phi^\top \lambda\|_\infty^2 \epsilon_s$ . Combining this with  
 607 the expression for the gradient computed earlier, we get  $|\lambda^\top (\Phi p_{f(s)} - \Phi p_{\cdot|s}^*)|^2 \leq 2\|\Phi^\top \lambda\|_\infty^2 \epsilon_s$ , thus  
 608 completing the proof of the main lemma. We now prove the lemma.

609 *Proof of Lemma F.7.* This is a variant of a classical result used in optimization and we prove it here  
 610 for completeness. For any  $\eta \in \mathbb{R}$  we have

$$\begin{aligned} \ell(\theta) - \ell^* &\stackrel{(a)}{\geq} \ell(\theta) - \ell(\theta - \eta \lambda) \\ &\stackrel{(b)}{\geq} \ell(\theta) - \left( \ell(\theta) + \langle \nabla \ell(\theta), -\eta \lambda \rangle + \frac{\eta^2}{2} \lambda^\top \nabla^2 \ell(\tilde{\theta}) \lambda \right) \\ &\stackrel{(c)}{\geq} \eta(\lambda^\top \nabla \ell(\theta)) - \frac{\eta^2 L}{2} \end{aligned}$$

611 where (a) follows from the definition of infimum and (b) follows from Taylor's expansion and (c)  
 612 follows from the smoothness condition in the statement of the lemma. Picking  $\eta = \frac{\lambda^\top \nabla \ell(\theta)}{L}$  gives us  
 613  $\ell(\theta) - \ell^* \geq \frac{1}{2L} |\lambda^\top \nabla \ell(\theta)|^2$ , thus completing the proof.  $\square$

614

□

615 **Lemma F.8.** For any task  $\mathcal{T}$  and classifier  $\mathbf{v} \in \mathbb{R}^V$  and predicted probabilities  $\{p_{\cdot|s}\}$

$$\ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v}) \leq \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) + \sqrt{\mathbf{v}^\top \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}}$$

616 where  $\Sigma_{p_{\mathcal{T}}}(g) = \mathbb{E}_{s \sim p_{\mathcal{T}}} [g(s)g(s)^\top]$  and  $\Delta_{\{p_{\cdot|s}\}}(s) = p_{\cdot|s} - p_{\cdot|s}^*$  are defined in Section D.

617 *Proof.* The following sequence of inequalities proves it

$$\begin{aligned} \ell_{\mathcal{T}}(\{p_{\cdot|s}\}, \mathbf{v}) &= \mathbb{E}_{(s,y) \sim p_{\mathcal{T}}} [\ell(\mathbf{v}^\top p_{\cdot|s}, y)] \stackrel{(a)}{\leq} \mathbb{E}_{(s,y) \sim p_{\mathcal{T}}} [\ell(\mathbf{v}^\top p_{\cdot|s}^*, y) + |\mathbf{v}^\top (p_{\cdot|s}^* - p_{\cdot|s})|] \\ &\stackrel{(b)}{\leq} \mathbb{E}_{(s,y) \sim p_{\mathcal{T}}} [\ell(\mathbf{v}^\top p_{\cdot|s}^*, y)] + \sqrt{\mathbb{E}_{s \sim p_{\mathcal{T}}} [|\mathbf{v}^\top (p_{\cdot|s}^* - p_{\cdot|s})|^2]} \\ &= \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) + \sqrt{\mathbf{v}^\top \left( \mathbb{E}_{s \sim p_{\mathcal{T}}} [(p_{\cdot|s}^* - p_{\cdot|s})(p_{\cdot|s}^* - p_{\cdot|s})^\top] \right) \mathbf{v}} \\ &= \ell_{\mathcal{T}}(\{p_{\cdot|s}^*\}, \mathbf{v}) + \sqrt{\mathbf{v}^\top \Sigma_{p_{\mathcal{T}}}(\Delta_{\{p_{\cdot|s}\}}) \mathbf{v}} \end{aligned}$$

618 where (a) follows from 1-lipschitzness of  $\ell$ , (b) follows from Jensen’s inequality. □

619 **Lemma F.9.** For matrices  $\mathbf{X}, \mathbf{Y} \in \mathbb{R}^{D \times D}$  s.t.  $\mathbf{X}, \mathbf{Y} \succcurlyeq 0$  and  $\mathbf{Y}$  is full rank, we have that

620  $\max_{\mathbf{a} \in \mathbb{R}^D, 0 < \|\mathbf{a}\| \leq \lambda} \frac{\mathbf{a}^\top \mathbf{X} \mathbf{a}}{\mathbf{a}^\top \mathbf{Y} \mathbf{a}} = \|\mathbf{Y}^{-\frac{1}{2}} \mathbf{X} \mathbf{Y}^{-\frac{1}{2}}\|_2$  for any norm  $\|\cdot\|$ .

621 *Proof.* Note that  $\frac{\mathbf{a}^\top \mathbf{X} \mathbf{a}}{\mathbf{a}^\top \mathbf{Y} \mathbf{a}}$  is independent of the scaling of  $\mathbf{a}$ . The following sequence of inequalities  
622 completes the proof

$$\begin{aligned} \max_{\mathbf{a} \in \mathbb{R}^D, 0 < \|\mathbf{a}\| \leq \lambda} \frac{\mathbf{a}^\top \mathbf{X} \mathbf{a}}{\mathbf{a}^\top \mathbf{Y} \mathbf{a}} &= \max_{\mathbf{a} \in \mathbb{R}^D} \frac{\mathbf{a}^\top \mathbf{X} \mathbf{a}}{\mathbf{a}^\top \mathbf{Y} \mathbf{a}} = \max_{\mathbf{a} \in \mathbb{R}^D} \frac{\mathbf{a}^\top \mathbf{X} \mathbf{a}}{(\mathbf{Y}^{\frac{1}{2}} \mathbf{a})^\top (\mathbf{Y}^{\frac{1}{2}} \mathbf{a})} \\ &= \max_{\mathbf{a} \in \mathbb{R}^D, \|\mathbf{Y}^{\frac{1}{2}} \mathbf{a}\|_2 = 1} \mathbf{a}^\top \mathbf{X} \mathbf{a} = \max_{\mathbf{b} \in \mathbb{R}^D, \|\mathbf{b}\|_2 = 1} (\mathbf{Y}^{-\frac{1}{2}} \mathbf{b})^\top \mathbf{X} (\mathbf{Y}^{-\frac{1}{2}} \mathbf{b}) \\ &= \max_{\mathbf{b} \in \mathbb{R}^D, \|\mathbf{b}\|_2 = 1} \mathbf{b}^\top \mathbf{Y}^{-\frac{1}{2}} \mathbf{X} \mathbf{Y}^{-\frac{1}{2}} \mathbf{b} = \|\mathbf{Y}^{-\frac{1}{2}} \mathbf{X} \mathbf{Y}^{-\frac{1}{2}}\|_2 \end{aligned}$$

623

□

## 624 G Experiment Details

625 For all experiments, we use the 117M parameter “small” GPT-2 model proposed in Radford et al.  
626 [2019] and implemented in HuggingFace Wolf et al. [2019]. We use the standard learning rate  
627 schedule and architecture provided in the initial publication. To learn a model on IMDB, we use a  
628 context size of 512 BPE tokens, and for the Amazon reviews dataset McAuley et al. [2015], we use  
629 the standard context length of 1,024 BPE tokens.

### 630 G.1 Solving downstream tasks using $f$ and $\Phi_{p_f}$

631 **Details about word subsets:** For all of the results presented in Table 1, we use a pre-trained GPT-2  
632 model. For SST, we use the prompt “This movie is ” when indicated. For AG News, we use the  
633 prompt “This article is about ” when indicated.

634 We compute the conditional probability of selecting a subset of words to complete the sentence.  
635 For AG News, this subset is: ‘world’, ‘politics’, ‘sports’, ‘business’, ‘science’, ‘financial’, ‘market’,  
636 ‘foreign’, ‘technology’, ‘international’, ‘stock’, ‘company’, ‘tech’, ‘technologies’. For SST, this  
637 subset is: ‘:’, ‘:’, ‘great’, ‘charming’, ‘flawed’, ‘classic’, ‘interesting’, ‘boring’, ‘sad’, ‘happy’,  
638 ‘terrible’, ‘fantastic’, ‘exciting’, ‘strong’. We account for BPE tokenization by using the encoding of

the word directly and the encoding of the word with a space prepended. We then filter to use only words that encode to a single BPE token.

For AG News, the class words we use are: 'foreign', 'sports', 'financial', 'scientific'. For SST, the class words we use are ' :)' and ' :( '.

**Tests on additional datasets:** We also test the performance of GPT-2 frozen embeddings  $f$  and the conditional mean embeddings  $g_{f,\Phi}(s) = \Phi p_{f(s)}$  on the DBPedia [Auer et al., 2007], Yahoo Answers [Zhang et al., 2015], TREC [Li and Roth, 2002], IMDb [Maas et al., 2011], Customer Review (CR) [Hu and Liu, 2004], and MPQA polarity [Wilson and Wiebe, 2003] datasets in Table 2. We limited the training set size to 200K for larger datasets (i.e., DBPedia and Yahoo Answers). For CR and MPQA, we created train-test splits with 75-25 percentage random splits of the data.

We find that  $g_{f,\Phi}$  consistently has comparable performance to  $f$  across non-sentiment and sentiment downstream classification tasks. We include results using a bag-of- $n$ -grams (BoNG) and Sentiment Neuron (mLSTM) [Radford et al., 2017], and we note that using 768-dimensional features is more sample efficient than BoNG.

For sentiment tasks, adding a prompt always boosts performance. We also demonstrate that much of the performance can be recovered by only looking at “positive” and “negative” or “:)” and “:(” as class words. Using these 2-dimensional features is even more sample-efficient than the standard 768-dimensional ones.

We also include results using the pre-trained BERT base cased model [Devlin et al., 2018, Wolf et al., 2019], using the embedding at the first token as input to the downstream task. We also tried using the mean embedding and last token embedding and found that the first token embedding is best. Moreover, the first token embedding is what is extracted in the traditional usage of BERT on downstream tasks.

Table 2: GPT-2 performance without fine-tuning on downstream task test sets with  $k$  classes. We provide the performance of bag-of- $n$ -grams as an approximate baseline for these tasks. DBPedia and Yahoo performances were reported in Zhang et al. [2015], and the other tasks were reported in Khodak et al. [2018]. We also include results from Sentiment Neuron [Radford et al., 2017] for the sentiment-related classification tasks: IMDb, CR, and MPQA. Furthermore, we include results from using BERT [Devlin et al., 2018] without fine-tuning, where we use the features produced for the first position as input to the linear classifier. An asterisk indicates we add a standard sentiment prompt “The sentiment is ” to each input. We also tested the performance of the conditional probability distribution over “positive” and “negative” as well as “:)” and “:(” on the sentiment-related tasks with and without the prompt.

Task	$k$	$f(s)$	$\Phi p_{f(s)}$	$p_{\cdot s}$ : pos,neg	$p_{\cdot s}$ : :),:(	BonG	mLSTM	BERT
<i>Non-sentiment</i>								
DBPedia	14	96.1%	88.5%	-	-	98.6% ( $n = 5$ )	-	98.3%
Yahoo	10	69.9%	57.8%	-	-	68.5% ( $n = 5$ )	-	64.7%
TREC	6	94.2%	88.0%	-	-	89.8% ( $n = 3$ )	-	91.0%
<i>Sentiment</i>								
IMDb	2	87.7%	83.0%	76.1%	72.3%	89.8% ( $n = 3$ )	92.3%	81.9%
IMDb*	-	87.8%	84.3%	77.8%	74.3%	-	-	83.7%
CR	2	92.3%	85.5%	80.0%	73.8%	78.3% ( $n = 3$ )	91.4%	90.5%
CR*	-	92.4%	90.5%	79.6%	81.4%	-	-	88.3%
MPQA	2	87.9%	82.1%	71.0%	70.5%	85.6% ( $n = 3$ )	88.5%	88.3%
MPQA*	-	88.5%	87.1%	71.6%	78.4%	-	-	88.4%

## G.2 Testing Quad objective

We first compare downstream performance of the Quad objective to the cross-entropy objective by training GPT-2 on the IMDb dataset [Maas et al., 2011]. Table 3 shows that features learned by Quad perform comparably to  $g_{f,\Phi}$  for  $f$  learned by the cross-entropy objective, which fits our theory since both are linear functions of  $p_{\cdot|s}^*$ .

Table 3: Comparing Quad features to standard cross-entropy features for GPT-2 trained on IMDB [Maas et al., 2011].

Task	$f(s)$ (xent)	$g_{f,\Phi}(s)$ (xent)	$f(s)$ (Quad, fixed $\Phi$ )	$f(s)$ (Quad, learned $\Phi$ )
SST	82.1%	79.9%	77.1%	77.3%
SST*	83.1%	81.1%	78.5%	80.7%




Figure 1: Fit of the learned quadratic function to the log partition function on various datasets for features computed by the full, pre-trained GPT-2. We also plot the  $y = x$  line for reference.

We then test two models with the same parametrization and initializations, one trained using our Quad objective and another trained with the standard language modeling objective using the Amazon product review dataset [McAuley et al., 2015] instead of IMDB. We slightly modify the standard architecture of GPT-2 to generate Tables 3 and 4. We add a single linear layer after the Transformer to add expressivity. Furthermore, instead of tying the input and output embeddings, we learn them separately so that  $f$  and  $\Phi$  are independent functions. We fix the input embeddings and the positional embeddings to be the parameters from the pre-trained GPT-2. We initialize  $\Phi$ , the output embeddings, using the singular vectors of the pre-trained word embeddings  $\Phi$ . Given our parameterization, initializing with the singular vectors is as expressive as initializing with the pretrained embeddings  $\Phi$  themselves; however it lends a better optimization landscape and speeds up training for our new objective.

We observe that even on a large dataset, training using Quad yields comparable performance to the language model on the SST task. Furthermore, adding a prompt consistently improves performance for both objectives.

Table 4: Comparing the downstream performance of features learned using Quad to  $\Phi p_{f(s)}$ , where  $f(s)$  is from an LM trained on the standard KL objective. All models were trained on the Amazon dataset. An asterisk indicates that we added the prompt “This movie is ” to each input. Note that the validation loss was still decreasing at the time of measurement.

Task	$f(s)$ (xent)	$\Phi p_{f(s)}$ (xent)	$f(s)$ (Quad, learned $\Phi$ )
SST	89.4%	89.7%	79.2%
SST*	89.7%	89.2%	84.3%

### G.3 Learning the quadratic approximation of the log-partition function

In Assumption 4.1, we assert that there is a quadratic fit for the log partition function, which allows us to show in Lemma 4.3 that a linear relation holds between  $f^*$  and  $\Phi p_{f^*}$ . We validate these theoretical findings by fitting a quadratic function to the log partition function for a subset of embeddings from the IMDB, SST, and AG News datasets (Figure 1). Here, we describe how we learned  $\mathbf{A}$ ,  $\mathbf{b}$  and  $\mathbf{c}$ . To ensure  $\mathbf{A}$  is symmetric and positive semi-definite as required, we parametrize  $\mathbf{A} = \mathbf{U}\mathbf{U}^T$ . Let  $\mu_\theta = \Phi p_\theta$ . We minimize the following objective function:

True log partition versus learned quadratic function




Figure 2: Fit of the learned quadratic function to the log partition function on various datasets for features computed by the full, pre-trained GPT-2. We also plot the  $y = x$  line for reference.

$$\mathcal{L}(\mathbf{U}, \mathbf{b}, c) = \mathbb{E}_{\theta} \left[ \lambda_1 \left( \log(Z_{\theta}) - \frac{1}{2} \theta^{\top} \mathbf{U} \mathbf{U}^{\top} \theta - \theta^{\top} \mathbf{b} - c \right)^2 + \lambda_2 \left\| \Phi p_{\theta} - \mathbf{U} \mathbf{U}^{\top} \theta - \mathbf{b} \right\|^2 \right]$$

688 In practice, we train only on the regression loss (i.e.,  $\lambda_1 = 0$ ,  $\lambda_2 = 1$ ) for the most promising results.  
689 We use 20,000 examples from a mix of IMDb, SST, and AG News embeddings as the training set.  
690 We used the Adam [Kingma and Ba, 2014] optimizer with learning rate 1e-3 for  $\mathbf{U}$  and learning rate  
691 1e-4 for  $\mathbf{b}$  and  $c$ . We decayed the learning rate every 50 steps by a factor of 0.1. We found the fit after  
692 8 epochs of training.

693 We further demonstrate the quality of the learned fit by plotting the true log partition and estimated  
694 log partition function for embeddings from other datasets in Figure 2.