

CSI - 3105 Design & Analysis of Algorithms

Course 12


Jean-Lou De Carufel

Fall 2019

Kruskal Algorithm (1956)

Approach : Maintain a forest. In each step, add an edge of minimum weight that does not create a cycle.


Start : At the beginning, each vertex is a (trivial) tree.




Kruskal Algorithm (1956)


Approach : Maintain a forest. In each step, add an edge of minimum weight that does not create a cycle.

Start : At the beginning, each vertex is a (trivial) tree.




One Iteration : Combine two trees using an edge of minimum weight.






Sort the edges by weight:


BC, BD, CD, CF, AD, DF, EF, AB, CE, AC






Sort the edges by weight:


BC, BD, CD, CF, AD, DF, EF, AB, CE, AC






Sort the edges by weight:


BC, BD, CD, CF, AD, DF, EF, AB, CE, AC






Sort the edges by weight:


BC, BD, CD, CF, AD, DF, EF, AB, CE, AC






Sort the edges by weight:


BC, BD, CD, CF, AD, DF, EF, AB, CE, AC





Sort the edges by weight:

BC, BD, CD, CF, AD, DF, EF, AB, CE, AC



Total weight: 14

Algorithm *Kruskal*(G)

Input: $G = (V, E)$, where $V = \{x_1, x_2, \dots, x_n\}$ and $m = |E|$.

Output: A minimum spanning tree of G .

```
1: Sort the edges of  $E$  by weight using Merge Sort:  $e_1, e_2, \dots, e_m$ 
2: for  $i = 1$  to  $n$  do
3:    $V_i = \{x_i\}$ 
4: end for
5:  $T = \{\}$ 
6: for  $k = 1$  to  $m$  do
7:   let  $u_k$  and  $v_k$  be the vertices of  $e_k$ .
8:   let  $i$  be the index such that  $u_k \in V_i$ 
9:   let  $j$  be the index such that  $v_k \in V_j$ 
10:  if  $i \neq j$  then
11:     $V_i = V_i \cup V_j$ 
12:     $V_j = \{\}$ 
13:     $T = T \cup \{\{u_k, v_k\}\}$ 
14:  end if
15: end for
16: return  $T$ 
```

Running time:

- Sorting: $O(m \log(m)) = O(m \log(n))$ time (do you see why?)

Running time:

- Sorting: $O(m \log(m)) = O(m \log(n))$ time (do you see why?)
- First For-loop: $O(n)$ time

Running time:

- Sorting: $O(m \log(m)) = O(m \log(n))$ time (do you see why?)
- First For-loop: $O(n)$ time
- Second For-loop:
 - Store T in a linked list. Total time to maintain this list: $O(n)$ time
 - Store the sets V_i using the Union-Find data structure.

Running time:

- Sorting: $O(m \log(m)) = O(m \log(n))$ time (do you see why?)
- First For-loop: $O(n)$ time
- Second For-loop:
 - Store T in a linked list. Total time to maintain this list: $O(n)$ time
 - Store the sets V_i using the Union-Find data structure.

In this second For-Loop, we do

- $2m$ **Find** operations
- $n - 1$ **Union** operations

So in total for the second For-Loop:

$$O(n) + O(m + n \log(n)) \text{ time}$$

Running time:

- Sorting: $O(m \log(m)) = O(m \log(n))$ time (do you see why?)
- First For-loop: $O(n)$ time
- Second For-loop:
 - Store T in a linked list. Total time to maintain this list: $O(n)$ time
 - Store the sets V_i using the Union-Find data structure.

In this second For-Loop, we do

- $2m$ **Find** operations
- $n - 1$ **Union** operations

So in total for the second For-Loop:

$$O(n) + O(m + n \log(n)) \text{ time}$$

So the total time is


$$O(m \log(n)) + O(n) + O(m + n \log(n)) = O(m \log(n))$$

Do you see why?

Conclusion: Kruskal computes an MST in $O(m \log(n))$ time.


Prim Algorithm (1957) [Jarník (1930), Dijkstra (1959)]

- Start :
- A is a set consisting of one (arbitrary) vertex of V .
 - T is an empty set of edges.




Prim Algorithm (1957) [Jarník (1930), Dijkstra (1959)]

- Start** :
- A is a set consisting of one (arbitrary) vertex of V .
 - T is an empty set of edges.




- One Iteration** :
- Take an edge $\{u, v\}$ of minimum weight such that $u \in A$ and $v \in Q$.
 - Add the edge $\{u, v\}$ to T .
 - Move v from Q to A .




Prim Algorithm (1957) [Jarník (1930), Dijkstra (1959)]

- Start** :
- A is a set consisting of one (arbitrary) vertex of V .
 - T is an empty set of edges.



- One Iteration** :
- Take an edge $\{u, v\}$ of minimum weight such that $u \in A$ and $v \in Q$.
 - Add the edge $\{u, v\}$ to T .
 - Move v from Q to A .



Repeat until $A = V$ (i.e. $Q = \{ \}$)!

Algorithm $\text{Prim}(G)$

Input: $G = (V, E)$ **Output:** A minimum spanning tree of G .

- 1: Let $r \in V$ be an arbitrary vertex.
 - 2: $A = \{r\}$
 - 3: $T = \{\}$
 - 4: **while** $A \neq V$ **do**
 - 5: find an edge $\{u, v\} \in E$ of minimum weight such that $u \in A$ and $v \in V \setminus A$.
 - 6: $A = A \cup \{v\}$
 - 7: $T = T \cup \{\{u, v\}\}$
 - 8: **end while**
 - 9: **return** T
-

Algorithm $\text{Prim}(G)$

Input: $G = (V, E)$ **Output:** A minimum spanning tree of G .

- 1: Let $r \in V$ be an arbitrary vertex.
 - 2: $A = \{r\}$
 - 3: $T = \{\}$
 - 4: **while** $A \neq V$ **do**
 - 5: find an edge $\{u, v\} \in E$ of minimum weight such that $u \in A$ and $v \in V \setminus A$.
 - 6: $A = A \cup \{v\}$
 - 7: $T = T \cup \{\{u, v\}\}$
 - 8: **end while**
 - 9: **return** T
-

How to find such an edge $\{u, v\}$?

Algorithm $\text{Prim}(G)$

Input: $G = (V, E)$ **Output:** A minimum spanning tree of G .

- 1: Let $r \in V$ be an arbitrary vertex.
 - 2: $A = \{r\}$
 - 3: $T = \{\}$
 - 4: **while** $A \neq V$ **do**
 - 5: find an edge $\{u, v\} \in E$ of minimum weight such that $u \in A$ and $v \in V \setminus A$.
 - 6: $A = A \cup \{v\}$
 - 7: $T = T \cup \{\{u, v\}\}$
 - 8: **end while**
 - 9: **return** T
-

How to find such an edge $\{u, v\}$?

By brute force, it takes $O(|E|)$ time.

Algorithm *Prim*(G)

Input: $G = (V, E)$ **Output:** A minimum spanning tree of G .

- 1: Let $r \in V$ be an arbitrary vertex.
 - 2: $A = \{r\}$
 - 3: $T = \{\}$
 - 4: **while** $A \neq V$ **do**
 - 5: find an edge $\{u, v\} \in E$ of minimum weight such that $u \in A$ and $v \in V \setminus A$.
 - 6: $A = A \cup \{v\}$
 - 7: $T = T \cup \{\{u, v\}\}$
 - 8: **end while**
 - 9: **return** T
-

How to find such an edge $\{u, v\}$?

By brute force, it takes $O(|E|)$ time.

So the total running time becomes $O(|V| \cdot |E|)$.


To improve the running time, we maintain extra information.

To improve the running time, we maintain extra information.

For each vertex y in Q ,

$\text{minweight}(y)$: minimum weight of any edge between y and a vertex of A

$\text{closest}(y)$: vertex x in A for which $\text{wt}(x, y) = \text{minweight}(y)$




To improve the running time, we maintain extra information.

For each vertex y in Q ,

$minweight(y)$: minimum weight of any edge between y and a vertex of A


$closest(y)$: vertex x in A for which $wt(x, y) = minweight(y)$




Observe that: a shortest edge $\{u, v\}$ connecting A and Q has weight

$$\min_{y \in Q} \{minweight(y)\}.$$


What happens if we move v from Q to A ?



What happens if we move v from Q to A ?



We update $\text{minweight}(w)$ and $\text{closest}(w)$ for $w = x, y, z$.



Algorithm *Prim*(G)

Input: $G = (V, E)$

Output: A minimum spanning tree of G .

```

1: Let  $r \in V$  be an arbitrary vertex
2:  $A = \{r\}$ 
3:  $T = \{ \}$ 
4: for each vertex  $y \neq r$  do
5:    $\text{minweight}(y) = \infty$ 
6:    $\text{closest}(y) = \text{NIL}$ 
7: end for
8: for each edge  $\{r, y\}$  do
9:    $\text{minweight}(y) = \text{wt}(r, y)$ 
10:   $\text{closest}(y) = r$ 
11: end for
12:  $Q = V \setminus \{r\}$ 
13:  $k = 1$  // Stores the size of  $A$ 
14: while  $k \neq n$  do
15:   Let  $v$  be the vertex of  $Q$  for which  $\text{minweight}(v)$  is minimum
16:    $u = \text{closest}(v)$ 
17:    $A = A \cup \{v\}$ 
18:    $Q = Q \setminus \{v\}$ 
19:    $T = T \cup \{\{u, v\}\}$ 
20:    $k = k + 1$ 
21:   for each edge  $\{v, y\}$  do
22:     if  $y \in Q$  and  $\text{wt}(v, y) < \text{minweight}(y)$  then
23:        $\text{minweight}(y) = \text{wt}(v, y)$ 
24:        $\text{closest}(y) = v$ 
25:     end if
26:   end for
27: end while
28: return  $T$ 

```

- Store the vertices of Q in a min-heap.
For each vertex $v \in Q$, the key of v is $\text{minweight}(v)$.
- Store T in a list.
- With each vertex of V , store one bit indicating whether the vertex belongs to A or to Q .

- Store the vertices of Q in a min-heap.
For each vertex $v \in Q$, the key of v is $\text{minweight}(v)$.
- Store T in a list.
- With each vertex of V , store one bit indicating whether the vertex belongs to A or to Q .

Running time:

- Up to the while loop: $O(n)$ time
(this includes the time to build the heap).

- Store the vertices of Q in a min-heap.
For each vertex $v \in Q$, the key of v is $\text{minweight}(v)$.
- Store T in a list.
- With each vertex of V , store one bit indicating whether the vertex belongs to A or to Q .

Running time:

- Up to the while loop: $O(n)$ time
(this includes the time to build the heap).
- One iteration of the while-loop:
 - extract_min : $O(\log(n))$ time
 - At most $\text{degree}(v)$ many decrease_key operations:
 $O(\text{degree}(v) \cdot \log(n))$ time

- Store the vertices of Q in a min-heap.
For each vertex $v \in Q$, the key of v is $\text{minweight}(v)$.
- Store T in a list.
- With each vertex of V , store one bit indicating whether the vertex belongs to A or to Q .

Running time:

- Up to the while loop: $O(n)$ time
(this includes the time to build the heap).
- One iteration of the while-loop:
 - extract_min : $O(\log(n))$ time
 - At most $\text{degree}(v)$ many decrease_key operations:
 $O(\text{degree}(v) \cdot \log(n))$ time
- Total time for the while-loop:

$$O\left(\sum_{v \in V} \text{degree}(v) \cdot \log(n)\right) = O(2m \log(n)) = O(m \log(n))$$

Conclusion: Prim computes an MST in $O(m \log(n))$ time.