

# CSI - 3105 Design & Analysis of Algorithms

## Course 2

Jean-Lou De Carufel

Fall 2019

# The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

# The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, ...

# The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

$$0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, \dots$$

---

**Algorithm** *fib*(*n*)

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n-1) + \text{fib}(n-2)$   
5: end if
```

---

# The Running Time of $\text{fib}(n)$

---

**Algorithm**  $\text{fib}(n)$

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

---

# The Running Time of $\text{fib}(n)$

---

**Algorithm**  $\text{fib}(n)$

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

---

Let  $T(n)$  be the number of steps when running  $\text{fib}(n)$ .

# The Running Time of $\text{fib}(n)$

---

**Algorithm**  $\text{fib}(n)$

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

---

Let  $T(n)$  be the number of steps when running  $\text{fib}(n)$ .

If  $n = 0$  or  $n = 1$ ,

# The Running Time of $\text{fib}(n)$

---

**Algorithm**  $\text{fib}(n)$

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```

1: if  $n \leq 1$  then
2:   return  $n$ 
3: else
4:   return  $\text{fib}(n-1) + \text{fib}(n-2)$ 
5: end if

```

---

Let  $T(n)$  be the number of steps when running  $\text{fib}(n)$ .

If  $n = 0$  or  $n = 1$ , we do

comparison " $n \leq 1$ "	}	2 steps
return value		



# The Running Time of $\text{fib}(n)$

If  $n \geq 2$ , we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$	:	1 step
call $\text{fib}(n - 1)$	:	?
compute $n - 2$	:	1 step
call $\text{fib}(n - 2)$	:	?
compute sum of two results	:	1 step
return output	:	1 step

# The Running Time of $\text{fib}(n)$

If  $n \geq 2$ , we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$	:	1 step
call $\text{fib}(n - 1)$	:	$T(n - 1)$ steps
compute $n - 2$	:	1 step
call $\text{fib}(n - 2)$	:	?
compute sum of two results	:	1 step
return output	:	1 step

# The Running Time of $\text{fib}(n)$

If  $n \geq 2$ , we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$	:	1 step
call $\text{fib}(n - 1)$	:	$T(n - 1)$ steps
compute $n - 2$	:	1 step
call $\text{fib}(n - 2)$	:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

# The Running Time of $\text{fib}(n)$

If  $n \geq 2$ , we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$	:	1 step
call $\text{fib}(n - 1)$	:	$T(n - 1)$ steps
compute $n - 2$	:	1 step
call $\text{fib}(n - 2)$	:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n - 1) + T(n - 2) + 5 & \text{if } n \geq 2. \end{cases}$$

# The Running Time of $\text{fib}(n)$

If  $n \geq 2$ , we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$	:	1 step
call $\text{fib}(n - 1)$	:	$T(n - 1)$ steps
compute $n - 2$	:	1 step
call $\text{fib}(n - 2)$	:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n - 1) + T(n - 2) + 5 & \text{if } n \geq 2. \end{cases}$$

What do we do with this?

# The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

# The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that  $T(n) \geq F_n$ . So the running time of  $\text{fib}(n)$  is at least  $F_n$ .

# The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that  $T(n) \geq F_n$ . So the running time of  $\text{fib}(n)$  is at least  $F_n$ .

The problem is that  $F_n$  is very large. Indeed, in Exercise #19, you will prove that  $F_n \geq 2^{n/2}$  for all  $n \geq 6$ .



# The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that  $T(n) \geq F_n$ . So the running time of  $\text{fib}(n)$  is at least  $F_n$ .

The problem is that  $F_n$  is very large. Indeed, in Exercise #19, you will prove that  $F_n \geq 2^{n/2}$  for all  $n \geq 6$ .

So  $\text{fib}(n)$  takes at least exponential time:  $\text{fib}(200)$  will not terminate during our lifetime!

# The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$


In Exercise #20, you will prove that  $T(n) \geq F_n$ . So the running time of  $\text{fib}(n)$  is at least  $F_n$ .

The problem is that  $F_n$  is very large. Indeed, in Exercise #19, you will prove that  $F_n \geq 2^{n/2}$  for all  $n \geq 6$ .


So  $\text{fib}(n)$  takes at least exponential time:  $\text{fib}(200)$  will not terminate during our lifetime!

Why is  $\text{fib}(n)$  so slow?

# The Running Time of $\text{fib}(n)$



# The Running Time of $\text{fib}(n)$



Too many things are called multiple times.

# A Better Algorithm

---

**Algorithm** *fib2*( $n$ )

---

**Input:** An integer  $n \geq 0$ .

**Output:**  $F_n$ .

```
1: if  $n \leq 1$  then
2:   return  $n$ 
3: else
4:   initialize array  $f[0..n]$ 
5:    $f[0] = 0$ 
6:    $f[1] = 1$ 
7:   for  $i = 2$  to  $n$  do
8:      $f[i] = f[i - 1] + f[i - 2]$ 
9:   end for
10:  return  $f[n]$ 
11: end if
```

---

The running time of  $\text{fib2}(n)$  is *linear in  $n$* , i.e. it is  $O(n)$ . In this case, we can even say that it is  $\Theta(n)$ .

The running time of  $\text{fib2}(n)$  is *linear in  $n$* , i.e. it is  $O(n)$ . In this case, we can even say that it is  $\Theta(n)$ .

Running time of  $\text{fib}(n)$ :    exponential

Running time of  $\text{fib2}(n)$ :    linear

The running time of  $\text{fib2}(n)$  is *linear in  $n$* , i.e. it is  $O(n)$ . In this case, we can even say that it is  $\Theta(n)$ .

Running time of  $\text{fib}(n)$ :    exponential

Running time of  $\text{fib2}(n)$ :    linear

**But!**



The running time of  $\text{fib2}(n)$  is *linear in  $n$* , i.e. it is  $O(n)$ . In this case, we can even say that it is  $\Theta(n)$ .

Running time of  $\text{fib}(n)$ : exponential

Running time of  $\text{fib2}(n)$ : linear

**But!** Is it realistic to say that  $\text{fib2}(n)$  takes a linear number of steps?

The running time of  $\text{fib2}(n)$  is *linear in  $n$* , i.e. it is  $O(n)$ . In this case, we can even say that it is  $\Theta(n)$ .

Running time of  $\text{fib}(n)$ : exponential

Running time of  $\text{fib2}(n)$ : linear

**But!** Is it realistic to say that  $\text{fib2}(n)$  takes a linear number of steps?

In our analysis, one step corresponds to

comparison	}	involving very large numbers
addition		
subtraction		

In kindergarden, we learned that

*Two  $n$ -bit numbers can be added in a linear number of bit-operations.*

In kindergarden, we learned that

*Two  $n$ -bit numbers can be added in a linear number of bit-operations.*

When running  $\text{fib2}(n)$ , we do roughly  $n$  additions of numbers, each of these numbers is at most  $F_n$ , each of these numbers has roughly  $n$  bits.

In kindergarden, we learned that

*Two  $n$ -bit numbers can be added in a linear number of bit-operations.*

When running  $\text{fib2}(n)$ , we do roughly  $n$  additions of numbers, each of these numbers is at most  $F_n$ , each of these numbers has roughly  $n$  bits.

Therefore,  $\text{fib2}(n)$  makes a *quadratic number* of bit-operations, i.e.  $O(n^2)$  bit-operations.

In kindergarden, we learned that

*Two  $n$ -bit numbers can be added in a linear number of bit-operations.*

When running  $\text{fib2}(n)$ , we do roughly  $n$  additions of numbers, each of these numbers is at most  $F_n$ , each of these numbers has roughly  $n$  bits.

Therefore,  $\text{fib2}(n)$  makes a *quadratic number* of bit-operations, i.e.  $O(n^2)$  bit-operations.

In Exercise #23, you will prove that the number of bit-operations done by  $\text{fib}(n)$  is  $O(n \cdot F_n)$ .

In kindergarden, we learned that

*Two  $n$ -bit numbers can be added in a linear number of bit-operations.*

When running  $\text{fib2}(n)$ , we do roughly  $n$  additions of numbers, each of these numbers is at most  $F_n$ , each of these numbers has roughly  $n$  bits.

Therefore,  $\text{fib2}(n)$  makes a *quadratic number* of bit-operations, i.e.  $O(n^2)$  bit-operations.

In Exercise #23, you will prove that the number of bit-operations done by  $\text{fib}(n)$  is  $O(n \cdot F_n)$ .

Therefore, the running time, in terms of bit-operations:

Running time of  $\text{fib}(n)$ : exponential

Running time of  $\text{fib2}(n)$ : quadratic

## Chapter 2: Divide-and-Conquer Algorithms

To solve a problem of size  $n$ :

- **Divide** the problem into subproblems, each of size  $< n$ .
- **Conquer**: Solve each subproblem recursively (and independantly of the other subproblems).
- **Combine/Merge** the solutions to the subproblems into a solution to the original problem.



## Chapter 2: Divide-and-Conquer Algorithms

To solve a problem of size  $n$ :

- **Divide** the problem into subproblems, each of size  $< n$ .
- **Conquer**: Solve each subproblem recursively (and independantly of the other subproblems).
- **Combine/Merge** the solutions to the subproblems into a solution to the original problem.

For a given problem,

- How do we divide the problem, into how many subproblems?
- How to combine/merge?

## Example: Merge Sort

To sort  $n$  numbers:

If  $n \leq 1$  : do nothing.

If  $n \geq 2$  : divide the  $n$  numbers arbitrarily into two sequences, both of size  $n/2$ , run Merge sort twice, once for each sequence.

Then merge the two sorted sequences into one sorted sequence.

## Example: Merge Sort

To sort  $n$  numbers:

If  $n \leq 1$  : do nothing.

If  $n \geq 2$  : divide the  $n$  numbers arbitrarily into two sequences, both of size  $n/2$ , run Merge sort twice, once for each sequence.

Then merge the two sorted sequences into one sorted sequence.

What is the running time?

Let  $T(n)$  be the running time of Merge Sort on an input of  $n$  numbers.

Let  $T(n)$  be the running time of Merge Sort on an input of  $n$  numbers.

From CSI-2110, we know that the merge step takes  $O(n)$  time.

Let  $T(n)$  be the running time of Merge Sort on an input of  $n$  numbers.

From CSI-2110, we know that the merge step takes  $O(n)$  time.

Hence, there is a constant  $c > 0$  such that

$$T(n) \leq \begin{cases} c & \text{if } n = 1, \\ 2T(n/2) + c \cdot n & \text{if } n \geq 2, \end{cases}$$

Let  $T(n)$  be the running time of Merge Sort on an input of  $n$  numbers.

From CSI-2110, we know that the merge step takes  $O(n)$  time.

Hence, there is a constant  $c > 0$  such that

$$T(n) \leq \begin{cases} c & \text{if } n = 1, \\ 2 T(n/2) + c \cdot n & \text{if } n \geq 2, \end{cases}$$

What do we do with this?

Let  $T(n)$  be the running time of Merge Sort on an input of  $n$  numbers.

From CSI-2110, we know that the merge step takes  $O(n)$  time.

Hence, there is a constant  $c > 0$  such that

$$T(n) \leq \begin{cases} c & \text{if } n = 1, \\ 2 T(n/2) + c \cdot n & \text{if } n \geq 2, \end{cases}$$

What do we do with this?

We solve by *unfolding*!



In general, if we do not assume anything about the value of  $c$ , we find  $T(n) \leq 2c n \log_2(n)$ .

In general, if we do not assume anything about the value of  $c$ , we find  $T(n) \leq 2c n \log_2(n)$ .

So the running time of Merge Sort is  $T(n) = O(n \log_2(n))$  if  $n$  is a power of two.

In general, if we do not assume anything about the value of  $c$ , we find  $T(n) \leq 2c n \log_2(n)$ .

So the running time of Merge Sort is  $T(n) = O(n \log_2(n))$  if  $n$  is a power of two.

For a general  $n$ , we have

$$T(n) \leq \begin{cases} c & \text{if } n = 1, \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + c \cdot n & \text{if } n \geq 2, \end{cases}$$

In general, if we do not assume anything about the value of  $c$ , we find  $T(n) \leq 2c n \log_2(n)$ .

So the running time of Merge Sort is  $T(n) = O(n \log_2(n))$  if  $n$  is a power of two.

For a general  $n$ , we have

$$T(n) \leq \begin{cases} c & \text{if } n = 1, \\ T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + c \cdot n & \text{if } n \geq 2, \end{cases}$$

By induction, we can prove that  $T(n) = O(n \log_2(n))$ .