

# Non-Euclidean High-Order Smooth Convex Optimization

**Juan Pablo Contreras\*\***

*Escuela de Ingeniería Industrial  
Universidad Diego Portales*

JUAN.CONTRERAS@UDP.CL

**Cristóbal Guzmán\***

*Institute for Mathematical and Computational Engineering  
Faculty of Mathematics and School of Engineering  
Pontificia Universidad Católica de Chile*

CRGUZMANP@MAT.UC.CL

**David Martínez-Rubio\***

*Signal Theory and Communications Department,  
Universidad Carlos III de Madrid, Spain*

DMRUBIO@ING.UC3M.ES

**Editors:** Nika Haghtalab and Ankur Moitra

## Abstract

We develop algorithms for the optimization of convex objectives that have Hölder continuous  $q$ -th derivatives by using a  $q$ -th order oracle, for any  $q \geq 1$ . Our algorithms work for general norms under mild conditions, including the  $\ell_p$ -settings for  $1 \leq p \leq \infty$ . We can also optimize structured functions that allow for inexactly implementing a non-Euclidean ball optimization oracle. We do this by developing a non-Euclidean inexact accelerated proximal point method that makes use of an *inexact uniformly convex regularizer*. We show a lower bound for general norms that demonstrates our algorithms are nearly optimal in high-dimensions in the black-box oracle model for  $\ell_p$ -settings and all  $q \geq 1$ , even in randomized and parallel settings. This new lower bound, when applied to the first-order smooth case, resolves an open question in parallel convex optimization.

## Acknowledgments

Research partially supported by ANID FONDECYT 1251029 grant, ANID FONDECYT Postdoctoral grant 3240505, National Center for Artificial Intelligence CENIA FB210017, Basal ANID, and by the Generación de Conocimiento grant PID2022-142506NA-I00.

---

. Extended abstract. Full version appears as [\[arxiv reference, 2411.08987\]](#)  
 . (\*) Equal contribution.  
 . (★) Work partially completed while at Pontificia Universidad Católica de Chile.