

# Time-Uniform, Self-Normalized Concentration for Vector-Valued Processes (Extended Abstract)

**Justin Whitehouse**  
**Zhiwei Steven Wu**  
**Aaditya Ramdas**

JWHITEHO@STANFORD.EDU  
ZSTEVENWU@ANDREW.CMU.EDU  
ARAMDAS@ANDREW.CMU.EDU

**Editors:** Nika Haghtalab and Ankur Moitra

Self-normalized processes arise naturally in many learning-related tasks, such as bandit learning (Kaufmann et al., 2016; Abbasi-Yadkori et al., 2011; Lattimore and Szepesvári, 2020) and online convex optimization (Jun and Orabona, 2019; Li and Orabona, 2020). While self-normalized concentration has been extensively studied for scalar-valued processes (Howard et al., 2020, 2021), there are few results for multivariate processes outside of the sub-Gaussian setting (de la Peña et al., 2009). In this work, we construct a general, self-normalized inequality for  $\mathbb{R}^d$ -valued processes that satisfy a simple yet broad “sub- $\psi$ ” tail condition, which generalizes assumptions based on cumulant generating functions (CGFs). We say a multivariate process  $(S_t)_{t \geq 0}$  is sub- $\psi$  with variance proxy  $(V_t)_{t \geq 0}$  if, for any  $\lambda \in \text{dom}(\psi)$  and  $\nu \in \mathbb{S}^{d-1}$ , there is a non-negative supermartingale  $(L_t^{\lambda, \nu})_{t \geq 0}$  such that

$$M_t^{\lambda, \nu} := \exp \{ \lambda \langle \nu, S_t \rangle - \psi(\lambda) \langle \nu, V_t \nu \rangle \} \leq L_t^{\lambda, \nu}, \quad \text{for all } t \geq 0.$$

As an example, if  $S_t = \sum_s X_s$  and  $\mathbb{E}_{t-1} |\langle \nu, X_t \rangle|^k \leq \frac{k!}{2} c^{k-2} \mathbb{E}_{t-1} \langle \nu, X_t \rangle^2$  for all directions  $\nu \in \mathbb{S}^{d-1}$  and some constant  $c > 0$ , one can show that  $S_t$  is sub- $\psi_{G,c}$  with variance proxy  $V_t := \sum_{s=1}^t \mathbb{E}_{s-1} X_s X_s^\top$ . Here,  $\psi_{G,c}(\lambda) = \frac{\lambda^2}{2(1-c\lambda)}$  is a bound on the CGF of a centered Gamma random variable. For a more complicated example, if  $\mathbb{E}_{t-1} \langle \nu, X_t \rangle^2 < \infty$  for all  $t$  and  $\nu \in \mathbb{S}^{d-1}$ , then one can show  $S_t$  is sub- $\psi_N$  with variance proxy  $V_t = \frac{1}{3} \sum_{s=1}^t X_s X_s^\top + \frac{2}{3} \sum_{s=1}^t \mathbb{E}_{s-1} X_s X_s^\top$ . Under the assumption that  $(S_t)_{t \geq 0}$  is sub- $\psi$  with variance proxy  $(V_t)_{t \geq 0}$ , one can show that, with high-probability

$$\|V_t^{-1/2} S_t\| \lesssim \sqrt{\gamma_{\min}(V_t)} \cdot (\psi^*)^{-1} \left( \frac{1}{\gamma_{\min}(V_t)} [\log \log(\gamma_{\max}(V_t)) + d \log \kappa(V_t)] \right) \quad (1)$$

for all  $t \geq 0$  simultaneously, where  $\psi^*$  is the convex conjugate of  $\psi$ , and  $\gamma_{\min}(V)$ ,  $\gamma_{\max}(V)$ , and  $\kappa(V)$  denote respectively the minimum eigenvalue, maximum eigenvalue, and the condition number of a matrix  $V$ . In the case  $\psi(\lambda) = \psi_N(\lambda) := \frac{\lambda^2}{2}$ , our bound becomes  $\|V_t^{-1/2} S_t\| \lesssim \sqrt{\log \log \gamma_{\max}(V_t) + d \log \kappa(V_t)}$ , which is generally incomparable to the  $O(\sqrt{\log \det(V_t)})$  rate method of mixtures bounds commonly leveraged in bandit optimization (de la Peña et al., 2009; Abbasi-Yadkori et al., 2011). In particular, when the variance proxy  $V_t$  is well-conditioned, our bound may be significantly tighter. Likewise, in the case  $\psi(\lambda) = \psi_{G,c}(\lambda)$ , our bound becomes

$$\|V_t^{-1/2} S_t\| \lesssim \sqrt{\log \log \gamma_{\max}(V_t) + d \log \kappa(V_t)} + \frac{c}{\sqrt{\gamma_{\min}(V_t)}} [\log \log \gamma_{\max}(V_t) + d \log \kappa(V_t)].$$

While we omit dependence on constants, tuning parameters, and failure probability for the sake of exposition, we note that all constants are small, and point to our main paper for a more thorough exposition.<sup>1</sup> From the general inequality in Equation (1), we derive an upper law of the iterated logarithm for sub- $\psi$  vector-valued processes that is unimprovable up to small constants. Further, we provide applications in prototypical statistical tasks, such as parameter estimation in online linear regression and bounded mean estimation via a new (multivariate) empirical Bernstein concentration inequality.

**Keywords:** Stochastic Processes, Martingales, Concentration Inequalities, Online Estimation

1. Extended Abstract. Full version available at <https://arxiv.org/abs/2310.09100v2>.

## References

- Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in Neural Information Processing Systems*, 24, 2011.
- Victor de la Peña, Tze Leung Lai, and Qi-Man Shao. *Self-normalized Processes: Limit Theory and Statistical Applications*. Springer, 2009.
- Steven R Howard, Aaditya Ramdas, Jon McAuliffe, and Jasjeet Sekhon. Time-uniform Chernoff bounds via nonnegative supermartingales. *Probability Surveys*, 17:257–317, 2020.
- Steven R Howard, Aaditya Ramdas, Jon McAuliffe, and Jasjeet Sekhon. Time-uniform, nonparametric, nonasymptotic confidence sequences. *The Annals of Statistics*, 49(2):1055–1080, 2021.
- Kwang-Sung Jun and Francesco Orabona. Parameter-free online convex optimization with sub-exponential noise. In *Conference on Learning Theory*, pages 1802–1823. PMLR, 2019.
- Emilie Kaufmann, Olivier Cappé, and Aurélien Garivier. On the complexity of best arm identification in multi-armed bandit models. *Journal of Machine Learning Research*, 17:1–42, 2016.
- Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, 2020.
- Xiaoyu Li and Francesco Orabona. A high probability analysis of adaptive SGD with momentum. *arXiv preprint arXiv:2007.14294*, 2020.