

# Estimating stationary mass, frequency by frequency

**Milind Nakul**

MNAKUL3@GATECH.EDU

*School of Industrial and Systems Engineering  
Georgia Institute of Technology  
Atlanta, USA*

**Vidya Muthukumar**

VMUTHUKUMAR8@GATECH.EDU

*Schools of Electrical and Computer Engineering  
and Industrial and Systems Engineering  
Georgia Institute of Technology  
Atlanta, USA*

**Ashwin Pananjady**

ASHWINPM@GATECH.EDU

*Schools of Industrial and Systems Engineering  
and Electrical and Computer Engineering  
Georgia Institute of Technology  
Atlanta, USA*

**Editors:** Nika Haghtalab and Ankur Moitra

## Abstract

Suppose we observe a trajectory of length  $n$  from an exponentially  $\alpha$ -mixing stochastic process over a finite but potentially large state space. We consider the problem of estimating the probability mass placed by the stationary distribution of any such process on elements that occur with a certain frequency in the observed sequence. We estimate this vector of probabilities in total variation distance, showing universal consistency in  $n$  and recovering known results for i.i.d. sequences as special cases. Our proposed methodology—implementable in linear time—carefully combines the plug-in (or empirical) estimator with a recently-proposed modification of the Good–Turing estimator called WINGIT, which was originally developed for Markovian sequences. En route to controlling the error of our estimator, we develop new performance bounds on WINGIT and the plug-in estimator for exponentially  $\alpha$ -mixing stochastic processes. Importantly, the extensively used method of Poissonization can no longer be applied in our non i.i.d. setting, and so we develop complementary tools—including concentration inequalities for a natural self-normalized statistic of mixing sequences—that may prove independently useful in the design and analysis of estimators for related problems. Simulation studies corroborate our theoretical findings.<sup>1</sup>

## Acknowledgments

This work was supported in part by the National Science Foundation through grants CCF-2107455, DMS-2210734, CCF-2239151 and IIS-2212182, and by research awards from Adobe, Amazon, and Mathworks.

## References

Milind Nakul, Vidya Muthukumar, and Ashwin Pananjady. Estimating stationary mass, frequency by frequency. *arXiv preprint arXiv:2503.12808*, 2025.

---

1. Extended abstract. Full version appears as [Nakul et al. \(2025\)](#).