

# Polynomial low degree hardness for Broadcasting on Trees (Extended Abstract)

**Han Huang**

*University of Missouri*

HHUANG@MISSOURI.EDU

**Elchanan Mossel**

*Massachusetts Institute of Technology*

ELMOS@MIT.EDU

**Editors:** Nika Haghtalab and Ankur Moitra

Broadcasting on trees is a fundamental model from statistical physics that plays an important role in information theory, noisy computation and phylogenetic reconstruction within computational biology and linguistics. While this model permits efficient linear-time algorithms for the inference of the root from the leaves, recent work suggests that non-trivial computational complexity may be required for inference.

The inference of the root state can be performed using the celebrated Belief Propagation (BP) algorithm, which achieves Bayes-optimal performance. Although BP runs in linear time using real arithmetic operations, recent research indicates that it requires non-trivial computational complexity using more refined complexity measures.

Moitra, Mossel, and Sandon demonstrated such complexity by constructing a Markov chain for which estimating the root better than random guessing (for typical inputs) is  $NC^1$ -complete. Kohler and Mossel constructed chains where, for trees with  $N$  leaves, achieving better-than-random root recovery requires polynomials of degree  $N^{\Omega(1)}$ . The papers above raised the question of whether such complexity bounds hold generally below the celebrated Kesten-Stigum bound.

The low degree method has emerged as a predictive tool for establishing computational hardness for statistical problems. This method postulate that *if all low degree functions are not good estimators, then the problem is computationally hard* see e.g. [Barak et al. \(2019\)](#); [Hopkins and Steurer \(2017\)](#); [Hopkins \(2018\)](#); [Schramm and Wein \(2020\)](#). (see also [Kunisky et al. \(2019\)](#) for a survey.)

Previously, the authors established a general degree lower bound of  $\Omega(\log N)$  below the Kesten-Stigum bound. Specifically, they proved that any function expressed as a linear combination of functions of at most  $O(\log N)$  leaves has vanishing correlation with the root. In this work, we get an exponential improvement of this lower bound by establishing an  $N^{\Omega(1)}$  degree lower bound, for any broadcast process in the whole regime below the Kesten-Stigum bound. We confirmed that the Kesten-Stigum bound is a sharp transition from feasibility via degree-1 estimators (simply counting leaf types) *above* KS to exponential-degree requirements *below* it. This result makrs the BOT model as an interesting counterexample to the “computational-hardness” belief on low-degree analysis.

## Acknowledgments

E.M. is supported by Simons-NSF collaboration on deep learning NSF DMS-2031883, Vannevar Bush Faculty Fellowship award ONR- N00014-20-1-2826, ARO MURI W911NF1910217 and a Simons Investigator Award in Mathematics (622132).

## References

- Boaz Barak, Samuel Hopkins, Jonathan Kelner, Pravesh K Kothari, Ankur Moitra, and Aaron Potechin. A nearly tight sum-of-squares lower bound for the planted clique problem. *SIAM Journal on Computing*, 48(2):687–735, 2019.
- Samuel Hopkins. *Statistical inference and the sum of squares method*. PhD thesis, Cornell University, 2018.
- Samuel Hopkins and David Steurer. Efficient bayesian estimation from few samples: community detection and related problems. In *2017 IEEE 58th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 379–390. IEEE, 2017.
- Dmitriy Kunisky, Alexander S Wein, and Afonso S Bandeira. Notes on computational hardness of hypothesis testing: Predictions using the low-degree likelihood ratio. *arXiv preprint arXiv:1907.11636*, 2019.
- Tselil Schramm and Alexander S Wein. Computational barriers to estimation from low-degree polynomials. *arXiv preprint arXiv:2008.02269*, 2020.