
Learning Randomized Reductions

Ferhat Erata¹ Orr Paradise² Thanos Typaldos¹ Timos Antonopoulos¹ ThanhVu Nguyen³
Shafi Goldwasser⁴ Ruzica Piskac¹

Abstract

Randomized self-reductions (RSRs) express $f(x)$ using f evaluated at random correlated points, enabling self-correcting programs, instance-hiding protocols, and applications in complexity theory and cryptography. Yet discovering RSRs has required manual expert derivation for over 40 years, limiting their practical use. We present Bitween for automated RSR learning. First, we formalize RSR learning with sample complexity analysis under correlated sampling. Second, we develop Vanilla Bitween, which integrates multiple backends (linear regression, genetic programming, symbolic regression, and mixed-integer programming). The linear regression backend outperforms the others, discovering RSRs for 43 of 80 functions (54%) in RSR-Bench, our benchmark suite, including the first known reduction for sigmoid. Third, we introduce Agentic Bitween, a neuro-symbolic approach where LLM agents propose novel query functions beyond the fixed set $(x + r, x - r, x \cdot r, x, r)$ in prior work. Agentic Bitween discovers RSRs for 64 of 80 functions (80%), outperforming pure neural baselines in both RSR discovery and verification accuracy.

1. Introduction

Random self-reducibility was first defined by Goldwasser & Micali (1984) in the context of worst-case to average-case reductions to show that concrete encryption schemes were hard on the average to break if the underlying problem was hard in the worst case. In subsequent work, Blum et al. (1993) introduced self-correcting programs, showing that a *self-corrector* can transform a program correct on most inputs into one correct on every input with high probability, using only black-box access. Such self-correctors exist for

any *randomly self-reducible* (RSR) function, where $f(x)$ can be recovered by computing f on random correlated points. RSRs have found applications in cryptography protocols (Goldwasser & Micali, 2019), average-case complexity (Feigenbaum & Fortnow, 1993), instance hiding (Abadi et al., 1987), result checkers (Blum et al., 1993), and interactive proof systems (Blum & Kannan, 1995; Goldwasser et al., 2019).

Yet for over four decades since Goldwasser and Micali’s original work, discovering RSR properties has remained a manual, expert-driven process. Previous work (Blum et al., 1993; Rubinfeld, 1999) required manual derivation by experts, and existing methods are limited to a handful of fixed query functions: $x + r$, $x - r$, $x \cdot r$, x , and r . This severely restricts discoverable RSRs, as many functions require sophisticated patterns involving derivatives, integrals, or domain-specific transformations. The core challenge is to construct a hypothesis space with the right query functions and algebraic relationships that enable the reduction.

We present BITWEEN¹ for automated RSR learning. Our approach samples programs on random values, uses regression with heuristics, attempts to find self-reductions, and formally verifies results. BITWEEN has two variants: Vanilla Bitween (V-BITWEEN) integrates different regression backends within the traditional fixed query functions setting, while Agentic Bitween (A-BITWEEN) integrates large language models with V-BITWEEN tools to dynamically discover novel query functions beyond the fixed set. On RSR-BENCH, our benchmark of 80 scientific and machine learning functions, V-BITWEEN demonstrates that the linear regression-based backend outperforms alternative backends including genetic programming (GPLEarn (Stephens, 2015)), symbolic regression (PySR (Cranmer, 2023)), and mixed-integer programming (Gurobi (Gurobi Optimization, LLC, 2026)) for RSR discovery, while A-BITWEEN discovers new RSR properties producing fewer false positives than pure neural approaches.

This work makes five key contributions: (1) introduces a rigorous theoretical framework for learning randomized self-reductions with formal definitions and sample com-

¹Yale University, USA ²EPFL, Switzerland ³George Mason University, USA ⁴UC Berkeley, USA. Correspondence to: Ferhat Erata <ferhat.erata@yale.edu>.

¹Code: <https://github.com/ferhaterata/learning-randomized-reductions>

plexity analysis; (2) builds V-BITWEEN, a regression-based pipeline integrating multiple symbolic backends, and demonstrates that its linear-regression backend is more suitable than the other backends with fixed query functions; (3) builds A-BITWEEN, a neuro-symbolic variant in which an LLM agent drives V-BITWEEN’s tools and proposes novel query functions beyond the standard set; (4) creates RSR-BENCH, a comprehensive benchmark of 80 scientific and machine-learning functions across 8 categories (basic arithmetic, exponential, logarithmic, trigonometric, hyperbolic, inverse trigonometric, machine-learning activations, and special mathematical functions), drawn from the self-testing literature and functional-equation theory; and (5) demonstrates that the framework generalizes beyond scalar functions to non-scalar algebraic structures (matrices, quaternions, octonions, Clifford and Lie algebras), with no architectural changes.

Conflict of Interest Disclosure. The authors declare no financial or non-financial conflicts of interest related to this work.

2. Motivating Example

In this section we illustrate the use of randomized self-reductions (RSR) and how BITWEEN computes them on the example of the sigmoid function, $\sigma(x) = 1/(1 + e^{-x})$. The sigmoid function is commonly used in neural networks (Han & Moraga, 1995). The program $\Pi(x)$ given in Figure 1 approximates the $\sigma(x)$ by using a Taylor series expansion. Here, Π denotes the implementation of sigmoid function σ . Clearly, $\Pi(x)$ computes only an approximate value of $\sigma(x)$. We invoked BITWEEN on Π and it derived the following RSR (using the linear regression-based backend):

$$\sigma(x) = \frac{\sigma(x+r)(\sigma(r)-1)}{2\sigma(x+r)\sigma(r) - \sigma(x+r) - \sigma(r)} \quad (1)$$

where r is some random value. We verified that indeed the sigmoid function satisfies Equation (1). To the best of our knowledge, this is the first known RSR for the sigmoid function. In this example, BITWEEN inferred this RSR with 15 independent and random samples of x and r . In the plot in Figure 1, we depict the value of $\Pi(x)$, identified on the graph with $\blacktriangle$, and the values of $\Pi(x+r)$, $\Pi(x-r)$ and $\Pi(r)$, shown on the graph with $\bullet$, $\blacksquare$ and $\star$. Notice that all $\blacktriangle$ ’s are lying on the line depicting $\sigma(x)$.

Moreover, our derived RSR computes $\sigma(x)$ by using only $\sigma(x+r)$ and $\sigma(r)$, although the algorithm of BITWEEN is computing Π on random (yet correlated) inputs $x+r$, $x-r$, and r . The learned RSR in Equation (1) can be used to compute the value of $\Pi(x)$ at any point x by evaluating $\Pi(x+r)$ and $\Pi(r)$. Since $\Pi(x) \neq \sigma(x)$ for some values of x , randomized reductions can be used to construct self-

correcting programs (Tomba & Woll, 1987; Blum et al., 1993; Rubinfeld, 1994).

The RSR in Equation (1) can also be used in an instance hiding protocol (Abadi et al., 1987). As an illustration, if a weak device needs to compute σ on its private input x , it can do that by sending computing requests to two powerful devices that do not communicate with each other: the first powerful device computes $\sigma(r)$ with random r , and the second powerful one computes $\sigma(x+r)$. After receiving their outputs, the weak device can compute $\sigma(x)$ by evaluating Equation (1).

Additionally, in this particular case the derived RSR can be used to reduce the computation costs. If a weak device computes the value of $\sigma(r)$ beforehand and stores it as some constant C , then the computation of $\sigma(x)$ simplifies to $\frac{\sigma(x+r)(C-1)}{2\sigma(x+r)C - \sigma(x+r) - C}$. While x is a double, $x+r$ might require less precision.

3. Related Work

Symbolic Regression as Computational Backend. Symbolic regression discovers mathematical expressions from data without assuming functional forms, using approaches ranging from genetic programming (Koza, 1992; Cranmer, 2023; Stephens, 2015), physics-inspired methods (Udrescu & Tegmark, 2020; Udrescu et al., 2020), to neural approaches (Petersen et al., 2021). Recent advances include RAG-SR (Zhang et al., 2025) (retrieval-augmented generation), ParFam (Scholl et al., 2025) (neural-guided continuous optimization), and MetaSymNet (Li et al., 2025) (adaptive tree-like networks).

Our task differs fundamentally: rather than discovering expressions from data, we seek randomized self-reduction properties for *known* mathematical functions. We use symbolic regression methods as computational backends; V-BITWEEN employs them within our regression-based learning framework to discover polynomial relationships among correlated query evaluations, while A-BITWEEN uses the inference and verification tools of V-BITWEEN with novel query functions. Within this framework, linear regression backend outperforms genetic programming (Stephens, 2015), symbolic regression (Cranmer, 2023), and MILP (Cozad & Sahinidis, 2018; Austel et al., 2017) backends. These methods often timeout or produce approximations insufficient for RSR verification. We also integrated recent methods (Zhang et al., 2025; Scholl et al., 2025; Li et al., 2025) as backends, but they did not perform reliably under our constraints (see Section 5); more systematic hyperparameter tuning may enable their use in future work.

Mathematical Discovery and Neuro-Symbolic Learning. Automated mathematical discovery dates back to AM (Lenat,

```

1 double Π(double x) {
2     const int trms = 30;
3     double sum = 1.0;
4     double trm = 1.0;
5     double neg_x = -x;
6     for (int n = 1; n < trms; n++) {
7         trm *= neg_x / n;
8         sum += trm;
9     }
10    return 1.0 / (1.0 + sum);
11 }
    
```




Figure 1. An approximate implementation of the sigmoid activation function used as oracle and a graph representing randomly selected points by BETWEEN which are then used to discover an RSR.

1976) and EURISKO (Lenat, 1983), with recent systems like the Ramanujan Machine (Raayoni et al., 2021) discovering mathematical constants and MathConcept (Davies et al., 2021) guiding mathematical intuition. Neural-symbolic integration has produced systems like Neural Module Networks (Andreas et al., 2016) and Neurosymbolic Programming (Chaudhuri et al., 2021). Recent LLM-based systems (GPT-4 (OpenAI, 2024), Claude (Anthropic, 2024), Llemma (Azerbayev et al., 2024)) demonstrate strong mathematical reasoning but suffer from hallucination. Our Agentic Between uniquely uses LLMs to discover novel query functions validated through symbolic regression, combining neural creativity with formal verification.

Self-Correcting Algorithms and Property Inference. The theoretical foundations of randomized self-reductions were established by Blum et al. (Blum et al., 1990; Lipton, 1991; Blum et al., 1993), showing that RSR properties enable self-correction for faulty programs. While program property inference tools like Daikon (Ernst et al., 2007) and DIG (Nguyen et al., 2012; 2021) discover invariants dynamically, they focus on program properties rather than mathematical functions and do not discover randomized reductions. Our work provides the first practical system for discovering RSRs, operationalizing decades-old theoretical results with a learning framework that goes beyond existing tools.

4. Theoretical Foundations

In this section, we give a definitional treatment of learning randomized self-reductions (RSRs). Our goal is to rigorously define the setting in which BETWEEN resides, which may be of independent interest for future theoretical work. Throughout this section, we will say that a set Z is *uniformly-samplable* if it can be equipped with a uniform distribution; we let $z \sim Z$ denote a uniformly random sample from Z .

We start from a definition of randomized self-reductions (Goldwasser & Micali, 1984). Our presentation takes after Lipton (1989) and Goldreich (2017), modified for convenience.

Definition 4.1 (Randomized self-reduction). Fix a uniformly-samplable *input domain* X , a *range* Y , and uniformly-samplable *randomness domain* R . Let $f: X \rightarrow Y$; $q_1, \dots, q_k: X \times R \rightarrow X$ (query functions); and $p: X \times R \times Y^k \rightarrow Y$ (recovery function) such that for all $i \in [k]$ and $x \in X$, $u_i := q_i(x, r)$ is distributed uniformly over X when $r \sim R$ is sampled uniformly at random.²

We say that $(q_1, \dots, q_k, r)$ is a (*perfect*) *randomized self-reduction (RSR)* for f if for all $r \in R$, letting $u_i := q_i(x, r)$ for all $i \in [k]$, the following holds:

$$f(x) = p(x, r, f(u_1), \dots, f(u_k)). \quad (2)$$

In other words, Equation (2) holds with probability 1 over randomly sampled $r \sim R$. For errors $\rho, \xi \in (0, 1)$, we say that $(q_1, \dots, q_k, p)$ is a (ρ, ξ) -*approximate randomized self-reduction* ((ρ, ξ) -RSR) for f if, for all but a ξ -fraction of $x \in X$, Equation (2) holds with probability $\geq 1 - \rho$ over the random samples $r \sim R$. That is, writing $\tilde{f} = p(x, r, f(u_1), \dots, f(u_k))$ where $u_i := q_i(x, r)$:

$$\Pr_{x \sim X} \left[\Pr_{r \sim R} [f(x) = \tilde{f}] \geq 1 - \rho \right] \geq 1 - \xi.$$

Given a class of query functions $Q \subseteq X^{X \times R}$ and recovery functions $P \subseteq Y^{X \times R \times Y^k}$, we let $\text{RSR}_k(Q, P)$ denote the class of functions $f: X \rightarrow Y$ for which there exist $q_1, \dots, q_k \in Q$ and $p \in P$ such that f is perfectly RSR with $(q_1, \dots, q_k, p)$. We write $\text{RSR}(Q, P)$ when the number of queries is irrelevant.

In the literature (Lipton, 1989; Goldreich, 2017), the query functions are defined as randomized functions of the input

²Importantly, the u_i ’s must only satisfy *marginal uniformity*, but may be correlated among themselves.

x to be recovered. That is, as random variables $\tilde{q}_i(x) \sim X$ rather than our deterministic $q_i(x, r) \in X$. The definitions are equivalent; we simply make the randomness in $\tilde{q}_i$ explicit by giving it r as input. This choice will have two benefits: (1) It makes explicit the amount of random bits used by the self-reduction, namely, $\log_2 |R|$. (2) It lets us think about the query functions as deterministic. This could allow one to relate traditional complexity measures (e.g., VC dimensions) of the function classes Q and P to those of the function f .

To elaborate more on the second point, let us restrict the discussion to polynomials over finite fields, i.e., $f: \mathbb{F}_n^m \rightarrow \mathbb{F}_n$ for some $n \in \mathbb{N}$. Lipton (1989) showed that even extremely simple choices of Q and P can be very expressive.

Fact 4.2 (Lipton, 1989). Any m -variate polynomial $f: \mathbb{F}_\ell^m \rightarrow \mathbb{F}_\ell$ of degree $d < \ell - 1$ is perfectly randomly self-reducible with $k = d + 1$ queries and randomness domain $R = \mathbb{F}_\ell^m$. Furthermore, the queries $q_1, \dots, q_{d+1}: \mathbb{F}_\ell^{2m} \rightarrow \mathbb{F}_\ell^m$ and recovery function $p: \mathbb{F}_\ell^{2m+d+1} \rightarrow \mathbb{F}_n$ are linear functions.

The question of interest is whether, given access to samples from $f \in \text{RSR}_k(Q, P)$, it is possible to learn an (approximate) RSR for f . Before we can continue, we must first specify how these samples are drawn. Typically, learners are either given input-output pairs $(x, f(x))$ where x 's are either *independent random samples*, or chosen by the learner herself. Learning RSRs will occur in an intermediate access type, in which x 's are drawn in a correlated manner. We formally define these access types next. Our presentation is based on that of O'Donnell (2014), who, like us, is focused on samples drawn from the uniform distribution. We note that learning from uniformly random samples has been studied extensively in the literature (Verbeurgt, 1990; Hancock, 1993; Kucera et al., 1994; Golea et al., 1996; Jackson et al., 2002; Klivans et al., 2004; Jackson & Servedio, 2006).

Definition 4.3 (Sample access). Fix a uniformly-samplable set X , function $f: X \rightarrow Y$ and a probabilistic algorithm Λ that takes as input m (labeled) samples from f . We consider three types of *sample access* to f : (1) *Independent random samples*: Λ is given $(x_j, f(x_j))_{j=1}^m$ for independent and uniformly sampled $x_j \sim X$. (2) *Correlated random samples*: Λ is given $(x_j, f(x_j))_{j=1}^m$ drawn from a distribution such that, for each $j \in [m]$, the marginal on x_j is uniformly random over X . However, different x_j 's may be correlated. (3) *Oracle queries*: During Λ 's execution, it can request the value $f(x)$ for any $x \in X$. The type of sample access will be explicitly stated, unless clear from context.

Remark 4.4. Facing forward, we note that more restrictive access types will correspond to more challenging settings of learning (formally defined in Definition 4.5). Intuitively (and soon, formally), if F is learnable from m independent samples, it is also learnable from m correlated samples, and

m oracle queries as well.

Learning from correlated samples is one of two main theoretical innovations introduced in this work (the other will appear shortly). We note that PAC learning (Valiant, 1984) requires learning under *any* distribution μ of inputs over X , whereas we consider learning only when samples are drawn from the uniform distribution over X (with possible correlation). Learning from correlated samples could be adapted to arbitrary distributions μ by considering correlated samples $(x_j, f(x_j))_j$ such that the marginal on each x_j is distributed according to μ . This interesting setting is beyond the scope of this work.

Finally, for an input x we will use $n = |x|$ to denote its length. This will allow us to place an *efficiency requirement* on the learner (e.g., polynomial time in n). For a class of functions F from inputs X to outputs Y , we will use F_n to denote the class restricted to inputs of length n , and similarly we let Q_n (resp. P_n) denote the restriction of the query (resp. recovery) class.³

Definition 4.5 (Learning RSR). Fix a reduction class $(Q, P) = (\bigcup_n Q_n, \bigcup_n P_n)$ and a function class $F = \bigcup_n F_n$ where $F_n \subseteq \text{RSR}_k(Q_n, P_n)$ for some constant $k \in \mathbb{N}$.⁴ A (Q, P, k) -learner Λ for F is a probabilistic algorithm that is given inputs $n \in \mathbb{N}$ and m samples of $f \in F_n$, collected in one of the three ways defined in Definition 4.3. Λ outputs query functions $q_1, \dots, q_k \in Q_n$ and a recovery function $p \in P_n$.

We say F is (Q, P) -RSR $_k$ -learnable if there exists a (Q, P, k) -learner Λ such that for all $f \in F$ and $\rho, \xi, \delta \in (0, 1)$, given $m := m(\rho, \xi, \delta)$ labeled samples from f , with probability $\geq 1 - \delta$ over the samples and randomness of Λ , Λ outputs $q_1, \dots, q_k \in Q$ and $p \in P$ that are (ρ, ξ) -RSR for f .

We say that F is *efficiently* (Q, P) -RSR $_k$ -learnable if Λ runs in time $\text{poly}(n, 1/\rho, 1/\xi, 1/\delta)$. The function $m(\rho, \xi, \delta)$ is called the *sample complexity* of the learner Λ . We will omit the (Q, P) prefix when it is clear from context.

Definition 4.5 takes after the classic notion of Probably Approximately Correct (PAC) learning (Valiant, 1984) in that it allows the learner a δ failure probability, and asks that the learned $q_1, \dots, q_k, r$ only approximately recover f . The main difference is that in Definition 4.5, Λ is required to output an approximate RSR for f , whereas in PAC learning it is required to output a function $\hat{f} \in F$ that approximates f itself; that is, such that $\hat{f}(x) = f(x)$ with high probability over $x \sim X$.

³This slight informality will allow us to avoid encumbering the reader with a subscript n throughout the paper.

⁴The requirement that $F_n \subseteq \text{RSR}_k(Q_n, R_n)$ is a *realizability assumption*. We leave the agnostic setting, in which $F_n \not\subseteq \text{RSR}_k(Q_n, R_n)$, to future work.

For a detailed comparison between RSR learning and PAC learning, including claims about their relative strengths and sample complexity relationships, see Claim A.1 and Claim A.2, and their proofs in the theory appendix. The Fundamental Theorem of Learning states that sample complexity of PAC-learning is tightly characterized by the VC-dimension of the function class F ; it is an open question to obtain an analogous Fundamental Theorem of RSR-Learning, which relates the sample complexity to “intrinsic” dimensions of Q , P , and $F \subseteq \text{RSR}(Q, P)$.

5. BITWEEN: Learning Randomized Self-Reductions

Algorithm Overview. BITWEEN expects correlated sample access to a program Π which is an alleged implementation of some unknown function f . The goal is to learn an RSR for f following our theoretical framework (Definition 4.5). BITWEEN is given the input domain X , the class of query functions Q , and recovery function degree bound d . At a high level, BITWEEN works as follows: (i) generate all monomials of degree $\leq d$ over symbolic variables $\Pi(q(x, r))$ for each query function $q \in Q$; (ii) construct a linear regression problem with a regressand for each monomial; (iii) query $\Pi(x_i)$ and $\Pi(q(x_i, r_i))$ for random $x, r \in X$; (iv) fit the regressands to the samples using sparsifying linear regression, thereby eliminating most monomials; (v) apply rational approximation to convert floating-point coefficients to interpretable rational forms. Algorithm 1 provides the complete algorithm description.

Regression Formulation and Loss Function. Bitween formulates RSR discovery as a supervised learning problem by treating each query function $q \in Q$ as a potential target variable. For each query q , we construct a regression problem where $\Pi(q(x_i, r_i))$ serves as the dependent variable and the monomials $V(x_i, r_i)$ over all query evaluations serve as features. The loss function for a given target query q is (writing $\Pi_i = \Pi(q(x_i, r_i))$ and $V_i = V(x_i, r_i)$):

$$\mathcal{L}_q(\mathbf{C}) = \frac{1}{m} \sum_{i=1}^m \left(\Pi_i - \sum_{V \in \mathcal{M}} C_V V_i \right)^2 + \lambda R(\mathbf{C})$$

where $\lambda > 0$ is the regularization parameter (selected via grid search), and $R(\mathbf{C}) = \|\mathbf{C}\|_1$ for Lasso or $R(\mathbf{C}) = \|\mathbf{C}\|_2^2$ for Ridge. Sparsification proceeds iteratively: after initial regression, monomials with coefficients below threshold are eliminated, and regression is repeated on reduced space until convergence. The optimization problem:

$$\hat{\mathbf{C}}_q = \arg \min_{\mathbf{C}} \mathcal{L}_q(\mathbf{C})$$

The term “modulo regression” in Algorithm 1’s caption reflects that the regression step (line 6) can use any backend. This modularity enables comparing optimization paradigms.

Algorithm 1 V-BITWEEN modulo regression

```

1: Input: Program  $\Pi$ , query class  $Q$ , recovery function degree bound  $d$ , input
   domain  $X$ , sample complexity  $m$ .
2: Output: Randomized self-reduction  $(q_1, \dots, q_k, p)$  or empty_tuple.
3:
4: For each query function  $q \in Q$ , initialize a variable  $v_q$ . //  $v_q$  for  $\Pi(q(x, r))$ 
5: Let  $\text{MON}$  be all monomials of degree at most  $d$  over the variables  $(v_q)_{q \in Q}$ .
6: For each monomial  $V \in \text{MON}$ , initialize the regressand  $C_V$ .
7: For each  $i \in [m]$ , sample input  $x_i \in X$  and randomness  $r_i \in X$ .
8: Query  $\Pi$  for the values  $\Pi(x_i)$  and  $\Pi(q(x_i, r_i))$  for each  $q \in Q$ .
9:
10: // We will fit  $\Pi(x) = \sum_V C_V \cdot V(x, r)$ 
11: Using sparsifying linear regression fit the regressands  $C_V$  to the equations


$$\Pi(x_1) = \sum_{V \in \text{MON}} C_V \cdot V(x_1, r_1), \dots, \Pi(x_m) = \sum_{V \in \text{MON}} C_V \cdot V(x_m, r_m)$$


12: // Convert to rationals
13: Let  $\widehat{C}_V$  denote the fitted regressands. Apply rational approximation to con-
   vert each fitted coefficient  $\widehat{C}_V$  to its best rational form  $\widehat{C}_V$  using maximum
   denominator constraint.
14:
15: Initialize an empty set of query functions  $\widehat{Q} \leftarrow \emptyset$ .
16: for each  $V \in \text{MON}$  do
17:   if  $\widehat{C}_V \neq 0$  then
18:     Add to  $\widehat{Q}$  all queries  $q$  such that the var  $v_q$  appears in the monomial  $V$ .
19:   end if
20: end for
21: Let  $(\widehat{q}_1, \dots, \widehat{q}_k) \leftarrow \widehat{Q}$  where  $k = |\widehat{Q}|$ . For each  $\widehat{q}_i$ , let  $\widehat{v}_i$  denote its
   corresponding variable defined in Section 5. Define the recovery function,


$$\widehat{p}(x, r, \widehat{v}_1, \dots, \widehat{v}_k) := \sum_{V: \widehat{C}_V \neq 0} \widehat{C}_V \cdot V(x, r).$$


22: return the randomized self-reduction  $(\widehat{q}_1, \dots, \widehat{q}_k, \widehat{p})$  or empty_tuple.
    
```

Key Technical Components. The implementation utilizes several involved components detailed in Section D. We first perform *supervised learning conversion* to transform the unsupervised RSR discovery problem into supervised regression, followed by *cross-validation* using grid search with 5-fold cross-validation for hyperparameter optimization. *Sparsification* through iterative dimensionality reduction eliminates irrelevant terms, while *rational approximation* converts floating-point coefficients to interpretable rational forms. Lastly, we verify the discovered properties using the simplification method of SymPy (Meurer et al., 2017) after converting them to zero-valued equations. The complexity analysis shows that for low-degree polynomials, BITWEEN operates in polynomial time $O(t_{\text{terms}} \times n_{\text{samples}} \times n_{\text{features}}^2)$, though the exponential growth of monomials with some degree necessitates careful *degree* and *query* selection in practice.

Experimental Framework. Our evaluation encompasses three distinct approaches to RSR discovery. The first is Vanilla Bitween (V-BITWEEN), our core symbolic-regression-based learning framework. Within the fixed query function paradigm, we integrate and compare the following backends: a multiple-linear regression backend utilizing Linear Regression, Ridge and Lasso (V-BITWEEN-LR), a mixed-integer linear programming backend using the Gurobi solver (Gurobi Optimization, LLC, 2026) (V-

BETWEEN-MILP), the PySR tool (Cranmer, 2023) that uses evolutionary algorithms for symbolic regression (V-BETWEEN-PySR), and the GPLearn tool (Stephens, 2015) that uses genetic programming (V-BETWEEN-PySR) for symbolic regression. We also integrated three recent backends, but could not make them work successfully, thus we do not include them in the evaluation. The first tool, RAG-SR (Zhang et al., 2025), for the hyper-parameters we tried either returned very long properties that we discard or timed out. The second, MetaSymNet (Li et al., 2025), was crashing in all benchmarks due to NumPy shape alignment errors. The last one, ParFam (Scholl et al., 2025), did return some verified properties, but only in 4/80 benchmarks and timed out in the rest. We leave for future work a more systematic hyper-parameter search that can potentially make those tools work under our constraints and time limits.

The second is Agentic Between (A-BETWEEN) representing our Neuro-Symbolic approach where large language models dynamically propose novel query functions beyond the fixed set $\{x + r, x - r, x \cdot r, x, r\}$ that in turn lead to new properties. The LLM agents are queried only once with the goal of discovering as many verified properties of the function of interest as possible. For this cause, they have in their disposal, aside from their mathematical knowledge, the following three tools. The first is the *symbolic_verify_tool* (Section F.2.2) that can be used to verify if a property equals to zero using the simplification method of SymPy (Meurer et al., 2017). The second is the *infer_property_tool* (Section F.2.1) that can select different V-BETWEEN backends (V-BETWEEN-LR is the default) to provide with functional terms in order to infer new properties. The provided functional terms correspond to the variables v_q of Algorithm 1 that implicitly encapsulate the query functions. For instance, if f is the function of interest, then the LLM agent can propose the functional term $f(x^r)$, in which case the corresponding query function is x^r . The third tool, *sequential_thinking_tool* (Model Context Protocol Community, 2024), allows the LLM agent to journal its thoughts, something that was empirically found useful for increasing the other tools’ usage and enhancing its overall response.

The last approach is Neural Research (N-RESEARCH), which is pure neural and serves as a comparison baseline for A-BETWEEN. It uses LLM agents with access only to the *sequential_thinking_tool*, because it enhances their exploration. Comparing this approach with A-BETWEEN highlights the importance of the other two tools in the RSR discovery task.

6. Empirical Evaluation

We evaluate Between on RSR-Bench, a benchmark suite of 80 mathematical functions spanning scientific computing




Figure 2. Performance heatmap of average verified RSRs across mathematical function categories. The dotted red line represents the boundary from symbolic to neural methods.

and machine learning applications. Our evaluation validates the two key contributions outlined in Section 1, namely that V-BETWEEN-LR is more suitable for RSR-bench with fixed query functions, and that A-BETWEEN discovers novel query functions.

RSR-Bench Benchmark Suite. We constructed RSR-Bench comprising 80 continuous real-valued functions from diverse mathematical domains: basic arithmetic (linear, squared, cube), exponential and logarithmic functions, trigonometric and hyperbolic functions, inverse trigonometric functions, machine learning activation functions (sigmoid, ReLU, GELU, etc.), loss functions, and special mathematical functions (gamma, error function, Gudermannian). Some benchmarks include ground-truth RSR properties with minimal query complexity, sourced from self-testing literature (Blum et al., 1993; Rubinfeld, 1999) and functional equation theory (Aczél, 1966; Kannappan, 2009).

Configuration. Experiments were conducted on a MacBook Pro with 32GB memory and Apple M1 Pro 10-core CPU. For trigonometric, hyperbolic, and exponential functions, we configured term generation up to degree 3; for others, degree 2. We used uniform sampling in $[-10, 10]$ with error bound $\delta = 0.001$. Each experiment was repeated 5 times for statistical significance with timeout of 1800 sec. For the LLMs we used GPT-OSS-120B (OpenAI, 2025) locally, and Claude-Sonnet-4 (Anthropic, 2025), Claude-Opus-4.1 (Anthropic, 2024)) remotely.

Aggregate Results. Table 1 shows aggregate information about the performance of different methods. The `results` category consists of the number of RSR, verified and unverified properties found by each method, while the `rsr`

Table 1. Aggregate evaluation information about the different methods. The format of results is "RSR/verified|unverified", where the verified (unverified) properties passed (failed) automatic mathematical validation, and the RSR properties are a manually confirmed subset of the verified ones. The coverage information shows the (rounded) percentage of benchmarks for which the method returned at least one RSR. The format of time is "min|average|max" to show the (rounded) runtime range of each method. Highlighted are the methods with the most RSR count, most RSR coverage and least average runtime.

V-BITWEEN	PySR	GPLearn	MILP	LR
results	61 / 61 60	48 / 48 54	74 / 74 29	87 / 87 46
rsr coverage	38%	32%	51%	54%
time (sec)	113 335 956	0 140 629	0 11 47	0 5 19
N-RESEARCH		GPT-OSS-120B	Claude-Sonnet-4	Claude-Opus-4.1
results		170 / 360 112	191 / 421 153	250 / 539 172
rsr coverage		62%	60%	64%
time (sec)		5 10 25	56 110 203	197 286 528
A-BITWEEN		GPT-OSS-120B	Claude-Sonnet-4	Claude-Opus-4.1
results		157 / 407 148	293 / 729 14	793 / 1628 26
rsr coverage		59%	66%	80%
time (sec)		6 30 252	94 160 274	221 378 900




Figure 3. A-BITWEEN’s intensive tool usage across all the benchmarks. Particularly useful proved the *sequential_thinking_tool* for guiding the exploration and helping the LLM agent.

coverage shows the percentage of the benchmarks, for which each method found at least one RSR. Also, runtime information is included and specifically the minimum, average and maximum values aggregated over all the benchmarks for each method. For each of the tree categories, the best scores among similar methods are highlighted, based on the highest RSR count, on the highest RSR coverage and on the least average runtime, respectively. Note that the RSRs of the neural methods are always less than half of the verified properties, since we manually filtered a large portion of trivial, redundant, or simply non-RSR properties, but we might still have missed some. Among the symbolic backends, V-BITWEEN-LR scores higher in all categories, while V-BITWEEN-MILP follows. Interestingly, it also returns more unverified properties than the latter. V-BITWEEN-PySR seems to be the slowest (possibly due to our selected hyper-parameters). However, the verified properties here are always RSRs, because we provided the methods with the appropriate terms. Looking, at the N-RESEARCH methods, N-RESEARCH-Claude-Opus-4.1 has the most RSRs and highest coverage, but the fastest among them is N-RESEARCH-GPT-OSS-120B, due to local inference. The similar situation holds for the A-BITWEEN

methods as well. Notice the big difference in the results of the neural methods compared to the symbolic ones. A-BITWEEN-Claude-Opus-4.1 has found 3 times more RSRs than N-RESEARCH-Claude-Opus-4.1, which has found 6 times more RSRs than V-BITWEEN-LR. The coverage as well as the runtime keep increasing as expected. Lastly, the significantly fewer unverified properties of A-BITWEEN compared to N-RESEARCH methods highlight the effect of the *symbolic_verify_tool* that tries to prevent the LLM from returning a non-verified property as an answer. Per-function results for all methods are tabulated in Tables 8 and 9 (V-BITWEEN) and Tables 10 to 15 (N-RESEARCH/A-BITWEEN with GPT-OSS-120B, Claude-Sonnet-4, and Claude-Opus-4.1).

Results per function category. In order to provide more insight into the difficulty of RSR discovery among categories of functions we grouped several benchmarks together and created 8 categories (details in Section G). For each method we calculated how many RSRs found per category as shown in the heatmap of Figure 2 with darker color representing higher counts. The red dotted line shows the boundary between the symbolic and neural methods. The

Table 2. Novel query functions discovered by Agentic Bitween beyond traditional fixed query functions $\{x + r, x - r, x \cdot r, x, r\}$. The query functions appear inside functional terms. For example, the functional term $f(x + \log(k))$ has query function $x + \log(k)$. All properties have been symbolically verified. The right column lists RSRs A-BITWEEN discovers via novel queries (e.g., $\log k$, $\sqrt{x^2 + y^2}$) or non-polynomial form (radicals, rational compositions, transcendental exponents).

Function	Fixed-query RSRs	Novel-query RSRs (A-BITWEEN)
Sigmoid	$f(x) - \frac{f(x+r)(f(r)-1)}{2f(x+r)f(r)-f(x+r)-f(r)} = 0$	$f(x + \log(k)) - \frac{k \cdot f(x)}{1+(k-1) \cdot f(x)} = 0 \mid f(nx) - \frac{f^n(x)}{(1-f(x))^n + f^n(x)} = 0$
Logarithm	$f(x \cdot y) - f(x) - f(y) = 0$	$f(x^n) - n \cdot f(x) = 0 \mid f(\sqrt{x \cdot y}) - \frac{f(x)+f(y)}{2} = 0$
Modulo	$f(x+r) = f(x) +_R f(r)$	$f(x+y) - f(f(x) + f(y)) = 0 \mid f(x \cdot y) - f(f(x) \cdot f(y)) = 0$
Gudermannian	<i>no RSR found</i>	$\tan(f(x+r)) + \tan(f(x-r)) - 2 \cosh(r) \tan(f(x)) = 0$
Softmax	$f(x+r, y+r) - f(x, y) = 0$	$f(x, y) f(y, z) f(z, x) - f(x, z) f(z, y) f(y, x) = 0$
Inverse	$f(x \cdot y) - f(x)f(y) = 0$	$f(rx) - f^2(x) \cdot f(\frac{r}{x}) = 0$
e^{x^2} (Gaussian)	<i>no RSR found</i>	$f(x) f(y) - f(\sqrt{x^2 + y^2}) = 0$
Sinh	$f(x)^2 - f(x+y)f(x-y) - f(y)^2 = 0$	$f(x+y) + f(x-y) - 2\sqrt{f(y)^2 + 1} f(x) = 0$
$e^{\sin x}$	<i>no RSR found</i>	$f(x-r) f(x+r) - f(x)^{2 \cos r} = 0$

heatmap is mostly aligned with the results of Table 1 showing that the neural methods return more RSRs on average than the symbolic ones. The interesting new information is that there are categories, which are difficult for all methods, such as inverse trigonometric and logarithmic functions, and even more for the symbolic methods that fail completely in the former ones (per-function counts in Tables 8 and 9). Additionally, the heatmap shows that the different V-BITWEEN methods seem to excel in different categories: V-BITWEEN-PySR in trigonometric and hyperbolic, V-BITWEEN-GPLearn in exponential, V-BITWEEN-MILP in hyperbolic, and V-BITWEEN-LR in the basic and machine learning categories. On the other hand regarding the neural methods, the A-BITWEEN variants almost always find more RSRs than their N-RESEARCH counterparts, highlighting again the importance of V-BITWEEN tools.

Novel Query Functions. A-BITWEEN’s ability to discover novel query functions beyond the traditional fixed set $\{x + r, x - r, x \cdot r, x, r\}$ is a key factor for finding more properties (including RSRs). Table 2 showcases some of the new query functions that A-BITWEEN discovered. It is worth clarifying at this point what a query function is. According to Algorithm 1, the query functions q comprise the query class Q and are used as arguments to the program Π to generate the variables $v_q = \Pi(q(x, \cdot))$. In practice, however, A-BITWEEN provides (to the *infer_property_tool*) the variables v_q (functional or other terms) instead of the queries q . Some examples of variables are $f(x)$, $f(\sqrt{x \cdot r})$, $f(f(x) \cdot f(y))$, $\log(k)$, where k is constant and f is the function (representing Π). In other words, the query functions are implicitly the arguments of the outermost function of interest f or other independent terms. The table highlights unique query functions, such as $x + \log(k)$ in Sigmoid’s term $f(x + \log(k))$, $f(x) + f(y)$ in Modulo’s term $f(f(x) + f(y))$, and $x + \log(a)$ in Softmax’s

term $f(x + \log(a))$, with the complete list in Table 20 in the Appendix. The Modulo fixed-query entry is the classical modular reduction of Blum et al. (1993); it relies on modular arithmetic (recombination via $+_R$, i.e., addition in $\mathbb{Z}_R$), which lies outside V-BITWEEN-LR’s search over real and integer arithmetic.

The *infer_property_tool* is the primary discovery tool, aside from the LLM’s mathematical background, but the *symbolic_verify_tool* also helps, because of the way it handles failures. When the LLM agent proposes a property that fails the verification, its simplified (non-zero) expression is returned back to the agent. In many cases, this feedback provides the missing piece to complete the equation, because the remaining expression can be subtracted from the original one in order for the equation to be zero. Figure 3 shows the tool utilization of the different neural methods per benchmark. A-BITWEEN-Claude-Opus-4.1, which was the best of its variant, utilized both tools more, something that led to more discovered properties and significantly fewer false positives (unverified properties) as shown in Table 1 compared to the N-RESEARCH methods. It is also interesting that GPT-OSS-120B did not utilize the tools as much as the other LLMs, which might also be part of the reason why it found fewer properties.

Computational Efficiency Analysis. Figure 4 provides insights on the computational efficiency across all methods and benchmarks. The runtime heatmap (left) reveals that V-BITWEEN-LR and V-BITWEEN-MILP run the fastest, whereas V-BITWEEN-PySR requires significantly more time for comparable RSR discovery. The A-BITWEEN variants (which are queried only once) run longer than their pure-neural counterparts because the tool-use loop adds iteration overhead; concretely, A-BITWEEN incurs roughly $1.2\text{--}1.8\times$ the runtime of N-RESEARCH using the same model. The




Figure 4. (Left) Runtime performance across methods and benchmarks highlighting the speed of V-BITWEEN-LR, V-BITWEEN-MILP and the overhead of A-BITWEEN variants. (Right) Token usage patterns correlate with the LLM’s ability to efficiently utilize them.

token usage heatmap (right) reflects the same tool-use overhead, with token consumption running at roughly $2.8\text{--}3.5\times$ that of N-RESEARCH. The increase stems from iterative tool interactions with V-BITWEEN, feedback loops from tool calls (some unsuccessful) that require re-reasoning, and the inherent complexity of discovering novel mathematical relationships. In return, the agent produces more verified properties containing a diverse set of query functions and unlocks RSRs for functions that V-BITWEEN-LR cannot reach with fixed queries: across 23 RSR-BENCH functions (e.g., modulo, Gudermannian, e^{x^2} , $1/x^2$, x^4 , $\lceil x \rceil$), V-BITWEEN-LR returns no verified RSRs while A-BITWEEN (Claude Opus 4.1) discovers up to 33 RSRs per function (see per-function tables in Section G).

Generalization to algebraic structures. RSR-BENCH targets scalar real-valued functions, but BITWEEN’s regression and verification pipeline is agnostic to the algebraic structure of the input domain. To probe how broadly the framework applies, we evaluated BITWEEN on 17 additional benchmarks drawn from non-scalar algebraic structures: 2×2 matrix functions ($\det$, tr , $\text{tr}(A^2)$), quaternion and octonion norms (additive and multiplicative), Clifford algebras $\text{Cl}(2, 0)$ and $\text{Cl}(3, 0)$, the Lie bracket $\text{tr}([A, B]^2)$ on $\mathfrak{gl}(2)$, the Killing form on $\mathfrak{sl}(2)$, elementary symmetric polynomials, power sums, and vector operations (norm-squared, cross-product norm). With no architectural changes, A-BITWEEN (Claude Opus 4.1 with *infer_property_tool* and *symbolic_verify_tool*) discovers verified RSRs for all 17 functions. V-BITWEEN-LR also handles most of these benchmarks unchanged (11 / 17). We report a more detailed breakdown in Section H.

Limitations. While our evaluation demonstrates significant advances, several limitations merit discussion. First, discovered RSR properties may contain redundancies where certain properties are algebraically derivable from others. Although Gröbner basis reduction (Buchberger, 2001; Cox

et al., 2025) could identify minimal generating sets, we refrained from applying it due to its NP-complete complexity, especially given the large number of RSRs discovered. Second, our approach is inherently incomplete, absence of discovered RSRs does not imply non-existence. The infinite space of possible query functions, numerical precision requirements, sampling strategies, and degree limits (2-3 in our experiments) constrain discovery. Functions without discovered RSRs may possess properties requiring higher-degree terms or alternative mathematical representations beyond our current framework. Finally, A-BITWEEN’s enhanced performance incurs increased runtime and token usage compared to the pure neural methods due to iterative tool interactions, though this overhead is justified by the the quantity and diversity of discovered RSRs.

7. Conclusion

BITWEEN provides the first systematic approach for learning RSRs from mathematical functions, transforming expert-driven discovery into an automated process. Our work delivers two key achievements that validate our contributions: First, V-BITWEEN demonstrates that the linear regression-based backend outperforms the other symbolic method backends for RSR discovery from correlated samples. Second, A-BITWEEN achieves a paradigm shift by dynamically discovering novel query functions through neuro-symbolic reasoning, moving beyond the fixed query set. On RSR-Bench’s 80 functions spanning scientific computing and machine learning, neuro-symbolic methods surpass the traditional symbolic ones on automated RSR discovery. The pipeline also generalizes beyond scalar functions to non-scalar algebraic structures. Future work includes regression backends over finite-field arithmetic and broader mathematical domains.

Acknowledgements

We thank the anonymous reviewers for their constructive feedback, which substantially improved this work. This material is based upon work supported in part by the Defense Advanced Research Projects Agency (DARPA) under Agreement No. HR00112590130 and by the NSF awards CCF-2219995, CNS-2245344, CCF-2318974, CCF-2422036, CCF-2319131, CCF-2238133, and CCF-2200621, and by an Amazon Research Award.

Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here. The randomized self-reductions discovered by our system enable self-correcting implementations of common machine-learning components such as the sigmoid activation, and could support privacy-preserving protocols based on instance hiding as well as verifiable-computation and result-checking protocols built on self-correctors.

References

- Abadi, M., Feigenbaum, J., and Kilian, J. On hiding information from an oracle. In *Proceedings of the Nineteenth Annual ACM Symposium on Theory of Computing*, STOC '87, pp. 195–203, New York, NY, USA, 1987. Association for Computing Machinery. ISBN 0897912217. doi: 10.1145/28395.28417. URL <https://doi.org/10.1145/28395.28417>.
- Aczél, J. *Lectures on functional equations and their applications*. Academic press, 1966.
- Andreas, J., Rohrbach, M., Darrell, T., and Klein, D. Neural Module Networks. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 39–48, Los Alamitos, CA, USA, June 2016. IEEE Computer Society. doi: 10.1109/CVPR.2016.12. URL <https://doi.org/10.1109/CVPR.2016.12>.
- Anthropic. Introducing the next generation of claude, Mar 2024. URL <https://www.anthropic.com/news/claude-3-family>. Accessed: 2025-09-16.
- Anthropic. Introducing claude 4, Feb 2025. URL <https://www.anthropic.com/news/claude-4>. Accessed: 2025-09-16.
- Austel, V., Dash, S., Gunluk, O., Horesh, L., Liberti, L., Nannicini, G., and Schieber, B. Globally optimal symbolic regression. *NIPS Workshop on Interpretable Machine Learning in Complex Systems*, 2017. doi: 10.48550/arXiv.1710.10720. URL <https://doi.org/10.48550/arXiv.1710.10720>.
- Azerbayev, Z., Schoelkopf, H., Paster, K., Dos Santos, M., McAleer, S., Jiang, Q., Deng, J., Biderman, S. R., and Welleck, S. Llemma: An open language model for mathematics. In Kim, B., Yue, Y., Chaudhuri, S., Fragkiadaki, K., Khan, M., and Sun, Y. (eds.), *International Conference on Learning Representations*, volume 2024, pp. 40622–40649, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/b225f5c7cd13615e9558c3931fa4e66f-Paper-Conference.pdf.
- Blum, M. and Kannan, S. Designing programs that check their work. *J. ACM*, 42(1):269–291, January 1995. ISSN 0004-5411. doi: 10.1145/200836.200880. URL <https://doi.org/10.1145/200836.200880>.
- Blum, M., Luby, M., and Rubinfeld, R. Self-testing/correcting with applications to numerical problems. In *Proceedings of the Twenty-Second Annual ACM Symposium on Theory of Computing*, STOC '90, pp. 73–83, New York, NY, USA, 1990. Association for Computing Machinery. ISBN 0897913612. doi: 10.1145/100216.100225. URL <https://doi.org/10.1145/100216.100225>.
- Blum, M., Luby, M., and Rubinfeld, R. Self-testing/correcting with applications to numerical problems. *J. Comput. Syst. Sci.*, 47(3):549–595, 1993. doi: 10.1016/0022-0000(93)90044-W. URL [https://doi.org/10.1016/0022-0000\(93\)90044-W](https://doi.org/10.1016/0022-0000(93)90044-W).
- Buchberger, B. Gröbner bases: A short introduction for systems theorists. In Moreno-Díaz, R., Buchberger, B., and Luis Freire, J. (eds.), *Computer Aided Systems Theory — EUROCAST 2001*, pp. 1–19, Berlin, Heidelberg, 2001. Springer Berlin Heidelberg. ISBN 978-3-540-45654-4. doi: 10.1007/3-540-45654-6_1. URL https://doi.org/10.1007/3-540-45654-6_1.
- Chaudhuri, S., Ellis, K., Polozov, O., Singh, R., Solar-Lezama, A., and Yue, Y. Neurosymbolic programming. *Found. Trends Program. Lang.*, 7(3):158–243, December 2021. ISSN 2325-1107. doi: 10.1561/25000000049. URL <https://doi.org/10.1561/25000000049>.
- Cox, D. A., Little, J., and O’Shea, D. *Ideals, Varieties, and Algorithms: An Introduction to Computational Algebraic Geometry and Commutative Algebra*. Undergraduate Texts in Mathematics. Springer Nature Switzerland, Cham, 5th edition, 2025. ISBN 978-3-031-91841-4. doi: 10.1007/978-3-031-91841-4. URL <https://doi.org/10.1007/978-3-031-91841-4>.

- Cozad, A. and Sahinidis, N. V. A global minlp approach to symbolic regression. *Math. Program.*, 170(1):97–119, July 2018. ISSN 0025-5610. doi: 10.1007/s10107-018-1289-x. URL <https://doi.org/10.1007/s10107-018-1289-x>.
- Cranmer, M. Interpretable machine learning for science with PySR and SymbolicRegression.jl, 2023. URL <https://arxiv.org/abs/2305.01582>.
- Davies, A., Veličković, P., Buesing, L., Blackwell, S., Zheng, D., Tomašev, N., Tanburn, R., Battaglia, P., Blundell, C., Juhász, A., et al. Advancing mathematics by guiding human intuition with ai. *Nature*, 600(7887):70–74, 2021. doi: 10.1038/s41586-021-04086-x. URL <https://doi.org/10.1038/s41586-021-04086-x>.
- De Rainville, F.-M., Fortin, F.-A., Gardner, M.-A., Parizeau, M., and Gagné, C. Deap: a python framework for evolutionary algorithms. In *Proceedings of the 14th Annual Conference Companion on Genetic and Evolutionary Computation*, GECCO '12, pp. 85–92, New York, NY, USA, 2012. Association for Computing Machinery. ISBN 9781450311786. doi: 10.1145/2330784.2330799. URL <https://doi.org/10.1145/2330784.2330799>.
- Ernst, M. D., Perkins, J. H., Guo, P. J., McCamant, S., Pacheco, C., Tschantz, M. S., and Xiao, C. The daikon system for dynamic detection of likely invariants. *Science of Computer Programming*, 69(1):35–45, 2007. ISSN 0167-6423. doi: 10.1016/j.scico.2007.01.015. URL <https://doi.org/10.1016/j.scico.2007.01.015>.
- Feigenbaum, J. and Fortnow, L. Random-Self-Reducibility of Complete Sets. *SIAM Journal on Computing*, 22(5): 994–1005, 1993. doi: 10.1137/0222061. URL <https://doi.org/10.1137/0222061>.
- Goldreich, O. *Introduction to Property Testing*. Cambridge University Press, 2017. doi: 10.1017/9781108135252. URL <https://doi.org/10.1017/9781108135252>.
- Goldstein, H., Cutler, J. W., Dickstein, D., Pierce, B. C., and Head, A. Property-based testing in practice. In *Proceedings of the IEEE/ACM 46th International Conference on Software Engineering*, ICSE '24, New York, NY, USA, 2024. Association for Computing Machinery. doi: 10.1145/3597503.3639581. URL <https://doi.org/10.1145/3597503.3639581>.
- Goldwasser, S. and Micali, S. Probabilistic encryption. *J. Comput. Syst. Sci.*, 28(2):270–299, 1984. doi: 10.1016/0022-0000(84)90070-9. URL [https://doi.org/10.1016/0022-0000\(84\)90070-9](https://doi.org/10.1016/0022-0000(84)90070-9).
- Goldwasser, S. and Micali, S. *Probabilistic encryption & how to play mental poker keeping secret all partial information*, pp. 173–201. Association for Computing Machinery, New York, NY, USA, 2019. ISBN 9781450372664. doi: 10.1145/3335741.3335749. URL <https://doi.org/10.1145/3335741.3335749>.
- Goldwasser, S., Micali, S., and Rackoff, C. *The knowledge complexity of interactive proof-systems*, pp. 203–225. Association for Computing Machinery, New York, NY, USA, 2019. ISBN 9781450372664. doi: 10.1145/3335741.3335750. URL <https://doi.org/10.1145/3335741.3335750>.
- Golea, M., Marchand, M., and Hancock, T. R. On learning μ -perceptron networks on the uniform distribution. *Neural Networks*, 9(1):67–82, 1996. ISSN 0893-6080. doi: 10.1016/0893-6080(95)00009-7. URL [https://doi.org/10.1016/0893-6080\(95\)00009-7](https://doi.org/10.1016/0893-6080(95)00009-7).
- Gurobi Optimization, LLC. Gurobi Optimizer Reference Manual, 2026. URL <https://www.gurobi.com>.
- Han, J. and Moraga, C. The influence of the sigmoid function parameters on the speed of backpropagation learning. In Mira, J. and Hernández, F. S. (eds.), *From Natural to Artificial Neural Computation, International Workshop on Artificial Neural Networks, IWANN '95, Malaga-Torremolinos, Spain, June 7-9, 1995, Proceedings*, volume 930 of *Lecture Notes in Computer Science*, pp. 195–201. Springer, 1995. doi: 10.1007/3-540-59497-3_175. URL https://doi.org/10.1007/3-540-59497-3_175.
- Hancock, T. R. Learning $k\mu$ decision trees on the uniform distribution. In *Proceedings of the Sixth Annual Conference on Computational Learning Theory*, COLT '93, pp. 352–360, New York, NY, USA, 1993. Association for Computing Machinery. ISBN 0897916115. doi: 10.1145/168304.168374. URL <https://doi.org/10.1145/168304.168374>.
- Jackson, J. C. and Servedio, R. A. On learning random DNF formulas under the uniform distribution. *Theory Comput.*, 2(8):147–172, 2006. doi: 10.4086/TOC.2006.V002A008. URL <https://doi.org/10.4086/toc.2006.v002a008>.
- Jackson, J. C., Klivans, A. R., and Servedio, R. A. Learnability beyond AC0. In Reif, J. H. (ed.), *Proceedings on 34th Annual ACM Symposium on Theory of Computing*, May 19-21, 2002, Montréal, Québec, Canada, pp. 776–784. ACM, 2002. doi: 10.1145/509907.510018. URL <https://doi.org/10.1145/509907.510018>.
- Kannappan, P. *Functional Equations and Inequalities with Applications*. Springer Monographs in Mathematics.

- Springer New York, NY, 2009. ISBN 978-0-387-89491-1. doi: 10.1007/978-0-387-89492-8. URL <https://doi.org/10.1007/978-0-387-89492-8>.
- Klivans, A. R., O’Donnell, R., and Servedio, R. A. Learning intersections and thresholds of halfspaces. *J. Comput. Syst. Sci.*, 68(4):808–840, 2004. doi: 10.1016/J.JCSS.2003.11.002. URL <https://doi.org/10.1016/j.jcss.2003.11.002>.
- Koza, J. R. *Genetic Programming: On the Programming of Computers by Means of Natural Selection*. MIT Press, Cambridge, MA, USA, 1992. ISBN 978-0-262-11170-6.
- Kroening, D. and Tautschnig, M. CBMC – C Bounded Model Checker. In Ábrahám, E. and Havelund, K. (eds.), *Tools and Algorithms for the Construction and Analysis of Systems*, pp. 389–391, Berlin, Heidelberg, 2014. Springer Berlin Heidelberg. ISBN 978-3-642-54862-8. doi: 10.1007/978-3-642-54862-8_26. URL https://doi.org/10.1007/978-3-642-54862-8_26.
- Kucera, L., Marchetti-Spaccamela, A., and Protasi, M. On learning monotone DNF formulae under uniform distributions. *Inf. Comput.*, 110(1):84–95, 1994. doi: 10.1006/INCO.1994.1024. URL <https://doi.org/10.1006/inco.1994.1024>.
- Lenat, D. B. *AM: An Artificial Intelligence Approach to Discovery in Mathematics as Heuristic Search*. Phd thesis, Stanford University, Stanford, CA, USA, 1976. URL <https://searchworks.stanford.edu/view/933075>.
- Lenat, D. B. Eurisko: A program that learns new heuristics and domain concepts: The nature of heuristics iii: Program design and results. *Artificial Intelligence*, 21(1): 61–98, 1983. ISSN 0004-3702. doi: 10.1016/S0004-3702(83)80005-8. URL [https://doi.org/10.1016/S0004-3702\(83\)80005-8](https://doi.org/10.1016/S0004-3702(83)80005-8).
- Li, Y., Li, W., Yu, L., Wu, M., Liu, J., Wei, S., Deng, Y., and Hao, M. Metasymnet: a tree-like symbol network with adaptive architecture and activation functions. In *Proceedings of the Thirty-Ninth AAAI Conference on Artificial Intelligence and Thirty-Seventh Conference on Innovative Applications of Artificial Intelligence and Fifteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI’25/IAAI’25/EAAI’25. AAAI Press, 2025. ISBN 978-1-57735-897-8. doi: 10.1609/aaai.v39i25.34915. URL <https://doi.org/10.1609/aaai.v39i25.34915>.
- Lipton, R. New directions in testing. *Distributed computing and cryptography*, 2:191–202, 1991.
- Lipton, R. J. New directions in testing. In Feigenbaum, J. and Merritt, M. (eds.), *Distributed Computing And Cryptography, Proceedings of a DIMACS Workshop, Princeton, New Jersey, USA, October 4-6, 1989*, volume 2 of *DIMACS Series in Discrete Mathematics and Theoretical Computer Science*, pp. 191–202. DIMACS/AMS, 1989. doi: 10.1090/DIMACS/002/13. URL <https://doi.org/10.1090/dimacs/002/13>.
- Meurer, A., Smith, C. P., Paprocki, M., Čertík, O., Kirpichev, S. B., Rocklin, M., Kumar, A., Ivanov, S., Moore, J. K., Singh, S., Rathnayake, T., Vig, S., Granger, B. E., Muller, R. P., Bonazzi, F., Gupta, H., Vats, S., Johansson, F., Pedregosa, F., Curry, M. J., Terrel, A. R., Roučka, v., Saboo, A., Fernando, I., Kulal, S., Cimrman, R., and Scopatz, A. Sympy: symbolic computing in python. *PeerJ Computer Science*, 3:e103, January 2017. ISSN 2376-5992. doi: 10.7717/peerj-cs.103. URL <https://doi.org/10.7717/peerj-cs.103>.
- Model Context Protocol Community. Sequential thinking mcp server. <https://github.com/modelcontextprotocol/servers/tree/main/src/sequentialthinking>, 2024. A detailed tool for dynamic and reflective problem-solving through thoughts.
- Nguyen, T., Kapur, D., Weimer, W., and Forrest, S. Using dynamic analysis to discover polynomial and array invariants. In Glinz, M., Murphy, G. C., and Pezzè, M. (eds.), *34th International Conference on Software Engineering, ICSE 2012, June 2-9, 2012, Zurich, Switzerland*, pp. 683–693. IEEE Computer Society, 2012. doi: 10.1109/ICSE.2012.6227149. URL <https://doi.org/10.1109/ICSE.2012.6227149>.
- Nguyen, T., Nguyen, K., and Dwyer, M. B. Using symbolic states to infer numerical invariants. *IEEE Transactions on Software Engineering*, 48(10):3877–3899, 2021.
- O’Donnell, R. *Analysis of Boolean Functions*. Cambridge University Press, 2014. ISBN 978-1-10-703832-5. URL <http://www.cambridge.org/de/academic/subjects/computer-science/algorithmic-complexity-computer-algebra-and-computational-g/analysis-boolean-functions>.
- OpenAI. GPT-4 technical report, 2024. URL <https://doi.org/10.48550/arXiv.2303.08774>.
- OpenAI. gpt-oss-120b & gpt-oss-20b model card, 2025. URL <https://doi.org/10.48550/arXiv.2508.10925>.
- Petersen, B. K., Landajuela, M., Mundhenk, T. N., Santiago, C. P., Kim, S., and Kim, J. T. Deep symbolic regression:

- Recovering mathematical expressions from data via risk-seeking policy gradients. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL <https://openreview.net/forum?id=m5Qsh0kBQG>.
- Raayoni, G., Gottlieb, S., Manor, Y., Pisha, G., Harris, Y., Mendlovic, U., Haviv, D., Hadad, Y., and Kaminer, I. Generating conjectures on fundamental constants with the ramanujan machine. *Nature*, 590(7844):67–73, 2021. doi: 10.1038/S41586-021-03229-4. URL <https://doi.org/10.1038/s41586-021-03229-4>.
- Rubinfeld, R. Robust functional equations with applications to self-testing/correcting, July 1994. URL <https://hdl.handle.net/1813/6221>.
- Rubinfeld, R. On the robustness of functional equations. *SIAM Journal on Computing*, 28(6):1972–1997, 1999. doi: 10.1137/S0097539796298625. URL <https://doi.org/10.1137/S0097539796298625>.
- Scholl, P., Bieker, K., Hauger, H., and Kutyniok, G. Parfam – (neural guided) symbolic regression via continuous global optimization. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=8y5Uf6oEiB>.
- Stephens, T. gplearn: Genetic programming in python, with a scikit-learn inspired api. <https://github.com/trevorstephens/gplearn>, 2015.
- Tompa, M. and Woll, H. Random self-reducibility and zero knowledge interactive proofs of possession of information. In *28th Annual Symposium on Foundations of Computer Science, Los Angeles, California, USA, 27-29 October 1987*, pp. 472–482. IEEE Computer Society, 1987. doi: 10.1109/SFCS.1987.49. URL <https://doi.org/10.1109/SFCS.1987.49>.
- Udrescu, S.-M. and Tegmark, M. AI Feynman: A physics-inspired method for symbolic regression. *Science Advances*, 6(16):eaay2631, 2020. doi: 10.1126/sciadv.aay2631. URL <https://doi.org/10.1126/sciadv.aay2631>.
- Udrescu, S.-M., Tan, A., Feng, J., Neto, O., Wu, T., and Tegmark, M. AI Feynman 2.0: Pareto-optimal symbolic regression exploiting graph modularity. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 4860–4871. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/hash/33a854e247155d590883b93bca53848a-Abstract.html.
- Valiant, L. G. A theory of the learnable. *Commun. ACM*, 27(11):1134–1142, November 1984. ISSN 0001-0782. doi: 10.1145/1968.1972. URL <https://doi.org/10.1145/1968.1972>.
- Verbeurgt, K. A. Learning DNF under the uniform distribution in quasi-polynomial time. In Fulk, M. A. and Case, J. (eds.), *Proceedings of the Third Annual Workshop on Computational Learning Theory, COLT 1990, University of Rochester, Rochester, NY, USA, August 6-8, 1990*, pp. 314–326. Morgan Kaufmann, 1990. URL <http://dl.acm.org/citation.cfm?id=92659>.
- Zhang, H., Chen, Q., XUE, B., Banzhaf, W., and Zhang, M. RAG-SR: Retrieval-augmented generation for neural symbolic regression. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=NdHka08uWn>.

A. Theory: RSR Learning vs PAC Learning

When samples are drawn uniformly and *independently* (Item 1 in Definition 4.3), PAC learnability is a strictly stronger form of learning than RSR learnability, as captured by the following two claims:

Claim A.1. Fix query class Q , recovery class P , and function class $F \subseteq \text{RSR}_k(Q, P)$. If F is (Uniform) PAC-learnable with sample complexity $m_{\text{PAC}}(\varepsilon, \delta)$, then it is RSR-learnable with sample complexity

$$m_{\text{RSR}}(\rho, \xi, \delta) \leq m_{\text{PAC}}(\min(\rho/k, \xi), \delta).$$

However, the RSR-learner may be inefficient.

We note that Claim A.1 is trivial when considering a class $F \subseteq \text{RSR}_k(Q, P)$ characterized by a single RSR, i.e., such that there exist $q_1, \dots, q_k \in Q$ and $p \in P$ such that Equation (2) holds with probability 1 for all $f \in F$. For one, this follows because the RSR-learner does not need any samples and may simply output $q_1, \dots, q_k, p$.⁵ This gives rise to the following claim.

Claim A.2. There exist classes $(Q, P) = (\bigcup_n Q_n, \bigcup_n P_n)$ and $F = \bigcup_n F_n \subseteq \text{RSR}(Q, P)$ such that F is efficiently RSR-learnable from 0 samples, but for any $\varepsilon \leq 1/2$, Uniform PAC-learning F_n requires $m_{\text{PAC}}(\varepsilon, \delta) \geq n$ oracle queries.

Consequently, Uniform PAC-learning F_n requires at least n correlated or independent random samples (see Remark 4.4).

B. Proofs

Proof of Claim A.1. Suppose $F \subseteq \text{RSR}_k(Q, P)$ is PAC-learnable with sample complexity $m_{\text{PAC}}(\varepsilon, \delta)$ and learner Λ_{PAC} . To RSR-learn F with errors (ρ, ξ, δ) , we let $\varepsilon = \min(\rho/k, \xi)$ and draw $m = m_{\text{PAC}}(\varepsilon, \delta)$ labeled samples $(x_i, f(x_i))_{i=1}^m$. The RSR-learner is described in Algorithm 2. For simplicity of notation, we will omit the input length n ; following this proof is a brief discussion of Algorithm 2's inefficiency with respect to n .

Algorithm 2 RSR-learning via PAC-learning.

- 1: **Input:** Query class Q , recovery class P , and hypothesis class $F \subseteq \text{RSR}_k(Q, P)$. Query complexity k and randomness domain R . Uniform PAC-learner Λ_{PAC} for F . Labeled samples $(x_i, y_i)_{i=1}^m$.
 - 2: **Output:** Query functions $\hat{q}_1, \dots, \hat{q}_k \in Q$ and recovery function $\hat{p} \in P$.
 - 3:
 - 4: Invoke Λ_{PAC} on samples $(x_i, y_i)_{i=1}^m$ to obtain a hypothesis $\hat{f} \in F$.
 - 5: **for** each Query functions $(q_1, \dots, q_k) \in Q^k$ and recovery function $p \in P$ **do**
 - 6: **for** $x \in X$ and $r \in R$ **do**
 - 7: Compute $u_i := q_i(x, r)$ for each $i \in [k]$.
 - 8: **if** $\hat{f}(x) \neq p(x, r, \hat{f}(u_1), \dots, \hat{f}(u_k))$ **then**
 - 9: Go to line 5. // Continue to the next $q_1, \dots, q_k, p$.
 - 10: **end if**
 - 11: **end for**
 - 12: Output $(\hat{q}_1, \dots, \hat{q}_k, p) := (q_1, \dots, q_k, p)$.
 - 13: **end for**
 - 14: Output $\perp$.
-

At a high level, the learner invokes Λ_{PAC} to obtain a hypothesis $\hat{f} \in F$ that is ε -close to the ground truth function f (with probability $\geq 1 - \delta$ over the samples). It then uses $\hat{f}$ to exhaustively search through possible query functions $\hat{q}_1, \dots, \hat{q}_k \in Q$ and recovery functions $\hat{p} \in P$, until it finds those that are a *perfect* RSR for $\hat{f}$.

To conclude the proof, we will show that, because $\hat{f}$ is ε -close to f , then $(\hat{q}_1, \dots, \hat{q}_k, \hat{p})$ is a (ρ, ξ) -RSR for f .

We say that $x \in X$ is *good* if $\hat{f}(x) = f(x)$. By choice of ε , we know that there are at least $(1 - \varepsilon)|X| \geq (1 - \xi)|X|$ many

⁵For a more nuanced reason, note that the sample complexity bound $m_{\text{PAC}}(\rho/k, \delta)$ trivializes: Any class F characterized by a single RSR has *distance* at least $1/k$, meaning that $\Pr_{z \sim X}[\hat{f}(z) \neq f(z)] \geq 1/k$ (Goldreich, 2017, Exercise 5.4). Thus, for any $\varepsilon = \rho/k < 1/k$, f is the only function in F that is ε -close to itself. In other words, learning within accuracy ε amounts to exactly recovering f .

good x 's. It therefore suffices to show that for any good x ,

$$\Pr_{r \sim R} \left[\begin{array}{l} f(x) = \hat{p}(x, rf(u_1), \dots, f(u_k)) \\ \text{where } \forall i \in [k] \ u_i := \hat{q}_i(x, r) \end{array} \right] \geq 1 - \varepsilon \cdot k \geq 1 - \rho.$$

The right inequality is by choice of $\varepsilon \leq \rho/k$. For the left inequality,

$$\begin{aligned} \Pr_{r \sim R} \left[\begin{array}{l} f(x) = \hat{p}(x, rf(u_1), \dots, f(u_k)) \\ \text{where } \forall i \in [k] \ u_i := \hat{q}_i(x, r) \end{array} \right] &\geq \\ \Pr_{r \sim R} \left[\begin{array}{l} f(u_1) = \hat{f}(u_1), \dots, f(u_k) = \hat{f}(u_k) \\ \text{where } \forall i \in [k] \ u_i := \hat{q}_i(x, r) \end{array} \right] &\geq \\ 1 - k \cdot \Pr_{x \sim X} [f(x) \neq \hat{f}(x)] &\geq 1 - k \cdot \varepsilon. \end{aligned}$$

Here, the first inequality is because $(\hat{q}_1, \dots, \hat{q}_k, \hat{p})$ is a perfect RSR for $\hat{f}$, the second is by a union bound and the fact that each u_i is distributed uniformly in X (Definition 4.1), and the last is because $\hat{f}$ is ε -close to f . $\square$

Note that, as mentioned in Claim A.1, the running time of the RSR-learner is not bounded by a polynomial in the number of samples m . In more detail, we denote

- $T_{\text{PAC}}(m)$: an upper-bound on the running time of the PAC learner Λ_{PAC} as a function of the number of samples $m = m_{\text{PAC}}(\min(\rho/k, \xi), \delta)$.
- $T_Q(n)$ (resp. $T_P(n)$): an upper-bound on the running time of query functions $q \in Q$ (resp. recovery function $p \in P$) as a function of the input length $n = |x|$.

Then the running time of the RSR-learner is

$$O(T_{\text{PAC}}(m) + |Q_n|^k \cdot |P_n| \cdot |X_n| \cdot |R_n| \cdot (k \cdot T_Q(n) + T_P(n))).$$

In particular, $|X_n|$ typically grows exponentially in n . Therefore, even if the PAC learner were efficient, the RSR-learner will not be efficient.

Proof sketch of Claim A.2. We will show a setting in which an RSR is “learnable” without any samples ($m \equiv 0$). However, without samples it will not be possible to PAC learn a hypothesis for f .

Consider the RSR that captures the so-called BLR relation $g(z) = g(z + \tilde{x}) - g(\tilde{x})$ for Boolean functions $g: \mathbb{F}_2^\ell \rightarrow \mathbb{F}_2$ (Blum et al., 1993). Indeed, this relation characterizes ℓ -variate linear functions over $\mathbb{F}_2$. In a nutshell, we will choose our reduction class (Q, P) to consist only of the reduction specified by the BLR relation, and the hypothesis class F to consist of all linear functions. Then, a (Q, P) -RSR₂ learner for F will always output the BLR relation, but on the other hand, PAC learning F requires a superconstant number of samples. Details follow.

We choose the input and randomness domains to be $X_n := R_n := \mathbb{F}_2^n$, and the range $Y_n = \mathbb{F}_2$. The query class Q_n consists of just two query functions

$$\begin{aligned} Q_n = \{q_n, q'_n\} \quad \text{where } q_n, q'_n: \mathbb{F}_2^n \times \mathbb{F}_2^n &\rightarrow \mathbb{F}_2^n, \\ q_n(x, r) &:= x + r, \\ q'_n(x, r) &:= r. \end{aligned}$$

The recovery class P_n is the singleton $P_n = \{p_n\}$ where $p_n(x, r, y, y') := y - y'$. Indeed, the trivial algorithm that takes no samples and outputs (q, q', p) is a (Q, P) -RSR₂ learner for any linear function $f: \mathbb{F}_2^n \rightarrow \mathbb{F}_2$.

On the other hand, fix $\varepsilon < 1/2$, $\delta < 1/2$ and number of samples $m < n$. Given m labeled samples $(x_i, f(x_i))_{i=1}^m$, there exists another linear function $f' \neq f$ such that $f'(z_i) = f(z_i)$ for all $i \in [m]$. The learner cannot do better than guess

between f and f' uniformly at random, in which case it outputs f' with probability $1/2$. Lastly, we note that any two different linear functions agree on *exactly* $1/2$ of the inputs in $\mathbb{F}_2^n$, therefore

$$\Pr_{x \sim X} [f(x) = f'(x)] \geq 1 - \varepsilon \iff f = f'.$$

All in all, we have

$$\Pr_{\substack{x_1, \dots, x_m \sim X \\ \hat{f} \leftarrow \Lambda(x_1, f(x_1), \dots, x_m, f(x_m))}} \left[\Pr_{x \sim X} [\hat{f}(x) = f(x)] \geq 1 - \varepsilon \right] = \Pr_{\substack{x_1, \dots, x_m \sim X \\ \hat{f} \leftarrow \Lambda(x_1, f(x_1), \dots, x_m, f(x_m))}} [\hat{f} = f] \leq 1/2 < 1 - \delta.$$

□

C. General definitions

Definition C.1 (Randomized reduction). Let

$$\begin{aligned} f: X &\rightarrow Y && \text{(Source function)} \\ g_1, \dots, g_k: U &\rightarrow V && \text{(Target functions)} \\ q_1, \dots, q_k: X \times R &\rightarrow U && \text{(Query functions)} \\ p: X \times R \times V^k &\rightarrow Y && \text{(Recovery function)} \end{aligned}$$

such that U and V are uniformly-samplable, and for all $i \in [k]$ and $x \in X$, $u_i := q_i(x, r)$ is distributed uniformly over U when $r \sim R$ is sampled uniformly at random.

We say that $(q_1, \dots, q_k, p)$ is a *perfect randomized reduction (RR)* from f to $(g_1, \dots, g_k)$ with k queries and $\log_2 |R|$ random bits if for all $x \in X$ and $r \in R$, letting $u_i := q_i(x, r)$ for all $i \in [k]$, the following holds:

$$f(z) = p(z, r, g_1(u_1), \dots, g_k(u_k)). \quad (3)$$

In other words, if Equation (3) holds with probability 1 over randomly sampled $r \in R$.

For errors $\rho, \xi \in (0, 1)$, we say that $(q_1, \dots, q_k, r)$ is a (ρ, ξ) -*approximate randomized reduction* $((\rho, \xi)$ -RR) from f to $(g_1, \dots, g_k)$ if, for all but a ξ -fraction of $x \in X$, Equation (3) holds with probability $\geq 1 - \rho$ over the random samples $r \sim R$. That is,

$$\Pr_{x \sim X} \left[\Pr_{r \sim R} \left[\begin{array}{l} f(x) = p(x, r, g_1(u_1), \dots, g_k(u_k)) \\ \text{where } \forall i \in [k] \ u_i := q_i(x, r) \end{array} \right] \geq 1 - \rho \right] \geq 1 - \xi.$$

Definition 4.1 is derived from Definition C.1 by letting $X = U$, $Y = V$, and $f = g_1 = \dots = g_k$. This is called a *randomized self-reduction (RSR)* for f .

D. Vanilla Bitween

We now illustrate how BITWEEN derived the above RSR.

BITWEEN applies a series of steps to learn randomized reductions (see Figure 5). BITWEEN takes a program Π as input and systematically constructs a query class using the input variable x and randomness r , such as $x + r, x - r, r$ (Step ①). The tool then independently and uniformly samples data using a specified distribution, evaluating target functions $\sigma(x + r), \sigma(x - r), \sigma(r), \dots$ by simulating σ with Π based on the sampled inputs (Step ②). Subsequently, BITWEEN constructs linear models by treating nonlinear terms as constant functions (Step ③). Since the model is unsupervised, it instantiates candidate models in parallel, where each model takes a distinct target function as its supervised variable (Step ④). The tool then uses various linear regression models, including Ridge and Lasso with fixed hyperparameters, and the best model is picked based on cross validation. Then it iteratively refines the model by eliminating irrelevant targets from this model (Step ⑤). The coefficients of the final model are further refined using a best rational approximation technique. Finally, BITWEEN validates these properties using the test dataset through property testing (Step ⑥). After validation, BITWEEN outputs the learned randomized self-reductions of the program Π with their corresponding errors.




Figure 5. Overview of V-BITWEEN.

Optionally, the user can refine the analysis by enabling a set of reduction techniques. First, BITWEEN creates an equivalence class of properties based on structural similarity (Step 8). Second, it applies Gröbner Basis (Buchberger, 2001) reduction to eliminate redundant properties (Step 9). Lastly, BITWEEN uses bounded model-checking (Kroening & Tautschnig, 2014) or property-based testing (Goldstein et al., 2024) to ensure correctness of the properties and eliminates any unsound ones (Step 10).

E. Experimental Hyperparameters

This section provides detailed hyperparameter configurations for all backends evaluated in our experiments, addressing reproducibility and fair comparison concerns.

E.1. Common Settings Across All Backends

All backends share the following configuration to ensure fair comparison:

E.2. Backend-Specific Configurations

Our hyperparameter selection follows three key principles. First, we ensure *fair comparison* by having all backends operate under the same time and computational budget constraints, ensuring no method receives unfair advantage through extended computation time. Second, we enforce *no per-function tuning* by using fixed hyperparameters across all 80 benchmark functions without per-function optimization. This mirrors real-world usage where methods must perform well across diverse problems without extensive tuning. Third, we follow *established defaults* by using recommended settings from each

Table 3. Common experimental settings shared across all backends.

Parameter	Setting
Function set	Addition, subtraction, multiplication
Degree bounds	2 (most functions); 3 (trigonometric, hyperbolic, exponential)
Error threshold	$\varepsilon = 0.001$
Sampling	$n = 30$ samples, uniform distribution
Domain	$[-10, 10]$ with domain-specific adjustments
Rational approximation	Maximum denominator = 20 (configurable)
Test split	80/20 train-test
Computational budget	Complete 80 benchmarks in ≈ 12 hours

Table 4. Detailed hyperparameter configurations for all evaluated backends. Settings were chosen to ensure fair comparison with consistent computational budgets and no per-function tuning.

Backend	Configuration
V-Bitween-LR	Grid Search Models: • Linear: <code>fit_intercept</code> $\in$ {False, True}, <code>positive</code> $\in$ {True, False} • Ridge: <code>alpha</code> $\in$ {1e-3, 1e-2, 1e-1, 100, 1000}, <code>fit_intercept</code> $\in$ {True, False} • Lasso: <code>alpha</code> $\in$ {1e-4, 1e-3, 1e-2, 1e-1, 100, 1000}, <code>fit_intercept</code> $\in$ {True, False} Cross-validation: 5-fold CV, Scoring: R^2
V-Bitween-PySR	Iterations: 50, Binary operators: $[+, \times]$ Populations: $\max(15, \text{cpu_count} \times 2)$ Timeout: Distributed across regressions Feature selection: Top 4 features, Precision: 3 decimal places
V-Bitween-GPLearn	Population: 1000, Generations: 20, Stopping: 0.01 Crossover: 0.7, Mutations: <code>subtree</code> =0.1, <code>hoist</code> =0.05, <code>point</code> =0.1 Sample fraction: 0.9, Parsimony: 0.01 Function set: (add, sub, mul)
V-Bitween-MILP	Solver: Gurobi (or PuLP), Variable bound: Domain-dependent Timeout: Distributed, Objective threshold: Configurable

method’s documentation or established conventions in the literature. For GPLearn, parameters follow DEAP (De Rainville et al., 2012) genetic programming standards. For PySR, we use settings recommended in its documentation with timeout management for fairness. For linear models, our grid search explores standard regularization ranges.

The key insight is that we evaluate each backend’s effectiveness for RSR discovery under realistic conditions, not performance under optimal tuning. This design choice ensures our comparison reflects practical applicability rather than best-case performance achievable through extensive hyperparameter search.

F. Bitween Agent Instructions

This appendix presents the complete prompts and instructions used by the Bitween agent for discovering randomized self-reductions. The agent employs a combination of system prompts and tool-specific instructions to guide its exploration of mathematical properties.

F.1. Agent System Prompt

The following system prompt defines the agent’s role and approach to discovering randomized self-reductions:

Bitween Agent System Prompt

You are exceptional at mathematics and at finding randomized self-reductions (RSRs) $\leftrightarrow$ for functions. An RSR is a powerful property where a function $f(x)$ can be $\leftrightarrow$ computed by evaluating f at random correlated points. You have deep mathematical $\leftrightarrow$ knowledge spanning algebra, analysis, group theory, and computational $\leftrightarrow$ mathematics. Your goal is to discover these reductions that reveal the hidden $\leftrightarrow$ mathematical structure of functions – showing how $f(x)$ relates to $f(x+r)$, $f(x-r) \leftrightarrow$, $f(r)$ for random r . These properties enable self-correction, instance hiding, $\leftrightarrow$

and other applications.

Think deeply: Each function has hidden symmetries and patterns. Your role is not ↩ just to find properties mechanically, but to understand WHY they exist. When you ↩ discover a property, it's a window into the function's soul - use it to guide ↩ your next exploration. Your mathematical insight and intuition are crucial - use ↩ them to guide your exploration and recognize elegant patterns.

You are allowed to respond only in the following format and do not forget to include ↩ all opening and closing XML tags in your response:

<reasoning>

Provide detailed mathematical reasoning. When you discover a property, explain ↩ WHY it holds based on the function's nature. Connect properties to show how they ↩ relate. If something fails verification, explain what you learned from it.

</reasoning>

<answer>

Only include properties that you have verified or have strong mathematical ↩ confidence in. Quality matters more than quantity.

</answer>

F.2. Tool Instructions

The agent utilizes two primary tools for discovering and verifying randomized self-reductions. Each tool has specific instructions embedded in its docstring to guide proper usage.

F.2.1. BITWEEN'S MAIN RSR DISCOVERY FUNCTION

The *infer_property_tool* uses data-driven approaches to discover polynomial relationships between function evaluations:

Bitween's Main RSR Discovery Function

Infer properties containing the 'exprs' as terms using linear regression.

Use this tool when you do not know a closed-form expression of property in order to ↩ try and find some properties that are based on 'exprs'.

This tool uses a data-driven approach, which means that it generates up to 'n' ↩ concrete samples of the provided 'exprs' randomly and then tries to find ↩ properties based on the 'exprs' that fit the data using the provided 'method'.

In order to find properties, the tool combines together all the 'exprs' up to '↩ max_degree'. For example:

if max_degree = 2, and exprs = ['f(x)', 'f(x-y)'], then

degree 1: ['f(x)', 'f(x-y)', '1']

degree 2: ['f(x)', 'f(x-y)', 'f(x)*f(x)', 'f(x)*f(x-y)', 'f(x-y)*f(x-y)', '1']

Notes:

- The 'exprs' should contain only the names of the functions that are defined in ↩ the tool's context and described in the docstring.
- The defined functions are the implementations of the function symbols that are ↩ used for the sample generation.

Args:

exprs: List of strings representing functional terms. The function symbol should ↩ only be one of the defined functions. These terms are very important in the ↩ success of the inference.

max_degree: The maximum degree that the term combination should reach. Usually ↩ it should not be too large.

`n`: The number of samples that need to be generated. Usually, more samples means more accuracy, but there are many cases that few samples, like 20, are sufficient enough.

`epsilon`: Tolerance for the mean squared error. The default value is good enough, but sometimes increasing the tolerance is beneficial, as more properties can be found.

`milp`: The solver to be used. You can experiment with the different solvers.

`var_bound`: The variable bound for the MILP algorithm. It specifies that the variables would be in the range `[-var_bound, var_bound]`. The default value works well.

`method`: The available MILP method to be used. If it is left `'None'`, then no MILP will be performed and the tool will fallback to `'Method.MULTIPLE_REGRESSION'`.

Returns:

A tuple with four items:

Three dictionaries all having identifiers as keys:

- The first dictionary is for the found equations. These are sympy expressions or equalities.
- The second dictionary is for the equations mean error
- The third dictionary is for the equations sample complexity

Pay attention to the second dictionary value with the mean error, because ideally it needs to be very close to zero.

An error message as the last item of the tuple, which when present can provide useful information when something went wrong.

F.2.2. BETWEEN'S SYMBOLIC VERIFICATION FUNCTION

The *symbolic_verify_tool* performs formal verification of discovered properties using symbolic mathematics:

Between's Symbolic Verification Function

Verify a sympy expression symbolically using mathematical derivations.

Use this tool when you need to verify that `'expr'` holds.

There are two cases in which this can happen:

- 1) `'expr'` is an equality with the right-hand-side being zero, or
- 2) `'expr'` is an expression that should equal to zero

The first case can be converted to the second if we keep only the left-hand-side of the equation.

This tool utilizes the sympy package, in order to parse `'expr'` and then symbolically simplify it. Verification is successful when the simplification leads to zero.

Notes:

- The provided `'expr'` should contain the symbolic functions defined in sympy's context for this tool. These are described in the docstring of the tool.

Example:

Defined functions:

```
def f(x):
    return sympy.Symbol("c") * x
```

```
>> symbolic_verify_tool("Eq(f(x) + f(y) - f(x+y), 0)")
>> True, ""
```

```
>> symbolic_verify_tool("f(x) + f(y) - f(x+y)")
>> True, ""
```

Args:

expr: A string representation of a sympy expression. If parsed by sympy, it $\hookrightarrow$ should lead to 'sympy.Expr' or 'sympy.Eq' that represents equality to zero.

Returns:

A tuple of (status, reason):
 - status is True if 'expr' is verified or False otherwise
 - reason states why the verification failed, which could be either error or $\hookrightarrow$ simplification to zero failed, reason is empty only when status is True

Pay attention to the reason part of the output as it conveys useful information $\hookrightarrow$ about what went wrong.

F.3. Agent Exploration Strategy

The agent's exploration strategy combines systematic search with mathematical intuition:

RSR Discovery Strategy

When searching for RSRs, think systematically:

1. Query Functions: What transformations of x make sense?
 - Additive: $x+r$, $x-r$, $x+2r$, etc.
 - Multiplicative: $x*r$, x/r (if applicable)
 - Compositions: $f(g(x+r))$ where g is related to f
2. Recovery Function: How do the queried values combine?
 - Linear combinations: $a*f(x+r) + b*f(x-r) + c*f(r)$
 - Products: $f(x+r)*f(x-r)*\dots$
 - Rational expressions: numerator/denominator forms
3. Mathematical Structure: What drives the relationship?
 - Symmetries (even, odd, periodic)
 - Algebraic identities (addition formulas, etc.)
 - Analytic properties (derivatives, series expansions)

Deep Exploration Strategy:

- When you find a property, ask: "Why does this hold? What does it tell me about the $\hookrightarrow$ function's structure?"
- Look for patterns: If $f(2x)$ has a special form, what about $f(3x)$, $f(4x)$?
- Consider special values: What happens at $x=0$, $x=\pi/4$, $x=\pi/2$?
- Explore symmetries: If you find one symmetry, are there related ones?
- Connect properties: How do discovered properties relate to each other?
- Form conjectures: Based on patterns, hypothesize new relationships

Quality over Quantity:

- Always verify discovered properties before including them in your answer
- If a property fails verification, analyze why - it might lead to insight
- Look for the most general form of a property
- Consider edge cases and domain restrictions

G. Evaluation Details

Function categories. The Tables 5 and 6 contain the functions that constitute each of the category of Figure 2.

Table 5. Function categories of Figure 2 (1-4)

Basic	Exponential	Logarithmic	Trigonometric
Identity	Exponential	Logarithm	Sine
Squared	Exp Minus One	Log2	Cosine
Cube	Exp Div By X	Log1p	Tangent
Fourth Power	Exp Div By X Composite	Logit	Cotangent
	2 to X	Log Cosine	Secant
	10 to X		Cosecant
	Exp X ²		Sinc
	Exp Cosine		Sinc Composite
	Exp Sin		

Table 6. Function categories of Figure 2 (5-8)

Hyperbolic	Inverse Trig.	ML Functions	Special
Hyperbolic Sine	Arcsine	Sigmoid	Gamma
Hyperbolic Cosine	Arccosine	Softmax2 1	Error Function
Hyperbolic Tangent	Arctangent	Softmax2 2	Gudermannian
	Hyperbolic Arcsine	ReLU	Square Root
	Hyperbolic Arccosine	Leaky ReLU	Cube Root
	Hyperbolic Arctangent	Swish	Absolute Value
		GELU	Sign
		Logistic	Floor
		Logistic Scaled	Ceiling
			Fractional Part

H. Generalization to Algebraic Structures

RSR-BENCH (Section 6) is restricted to scalar real-valued functions. To assess whether the BITWEEN pipeline applies more broadly, we constructed an additional benchmark set of 17 functions drawn from non-scalar algebraic structures, ranging from 2×2 matrices through non-associative algebras and Lie algebras. Functions over multi-dimensional inputs are encoded as scalars by flattening their inputs; BITWEEN’s symbolic and agentic backends operate unchanged. We use a 1800 s timeout per benchmark, matching the configuration of Section 6. The full set of benchmarks covers: 2×2 matrix functions (det additive/multiplicative, tr , $\text{tr}(A^2)$); quaternion norms ($\|q\|^2$, $\|q_1 q_2\|^2$); octonion norms ($\|o\|^2$, $\|o_1 o_2\|^2$); Clifford-algebra norms ($\text{Cl}(3, 0)$ conjugation norm, $\text{Cl}(2, 0)$ “determinant”); Lie-algebra invariants ($\text{tr}([A, B]^2)$ on $\mathfrak{gl}(2)$, the Killing form $B(X, X)$ on $\mathfrak{sl}(2)$); elementary symmetric polynomials e_2, e_3 and power sum p_2 over three variables; and vector operations ($\|v\|^2$ in 2D, $\|a \times b\|^2$).

Table 7. Aggregate evaluation information about the different methods on algebraic structures. The format of results is "RSR/verified|unverified", where the verified (unverified) properties passed (failed) automatic mathematical validation, and the RSR properties are a manually confirmed subset of the verified ones. The coverage information shows the (rounded) percentage of benchmarks for which the method returned at least one RSR. The format of time is "min|average|max" to show the (rounded) runtime range of each method. Highlighted are the methods with the most RSR count, most RSR coverage and least average runtime.

V-BITWEEN	PySR	GPLearn	MILP	LR
results	12 / 16 6	12 / 17 6	12 / 16 0	12 / 16 0
rsr coverage	65%	65%	65%	65%
time (sec)	7 60 306	0 54 344	0 2 9	0 1 6
N-RESEARCH		GPT-OSS-120B	Claude-Sonnet-4	Claude-Opus-4.1
results		79 / 121 3	76 / 134 7	107 / 203 8
rsr coverage		88%	88%	100%
time (sec)		6 14 31	46 64 99	174 269 363
A-BITWEEN		GPT-OSS-120B	Claude-Sonnet-4	Claude-Opus-4.1
results		79 / 105 0	139 / 294 0	170 / 371 0
rsr coverage		100%	94%	100%
time (sec)		8 16 41	81 114 160	238 378 554

Coverage. A-BITWEEN (Claude Opus 4.1 with *infer_property_tool* and *symbolic_verify_tool*) discovers verified RSRs on all 17/17 benchmarks (170 RSRs out of 371 verified properties in total; the complete list of discovered RSRs per benchmark is given in Table 21). V-BITWEEN-LR, restricted to the fixed query class $\{x+r, x-r, x \cdot r, x, r\}$ and polynomial recovery, returns 12 RSRs out of 16 verified properties across 11/17 benchmarks. Moreover, A-BITWEEN randomizes variables individually, illustrating the same query-function flexibility observed in Section 6. The purpose of this section is to demonstrate the breadth of the framework’s applicability; the algebraic benchmarks are reported separately from RSR-BENCH.

Implementation notes. The benchmarks are encoded as ordinary scalar-valued Python functions over flattened inputs; e.g., 2×2 matrices become $\mathbb{R}^4$ inputs and quaternions $\mathbb{R}^4$. The *infer_property_tool* and *symbolic_verify_tool* require no modification: the variables v_q continue to denote evaluations of the function at correlated samples, and the regression backend operates on monomials of those variables exactly as in Algorithm 1. For benchmarks whose input space splits into multiple natural components (e.g., $\|\mathbf{a} \times \mathbf{b}\|^2$ in two vectors $\mathbf{a}, \mathbf{b}$, or $\|q_1 q_2\|^2$ in two quaternions), the additive query functions randomize one component at a time, yielding RSRs that are linear in the other. We treat redundancy across the discovered properties the same way as in the main evaluation: properties that are algebraic consequences of others are not pruned, since Gröbner-basis reduction is impractical at the scale of properties BITWEEN produces.

Caveat. The verified properties hold with respect to the specific implementations of the benchmarks. We did not pursue Lie superalgebras, Moufang loops, or higher-rank simple Lie algebras, which were suggested as natural follow-ups, but we believe the same pipeline applies to those settings without architectural changes.

Detailed results. The complete list of verified RSRs discovered by A-BITWEEN (Claude Opus 4.1) on each of the 17 algebraic benchmarks is provided in Table 21. All runs use a 1800 s timeout per benchmark.

Table 8. RSR-Bench: Detailed results for V-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

V-Bitween		PySR		GPLearn		MILP		LR	
#	name	results	time	results	time	results	time	results	time
1	identity	2/2/0	36.74	2/2/0	1.86	2/2/0	0.83	2/2/0	1.35
2	exp	2/2/0	84.36	2/2/0	34.67	2/2/0	0.66	2/2/0	2.17
3	exp_minus_one	2/2/0	93.27	2/2/0	48.27	2/2/0	1.87	2/2/0	0.75
4	exp_div_by_x	0/0/0	142.38	0/0/0	68.18	0/0/0	0.25	0/0/0	0.67
5	exp_div_by_x_composite	1/1/0	85.61	1/1/0	80.46	1/1/0	1.26	1/1/0	0.98
6	floudas	2/2/0	22.66	2/2/0	0.61	2/2/0	0.73	2/2/0	0.39
7	mean	4/4/0	31.44	4/4/0	0.46	4/4/0	3.27	4/4/0	0.21
8	tan	3/3/1	273.17	2/2/0	141.97	1/1/0	22.3	3/3/0	2.81
9	cot	3/3/0	254.61	0/0/0	157.35	3/3/0	34.75	3/3/0	3.02
10	diff_squares	3/3/0	274.16	2/2/0	243.92	2/2/0	46.75	3/3/0	3.78
11	inverse_square	0/0/0	97.24	0/0/0	70.13	1/1/0	0.6	0/0/0	0.38
12	inverse	3/3/0	94.69	1/1/0	74.1	3/3/0	0.83	3/3/0	0.41
13	inverse_add	3/3/0	93.8	0/0/0	68.15	1/1/0	0.41	1/1/0	0.33
14	inverse_cot_plus_one	1/1/0	161.02	1/1/0	88.65	1/1/0	4.18	0/0/0	0.96
15	inverse_tan_plus_one	0/0/0	178.24	0/0/0	104.31	1/1/0	0.91	1/1/0	1.28
16	x_over_one_minus_x	0/0/1	93.79	0/0/0	100.09	1/1/0	0.64	1/1/0	1.65
17	minus_x_over_one_minus_x	0/0/0	94.49	0/0/0	89.45	1/1/0	0.55	1/1/0	0.73
18	cos	5/5/1	93.23	1/1/0	92.93	3/3/0	1.11	2/2/0	0.64
19	cosh	1/1/0	100.84	2/2/0	71.77	4/4/0	1.2	1/1/0	0.47
20	squared	2/2/1	98.75	1/1/0	65.64	1/1/0	11.93	2/2/1	0.73
21	sin	1/1/0	95.38	0/0/0	86.78	1/1/0	0.54	1/1/0	0.38
22	sinh	1/1/0	102.81	1/1/0	102.08	1/1/0	0.49	1/1/0	0.77
23	cube	0/0/0	103.71	0/0/0	123.07	0/0/0	1.31	1/1/1	0.77
24	log	1/1/0	14.34	1/1/0	0.24	1/1/0	0.09	1/1/0	0.13
25	sec	1/1/0	339.32	0/0/0	209.71	1/1/0	1.25	1/1/0	3.31
26	csc	0/0/2	868.85	0/0/1	629.41	2/2/3	9.5	2/2/1	19.12
27	sinc	1/1/2	478.63	0/0/0	362.93	1/1/0	19.31	1/1/0	3.51
28	sinc_composite	1/1/0	54.27	1/1/0	50.63	1/1/0	0.35	1/1/0	0.36
29	mod	0/0/1	12.78	0/0/1	0.28	0/0/1	0.06	0/0/1	0.13
30	mod_mult	0/0/1	21.33	0/0/1	31.51	0/0/1	0.12	0/0/1	0.18
31	int_mult	1/1/0	21.71	1/1/0	21.69	1/1/0	0.15	1/1/0	0.14
32	tanh	4/4/6	398.92	0/0/0	203.55	1/1/0	28.5	0/0/6	6.83
33	sigmoid	0/0/1	261.08	0/0/4	181.58	0/0/0	36.86	3/3/1	8.86
34	softmax2_1	2/2/1	95.08	1/1/0	51.6	1/1/0	1.16	1/1/1	0.79
35	softmax2_2	1/1/1	97.74	1/1/0	51.4	1/1/0	1.17	1/1/1	0.55
36	logistic	0/0/1	115.95	0/0/3	91.79	0/0/0	0.88	1/1/0	1.23
37	logistic_scaled	0/0/4	390.35	0/0/0	260.57	1/1/0	25.83	3/3/0	5.67
38	square_loss	0/0/0	107.76	0/0/0	101.82	4/4/0	1.36	1/1/0	1.1
39	savage_loss_library	0/0/0	322.96	0/0/12	175.99	0/0/0	27.03	1/1/0	2.44
40	savage_loss_basis	0/0/0	775.25	0/0/5	328.33	0/0/0	14.19	0/0/0	3.67

Table 9. RSR-Bench: Detailed results for V-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

V-Bitween		PySR		GPLearn		MILP		LR	
#	name	results	time	results	time	results	time	results	time
41	arcsin	0/0/0	409.19	0/0/7	187.35	0/0/0	38.08	0/0/0	11.47
42	arccos	0/0/0	405.79	0/0/0	212.76	0/0/0	37.84	0/0/0	17.46
43	arctan	0/0/1	420.99	0/0/0	194.35	0/0/0	21.68	0/0/0	10.6
44	arcsinh	0/0/0	705.85	0/0/0	218.16	0/0/0	15.77	0/0/0	11.94
45	arccosh	0/0/2	437.76	0/0/0	227.02	0/0/0	39.79	0/0/0	15.13
46	arctanh	0/0/0	405.8	0/0/0	165.81	0/0/0	32.1	0/0/0	10.37
47	relu	0/0/4	445.76	0/0/1	165.87	0/0/4	2.17	0/0/4	6.25
48	leaky_relu	0/0/0	587.97	0/0/0	201.53	0/0/0	2.75	0/0/0	5.45
49	swish	0/0/0	431.13	0/0/0	182.83	0/0/0	2.92	0/0/0	11.93
50	gelu	0/0/1	432.02	0/0/0	214.08	0/0/0	4.52	0/0/0	12.39
51	log1p	0/0/0	432.69	0/0/0	191.36	0/0/0	34.14	0/0/0	9.02
52	logit	0/0/0	449.87	0/0/0	206.99	0/0/0	17.37	0/0/0	14.04
53	log2	0/0/0	474.67	0/0/0	195.46	0/0/0	33.97	0/0/0	12.23
54	sqrt	0/0/1	446.9	5/5/0	182.35	2/2/1	37.65	3/3/1	3.98
55	cbrt	0/0/0	396.97	2/2/0	180.51	4/4/0	11.34	4/4/0	6.92
56	x_to_x	0/0/0	521.45	0/0/0	149.54	0/0/0	1.28	0/0/0	1.56
57	floor	0/0/0	496.39	0/0/0	188.08	0/0/3	5.27	0/0/3	8.67
58	ceil	0/0/0	492.95	0/0/0	167.71	0/0/3	4.93	0/0/3	8.75
59	frac	0/0/1	452.08	0/0/0	128.81	0/0/3	36.97	0/0/3	8.5
60	erf	0/0/1	444.8	0/0/1	122.66	0/0/0	27.43	0/0/0	8.34
61	gamma	0/0/0	550.09	0/0/0	155.98	0/0/0	1.31	0/0/0	2.24
62	exp_sin	0/0/1	510.29	0/0/0	116.89	0/0/0	3.01	0/0/0	8.59
63	sin_exp	0/0/1	504.2	0/0/0	115.65	0/0/0	5.03	0/0/0	4.98
64	log_cos	0/0/0	539.73	0/0/0	158.95	0/0/0	3.67	0/0/0	8.17
65	sqrt_one_plus_x2	0/0/1	537.75	0/0/0	209.0	1/1/0	32.81	5/5/0	5.22
66	abs	0/0/1	535.01	0/0/0	203.38	1/1/3	21.06	0/0/3	3.76
67	sign	0/0/6	377.98	1/1/10	34.32	0/0/7	5.82	0/0/9	3.53
68	gudermannian	0/0/1	463.92	0/0/0	196.04	0/0/0	24.08	0/0/2	8.93
69	2_to_x	2/2/6	431.65	3/3/4	60.22	2/2/0	4.01	3/3/1	3.25
70	10_to_x	3/3/2	488.72	4/4/1	57.09	2/2/0	1.77	3/3/1	0.89
71	pade_1_1	1/1/0	598.43	0/0/0	156.02	3/3/0	3.87	1/1/0	3.68
72	pade_2_2	0/0/0	494.0	0/0/0	193.74	0/0/0	3.43	0/0/0	9.83
73	continued_fraction_golden	0/0/4	443.65	0/0/2	176.31	0/0/0	37.05	1/1/0	4.26
74	continued_fraction_tan	0/0/0	500.75	0/0/1	124.89	0/0/0	7.69	0/0/0	6.07
75	mobius_simple	0/0/0	956.05	0/0/0	150.68	0/0/0	2.39	3/3/0	4.44
76	mobius_inversion	3/3/0	452.98	3/3/0	127.35	3/3/0	21.44	8/8/2	1.7
77	mobius_cayley	0/0/0	526.53	0/0/0	156.34	3/3/0	12.62	1/1/0	4.88
78	exp_x2	1/1/1	478.56	1/1/0	127.6	0/0/0	1.69	0/0/0	3.04
79	exp_cos	0/0/1	427.17	0/0/0	112.78	0/0/0	5.97	0/0/0	14.4
80	fourth	0/0/0	615.54	0/0/0	201.74	0/0/0	0.86	0/0/0	2.77

Table 10. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows $RSR/verified/unverified$ where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-GPT-OSS-120B			A-BITWEEN-GPT-OSS-120B		
#	name	results	time	tokens	results	time	tokens
1	identity	4 / 9 0	5.0	3189	5 / 10 0	12.18	19546
2	exp	4 / 5 0	5.91	3307	3 / 6 0	8.08	9901
3	exp_minus_one	4 / 7 0	7.53	3761	2 / 10 0	17.49	21078
4	exp_div_by_x	5 / 6 0	10.28	4576	4 / 5 0	22.49	21765
5	exp_div_by_x_composite	1 / 9 0	8.33	3858	3 / 15 0	32.1	33683
6	floudas	10 / 11 0	6.49	3539	5 / 12 0	10.33	15133
7	mean	17 / 19 2	9.32	4375	12 / 14 0	16.06	17109
8	tan	2 / 4 2	7.95	3788	2 / 5 0	26.22	23025
9	cot	0 / 2 5	6.43	3323	2 / 5 1	14.97	11447
10	diff_squares	4 / 8 2	8.44	4055	6 / 8 0	18.65	17460
11	inverse_square	1 / 5 0	7.47	3680	7 / 11 0	22.17	22478
12	inverse	5 / 9 0	11.72	4649	4 / 7 0	13.63	15475
13	inverse_add	3 / 7 0	8.2	3981	8 / 8 0	27.81	23614
14	inverse_cot_plus_one	2 / 3 1	19.42	6405	2 / 4 3	107.55	67560
15	inverse_tan_plus_one	2 / 5 1	17.44	6014	0 / 4 0	73.4	109990
16	x_over_one_minus_x	2 / 5 0	19.69	8973	4 / 6 0	41.92	30901
17	minus_x_over_one_minus_x	0 / 7 0	14.35	5409	0 / 5 0	16.25	11941
18	cos	7 / 7 0	9.42	3976	4 / 10 0	35.15	38658
19	cosh	2 / 4 0	7.94	3734	3 / 6 0	20.9	25845
20	squared	3 / 4 0	12.75	7230	2 / 7 0	10.43	10512
21	sin	4 / 10 0	8.93	4030	0 / 2 0	11.74	10480
22	sinh	2 / 4 1	10.15	4103	0 / 5 1	35.28	42813
23	cube	5 / 8 0	7.67	3780	5 / 9 0	21.03	26383
24	log	0 / 1 5	6.84	3474	0 / 0 1	13.22	19897
25	sec	4 / 5 3	10.63	4326	0 / 4 0	43.39	30912
26	csc	1 / 4 0	9.75	4093	3 / 4 0	16.41	11737
27	sinc	1 / 7 0	8.62	4002	2 / 11 0	23.23	17932
28	sinc_composite	1 / 5 0	9.51	4216	2 / 7 0	43.36	40851
29	mod	4 / 5 1	7.8	3649	4 / 4 1	8.79	10080
30	mod_mult	9 / 9 7	9.31	4044	3 / 5 0	8.47	5765
31	int_mult	11 / 13 0	10.09	4525	8 / 12 0	31.07	29253
32	tanh	2 / 4 2	8.83	3722	1 / 3 0	47.63	39230
33	sigmoid	2 / 4 0	9.08	4156	1 / 5 0	18.01	20921
34	softmax2_1	1 / 5 0	7.76	3879	2 / 6 0	17.55	20694
35	softmax2_2	1 / 2 0	10.21	4300	1 / 7 0	15.79	16261
36	logistic	3 / 4 0	8.13	3920	2 / 3 0	19.54	21233
37	logistic_scaled	3 / 3 0	8.05	3872	2 / 2 0	10.59	10646
38	square_loss	2 / 4 1	9.79	4272	4 / 5 0	52.86	62763
39	savage_loss_library	2 / 8 0	11.98	5023	0 / 5 0	11.01	10825
40	savage_loss_basis	2 / 6 0	14.52	5554	2 / 11 0	57.85	53468

Table 11. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-GPT-OSS-120B			A-BITWEEN-GPT-OSS-120B		
#	name	results	time	tokens	results	time	tokens
41	arcsin	0/0 6	10.44	4436	0/2 3	31.74	34589
42	arccos	0/0 5	10.0	4261	0/0 7	21.21	27216
43	arctan	0/0 4	9.25	4135	0/2 0	18.67	29481
44	arcsinh	0/2 4	10.2	4354	0/0 4	13.22	11458
45	arccosh	0/0 5	11.37	4572	0/1 3	20.66	21602
46	arctanh	0/2 5	9.82	4218	0/1 0	14.3	11234
47	relu	0/0 4	8.43	3894	0/2 0	40.32	51998
48	leaky_relu	0/0 4	13.76	4855	0/0 4	32.38	28132
49	swish	0/2 1	8.85	4073	1/3 0	70.09	75791
50	gelu	0/2 1	8.34	4019	0/1 0	10.59	10582
51	log1p	0/0 4	8.01	3895	1/2 4	16.54	16582
52	logit	1/1 4	13.46	5076	0/3 3	31.77	29399
53	log2	0/2 4	8.55	4090	2/4 4	33.68	45642
54	sqrt	0/1 1	8.48	3882	3/5 0	29.06	42396
55	cbirt	3/4 1	11.43	4665	0/1 5	40.94	31058
56	x_to_x	0/1 2	10.77	4366	0/1 0	15.45	19851
57	floor	0/1 5	6.57	3491	0/6 0	14.17	15410
58	ceil	0/2 2	6.85	3563	0/1 0	56.9	66779
59	frac	1/2 3	11.26	4556	1/4 0	19.79	25604
60	erf	0/2 0	6.7	3459	0/4 0	11.88	14933
61	gamma	0/3 0	9.22	3957	0/3 0	31.18	39199
62	exp_sin	0/5 0	8.36	3925	0/4 0	10.46	14966
63	sin_exp	0/1 1	10.36	4137	0/2 0	19.84	21250
64	log_cos	1/4 2	13.99	5051	0/3 1	15.67	11650
65	sqrt_one_plus_x2	0/3 2	14.16	5348	1/4 1	46.84	37355
66	abs	1/4 1	10.39	4227	4/6 0	11.4	10791
67	sign	0/2 3	6.23	3471	0/4 0	33.17	34550
68	gudermannian	0/5 2	13.08	4868	0/8 2	52.66	50558
69	2_to_x	5/7 0	5.96	3355	5/10 0	8.13	10067
70	10_to_x	7/9 1	6.53	3494	2/5 0	7.55	9789
71	pade_1_1	2/5 0	16.79	5985	3/6 0	49.99	25746
72	pade_2_2	0/4 0	17.69	5930	0/4 0	164.45	105694
73	continued_fraction_golden	2/5 0	25.08	7678	0/4 0	26.55	22953
74	continued_fraction_tan	0/3 0	11.2	6984	0/0 0	251.72	232694
75	mobius_simple	0/3 1	13.62	5089	1/6 0	30.44	38140
76	mobius_inversion	2/8 1	11.4	4706	3/7 0	12.87	11063
77	mobius_cayley	0/4 0	7.91	3878	0/7 0	26.27	22717
78	exp_x2	3/5 0	11.04	4564	4/6 0	20.34	21969
79	exp_cos	1/4 0	7.26	3615	0/0 0	6.23	5211
80	fourth	3/5 0	15.12	5412	6/7 0	16.22	16052

Table 12. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Sonnet-4			A-BITWEEN-Claude-Sonnet-4		
#	name	results	time	tokens	results	time	tokens
1	identity	11 / 14 0	76.56	72523	19 / 23 0	94.34	116045
2	exp	5 / 8 0	77.48	59248	14 / 19 0	134.85	208352
3	exp_minus_one	6 / 11 0	98.56	85650	3 / 9 0	103.21	160117
4	exp_div_by_x	5 / 8 0	127.98	117226	8 / 14 0	137.4	225614
5	exp_div_by_x_composite	1 / 9 0	79.04	73199	2 / 13 0	148.67	203231
6	floudas	13 / 13 0	62.46	46710	15 / 19 0	154.68	198116
7	mean	4 / 11 1	100.16	105685	8 / 20 0	178.9	210267
8	tan	4 / 8 2	79.16	64851	3 / 5 0	202.07	333322
9	cot	2 / 4 2	73.75	62706	3 / 6 0	168.8	386351
10	diff_squares	4 / 7 1	96.7	84077	7 / 15 0	166.54	210554
11	inverse_square	2 / 7 5	126.61	115485	6 / 13 0	110.32	163837
12	inverse	9 / 11 2	100.67	84224	15 / 20 0	153.24	269970
13	inverse_add	3 / 9 0	100.85	95844	1 / 7 0	119.14	191288
14	inverse_cot_plus_one	2 / 5 2	116.52	104265	0 / 6 0	151.78	266758
15	inverse_tan_plus_one	0 / 3 5	91.41	83102	2 / 8 0	162.67	260041
16	x_over_one_minus_x	1 / 2 0	202.51	226427	6 / 15 0	177.07	191624
17	minus_x_over_one_minus_x	0 / 4 0	95.87	95647	1 / 8 0	117.35	194789
18	cos	6 / 7 0	91.58	80138	7 / 14 0	177.47	308873
19	cosh	3 / 8 0	87.88	87287	3 / 8 0	122.56	165593
20	squared	3 / 7 0	73.48	60871	6 / 12 0	124.13	182489
21	sin	3 / 10 2	67.0	47290	4 / 10 0	179.48	294937
22	sinh	2 / 5 0	147.78	150742	1 / 4 0	148.37	262618
23	cube	5 / 7 1	98.34	79978	4 / 9 0	194.06	343691
24	log	1 / 1 9	89.79	73665	17 / 24 0	135.96	185441
25	sec	1 / 6 0	98.13	82419	0 / 8 0	199.81	275778
26	csc	0 / 9 0	163.98	154195	5 / 12 0	174.57	285118
27	sinc	0 / 6 0	83.94	64799	0 / 9 0	146.52	220690
28	sinc_composite	3 / 15 0	153.86	175108	1 / 7 0	142.12	242393
29	mod	1 / 2 1	146.86	145929	5 / 9 0	162.08	298231
30	mod_mult	1 / 1 19	120.25	109989	5 / 8 0	167.53	278986
31	int_mult	17 / 17 0	87.26	66961	19 / 19 0	157.15	226960
32	tanh	3 / 4 2	87.46	63696	4 / 5 2	161.2	226237
33	sigmoid	1 / 6 0	97.47	79153	3 / 8 0	188.38	306074
34	softmax2_1	2 / 5 0	80.65	74336	4 / 6 0	165.05	165683
35	softmax2_2	1 / 4 0	66.76	57991	1 / 6 0	171.52	240254
36	logistic	2 / 2 0	107.38	108422	5 / 5 0	141.15	205841
37	logistic_scaled	3 / 3 2	102.05	98842	8 / 9 0	122.04	175021
38	square_loss	2 / 10 0	133.55	122573	2 / 12 0	143.37	199591
39	savage_loss_library	0 / 6 0	120.28	100351	0 / 9 0	213.01	296163
40	savage_loss_basis	0 / 6 0	114.16	109035	2 / 10 0	223.81	213704

Table 13. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Sonnet-4			A-BITWEEN-Claude-Sonnet-4		
#	name	results	time	tokens	results	time	tokens
41	arcsin	0 / 1 6	77.42	60105	0 / 1 0	161.95	232643
42	arccos	0 / 0 5	112.17	104437	0 / 0 0	137.84	241726
43	arctan	0 / 1 8	114.72	107970	0 / 3 0	111.68	184977
44	arcsinh	0 / 1 4	81.59	61588	0 / 5 0	227.07	208540
45	arccosh	0 / 0 5	120.48	112024	0 / 0 3	160.19	302966
46	arctanh	0 / 1 4	75.03	61774	0 / 2 0	102.59	176189
47	relu	0 / 2 3	112.18	88873	5 / 8 0	134.31	226563
48	leaky_relu	0 / 0 4	111.95	105469	0 / 10 0	180.71	280483
49	swish	0 / 2 4	112.38	110649	0 / 7 0	211.97	321363
50	gelu	0 / 2 0	129.33	125500	0 / 6 0	274.03	322350
51	log1p	0 / 0 7	77.15	67781	0 / 4 0	214.99	433175
52	logit	0 / 0 3	144.16	153917	0 / 0 4	117.14	191204
53	log2	0 / 0 12	76.52	52740	0 / 0 5	118.1	162297
54	sqrt	1 / 2 6	86.29	64946	2 / 12 0	133.11	206511
55	cbrt	3 / 4 5	93.54	80906	1 / 15 0	144.53	249495
56	x_to_x	0 / 1 3	158.74	157957	0 / 1 0	175.04	337040
57	floor	0 / 2 5	130.91	136532	0 / 9 0	130.67	204937
58	ceil	0 / 0 0	113.27	110042	0 / 12 0	234.86	260619
59	frac	1 / 4 0	106.57	97760	1 / 6 0	114.14	198688
60	erf	0 / 1 0	90.93	75869	2 / 6 0	196.71	199673
61	gamma	5 / 8 0	95.86	66116	0 / 14 0	165.25	299349
62	exp_sin	0 / 6 0	99.55	102723	0 / 7 0	222.81	290241
63	sin_exp	0 / 3 2	157.06	158149	0 / 0 0	170.98	245223
64	log_cos	0 / 3 0	145.15	148474	0 / 5 0	155.88	262451
65	sqrt_one_plus_x2	6 / 7 0	141.78	134318	1 / 6 0	107.62	177635
66	abs	5 / 8 2	106.28	82975	6 / 12 0	142.01	247902
67	sign	0 / 2 7	121.97	111417	0 / 11 0	172.27	382770
68	gudermannian	0 / 2 0	109.23	100320	2 / 7 0	175.51	344911
69	2_to_x	10 / 15 0	94.2	83447	10 / 17 0	101.73	151991
70	10_to_x	6 / 8 0	55.87	43108	13 / 28 0	149.53	256135
71	pade_1_1	1 / 3 0	139.04	136232	3 / 7 0	146.41	265396
72	pade_2_2	0 / 3 0	147.66	148441	0 / 1 0	219.03	256213
73	continued_fraction_golden	1 / 3 0	185.05	185452	0 / 5 0	190.18	281724
74	continued_fraction_tan	0 / 2 0	94.36	94952	0 / 1 0	157.35	194440
75	mobius_simple	0 / 1 2	153.37	164887	2 / 5 0	224.84	279928
76	mobius_inversion	8 / 10 0	100.41	105920	8 / 16 0	141.2	236443
77	mobius_cayley	5 / 7 0	144.87	147153	3 / 6 0	110.09	199569
78	exp_x2	3 / 10 0	116.7	104140	6 / 9 0	112.76	149970
79	exp_cos	0 / 9 0	162.77	162208	2 / 13 0	158.7	231738
80	fourth	4 / 6 0	154.29	154470	7 / 9 0	229.93	349467

Table 14. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Opus-4.1			A-BITWEEN-Claude-Opus-4.1		
#	name	results	time	tokens	results	time	tokens
1	identity	18 / 20 0	200.05	46180	28 / 37 0	301.54	159252
2	exp	13 / 15 0	212.57	59273	28 / 31 0	269.8	137316
3	exp_minus_one	3 / 8 0	255.87	77856	12 / 19 0	317.52	148351
4	exp_div_by_x	1 / 8 0	296.98	123087	0 / 15 0	318.15	232014
5	exp_div_by_x_composite	5 / 25 0	370.11	113845	6 / 42 1	366.22	237713
6	floudas	14 / 15 0	225.77	60121	22 / 32 0	285.66	128678
7	mean	7 / 12 0	203.03	67272	40 / 61 0	346.67	143195
8	tan	4 / 4 2	298.87	106900	13 / 16 0	404.2	290118
9	cot	6 / 7 7	420.23	157075	5 / 18 0	396.39	308880
10	diff_squares	12 / 19 0	275.27	73524	7 / 13 0	418.23	233297
11	inverse_square	5 / 11 1	243.34	72722	13 / 22 0	331.21	191108
12	inverse	7 / 8 0	244.48	90119	12 / 15 0	235.62	153950
13	inverse_add	2 / 4 1	305.34	92624	4 / 16 0	339.21	175359
14	inverse_cot_plus_one	0 / 3 1	424.63	165347	4 / 19 0	407.26	313258
15	inverse_tan_plus_one	0 / 4 2	465.36	187034	1 / 25 0	434.04	373149
16	x_over_one_minus_x	5 / 9 0	296.43	80772	2 / 13 0	346.08	196981
17	minus_x_over_one_minus_x	1 / 5 3	404.34	184974	5 / 19 0	363.82	263690
18	cos	4 / 9 1	284.28	79514	8 / 18 0	335.22	194115
19	cosh	5 / 9 1	271.15	93621	11 / 20 0	324.89	235510
20	squared	4 / 8 0	260.3	73784	10 / 16 0	224.1	143345
21	sin	4 / 13 1	237.38	62584	23 / 28 0	329.83	197811
22	sinh	6 / 9 0	279.63	67028	23 / 31 0	449.44	315958
23	cube	6 / 9 0	211.81	66937	14 / 22 0	368.5	199232
24	log	0 / 0 12	223.29	59375	26 / 40 0	324.23	159466
25	sec	1 / 9 0	288.42	97191	3 / 17 0	378.29	250548
26	csc	2 / 8 0	358.18	142461	6 / 31 0	319.37	193804
27	sinc	0 / 9 0	311.54	103961	0 / 14 0	320.5	230150
28	sinc_composite	3 / 14 0	364.92	140236	3 / 13 0	423.02	252940
29	mod	4 / 8 1	208.58	57396	31 / 42 0	332.05	202822
30	mod_mult	6 / 8 1	234.27	55183	33 / 39 0	382.8	237518
31	int_mult	10 / 10 0	228.53	49844	25 / 29 0	220.67	101388
32	tanh	3 / 3 7	261.71	80280	8 / 9 0	351.45	206856
33	sigmoid	4 / 6 0	240.92	63287	6 / 19 0	367.14	235749
34	softmax2_1	2 / 5 0	260.71	87180	24 / 29 0	338.26	201190
35	softmax2_2	5 / 8 0	250.19	91066	21 / 34 0	343.32	227790
36	logistic	5 / 5 0	257.88	69555	6 / 14 0	381.24	219871
37	logistic_scaled	3 / 4 0	213.99	68698	15 / 23 0	575.24	298606
38	square_loss	4 / 9 0	292.58	81269	9 / 20 0	298.97	189401
39	savage_loss_library	0 / 12 0	270.58	67264	0 / 35 0	303.3	226778
40	savage_loss_basis	0 / 9 0	340.36	103239	8 / 28 0	431.14	255511

Table 15. RSR-Bench: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Opus-4.1			A-BITWEEN-Claude-Opus-4.1		
#	name	results	time	tokens	results	time	tokens
41	arcsin	2 / 3 4	304.19	98021	0 / 7 0	290.31	191672
42	arccos	0 / 0 7	249.58	87211	0 / 6 1	510.23	435457
43	arctan	0 / 1 6	252.2	72400	3 / 14 0	424.65	327069
44	arcsinh	0 / 1 6	239.96	72050	0 / 8 0	353.73	253236
45	arccosh	0 / 1 7	239.56	72373	0 / 0 7	385.6	262906
46	arctanh	0 / 1 7	202.57	50510	0 / 2 0	326.58	244283
47	relu	2 / 3 4	225.65	64591	5 / 16 0	448.69	314460
48	leaky_relu	0 / 3 6	270.11	75902	0 / 20 0	359.8	285997
49	swish	0 / 0 4	335.46	102736	0 / 4 0	411.51	286770
50	gelu	0 / 3 0	327.78	96863	0 / 9 0	400.62	171302
51	log1p	0 / 0 9	288.02	75889	0 / 4 0	412.63	335255
52	logit	0 / 0 5	308.0	94324	0 / 8 0	303.32	187537
53	log2	0 / 0 13	252.66	59312	0 / 0 11	331.74	224658
54	sqrt	0 / 7 5	196.82	50987	9 / 19 0	331.5	232788
55	cbrt	2 / 5 7	216.22	66906	12 / 22 0	508.04	278595
56	x_to_x	0 / 2 4	355.42	103767	0 / 8 1	567.0	522896
57	floor	0 / 0 3	251.19	85520	7 / 13 0	362.04	195537
58	ceil	0 / 5 1	231.07	58108	10 / 28 3	365.51	258759
59	frac	4 / 8 0	329.73	102805	4 / 13 0	513.19	240610
60	erf	0 / 2 0	280.5	92957	2 / 8 0	308.37	145059
61	gamma	2 / 7 1	233.47	59776	4 / 15 0	386.5	232067
62	exp_sin	2 / 9 1	227.16	59176	1 / 19 0	458.67	211398
63	sin_exp	0 / 1 3	254.33	73454	0 / 10 0	900.25	472386
64	log_cos	0 / 4 5	385.91	116767	1 / 13 0	338.82	216373
65	sqrt_one_plus_x2	4 / 7 1	371.89	115559	15 / 30 2	380.53	250673
66	abs	2 / 9 0	210.16	65369	9 / 22 0	365.03	264478
67	sign	0 / 3 5	222.92	54718	4 / 26 0	402.38	276697
68	gudermannian	2 / 3 1	340.9	115021	25 / 36 0	559.15	375409
69	2_to_x	11 / 15 0	209.92	57730	34 / 47 0	290.53	167144
70	10_to_x	11 / 16 0	214.86	47893	40 / 52 0	319.82	168196
71	pade_1_1	4 / 10 0	528.34	217531	3 / 11 0	444.68	331608
72	pade_2_2	0 / 2 0	397.38	209315	1 / 8 0	426.83	336419
73	continued_fraction_golden	0 / 0 7	385.87	117716	5 / 5 0	443.99	217405
74	continued_fraction_tan	0 / 2 3	302.93	92904	3 / 18 0	538.26	447376
75	mobius_simple	1 / 5 5	476.6	167430	10 / 17 0	445.0	272165
76	mobius_inversion	9 / 12 0	216.82	48270	22 / 32 0	326.77	178978
77	mobius_cayley	1 / 6 1	343.72	105845	4 / 14 0	385.37	275445
78	exp_x2	3 / 7 0	229.39	61074	15 / 24 0	235.73	128081
79	exp_cos	0 / 8 0	310.36	125098	5 / 17 0	335.22	179198
80	fourth	4 / 7 0	360.49	113135	11 / 19 0	327.59	195651

Table 16. Algebraic: Detailed results for V-BITWEEN. Results format shows $RSR/verified/unverified$ where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

V-Bitween		PySR		GPLEarn		MILP		LR	
#	name	results	time	results	time	results	time	results	time
A01	det2x2_additive	1 / 1 1 0	189.13	1 / 1 1 0	35.81	1 / 1 1 0	0.62	1 / 1 1 0	5.16
A02	det2x2_multiplicative	0 / 1 1 1	23.11	0 / 1 1 2	20.25	0 / 1 1 0	0.07	0 / 1 1 0	0.33
A03	trace2x2	2 / 2 1 0	6.68	2 / 2 1 0	0.24	2 / 2 1 0	0.06	2 / 2 1 0	0.1
A04	quaternion_norm_sq	1 / 1 1 0	39.85	1 / 1 1 0	42.96	1 / 1 1 0	9.24	1 / 1 1 0	0.45
A05	quaternion_norm_sq_mult	0 / 1 1 0	26.74	0 / 1 1 0	21.35	0 / 1 1 0	0.08	0 / 1 1 0	0.31
A06	trace_squared_2x2	1 / 1 1 0	37.98	1 / 1 1 0	37.43	1 / 1 1 0	0.44	1 / 1 1 0	0.48
A07	elem_sym_e2	1 / 1 1 0	31.25	1 / 1 1 0	37.32	1 / 1 1 0	0.44	1 / 1 1 0	0.45
A08	elem_sym_e3	0 / 0 1 0	105.73	0 / 0 1 0	104.03	0 / 0 1 0	0.44	0 / 0 1 0	1.12
A09	power_sum_p2	1 / 1 1 0	29.94	1 / 1 1 0	45.61	1 / 1 1 0	0.42	1 / 1 1 0	0.47
A10	dot_product_2d	1 / 1 1 0	30.53	1 / 1 1 0	27.38	1 / 1 1 0	0.38	1 / 1 1 0	0.45
A11	cross_product_sq	1 / 1 1 0	32.23	1 / 1 1 0	33.18	1 / 1 1 0	0.5	1 / 1 1 0	0.52
A12	octonion_norm_sq	1 / 1 1 0	46.28	1 / 1 1 0	58.63	1 / 1 1 0	9.33	1 / 1 1 0	5.59
A13	octonion_norm_sq_mult	0 / 1 1 0	22.44	0 / 2 1 0	21.73	0 / 1 1 0	0.15	0 / 1 1 0	0.36
A14	cl3_conj_norm	1 / 1 1 0	34.01	1 / 1 1 0	34.95	1 / 1 1 0	9.33	1 / 1 1 0	0.57
A15	cl2_det_mult	0 / 1 1 0	22.73	0 / 1 1 0	20.29	0 / 1 1 0	0.08	0 / 1 1 0	0.3
A16	lie_bracket_trace_sq	0 / 0 1 5	305.86	0 / 0 1 4	344.36	0 / 0 1 0	3.16	0 / 0 1 0	2.73
A17	sl2_killing	1 / 1 1 0	38.41	1 / 1 1 0	33.4	1 / 1 1 0	0.46	1 / 1 1 0	0.44

Table 17. Algebraic: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows $RSR/verified/unverified$ where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-GPT-OSS-120B			A-BITWEEN-GPT-OSS-120B		
#	name	results	time	tokens	results	time	tokens
A01	det2x2_additive	6 / 8 1 0	15.76	4579	5 / 7 1 0	20.47	19345
A02	det2x2_multiplicative	6 / 10 1 0	13.9	5161	4 / 6 1 0	11.28	11966
A03	trace2x2	4 / 4 1 0	6.5	3785	7 / 7 1 0	9.83	10999
A04	quaternion_norm_sq	3 / 4 1 1	11.39	4175	8 / 8 1 0	18.99	11047
A05	quaternion_norm_sq_mult	1 / 5 1 0	10.65	4108	3 / 5 1 0	11.86	16897
A06	trace_squared_2x2	7 / 10 1 1	9.66	4744	8 / 8 1 0	14.79	12732
A07	elem_sym_e2	3 / 3 1 0	16.39	4837	2 / 4 1 0	12.32	13168
A08	elem_sym_e3	6 / 12 1 0	6.22	3777	6 / 8 1 0	8.29	10949
A09	power_sum_p2	6 / 6 1 0	11.22	3902	6 / 6 1 0	11.22	12535
A10	dot_product_2d	5 / 6 1 0	14.48	3719	6 / 6 1 0	9.49	11320
A11	cross_product_sq	3 / 9 1 0	31.0	5217	4 / 7 1 0	27.69	18328
A12	octonion_norm_sq	16 / 18 1 0	17.26	5132	4 / 5 1 0	13.25	12035
A13	octonion_norm_sq_mult	0 / 0 1 0	12.56	4668	1 / 5 1 0	16.21	17749
A14	cl3_conj_norm	4 / 5 1 0	17.34	5273	3 / 3 1 0	15.43	12706
A15	cl2_det_mult	0 / 7 1 0	12.69	4398	1 / 7 1 0	40.69	52272
A16	lie_bracket_trace_sq	2 / 5 1 0	19.53	14239	4 / 6 1 0	22.28	27525
A17	sl2_killing	7 / 9 1 1	12.48	4336	7 / 7 1 0	10.31	11258

Table 18. Algebraic: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Sonnet-4			A-BITWEEN-Claude-Sonnet-4		
#	name	results	time	tokens	results	time	tokens
A01	det2x2_additive	4 / 6 2	55.95	49719	14 / 16 0	138.87	234404
A02	det2x2_multiplicative	10 / 12 0	99.18	64550	12 / 23 0	105.28	147632
A03	trace2x2	9 / 11 0	52.46	47188	9 / 14 0	80.55	119385
A04	quaternion_norm_sq	5 / 5 1	64.93	50467	14 / 16 0	93.87	133266
A05	quaternion_norm_sq_mult	0 / 7 0	57.15	50592	3 / 21 0	91.71	164029
A06	trace_squared_2x2	5 / 5 0	71.3	60141	6 / 16 0	115.77	221481
A07	elem_sym_e2	1 / 4 0	73.57	63566	9 / 28 0	145.11	234221
A08	elem_sym_e3	13 / 19 0	54.67	49602	15 / 21 0	95.47	162069
A09	power_sum_p2	7 / 13 0	55.24	47526	6 / 15 0	94.17	146005
A10	dot_product_2d	5 / 9 0	46.22	42052	14 / 22 0	130.86	198969
A11	cross_product_sq	2 / 8 0	83.01	81392	5 / 14 0	104.87	182784
A12	octonion_norm_sq	2 / 6 0	47.03	45745	5 / 7 0	94.66	131503
A13	octonion_norm_sq_mult	0 / 8 0	58.78	53718	0 / 24 0	160.12	280372
A14	cl3_conj_norm	3 / 5 0	60.3	51419	10 / 19 0	137.55	251781
A15	cl2_det_mult	4 / 7 3	83.58	59035	1 / 10 0	88.38	179987
A16	lie_bracket_trace_sq	2 / 3 1	75.84	55809	5 / 14 0	159.16	271438
A17	sl2_killing	4 / 6 0	52.8	46161	11 / 14 0	107.25	163476

Table 19. Algebraic: Detailed results for N-RESEARCH and A-BITWEEN. Results format shows *RSR/verified/unverified* where the *verified*, *unverified* properties passed or failed automatic mathematical confirmation, respectively, while the *RSR* properties are a manually confirmed subset of the *verified* ones.

Models		N-RESEARCH-Claude-Opus-4.1			A-BITWEEN-Claude-Opus-4.1		
#	name	results	time	tokens	results	time	tokens
A01	det2x2_additive	7 / 10 6	252.76	71500	17 / 40 0	554.24	280420
A02	det2x2_multiplicative	7 / 13 0	362.74	90413	13 / 19 0	386.44	178343
A03	trace2x2	6 / 6 0	176.23	54962	15 / 23 0	237.91	117715
A04	quaternion_norm_sq	6 / 16 0	321.93	86532	5 / 15 0	337.02	179555
A05	quaternion_norm_sq_mult	2 / 15 0	215.62	48693	5 / 18 0	326.19	164759
A06	trace_squared_2x2	10 / 10 0	271.66	93206	16 / 33 0	369.57	228161
A07	elem_sym_e2	13 / 20 2	252.41	68016	12 / 30 0	399.43	244630
A08	elem_sym_e3	20 / 29 0	205.13	44957	6 / 26 0	285.19	124842
A09	power_sum_p2	6 / 18 0	345.3	109908	6 / 19 0	340.02	219582
A10	dot_product_2d	5 / 10 0	330.72	98516	8 / 23 0	342.45	190731
A11	cross_product_sq	6 / 13 0	359.97	108035	6 / 24 0	446.47	345199
A12	octonion_norm_sq	2 / 8 0	276.03	76601	17 / 21 0	406.52	213186
A13	octonion_norm_sq_mult	2 / 7 0	174.11	51683	2 / 16 0	419.99	221112
A14	cl3_conj_norm	3 / 6 0	287.14	78846	16 / 18 0	551.5	261547
A15	cl2_det_mult	3 / 9 0	235.26	58136	6 / 12 0	385.72	267183
A16	lie_bracket_trace_sq	4 / 5 0	262.53	66237	3 / 9 0	329.84	198547
A17	sl2_killing	5 / 8 0	247.99	74198	17 / 25 0	300.77	179231

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench. Results show comprehensive mathematical relationships discovered through novel query functions.

Function	Discovered RSR Properties
1. Identity	$ \begin{aligned} &f(r) + f(x) - f(r + x) = 0 \\ &-f(x) - f(y) + f(x + y) = 0 \\ &-f(x) + f(y) + f(x - y) = 0 \\ &-f(r) - f(x) + f(r + x) = 0 \\ &-f(r) + f(x) - f(-r + x) = 0 \\ &f(2x) - 2f(y) - 2f(x - y) = 0 \\ &2f(x) - f(-r + x) - f(r + x) = 0 \\ &-2f(r) - f(-r + x) + f(r + x) = 0 \\ &-2f(x) + f(-r + x) + f(r + x) = 0 \\ &-af(x) - bf(y) + f(ax + by) = 0 \\ &-af(x) - bf(r) + f(ax + br) = 0 \\ &-3f(r) - 2f(x) + f(3r + 2x) = 0 \\ &-2f(r) - f(-r + x) + f(r + x) = 0 \\ &-f(z) - f(x + y) + f(x + y + z) = 0 \\ &-4f(r) - f(-2r + x) + f(2r + x) = 0 \\ &-2f(x) + f(-2r + x) + f(2r + x) = 0 \\ &-6f(r) - f(-3r + x) + f(3r + x) = 0 \\ &-2f(x) + f(-ar + x) + f(ar + x) = 0 \\ &-2af(r) - f(-ar + x) + f(ar + x) = 0 \\ &f(r) + f(y) - f(r + x) + f(x - y) = 0 \\ &f(x) - \frac{f(-r + x)}{2} - \frac{f(r + x)}{2} = 0 \\ &-f(x) - f(y) - f(z) + f(x + y + z) = 0 \\ &-f(x) - f(y) + f(z) + f(x + y - z) = 0 \\ &-f(x) + f(y) + f(z) + f(x - y - z) = 0 \\ &-2f(y) + f(-r + x) + f(r + x) - 2f(x - y) = 0 \\ &14f(r) - 2f(2r) + 2f(-2r + x) + f(-r + x) - f(r + x) - 2f(2r + x) = 0 \\ &-2f(r) + 11f(2r) + 4f(-2r + x) + 2f(-r + x) - 2f(r + x) \\ &\quad - 4f(2r + x) = 0 \\ &2f\left(\frac{x}{2}\right) + 4f(x) - 7f(3x) + 4f(-2r + x) + 4f(-r + x) + 4f(r + x) \\ &\quad + 4f(2r + x) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
2. Exponential	$-f^n(x) + f(nx) = 0$ $f^2(r+x) - f(2r+2x) = 0$ $f^2(x-y) - f(2x-2y) = 0$ $-f(-2r+2x) + f^2(-r+x) = 0$ $-f(r)f(x) + f(r+x) = 0$ $f(r)f(-r+x) - f(x) = 0$ $-f(x)f(y) + f(x+y) = 0$ $-f(x) + f(y)f(x-y) = 0$ $-f(3r)f(x) + f(3r+x) = 0$ $-f^2(r)f(x) + f(2r+x) = 0$ $f^2(r)f(-2r+x) - f(x) = 0$ $f(s)f(r-s+x) - f(r+x) = 0$ $f(z)f(x+y-z) - f(x+y) = 0$ $-f(r)f(r+x) + f(2r+x) = 0$ $-f^3(r)f(x) + f(3r+x) = 0$ $-f(2x) + f(-r+x)f(r+x) = 0$ $f(r)f(-r+s+x) - f(s+x) = 0$ $-f(s)f(r+x) + f(r+s+x) = 0$ $-f(x)f(r+s) + f(r+s+x) = 0$ $f(-r+y)f(r+x) - f(x+y) = 0$ $-f(2r)f(2x) + f^2(r+x) = 0$ $-f^2(x) + f(-r+x)f(r+x) = 0$ $f(r+x)f(r+y) - f(2r+x+y) = 0$ $-f(2x) + f(-2r+x)f(2r+x) = 0$ $-f^2(2x) + f^2(-r+x)f^2(r+x) = 0$ $f(x)f(y)f(z) - f(x+y+z) = 0$ $-f(x)f(y)f(z) + f(x+y+z) = 0$ $-f(a)f(b)f(x) + f(a+b+x) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
3. Exp Minus One	$\begin{aligned} & (f(r) + 1) f(x) + f(r) - f(r + x) = 0 \\ & -f(x)f(y) - f(x) - f(y) + f(x + y) = 0 \\ & (f(-r) + 1) f(x) + f(-r) - f(-r + x) = 0 \\ & -f(2r)f(x) - f(2r) - f(x) + f(2r + x) = 0 \\ & -f(r)f(2x) - f(r) - f(2x) + f(r + 2x) = 0 \\ & f(r)f(-r + x) + f(r) - f(x) + f(-r + x) = 0 \\ & -f(-z)f(x + y) - f(-z) - f(x + y) + f(x + y - z) = 0 \\ & -f\left(\frac{x}{2}\right)f\left(\frac{y}{2}\right) - f\left(\frac{x}{2}\right) - f\left(\frac{y}{2}\right) + f\left(\frac{x}{2} + \frac{y}{2}\right) = 0 \\ & f(-r)f(r) + f(-r) - 3f(r)f(x) - 2f(r) - 3f(x) + 3f(r + x) = 0 \\ & -f(x)f(y)f(z) - f(x)f(y) - f(x)f(z) - f(x) - f(y)f(z) - f(y) - f(z) \\ & \quad + f(x + y + z) = 0 \\ & -f(r)f(s)f(x) - f(r)f(s) - f(r)f(x) - f(r) - f(s)f(x) - f(s) - f(x) \\ & \quad + f(r + s + x) = 0 \\ & -((f(-r) + 1) f(r) + (f(r) + 1) f(-r)) f(x) - (f(-r) + 1) (f(r) + 1) f^2(x) \\ & \quad - f(-r)f(r) + f(-r + x)f(r + x) = 0 \end{aligned}$
4. Exp Div By X Composite	$\begin{aligned} & xf(x + y) + yf(x + y) - h(x + y) = 0 \\ & xf(x - y) - yf(x - y) - h(x - y) = 0 \\ & (x + y + z) f(x + y + z) - h(x + y + z) = 0 \\ & (r + x) f(r + x) - h(r)h(x) = 0 \\ & (-r + x) f(-r + x) - \frac{h(x)}{h(r)} = 0 \\ & (x + y + z) f(x + y + z) - h(x)h(y)h(z) = 0 \end{aligned}$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
6. Floudas	$ \begin{aligned} & -r - f(x, y) + f(r + x, y) = 0 \\ & -s - f(x, y) + f(x, s + y) = 0 \\ & -r - s - f(x, y) + f(r + x, s + y) = 0 \\ & -s - f(r + x, y) + f(r + s + x, y) = 0 \\ & -s - f(x, r + y) + f(x, r + s + y) = 0 \\ & -2s - f(r + x, -s + y) + f(r + x, s + y) = 0 \\ & -2r - f(-r + x, s + y) + f(r + x, s + y) = 0 \\ & f(x, y) - 2f(r + x, y) + f(2r + x, y) = 0 \\ & f(x, y) - 2f(x, s + y) + f(x, 2s + y) = 0 \\ & 2f(x, y) - f(-r + x, y) - f(r + x, y) = 0 \\ & -2f(x, y) + f(-r + x, y) + f(r + x, y) = 0 \\ & -2f(x, y) + f(x, -s + y) + f(x, s + y) = 0 \\ & -x(a + c) - y(b + d) + f(ax + by, cx + dy) = 0 \\ & -2f(x, y) + f(-r + x, -s + y) + f(r + x, s + y) = 0 \\ & -2f(x, y) + f(-r + x, s + y) + f(r + x, -s + y) = 0 \\ & f(x, y) - f(x, s + y) - f(r + x, y) + f(r + x, s + y) = 0 \\ & f(x, y) - f(a + x, y) - f(b + x, y) + f(a + b + x, y) = 0 \\ & f(x, y) - f(x, a + y) - f(x, b + y) + f(x, a + b + y) = 0 \\ & -f(x, y) + f(x, s + y) + f(r + x, y) - f(r + x, s + y) = 0 \\ & f(x, y) - f(r + x, t + y) - f(s + x, y) + f(r + s + x, t + y) = 0 \\ & -f(x, y) + f(a + x, b + y) + f(c + x, d + y) - f(a + c + x, b + d + y) = 0 \\ & 2f(x, y) - f(x, r + y) - f(x, s + y) - f(x, t + y) + f(x, r + s + t + y) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
7. Mean	$ \begin{aligned} &f(0, y, x + z) - f(x, y, z) = 0 \\ &f(0, x + y, z) - f(x, y, z) = 0 \\ &-f(x, y, z) + f(x + y, 0, z) = 0 \\ &-f(x, y, z) + f(x, y + z, 0) = 0 \\ &-f(x, y, z) + f(x + y, z, 0) = 0 \\ &-f(x, y, z) + f(z, 0, x + y) = 0 \\ &f(0, x + y + z, 0) - f(x, y, z) = 0 \\ &f(0, 0, x + y + z) - f(x, y, z) = 0 \\ &-f(x, y, z) + f(x + y + z, 0, 0) = 0 \\ &-f(x, y, r + z) + f(r + x, y, z) = 0 \\ &-f(x, y, r + z) + f(x, r + y, z) = 0 \\ &-f(x, r + y, z) + f(r + x, y, z) = 0 \\ &-f(x, y, z) + f(r + x, -r + y, z) = 0 \\ &-f(x, y, z) + f(x, r + y, -r + z) = 0 \\ &-f(x, y, z) + f(r + x, y, -r + z) = 0 \\ &-f(x, y, -r + z) + f(-r + x, y, z) = 0 \\ &-f(x, y, -r + z) + f(x, -r + y, z) = 0 \\ &-f(x, y, z) + f(r + x, s + y, -r - s + z) = 0 \\ &-f(r, 0, 0) - f(x, y, z) + f(r + x, y, z) = 0 \\ &-f(0, r, 0) - f(x, y, z) + f(x, r + y, z) = 0 \\ &-f(0, 0, r) - f(x, y, z) + f(x, y, r + z) = 0 \\ &-f(r, s, 0) - f(x, y, z) + f(r + x, s + y, z) = 0 \\ &-f(r, 0, s) - f(x, y, z) + f(r + x, y, s + z) = 0 \\ &-f(0, r, s) - f(x, y, z) + f(x, r + y, s + z) = 0 \\ &-2f(r, 0, 0) - f(x, y, z) + f(2r + x, y, z) = 0 \\ &-f(r, r, 0) - f(x, y, z) + f(r + x, r + y, z) = 0 \\ &-f(r, 0, r) - f(x, y, z) + f(r + x, y, r + z) = 0 \\ &-f(0, r, r) - f(x, y, z) + f(x, r + y, r + z) = 0 \\ &-f(x, y, z) + f\left(r + x, -\frac{r}{2} + y, -\frac{r}{2} + z\right) = 0 \\ &-f(r, r, r) - f(x, y, z) + f(r + x, r + y, r + z) = 0 \\ &-f(r, s, t) - f(x, y, z) + f(r + x, s + y, t + z) = 0 \\ &-2f(r, 0, 0) - f(-r + x, y, z) + f(r + x, y, z) = 0 \\ &-2f(0, r, 0) - f(x, -r + y, z) + f(x, r + y, z) = 0 \\ &-2f(0, 0, r) - f(x, y, -r + z) + f(x, y, r + z) = 0 \\ &-2f(x, y, z) + f(-r + x, -s + y, z) + f(r + x, s + y, z) = 0 \\ &-2f(x, y, z) + f(-r + x, y, -s + z) + f(r + x, y, s + z) = 0 \\ &-2f(x, y, z) + f(x, -r + y, -s + z) + f(x, r + y, s + z) = 0 \\ &-2f(x, y, z) + f(-r + x, -s + y, -t + z) + f(r + x, s + y, t + z) = 0 \\ &f(x, x, x) + f(y, y, y) + f(z, z, z) - f(x + y + z, x + y + z, x + y + z) = 0 \\ &f\left(\frac{r}{3}, \frac{r}{3}, \frac{r}{3}\right) - f(x, y, z) + f\left(-\frac{r}{3} + x, -\frac{r}{3} + y, -\frac{r}{3} + z\right) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
8. Tangent	$f(x - y) - \frac{f(x) - f(y)}{f(x)f(y) + 1} = 0$ $f(x + y) - \frac{f(x) + f(y)}{-f(x)f(y) + 1} = 0$ $-f(r)f(x)f(r + x) - f(r) - f(x) + f(r + x) = 0$ $f(r)f(x)f(-r + x) + f(r) - f(x) + f(-r + x) = 0$ $-f(r)f(2x)f(r + 2x) - f(r) - f(2x) + f(r + 2x) = 0$ $-f(2r)f(x)f(2r + x) - f(2r) - f(x) + f(2r + x) = 0$ $f(r)f(2x)f(-r + 2x) + f(r) - f(2x) + f(-r + 2x) = 0$ $f(2r)f(x)f(-2r + x) + f(2r) - f(x) + f(-2r + x) = 0$ $-f(s)f(r + x)f(r + s + x) - f(s) - f(r + x) + f(r + s + x) = 0$ $(-f^2(r)f^2(x) + 1)f(-r + x)f(r + x) + f^2(r) - f^2(x) = 0$ $(-f^2(r)f^2(x) + 1)(-f(-r + x) + f(r + x)) - 2(f^2(x) + 1)f(r) = 0$ $f(r)f(-r + x) - f(r)f(r + x) + f(x)f(-r + x) + f(x)f(r + x)$ $-2f(-r + x)f(r + x) = 0$ $-(-f(x)f(y) - f(x)f(z) - f(y)f(z) + 1)f(x + y + z) - f(x)f(y)f(z) + f(x)$ $+ f(y) + f(z) = 0$
9. Cotangent	$(f(x) + f(y))f(x + y) - f(x)f(y) + 1 = 0$ $(f(x) - f(y))f(x - y) + f(x)f(y) + 1 = 0$ $-(f(x) + f(y))f(x + y) + f(x)f(y) - 1 = 0$ $-2f(x)f(y) - f(x)f(x - y) + f(x)f(x + y) + f(y)f(x - y)$ $+ f(y)f(x + y) = 0$ $-2f(r)f(x) + f(r)f(-r + x) + f(r)f(r + x) - f(x)f(-r + x)$ $+ f(x)f(r + x) = 0$
10. Difference of Squares	$-2f(x, y) + f(-r + x, -r + y) + f(r + x, r + y) = 0$ $-2f(x, y) + f(-r + x, r + y) + f(r + x, -r + y) = 0$ $-2rx + 2sy - f(r, s) - f(x, y) + f(r + x, s + y) = 0$ $-2f(r, 0) - 2f(x, y) + f(-r + x, y) + f(r + x, y) = 0$ $8rx + f(-r + x, -s + y) + f(-r + x, s + y) - f(r + x, -s + y)$ $- f(r + x, s + y) = 0$ $-8sy + f(-r + x, -s + y) - f(-r + x, s + y) + f(r + x, -s + y)$ $- f(r + x, s + y) = 0$ $-4r^2 + 4s^2 - 4f(x, y) + f(-r + x, -s + y) + f(-r + x, s + y)$ $+ f(r + x, -s + y) + f(r + x, s + y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
11. Inverse Square	$f(xy) - \frac{1}{x^2y^2} = 0$ $(x+y)^2 f(x+y) - 1 = 0$ $(x-y)^2 f(x-y) - 1 = 0$ $f\left(\frac{x}{y}\right) - \frac{y^2}{x^2} = 0$ $-y^2 f(x) + f\left(\frac{x}{y}\right) = 0$ $f(2x+y) - \frac{1}{(2x+y)^2} = 0$ $f(2x-y) - \frac{1}{(2x-y)^2} = 0$ $f(x+y+z) - \frac{1}{(x+y+z)^2} = 0$ $f(x-y-z) - \frac{1}{(x-y-z)^2} = 0$ $f(ax+by) - \frac{1}{(ax+by)^2} = 0$ $(x^2 - y^2)^2 f(x-y)f(x+y) - 1 = 0$ $(x-y)^2 (x+y)^2 f(x-y)f(x+y) - 1 = 0$ $-2f(x)f(y) + f(x)f(x-y) + f(x)f(x+y) + f(y)f(x-y) + f(y)f(x+y)$ $-8f(x-y)f(x+y) = 0$
12. Inverse	$cf(cx) - f(x) = 0$ $-rf(x) + f\left(\frac{x}{r}\right) = 0$ $-xf(r) + f\left(\frac{r}{x}\right) = 0$ $-cf(x) + f\left(\frac{x}{c}\right) = 0$ $f\left(\frac{x}{r}\right)f\left(\frac{r}{x}\right) - 1 = 0$ $-f(r)f(x) + f(rx) = 0$ $f(r) - f(x)f\left(\frac{r}{x}\right) = 0$ $-f^2(x)f\left(\frac{r}{x}\right) + f(rx) = 0$ $f(-r+x)f(r+x) - f(-r^2+x^2) = 0$ $2rf(-r^2+x^2) - f(-r+x) + f(r+x) = 0$ $-2xf(-r^2+x^2) + f(-r+x) + f(r+x) = 0$ $-2f(r)f(x) + f(r)f(-r+x) + f(r)f(r+x) - f(x)f(-r+x)$ $+ f(x)f(r+x) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
13. Inverse Add	$f(x)f(y) - f(xy + x + y) = 0$ $f(x)f(y)f(z) - f(xyz + xy + xz + x + yz + y + z) = 0$ $-f(x)f(-r + x) - f(x)f(r + x) + 2f(-r + x)f(r + x) = 0$ $f(w)f(x)f(y)f(z) - f(wxyz + wxy + wxz + wx + wyz + wy + wz + w + xyz + xy + xz + x + yz + y + z) = 0$
14. Inverse Cot Plus One	$f(y)f(x + y) + f(x + y)f\left(-y + \frac{\pi}{2}\right) - f(x + y) = 0$ $f(y)f(x - y) + f(x - y)f\left(-y + \frac{\pi}{2}\right) - f(x - y) = 0$ $2f(r)f(x)f(r + x) - 2f(r)f(x) + f(r) + f(x) - f(r + x) = 0$ $2f(r)f(x)f(-r + x) - 2f(r)f(-r + x) + f(r) - f(x) + f(-r + x) = 0$
15. Inverse Tan Plus One	$(\sin(r + x) + \cos(r + x))f(r + x) - \cos(r + x) = 0$
16. X Over One Minus X	$-f(r)f(x) + f(r)f(rx) + f(x)f(rx) + f(rx) = 0$ $-f(x)f(-r + x) - f(x)f(r + x) - 2f(x) + 2f(-r + x)f(r + x) + f(-r + x) + f(r + x) = 0$
17. Minus X Over One Minus X	$-r - x + f(f(r + x)) = 0$ $r - x + f(f(-r + x)) = 0$ $-(1 - r)f(r) - (1 - x)f(x) + (-r - x + 1)f(r + x) = 0$ $-f(r)f(x) + f(r)f(rx) + f(x)f(rx) - f(rx) = 0$ $-f(x)f(-r + x) - f(x)f(r + x) + 2f(x) + 2f(-r + x)f(r + x) - f(-r + x) - f(r + x) = 0$
18. Cosine	$2f(x)f(y) - f(x - y) - f(x + y) = 0$ $-2f(x)f(y) + f(x - y) + f(x + y) = 0$ $f(x) - 2f(y)f(x - y) + f(x - 2y) = 0$ $-2f(r)f(x) + f(-r + x) + f(r + x) = 0$ $-2f(r)f(r + x) + f(x) + f(2r + x) = 0$ $-2f(x)f(nr) + f(-nr + x) + f(nr + x) = 0$ $f^2(r) - 2f(r)f(x)f(r + x) + f^2(x) + f^2(r + x) - 1 = 0$ $-2f^2(x) + 4f(x)f(y)f(x + y) - 2f^2(y) - 2f^2(x + y) + 2 = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
19. Hyperbolic Cosine	$2f(x)f(y) - f(x - y) - f(x + y) = 0$ $-2f(x)f(y) + f(x - y) + f(x + y) = 0$ $-2f(r)f(x) + f(-r + x) + f(r + x) = 0$ $-2f(r)f(x) + f(-r + x) + f(r + x) = 0$ $f^2(x) + f^2(y) - f(x - y)f(x + y) - 1 = 0$ $-f^2(x) - f^2(y) + f(x - y)f(x + y) + 1 = 0$ $f(r)f(-r + x) + f(r)f(r + x) - f(2r)f(x) - f(x) = 0$ $-f(r)f(2x) - f(r) + f(x)f(-r + x) + f(x)f(r + x) = 0$ $f(x)f(z) + f(y)f(x + y + z) - f(x + y)f(y + z) - f(x + z) = 0$ $f(x)f(y) + f(z)f(x + y + z) - f(x + y) - f(x + z)f(y + z) = 0$ $f(x)f(x + y + z) + f(y)f(z) - f(x + y)f(x + z) - f(y + z) = 0$
20. Squared	$-n^2f(x) + f(nx) = 0$ $2f(x) + 2f(y) - f(x - y) - f(x + y) = 0$ $-2f(x) - 2f(y) + f(x - y) + f(x + y) = 0$ $-2f(a) - 2f(b) + f(a - b) + f(a + b) = 0$ $-2f(r) - 2f(x) + f(-r + x) + f(r + x) = 0$ $f(2x) + 4f(y) - 2f(x - y) - 2f(x + y) = 0$ $2xy + 2xz + 2yz + f(x) + f(y) + f(z) - f(x + y + z) = 0$ $-4f(r) - f(x) + f(-r + x) - f(r + x) + f(2r + x) = 0$ $f(x) + f(y) + f(z) - f(x + y) - f(x + z) - f(y + z) + f(x + y + z) = 0$ $f(x) + f(y) + f(z) - f(x + y) - f(x + z) - f(y + z) + f(x + y + z) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
21. Sine	$f^2(x) - f^2(y) - f(x - y)f(x + y) = 0$ $f^2(r) - f^2(x) + f(-r + x)f(r + x) = 0$ $f^2(r) + f(x)f(2r + x) - f^2(r + x) = 0$ $f^2(a) - f^2(x) + f(-a + x)f(a + x) = 0$ $-f^2(x) + f^2(y) + f(x - y)f(x + y) = 0$ $f(2x)f(2y) + f^2(x - y) - f^2(x + y) = 0$ $f(x)f(2y) - f(y)f(x - y) - f(y)f(x + y) = 0$ $f(x)f(x - y) - f(x)f(x + y) + f(2x)f(y) = 0$ $f(r)f(-r + x) + f(r)f(r + x) - f(2r)f(x) = 0$ $-f(r)f(x) - f(r)f(2r + x) + f(2r)f(r + x) = 0$ $f^2(x)f(y) - f^3(y) - f(y)f(x - y)f(x + y) = 0$ $-f(x)f(x - y) + f(y)f(2y) + f(x - 2y)f(x + y) = 0$ $f(r)f(2r) - f(x)f(r + x) + f(-r + x)f(2r + x) = 0$ $-f^2(x)f(x + y) + f^2(y)f(x + y) + f(x - y)f^2(x + y) = 0$ $-f^2(x)f(x - y) + f^2(y)f(x - y) + f^2(x - y)f(x + y) = 0$ $f^2(x)f(2y) - 2f(x)f(y)f(x + y) + f(2x)f^2(y) = 0$ $-f^2(x)f(z) + f^2(y)f(z) + f(z)f(x - y)f(x + y) = 0$ $f^2(x)f(x - y) - f^2(x)f(x + y) + f(x)f(2x)f(y) = 0$ $f^2(x)f(2x) - f(2x)f^2(y) - f(2x)f(x - y)f(x + y) = 0$ $f^2(x)f(x + 2y) - f^2(y)f(x + 2y) - f(x - y)f(x + y)f(x + 2y) = 0$ $f^2(x)f(x - 2y) - f^2(y)f(x - 2y) - f(x - 2y)f(x - y)f(x + y) = 0$ $f(x)f^2(2y) - f(y)f(2y)f(x - y) - f(y)f(2y)f(x + y) = 0$ $f(x)f(2x)f(x - y) - f(x)f(2x)f(x + y) + f^2(2x)f(y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
22. Hyperbolic Sine	$f^2(x) - f^2(y) - f(x - y)f(x + y) = 0$ $-f^2(x) + f^2(y) + f(x - y)f(x + y) = 0$ $f^2(r) - f^2(x) + f(-r + x)f(r + x) = 0$ $f^2(r) - f^2(x) + f(-r + x)f(r + x) = 0$ $2\sqrt{f^2(y) + 1}f(x) - f(x - y) - f(x + y) = 0$ $2\sqrt{f^2(x) + 1}f(y) + f(x - y) - f(x + y) = 0$ $-2\sqrt{f^2(y) + 1}f(x) + f(x - y) + f(x + y) = 0$ $-2\sqrt{f^2(x) + 1}f(y) - f(x - y) + f(x + y) = 0$ $-2\sqrt{f^2(x) + 1}f(r) + f(r - x) + f(r + x) = 0$ $-2\sqrt{f^2(x) + 1}f(y) + f(-x + y) + f(x + y) = 0$ $-2\sqrt{f^2(y) + 1}f(x) - f(-x + y) + f(x + y) = 0$ $-2\sqrt{f^2(x) + 1}f(r) - f(-r + x) + f(r + x) = 0$ $-2\sqrt{f^2(x) + 1}f(3r) - f(-3r + x) + f(3r + x) = 0$ $-2\sqrt{f^2(x) + 1}f(2r) - f(-2r + x) + f(2r + x) = 0$ $-2(2f^2(r) + 1)f(x) + f(-2r + x) + f(2r + x) = 0$ $f(x)f(2y) - f(y)f(x - y) - f(y)f(x + y) = 0$ $f(r)f(-r + x) + f(r)f(r + x) - f(2r)f(x) = 0$ $-4(f^2(y) + 1)f^2(x) + (f(x - y) + f(x + y))^2 = 0$ $-(4f^2(x) + 4)f^2(y) + (-f(x - y) + f(x + y))^2 = 0$ $f^2(r)f(x) - f^3(x) + f(x)f(-r + x)f(r + x) = 0$ $-4(f^2(x) + 1)f^2(y) + (-f(x - y) + f(x + y))^2 = 0$ $-f^2(r)f(x) + f^3(x) - f(x)f(-r + x)f(r + x) = 0$ $f(x)f(x - 2y) - f(x)f(x + 2y) + 2f(2x)f(2y) + f^2(x - y) - f^2(x + y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
23. Cube	$ \begin{aligned} & -n^3 f(x) + f(nx) = 0 \\ & -8f(x+y) + f(2x+2y) = 0 \\ & -27f(x+y) + f(3x+3y) = 0 \\ & -y^3 f(x) + f(x)f(y) = 0 \\ & -6xy^2 - 2f(x) + f(x-y) + f(x+y) = 0 \\ & -6x^2y - 2f(y) - f(x-y) + f(x+y) = 0 \\ & -6ab^2 - 2f(a) + f(a-b) + f(a+b) = 0 \\ & -6a^2b - 2f(b) - f(a-b) + f(a+b) = 0 \\ & -6r^2x - 2f(x) + f(-r+x) + f(r+x) = 0 \\ & -6rx^2 - 2f(r) - f(-r+x) + f(r+x) = 0 \\ & -24a^2b - 2f(b) - f(2a-b) + f(2a+b) = 0 \\ & 3xy(x-y) - f(x) + f(y) + f(x-y) = 0 \\ & -3xy(x+y) - f(x) - f(y) + f(x+y) = 0 \\ & -6abc + f(a) + f(b) + f(c) - f(a+b) - f(a+c) - f(b+c) \\ & \quad + f(a+b+c) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
24. Logarithm	$ \begin{aligned} &-2f(x) + f(x^2) = 0 \\ &-3f(x) + f(x^3) = 0 \\ &-4f(x) + f(x^4) = 0 \\ &-5f(x) + f(x^5) = 0 \\ &-nf(x) + f(x^n) = 0 \\ &-rf(x) + f(x^r) = 0 \\ &-2f(r) + f(r^2) = 0 \\ &-yf(x) + f(x^y) = 0 \\ &f\left(\frac{1}{x}\right) + f(x) = 0 \\ &3f(x^2) - 2f(x^3) = 0 \\ &-abf(x) + f(x^{ab}) = 0 \\ &6f(\sqrt{x}) - f(x^3) = 0 \\ &9f(\sqrt[3]{x}) - f(x^3) = 0 \\ &f(\sqrt{x}) - \frac{f(x)}{2} = 0 \\ &f(\sqrt[3]{x}) - \frac{f(x)}{3} = 0 \\ &f\left(x^{\frac{1}{n}}\right) - \frac{f(x)}{n} = 0 \\ &-f(r) - f(x) + f(rx) = 0 \\ &-f(x) - f(y) + f(xy) = 0 \\ &-\frac{mf(x)}{n} + f\left(x^{\frac{m}{n}}\right) = 0 \\ &f(r) - f(x) + f\left(\frac{x}{r}\right) = 0 \\ &-2f(r) - f(x) + f(r^2x) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
25. Logarithm (cont.)	$f(x) - f(y) - f\left(\frac{x}{y}\right) = 0$ $-2f(y) - f\left(\frac{x}{y}\right) + f(xy) = 0$ $-af(x) - bf(y) + f(x^a y^b) = 0$ $-2f(x) - 2f(y) + f(x^2 y^2) = 0$ $-2f(x) - 3f(y) + f(x^2 y^3) = 0$ $-af(x) + bf(y) + f(x^a y^{-b}) = 0$ $f(r) - f\left(\frac{x}{y}\right) + f\left(\frac{x}{ry}\right) = 0$ $-2f(x) + 3f(y) + f\left(\frac{x^2}{y^3}\right) = 0$ $-\frac{af(x)}{b} + f\left((x^a)^{\frac{1}{b}}\right) = 0$ $-nf(x) - nf(y) + f((xy)^n) = 0$ $-f(r) - f(x) - f(y) + f(rxy) = 0$ $-f(x) - f(y) - f(z) + f(xyz) = 0$ $-\frac{f(x)}{2} - \frac{f(y)}{2} + f(\sqrt{xy}) = 0$ $f(r) - f(x) - f(y) + f\left(\frac{xy}{r}\right) = 0$ $-f(x) - f(y) + f(z) + f\left(\frac{xy}{z}\right) = 0$ $-f(x) + f(y) + f(z) + f\left(\frac{x}{yz}\right) = 0$ $-f(y) + f(ry) - f\left(\frac{x}{y}\right) + f\left(\frac{x}{ry}\right) = 0$ $-f(y) + f(rx) - 2f\left(\frac{x}{y}\right) + f\left(\frac{x}{ry}\right) = 0$ $-2f(y) - 2f\left(\frac{x}{y}\right) + f\left(\frac{x}{ry}\right) + f(rxy) = 0$
26. Secant	$f(r+x) \cos(r+x) - 1 = 0$ $f(-r+x) \cos(r-x) - 1 = 0$ $(-f^2(x) \sin^2(r) + 1) f(-r+x) f(r+x) - f^2(x) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
26. Cosecant	$(\cos(x-y) - \cos(x+y)) f(x)f(y) - 2 = 0$ $(\sin^2(x) - \sin^2(y)) f(x-y)f(x+y) - 1 = 0$ $(\sin(x)\cos(y) + \sin(y)\cos(x)) f(x+y) - 1 = 0$ $(\sin(x)\cos(y) - \sin(y)\cos(x)) f(x-y) - 1 = 0$ $f(x-y)f(x+y) - \frac{1}{\sin^2(x)\cos^2(y) - \sin^2(y)\cos^2(x)} = 0$ $f(x+y)\sin(x)\cos(y) + f(x+y)\sin(y)\cos(x) - f(x+y)\sin(x+y) = 0$
28. Sinc Composite	$f(x+y)\text{rsr}_x(x,y) - \text{rsr}_{\sin}(x,y) = 0$ $2xf(x)f(2y) - xf(y)f(x-y) - xf(y)f(x+y) + yf(y)f(x-y) - yf(y)f(x+y) = 0$ $xf(x)f(x-y) - xf(x)f(x+y) - yf(x)f(x-y) - yf(x)f(x+y) + 2yf(2x)f(y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
29. Modulo	$ \begin{aligned} & -f(x) + f(Ry + x) = 0 \\ & -f(x) + f(Rk + x) = 0 \\ & -f(x) + f(-Rn + x) = 0 \\ & -f(2x) + f(R + 2x) = 0 \\ & -f(R - x) + f(2R - x) = 0 \\ & f(nx) - f(nf(x)) = 0 \\ & -f(af(x)) + f(Rb + ax) = 0 \\ & f(xy) - f(f(x)f(y)) = 0 \\ & f(rx) - f(f(r)f(x)) = 0 \\ & f(x + y) - f(f(x) + f(y)) = 0 \\ & -f(af(x)) + f(x(Rb + a)) = 0 \\ & f(r + x) - f(f(r) + f(x)) = 0 \\ & -f(f(x)f(y)) + f(R + xy) = 0 \\ & -f(f(x)f(y)) + f(Rz + xy) = 0 \\ & -f(f(x)f(y)) + f(-R + xy) = 0 \\ & -f(f(x) + f(y)) + f(R + x + y) = 0 \\ & -f(f(x) + f(y)) + f(-R + x + y) = 0 \\ & f(ax + by) - f(af(x) + bf(y)) = 0 \\ & -f(f(x) + f(y)) + f(-Rz + x + y) = 0 \\ & f(x(R + y)) - f(f(x)f(y)) = 0 \\ & f(xyz) - f(f(x)f(y)f(z)) = 0 \\ & f(y(r + x)) - f(f(y)f(r + x)) = 0 \\ & f(x + y + z) - f(f(x) + f(y) + f(z)) = 0 \\ & f(r + s + x) - f(f(r) + f(s) + f(x)) = 0 \\ & f(r + x + y) - f(f(r) + f(x) + f(y)) = 0 \\ & f((R + x)(R + y)) - f(f(x)f(y)) = 0 \\ & -f(f(x) + f(y) + f(z)) + f(-Rw + x + y + z) = 0 \\ & f(ax + by + cz) - f(af(x) + bf(y) + cf(z)) = 0 \\ & f(wxyz) - f(f(w)f(x)f(y)f(z)) = 0 \\ & f((r + x)(s + y)) - f(f(r + x)f(s + y)) = 0 \\ & f(r + s + t + x) - f(f(r) + f(s) + f(t) + f(x)) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
30. Modulo Multiplication	$f(x, y) - f(xy, 1) = 0$ $f(x, yz) - f(y, xz) = 0$ $f(xy, z) - f(yz, x) = 0$ $-f(1, xy) + f(x, y) = 0$ $-f(x, ry) + f(rx, y) = 0$ $f(rx, sy) - f(sx, ry) = 0$ $f(xy, wz) - f(xz, wy) = 0$ $-f(x, 1) + f\left(\frac{x}{y}, y\right) = 0$ $-f(1, y) + f\left(x, \frac{y}{x}\right) = 0$ $-f(1, y) + f\left(\frac{1}{x}, xy\right) = 0$ $f\left(x, \frac{1}{y}\right) - f\left(\frac{x}{y}, 1\right) = 0$ $f(x, yz) - f(f(x, y), z) = 0$ $-f\left(1, \frac{y}{x}\right) + f\left(\frac{1}{x}, y\right) = 0$ $-f(x, f(y, z)) + f(xy, z) = 0$ $f(x, y^2) - f(f(x, y), y) = 0$ $-f(x, f(x, y)) + f(x^2, y) = 0$ $-f(ab, f(x, y)) + f(ax, by) = 0$ $-f(rs, f(x, y)) + f(rx, sy) = 0$ $-f(x^2, f(y, z)) + f(xy, xz) = 0$ $-f(x, f(xy, z)) + f(x^2y, z) = 0$ $f(x, y^2z^2) - f(f(x, y^2), z^2) = 0$ $f(x, f(y, z)) - f(y, f(x, z)) = 0$ $f(x, f(y, z)) - f(z, f(x, y)) = 0$ $-f(x^2, f(y^2, z)) + f(x^2y^2, z) = 0$ $-f(x, f(y, z)) + f(f(x, y), z) = 0$ $f(x, wyz) - f(f(f(x, y), z), w) = 0$ $f(x, y^3) - f(f(f(x, y), y), y) = 0$ $f(x, aby) - f(f(f(x, a), b), y) = 0$ $-f(x, f(y, f(z, w))) + f(xyz, w) = 0$ $-f(x, f(x, f(x, y))) + f(x^3, y) = 0$ $-f(a, f(b, f(x, y))) + f(abx, y) = 0$ $-f(z, f(x, f(y, w))) + f(xyz, w) = 0$ $f(f(x, y), f(z, w)) - f(f(x, z), f(y, w)) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
31. Integer Multiplication	$f(x, y) - f(y, x) = 0$ $-cf(x, y) + f(cx, y) = 0$ $-cf(x, y) + f(x, cy) = 0$ $-f(x, 3y) + f(3x, y) = 0$ $-nf(x, y) + f(nx, y) = 0$ $-nf(x, y) + f(x, ny) = 0$ $-abf(x, y) + f(ax, by) = 0$ $-4f^2(x, y) + f^2(x, 2y) = 0$ $-4f^2(x, y) + f^2(2x, y) = 0$ $-f(x - y, x + y) + f(x + y, x - y) = 0$ $-f(r, y) - f(x, y) + f(r + x, y) = 0$ $-f(x, s) - f(x, y) + f(x, s + y) = 0$ $-f(y, x) - f(y, y) + f(x + y, y) = 0$ $f(x, x) - f(y, y) - f(x - y, x + y) = 0$ $-f(x, x) + f(y, y) + f(x + y, x - y) = 0$ $f(x, y)f(r + x, s + y) - f(x, s + y)f(r + x, y) = 0$ $f(x, x + y) - f(y, x) - f(y, y) - f(x - y, x + y) = 0$ $f(x, y)f(-r + x, -s + y) - f(x, -s + y)f(-r + x, y) = 0$ $-f(r, s) - f(r, y) - f(x, s) - f(x, y) + f(r + x, s + y) = 0$ $f(r, s) - f(r, y) + f(x, s) - f(x, y) + f(r + x, -s + y) = 0$ $f(r, s) + f(r, y) - f(x, s) - f(x, y) + f(-r + x, s + y) = 0$ $-f(r, r) - f(r, y) - f(x, r) - f(x, y) + f(r + x, r + y) = 0$ $-f(r, s) + f(r, y) + f(x, s) - f(x, y) + f(-r + x, -s + y) = 0$ $-f(r, s) - 2f(r, y) - 2f(x, s) - 4f(x, y) + f(r + 2x, s + 2y) = 0$ $-f(x, -s + y)f(-r + x, y)f(r + x, s + y)$ $+ f(x, s + y)f(-r + x, -s + y)f(r + x, y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
32. Hyperbolic Tangent	$f(r+x) - \frac{f(r)+f(x)}{f(r)f(x)+1} = 0$ $f(-r+x) - \frac{-f(r)+f(x)}{-f(r)f(x)+1} = 0$ $f(2r+2x) - \frac{f(2r)+f(2x)}{f(2r)f(2x)+1} = 0$ $f(x)f(y)f(x-y) + f(x) - f(y) - f(x-y) = 0$ $f(-r+x)f(r+x) - \frac{-f^2(r)+f^2(x)}{-f^2(r)f^2(x)+1} = 0$ $-\frac{2(1-f^2(x))f(r)}{-f^2(r)f^2(x)+1} - f(-r+x) + f(r+x) = 0$ $f(x)f(x-y) + f(x)f(x+y) + f(y)f(x-y) - f(y)f(x+y) - 2f(x-y)f(x+y) = 0$ $f(r)f(-r+x) - f(r)f(r+x) + f(x)f(-r+x) + f(x)f(r+x) - 2f(-r+x)f(r+x) = 0$
33. Sigmoid	$-\frac{kf(x)}{(k-1)f(x)+1} + f(x+\log(k)) = 0$ $f(nx) - \frac{f^n(x)}{(1-f(x))^n + f^n(x)} = 0$ $((1-f(x))(1-f(y)) + f(x)f(y))f(x+y) - f(x)f(y) = 0$ $((1-f(x))(1-f(-y)) + f(x)f(-y))f(x-y) - f(x)f(-y) = 0$ $f(x+y+z) - \frac{f(z)f(x+y)}{(1-f(z))(1-f(x+y)) + f(z)f(x+y)} = 0$ $-(1-f(y))f(x) + ((1-f(x))f(y) + (1-f(y))f(x))f(x-y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
34. Softmax2 1	$f(0, y) - f(x, x + y) = 0$ $f(x, y) - f(x - y, 0) = 0$ $f(x, x - y) - f(y, 0) = 0$ $f(x, y) - \frac{1}{e^{-x+y} + 1} = 0$ $-f(x, 0) + f(x + y, y) = 0$ $-f(0, y) + f(x, x + y) = 0$ $-f(0, y) + f(x - y, x) = 0$ $f(x, 0) + f(y, x + y) - 1 = 0$ $f(x, y) - f(r + x - y, r) = 0$ $-f(x, y) + f(r + x, r + y) = 0$ $f(x, r + y) - f(-r + x, y) = 0$ $-f(x, r + y) + f(-r + x, y) = 0$ $-f(x, -r + y) + f(r + x, y) = 0$ $f(x, x + y) + f(x + y, x) - 1 = 0$ $f(y, x + y) + f(x + y, y) - 1 = 0$ $f(y, r + x) + f(r + x, y) - 1 = 0$ $f(x, r + y) + f(r + y, x) - 1 = 0$ $-f(x, y) + f(-r + x, -r + y) = 0$ $f(2x, 2y) - f(x - y, -x + y) = 0$ $-f(s + x, y) + f(r + s + x, r + y) = 0$ $f(r + x, s + y) + f(s + y, r + x) - 1 = 0$ $-f^2(x, y) + f(x, y)f(r + x, r + y) = 0$ $-(1 - f(x, y))f(x, y) + f(x, y)f(y, x) = 0$ $f(x, y)f(y, z)f(z, x) - f(x, z)f(y, x)f(z, y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
35. Softmax2 2	$f(y, x) + f(x - y, 0) - 1 = 0$ $f(x, y) - f(x - z, y - z) = 0$ $-f(x, y) + f(r + x, r + y) = 0$ $f(0, -x + y) + f(y, x) - 1 = 0$ $-f(x, y) + f(a + x, a + y) = 0$ $f(y, x) + f(r + x, r + y) - 1 = 0$ $f(x, r + x) + f(r + x, x) - 1 = 0$ $f(y, r + x) + f(r + x, y) - 1 = 0$ $f(x, r + y) + f(r + y, x) - 1 = 0$ $f(y, x) + f(-r + x, -r + y) - 1 = 0$ $f(r + x, s + y) - f(r - s + x, y) = 0$ $f(a + x, b + y) - f(a - b + x, y) = 0$ $-\frac{a}{a + e^x} + f(x, \log(a)) = 0$ $f(-r + x, -s + y) - f(-r + s + x, y) = 0$ $-\frac{b}{a + b} + f(\log(a), \log(b)) = 0$ $(ae^x + e^y) f(x + \log(a), y) - e^y = 0$ $-be^y + (be^y + e^x) f(x, y + \log(b)) = 0$ $-f^2(y, x) + 2f(y, x) + f^2(x - y, 0) - 1 = 0$ $-\frac{e^x + e^y}{e^y + e^{c+x}} + \frac{f(c + x, y)}{f(x, y)} = 0$ $-\frac{be^y}{ae^x + be^y} + f(x + \log(a), y + \log(b)) = 0$ $f(x, y)f(y, z)f(z, x) - f(x, z)f(y, x)f(z, y) = 0$
36. Logistic	$-L + f(x) + f(-x + 2x_0) = 0$ $-L + f(nr + x) + f(-nr - x + 2x_0) = 0$ $f(-r)f^2(r + x) + f(r)f^2(r + x) - f^2(r + x) = 0$ $f(-r)f^2(-r + x) + f(r)f^2(-r + x) - f^2(-r + x) = 0$ $f(r)f(-r + x) - f(r)f(r + x) + f(x)f(-r + x) + f(x)f(r + x) - f(x)$ $-2f(-r + x)f(r + x) + f(r + x) = 0$ $f(r)f(-r + x_0) - f(r)f(r + x_0) + f(x_0)f(-r + x_0) + f(x_0)f(r + x_0) - f(x_0)$ $-2f(-r + x_0)f(r + x_0) + f(r + x_0) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
37. Logistic Scaled	$f(-nr) + f(nr) - 3 = 0$ $-L + f(-ar) + f(ar) = 0$ $-L + f(x) + f(-x + 2x_0) = 0$ $-L + f(x) + f(-x + 2x_0) = 0$ $-L + f(-r + x_0) + f(r + x_0) = 0$ $-L + f(r + x) + f(-r - x + 2x_0) = 0$ $-L + f(-r + x) + f(r - x + 2x_0) = 0$ $-L + f(-nr + x_0) + f(nr + x_0) = 0$ $-L + f(nr + x) + f(-nr - x + 2x_0) = 0$ $-L + f(ar + x) + f(-ar - x + 2x_0) = 0$ $Lf(x) - f^2(x) - f(x)f(-x + 2x_0) = 0$ $-Lf(x) + f^2(x) + f(x)f(-x + 2x_0) = 0$ $(L - f(x))f(x) - f(x)f(-x + 2x_0) = 0$ $f(r)f(-r + x) - f(r)f(r + x) + f(x)f(-r + x) + f(x)f(r + x) - 3f(x)$ $-2f(-r + x)f(r + x) + 3f(r + x) = 0$ $f(2r)f(-2r + x) - f(2r)f(2r + x) + f(x)f(-2r + x) + f(x)f(2r + x) - 3f(x)$ $-2f(-2r + x)f(2r + x) + 3f(2r + x) = 0$
38. Square Loss	$-\left(1 - \frac{x}{c}\right)^2 + f\left(\frac{x}{c}\right) = 0$ $-h - 2x + 2 + \frac{-f(x) + f(h + x)}{h} = 0$ $-2h^2 - 2f(x) + f(-h + x) + f(h + x) = 0$ $-(1 - c)^2 f(x) + f(c(1 - x) + x) = 0$ $-2f(x) - 2f(1 - y) + f(x - y) + f(x + y) = 0$ $-2f(x) - 2f(1 - r) + f(-r + x) + f(r + x) = 0$ $-2f(ax) + f(ax - by) + f(ax + by) - 2f(-by + 1) = 0$ $-2x - 2y - (1 - y)(2 - 2x) - f(x) - f(y) + f(x + y) + 3 = 0$ $\left(\frac{x}{2} - \frac{y}{2}\right)^2 - \frac{f(x)}{2} - \frac{f(y)}{2} + f\left(\frac{x}{2} + \frac{y}{2}\right) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
40. Savage Loss Basis	$(g(x - y) + 1)^2 f(x - y) - 1 = 0$ $(g(r + x) + 1)^2 f(r + x) - 1 = 0$ $(g(-r + x) + 1)^2 f(-r + x) - 1 = 0$ $(g(x)g(y) + 1)^2 f(x + y) - 1 = 0$ $f(x + y) - \frac{1}{(g(x)g(y) + 1)^2} = 0$ $(g(x) + g(y))^2 f(x - y) - g^2(y) = 0$ $(g(x) + g(r + x))^2 f(r) - g^2(x) = 0$ $f(x - y) - \frac{g^2(y)}{(g(x) + g(y))^2} = 0$
43. Arctangent	$-\frac{x - y}{xy + 1} + \tan(f(x) - f(y)) = 0$ $-\frac{x + y}{-xy + 1} + \tan(f(x) + f(y)) = 0$ $\cos(f(x) + f(y)) - \frac{-xy + 1}{\sqrt{(x^2 + 1)(y^2 + 1)}} = 0$
47. ReLU	$f(\max(x, y)) - \max(f(x), f(y)) = 0$ $f(\min(x, y)) - \min(f(x), f(y)) = 0$ $-f(x)f(y) + f(f(x)f(y)) = 0$ $-f(\max(x, y)) + \max(f(x), f(y)) = 0$ $-f(\min(x, y)) + \min(f(x), f(y)) = 0$
54. Square Root	$r - x + f^2(-r + x) = 0$ $-r - x + f^2(r + x) = 0$ $-2r - f^2(-r + x) + f^2(r + x) = 0$ $-2x + f^2(-r + x) + f^2(r + x) = 0$ $r^2 - x^2 + f^2(-r + x)f^2(r + x) = 0$ $f^2(r) + f^2(x) - f^2(r + x) = 0$ $-2f^2(x) + f^2(-r + x) + f^2(r + x) = 0$ $-2f^3(x) + f(x)f^2(-r + x) + f(x)f^2(r + x) = 0$ $-2f(r)f^2(x) + f(r)f^2(-r + x) + f(r)f^2(r + x) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
55. Cube Root	$ \begin{aligned} & -xy + f^3(xy) = 0 \\ & -x - y + f^3(x + y) = 0 \\ & -x + y + f^3(x - y) = 0 \\ & -2f^3(x) + f^3(-r + x) + f^3(r + x) = 0 \\ & -6f^3(y) + 2f^3(2y) - f^3(x - y) + f^3(x + y) = 0 \\ & -6f^3(x) + 2f^3(2x) + f^3(x - y) + f^3(x + y) = 0 \\ & -2f^3(y) + 3f^3(2y) + 2f^3(x - y) - 2f^3(x + y) = 0 \\ & f^3(x) + 2f^3(2x) + f^3(y) + 2f^3(2y) - 5f^3(x + y) = 0 \\ & f^3(x) + 2f^3(2x) - f^3(y) - 2f^3(2y) - 5f^3(x - y) = 0 \\ & -f^3(r) - 2f^3(2r) + 5f^3(3r) + 2f^3(-2r + x) + f^3(-r + x) - f^3(r + x) \\ & \quad - 2f^3(2r + x) = 0 \\ & -f^3(r) + 10f^3(2r) - 3f^3(3r) + 2f^3(-2r + x) + f^3(-r + x) - f^3(r + x) \\ & \quad - 2f^3(2r + x) = 0 \\ & 60f^3(r) - 5f^3(2r) - 8f^3(3r) + 5f^3(-2r + x) + 3f^3(-r + x) - 3f^3(r + x) \\ & \quad - 5f^3(2r + x) = 0 \end{aligned} $
57. Floor	$ \begin{aligned} & -f(x)f(y) + f(xy) - f(xy - \lfloor x \rfloor \lfloor y \rfloor) = 0 \\ & -f(x) - f(y) + f(x + y) - f(x + y - \lfloor x \rfloor - \lfloor y \rfloor) = 0 \\ & -f(r) - f(x) + f(r + x) - f(r + x - \lfloor r \rfloor - \lfloor x \rfloor) = 0 \\ & f(r) - f(x) + f(-r + x) - f(-r + x + \lfloor r \rfloor - \lfloor x \rfloor) = 0 \\ & -2f(r) - f(x) + f(2r + x) - f(2r + x - 2\lfloor r \rfloor - \lfloor x \rfloor) = 0 \\ & -f(s) - f(r + x) + f(r + s + x) - f(r + s + x - \lfloor s \rfloor - \lfloor r + x \rfloor) = 0 \\ & -f(x) - f(y) - f(z) + f(x + y + z) - f(x + y + z - \lfloor x \rfloor - \lfloor y \rfloor - \lfloor z \rfloor) = 0 \end{aligned} $
58. Ceiling	$ \begin{aligned} & f(x + y - f(x + y)) = 0 \\ & -f(x + y) + f(f(x + y)) = 0 \\ & -f(x) - f(y) + f(x + f(y)) = 0 \\ & -f(x) + f(y) + f(x - f(y)) = 0 \\ & -f(x) - f(y) + f(y + f(x)) = 0 \\ & -f(x)f(y) + f(f(x)f(y)) = 0 \\ & -f(x) - f(y) + f(f(x) + f(y)) = 0 \\ & -f(x) + f(y) + f(f(x) - f(y)) = 0 \\ & -f(x)f(y)f(z) + f(f(x)f(y)f(z)) = 0 \\ & -f(x) - f(y) - f(z) + f(f(x) + f(y) + f(z)) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
59. Fractional Part	$-f(x) + f(x + \lfloor y \rfloor) = 0$ $f(xy) - f(xy - \lfloor x \rfloor \lfloor y \rfloor) = 0$ $f(x) + f(y) - f(x + y) - \lfloor f(x) + f(y) \rfloor = 0$ $f(x) + f(y) - f(x + y) + \lfloor x \rfloor + \lfloor y \rfloor - \lfloor x + y \rfloor = 0$
60. Error Function	$f(-ax) + f(ax) = 0$ $f\left(-\frac{x}{a}\right) + f\left(\frac{x}{a}\right) = 0$
61. Gamma	$-yf(x)f(y) + f(x)f(y+1) = 0$ $-xyf(x)f(y) + f(x+1)f(y+1) = 0$ $-yf(y)f(x-1) + f(x-1)f(y+1) = 0$ $-x(x+1)f(x)f(y) + f(y)f(x+2) = 0$
62. Exp Sin	$-f^{2\cos(r)}(x) + f(-r+x)f(r+x) = 0$
64. Log Co-sine	$f(x-y) + f(x+y) - \log(\cos(x-y)) - \log(\cos(x+y)) = 0$
65. Square Root of $1 + X^2$	$-x^2y^2 + f^2(xy) - 1 = 0$ $-x^2 + y^2 + f^2(x) - f^2(y) = 0$ $-4rx - f^2(-r+x) + f^2(r+x) = 0$ $2xy - f^2(x) - f^2(y) + f^2(x-y) + 1 = 0$ $-2xy - f^2(x) - f^2(y) + f^2(x+y) + 1 = 0$ $2r^2 + 2f^2(x) - f^2(-r+x) - f^2(r+x) = 0$ $-(x^2+1)(y^2+1) + f^2(x)f^2(y) = 0$ $-2r^2 - 2f^2(x) + f^2(-r+x) + f^2(r+x) = 0$ $4x^2y^2 - (x^2+y^2+1)^2 + f^2(x-y)f^2(x+y) = 0$ $4x^2y^2 - (x^2+y^2+1)^2 + f^2(x-y)f^2(x+y) = 0$ $-\sqrt{c^2 + f^2(x) - 1} + f\left(\frac{x}{ c }\right) c = 0$ $r^2 + f^2(x) - \frac{f^2(-r+x)}{2} - \frac{f^2(r+x)}{2} = 0$ $-2f^2(x) - 2f^2(y) + f^2(x-y) + f^2(x+y) + 2 = 0$ $-\sqrt{x^2 - 2xy + y^2 + 1}\sqrt{x^2 + 2xy + y^2 + 1} + f(x-y)f(x+y) = 0$ $4x^2y^2 - (f^2(x) + f^2(y) - 1)^2 + f^2(x-y)f^2(x+y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
66. Absolute Value	$-f(x) c + f(cx) = 0$ $-f(x)f(y) + f(xy) = 0$ $f^2(x)f^2(y) - f^2(xy) = 0$ $-f^2(r)f^2(x) + f^2(rx) = 0$ $-\frac{f(x)}{f(y)} + f\left(\frac{x}{y}\right) = 0$ $f((-r+x)(r+x)) - f(-r^2+x^2) = 0$ $-f^2(x) - f^2(y) + f^2(\sqrt{x^2+y^2}) = 0$ $-2f^2(r) - 2f^2(x) + f^2(-r+x) + f^2(r+x) = 0$ $-14f^2(x) - 2f^2(y) - f^2(x-y) - f^2(x+y) + 2f^2(2x-y) + 2f^2(2x+y) = 0$
67. Sign	$f^3(xy) - f(xy) = 0$ $f^5(xy) - f(xy) = 0$ $f^3(x+y) - f(x+y) = 0$ $f^3(x-y) - f(x-y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
68. Guder-mannian	$2 \sinh(x) \cosh(r) + \sinh(r-x) - \sinh(r+x) = 0$ $2 \sinh(r) \cosh(x) - \sinh(r-x) - \sinh(r+x) = 0$ $\sinh(r) \cosh(r+x) + \sinh(x) - \sinh(r+x) \cosh(r) = 0$ $-\sinh(r) \cosh(r-x) + \sinh(x) + \sinh(r-x) \cosh(r) = 0$ $f(r) - \operatorname{atan}\left(\frac{\sinh(r-x) + \sinh(r+x)}{2 \cosh(x)}\right) = 0$ $f(x) - \operatorname{atan}\left(\frac{-\sinh(r-x) + \sinh(r+x)}{2 \cosh(r)}\right) = 0$ $f(x+y) - \operatorname{atan}(\sinh(x) \cosh(y) + \sinh(y) \cosh(x)) = 0$ $f(r+x) - \operatorname{atan}(\sinh(r) \cosh(x) + \sinh(x) \cosh(r)) = 0$ $2 \tan(f(x)) \cosh(r) - \tan(f(-r+x)) - \tan(f(r+x)) = 0$ $f(-r+x) + \operatorname{atan}(\sinh(r) \cosh(x) - \sinh(x) \cosh(r)) = 0$ $2 \tan(f(x)) \cosh(r) - \tan(f(-r+x)) - \tan(f(r+x)) = 0$ $2 \tan(f(r)) \cosh(x) + \tan(f(-r+x)) - \tan(f(r+x)) = 0$ $f(x) - \operatorname{atan}\left(\frac{-\sinh(r-x) + \sinh(r+x)}{2\sqrt{\sinh^2(r) + 1}}\right) = 0$ $-\frac{\tan(f(-r+x)) + \tan(f(r+x))}{2 \cosh(r)} + \tan(f(x)) = 0$ $\tan(f(x) - f(y)) - \frac{\sinh(x) - \sinh(y)}{\sinh(x) \sinh(y) + 1} = 0$ $\tan(f(x) + f(y)) - \frac{\sinh(x) + \sinh(y)}{-\sinh(x) \sinh(y) + 1} = 0$ $2\sqrt{\sinh^2(r) + 1} \tan(f(x)) - \tan(f(-r+x)) - \tan(f(r+x)) = 0$ $2\sqrt{\sinh^2(r) + 1} \tan(f(x)) - \tan(f(-r+x)) - \tan(f(r+x)) = 0$ $(\sinh(x) \sinh(y) + 1) \tan(f(x) - f(y)) - \sinh(x) + \sinh(y) = 0$ $(-\sinh(x) \sinh(y) + 1) \tan(f(x) + f(y)) - \sinh(x) - \sinh(y) = 0$ $f(x) - \operatorname{atan}\left(\frac{\tan(f(-r+x)) + \tan(f(r+x))}{2 \cosh(r)}\right) = 0$ $-\frac{\tan(f(-r+x)) + \tan(f(r+x))}{2\sqrt{\sinh^2(r) + 1}} + \tan(f(x)) = 0$ $f(r) - \operatorname{atan}\left(\frac{-\tan(f(-r+x)) + \tan(f(r+x))}{2 \cosh(x)}\right) = 0$ $f(x+y) - \operatorname{atan}\left(\sqrt{\sinh^2(x) + 1} \sinh(y) + \sqrt{\sinh^2(y) + 1} \sinh(x)\right) = 0$ $f(x+y)$ $-\operatorname{atan}\left(\sqrt{\tan^2(f(x)) + 1} \tan(f(y)) + \sqrt{\tan^2(f(y)) + 1} \tan(f(x))\right) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
69. 2 to X	$-f^n(x) + f(nx) = 0$ $f^2(r+x) - f(2r+2x) = 0$ $f(r)f(x) - f(r+x) = 0$ $-f(x)f(y) + f(x+y) = 0$ $-f(x) + f(y)f(x-y) = 0$ $-f(r)f(x) + f(r+x) = 0$ $f(-r)f(r+x) - f(x) = 0$ $f(r)f(-r+x) - f(x) = 0$ $f(-r)f(x) - f(-r+x) = 0$ $-f(-r)f(x) + f(-r+x) = 0$ $-f(2x) + f(x-y)f(x+y) = 0$ $-f^2(x)f(y) + f(2x+y) = 0$ $-f(x)f^2(y) + f(x+2y) = 0$ $f^2\left(\frac{x}{2} + \frac{y}{2}\right) - f(x+y) = 0$ $-\frac{f(x)}{f(y)} + f(x-y) = 0$ $f(-r+x) - \frac{f(x)}{f(r)} = 0$ $-f^2(y)f(x-y) + f(x+y) = 0$ $-f(2x) + f(-r+x)f(r+x) = 0$ $-f(x) + \frac{f(x+y)}{f(y)} = 0$ $-f^2(x) + f(-r+x)f(r+x) = 0$ $-f^3(y)f(x-y) + f(x+2y) = 0$ $-f(x) + \frac{f(x-y)}{f(-y)} = 0$ $-f^3(y)f^2(x-y) + f(2x+y) = 0$ $-f(2y) + \frac{f(x+y)}{f(x-y)} = 0$ $-f^4(y)f^2(x-y) + f^2(x+y) = 0$ $-f(x) + \frac{f(x+y+z)}{f(y+z)} = 0$ $f(x)f(z) - f(y)f(x-y+z) = 0$ $-f(4y) + \frac{f^2(x+y)}{f^2(x-y)} = 0$ $-f(x)f(y)f(z) + f(x+y+z) = 0$ $-f(x)f(-y)f(z) + f(x-y+z) = 0$ $-f(x)f(y)f(-z) + f(x+y-z) = 0$ $-\frac{f(x)f(z)}{f(y)} + f(x-y+z) = 0$ $-\frac{f(x)f(y)}{f(z)} + f(x+y-z) = 0$ $-f^2(x)f(-y)f(y) + f(x-y)f(x+y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
70. 10 to X	$f(-r)f(r) - 1 = 0$ $f^y(x) - f(xy) = 0$ $-f^n(x) + f(nx) = 0$ $-f^a(x) + f(ax) = 0$ $-f^y(x) + f(xy) = 0$ $f^{\frac{1}{n}}(x) - f\left(\frac{x}{n}\right) = 0$ $-f(x)f(y) + f(x+y) = 0$ $f(-r)f(r+x) - f(x) = 0$ $f(r)f(-r+x) - f(x) = 0$ $-f^{\frac{1}{y}}(x) + f\left(\frac{x}{y}\right) = 0$ $-f(x)f(-y) + f(x-y) = 0$ $-f(-r)f(r+x) + f(x) = 0$ $-f(r)f(-r+x) + f(x) = 0$ $-f(2r)f(x) + f(2r+x) = 0$ $-f(r)f^2(x) + f(r+2x) = 0$ $-f^2(r)f(x) + f(2r+x) = 0$ $-f(2y)f(x-y) + f(x+y) = 0$ $-f^2(r)f(x) + f(2r+x) = 0$ $-\frac{f(x)}{f(y)} + f(x-y) = 0$ $-f^2(y)f(x-y) + f(x+y) = 0$ $-f^2(x) + f(x-y)f(x+y) = 0$ $-f(2x)f(2y) + f(2x+2y) = 0$ $-f^2(x) + f(-r+x)f(r+x) = 0$ $-f^a(x)f^b(y) + f(ax+by) = 0$ $f(-2r+x) - \frac{f(x)}{f^2(r)} = 0$ $-\frac{f^2(x)}{f(y)} + f(2x-y) = 0$ $-\frac{f^3(x)}{f^2(y)} + f(3x-2y) = 0$ $-f(x)f(y)f(z) + f(x+y+z) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
70. 10 to X (cont.)	$-f(x)f(y) + f^2\left(\frac{x}{2} + \frac{y}{2}\right) = 0$ $-f(x)f(y)f(-z) + f(x+y-z) = 0$ $\sqrt{f(x)f(y)} - f\left(\frac{x}{2} + \frac{y}{2}\right) = 0$ $-\frac{f(x)}{f(y)f(z)} + f(x-y-z) = 0$ $-\frac{f(x)f(y)}{f(z)} + f(x+y-z) = 0$ $-\frac{f(x)f(z)}{f(y)} + f(x-y+z) = 0$ $-\frac{f(x)f(y)}{f(z)} + f(x+y-z) = 0$ $-af(x) + f\left(x + \frac{\log(a)}{\log(10)}\right) = 0$ $-f^a(x)f^b(y)f^c(z) + f(ax+by+cz) = 0$ $-f^2(x)f(-y)f(y) + f(x-y)f(x+y) = 0$ $-(f(-r) + f(r))f(x) + f(-r+x) + f(r+x) = 0$ $-(-f(-r) + f(r))f(x) - f(-r+x) + f(r+x) = 0$
71. Pade 1,1	$-\frac{x}{2} - \frac{y}{2} + \frac{f(x+y)-1}{f(x+y)+1} = 0$ $-\frac{x}{2} + \frac{y}{2} + \frac{f(x-y)-1}{f(x-y)+1} = 0$ $f(x)f(x-y) + f(x)f(x+y) + 2f(x) - 2f(x-y)f(x+y) - f(x-y) - f(x+y) = 0$
72. Pade 2,2	$f(-x-y)f(-x+y)f(x-y)f(x+y) - 1 = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
73. Continued Fraction Golden	$ \begin{aligned} &2f(r)f(r-s) + 2f(r)f(r+s) - 6f(r) - 4f(r-s)f(r+s) \\ &\quad + 3f(r-s) + 3f(r+s) = 0 \\ &-2f(x)f(-r+x) - 2f(x)f(r+x) + 6f(x) + 4f(-r+x)f(r+x) \\ &\quad - 3f(-r+x) - 3f(r+x) = 0 \\ &-2f(r)f(r+x) + 4f(r)f(r+2x) - 3f(r) - 2f(r+x)f(r+2x) + 6f(r+x) \\ &\quad - 3f(r+2x) = 0 \\ &2f(rx)f(rx-s) + 2f(rx)f(rx+s) - 6f(rx) - 4f(rx-s)f(rx+s) \\ &\quad + 3f(rx-s) + 3f(rx+s) = 0 \\ &2f(x)f(-r-s+x) - 4f(x)f(-r+s+x) - 4f(x)f(r-s+x) \\ &\quad + 2f(x)f(r+s+x) + 6f(x) - 4f(-r-s+x)f(r+s+x) \\ &\quad + 3f(-r-s+x) + 8f(-r+s+x)f(r-s+x) \\ &\quad - 6f(-r+s+x) - 6f(r-s+x) + 3f(r+s+x) = 0 \end{aligned} $
74. Continued Fraction Tan	$ \begin{aligned} &-nx(-n^2x^2 + 15) + (-6n^2x^2 + 15)f(nx) = 0 \\ &15n^2f\left(\frac{x}{n}\right) - 15nx - 6x^2f\left(\frac{x}{n}\right) + \frac{x^3}{n} = 0 \\ &(15n^2 - 6x^2)f\left(\frac{x}{n}\right) - \frac{x(15n^2 - x^2)}{n} = 0 \end{aligned} $
75. Mobius Simple	$ \begin{aligned} &-x + f\left(\frac{-b+dx}{a-cx}\right) = 0 \\ &-\frac{arx+b}{crx+d} + f(rx) = 0 \\ &-r(ad-bc) + (cx+d)(-f(x) + f(r+x))(cr+cx+d) = 0 \\ &-\frac{ad-bc}{(-cr+cx+d)(cr+cx+d)} + \frac{-f(-r+x) + f(r+x)}{2r} = 0 \\ &-\frac{(r+s)(ad-bc)}{(cx+d)(cr+cs+cx+d)} - f(x) + f(r+s+x) = 0 \\ &f(x)f(y) - f(x+y) - \frac{-ax-ay-b+(cx+cy+d)f(x)f(y)}{cx+cy+d} = 0 \\ &f(r)f(s) - f(r+s) - \frac{-ar-as-b+(cr+cs+d)f(r)f(s)}{cr+cs+d} = 0 \\ &-\frac{(-ar+ax+b)(ar+ax+b)}{(-cr+cx+d)(cr+cx+d)} + f(-r+x)f(r+x) = 0 \\ &-\frac{(x_1-x_2)(x_3-x_4)}{(x_1-x_4)(-x_2+x_3)} + \frac{(f(x_1)-f(x_2))(f(x_3)-f(x_4))}{(f(x_1)-f(x_4))(-f(x_2)+f(x_3))} = 0 \\ &2rf(r)f(-x) - 2rf(-x)f(-r+x) - 2xf(r)f(-x) + 2xf(r)f(-r+x) \\ &+ 9f(r)f(-x)f(-r+x) - f(r)f(-x) - f(r)f(-r+x) - f(-x)f(-r+x) = 0 \end{aligned} $

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
76. Mobius Inversion	$f(x+y) - \frac{1}{x+y} = 0$ $f(x-y) - \frac{1}{x-y} = 0$ $(x+y)f(x+y) - 1 = 0$ $(x-y)f(x-y) - 1 = 0$ $f(ax+by) - \frac{1}{ax+by} = 0$ $f(cx) - \frac{f(x)}{c} = 0$ $-yf(x) + f\left(\frac{x}{y}\right) = 0$ $xf(x+y) + yf(x+y) - 1 = 0$ $xf(x-y) - yf(x-y) - 1 = 0$ $-f(x)f(y) + f(xy) = 0$ $f(y)f(x+y) - f(xy+y^2) = 0$ $f(y)f(x-y) - f(xy-y^2) = 0$ $f(x)f(x+y) - f(x^2+xy) = 0$ $f(x-y)f(x+y) - f(x^2-y^2) = 0$ $f(xy+z) - \frac{f(z)}{xyf(z)+1} = 0$ $f(x)f(y)f(z) - f(xyz) = 0$ $-2xf(x^2-y^2) + f(x-y) + f(x+y) = 0$ $x^2f(x-y)f(x+y) - y^2f(x-y)f(x+y) - 1 = 0$ $f(x)f(y) + f(x)f(x-y) - f(y)f(x-y) = 0$ $-f(x)f(y) + f(x)f(x+y) + f(y)f(x+y) = 0$ $-f(y)f(x-y) + f(y)f(x+y) + 2f(x-y)f(x+y) = 0$ $-(x+y+z)f(xyz) + f(x)f(y) + f(x)f(z) + f(y)f(z) = 0$
77. Mobius Cayley	$f(y)f(z)f(yz) - f(y) - f(z) + f(yz) = 0$ $f(x)f(y)f(xy) - f(x) - f(y) + f(xy) = 0$ $f(x)f(yz)f(xyz) - f(x) - f(yz) + f(xyz) = 0$ $f(x)f(x-y) + f(x)f(x+y) - 2f(x) - 2f(x-y)f(x+y) + f(x-y) + f(x+y) = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
78. Exp X^2	$-f^{a^2}(x) + f(ax) = 0$ $-f^{y^2}(x) + f(xy) = 0$ $f(x)f(y) - f(\sqrt{x^2 + y^2}) = 0$ $-f^2(x)f^2(y) + f(x - y)f(x + y) = 0$ $-f^2(a)f^2(x) + f(-a + x)f(a + x) = 0$ $-f^2(2x)f^2(y) + f(2x - y)f(2x + y) = 0$ $-f^2(x)f^2(2y) + f(x - 2y)f(x + 2y) = 0$ $f(\sqrt{2}x)f(\sqrt{2}y) - f(x - y)f(x + y) = 0$ $f(x)f(y)f(z) - f(\sqrt{x^2 + y^2 + z^2}) = 0$ $-f^2(ax)f^2(by) + f(ax - by)f(ax + by) = 0$ $-f^2(z)f^2(x + y) + f(x + y - z)f(x + y + z) = 0$ $-f^2(x)f^2(y + z) + f(x - y - z)f(x + y + z) = 0$ $-f^2(x)f^2(y - z) + f(x - y + z)f(x + y - z) = 0$ $-f^2(x)f^4(y)f^2(z) + f(x - y)f(x + y)f(y - z)f(y + z) = 0$ $-f^4(x)f^4(y)f^4(z) + f(x - y - z)f(x - y + z)f(x + y - z)f(x + y + z) = 0$
79. Exp Co-sine	$f(r + x)f(r + x + \pi) - 1 = 0$ $f(-r + x)f(-r + x + \pi) - 1 = 0$ $f\left(r - \frac{\pi}{2}\right)f\left(r + \frac{\pi}{2}\right) - 1 = 0$ $f\left(r + x - \frac{\pi}{2}\right)f\left(r + x + \frac{\pi}{2}\right) - 1 = 0$ $f\left(-r + x - \frac{\pi}{2}\right)f\left(-r + x + \frac{\pi}{2}\right) - 1 = 0$

Table 20. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across RSR-Bench (continued)

Function	Discovered RSR Properties
80. Fourth Power	$-c^4 f(x) + f(cx) = 0$ $-f(x)f(y) + f(xy) = 0$ $f(x-y)f(x+y) - f(x^2 - y^2) = 0$ $-\frac{f(x)}{f(y)} + f\left(\frac{x}{y}\right) = 0$ $f(-a+x)f(a+x) - f(-a^2 + x^2) = 0$ $12x^2y^2 + 2f(x) + 2f(y) - f(x-y) - f(x+y) = 0$ $-12r^2x^2 - 2f(r) - 2f(x) + f(-r+x) + f(r+x) = 0$ $-48x^2y^2 - 2f(2x) - 2f(y) + f(2x-y) + f(2x+y) = 0$ $-24f(r) + 6f(x) + f(-2r+x) - 4f(-r+x) - 4f(r+x) + f(2r+x) = 0$ $-20f(x) + f(-3r+x) - 6f(-2r+x) + 15f(-r+x) + 15f(r+x)$ $-6f(2r+x) + f(3r+x) = 0$ $-24x^2y^2 - 24x^2z^2 - 24y^2z^2 - 4f(x) - 4f(y) - 4f(z) + f(x-y-z)$ $+f(x-y+z) + f(x+y-z) + f(x+y+z) = 0$

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (A01–A17). Notation: DP = $\text{Cl}(2, 0)$ product determinant; DPM = matrix-product determinant; DT = $\text{Cl}(2, 0)$ determinant; OP = octonion-product norm²; QN = quaternion norm²; QP = quaternion-product norm².

Function	Discovered RSR Properties
A01. $\det(A)$ (add.)	$ \begin{aligned} & -kf(a, b, c, d) + f(ak, b, ck, d) = 0 \\ & -kf(a, b, c, d) + f(a, bk, c, dk) = 0 \\ & -f(x, y, z, w) + f(x + y, y, w + z, w) = 0 \\ & -f(x, y, z, w) + f(x, x + y, z, w + z) = 0 \\ & -k_1k_2f(a, b, c, d) + f(ak_1, bk_1, ck_2, dk_2) = 0 \\ & -kf(1, 1, c, d) - f(a, b, c, d) + f(a + k, b + k, c, d) = 0 \\ & -kf(a, b, 1, 1) - f(a, b, c, d) + f(a, b, c + k, d + k) = 0 \\ & -2f(x, y, z, w) + f(x, y, z, w + z) + f(x, x + y, z, w) = 0 \\ & -2f(x, y, z, w) + f(x, y, w + z, w + z) + f(x + y, x + y, z, w) = 0 \\ & -f(x, y, z, w) - f(x, y, z, w + z) + f(x, y, w + z, w + z) \\ & \quad + f(x + y, y, z, w) = 0 \\ & -f(x, y, z, w) + f(x, y, z, w + z) + f(x, y, w + z, w) \\ & \quad - f(x, y, w + z, w + z) = 0 \\ & -f(a, b, c + s, d) + f(a, b, c + s, d + t) + f(a, b + s, c, d) \\ & \quad - f(a, b + s, c, d + t) = 0 \\ & -f(a, b, c, d) + f(a, b, c, d + r_4) + f(a, b + r_2, c, d) \\ & \quad - f(a, b + r_2, c, d + r_4) = 0 \\ & -f(a, b, c, d) + f(a, b, c, d + r_4) + f(a, b, c + r_3, d) \\ & \quad - f(a, b, c + r_3, d + r_4) = 0 \\ & f(a, b, c, d + r_4) - f(a, b + r_2, c, d + r_4) - f(a + r_1, b, c, d) \\ & \quad + f(a + r_1, b + r_2, c, d) = 0 \\ & f(a, b, c, d + r_4) - f(a, b, c + r_3, d + r_4) - f(a + r_1, b, c, d) \\ & \quad + f(a + r_1, b, c + r_3, d) = 0 \\ & -f(a_1, b_1, c_1, d_1) - f(a_1, b_2, c_1, d_2) \\ & -f(a_2, b_1, c_2, d_1) - f(a_2, b_2, c_2, d_2) \\ & \quad + f(a_1 + a_2, b_1 + b_2, c_1 + c_2, d_1 + d_2) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A02. $\det(A)$ (mult.)	$ \begin{aligned} & -kf(a, b, c, d) + f(ak, bk, c, d) = 0 \\ & -kf(a, b, c, d) + f(a, b, ck, dk) = 0 \\ & -dr - f(a, b, c, d) + f(a + r, b, c, d) = 0 \\ & -ar - f(a, b, c, d) + f(a, b, c, d + r) = 0 \\ & -f(0, r, c, d) - f(a, b, c, d) + f(a, b + r, c, d) = 0 \\ & -f(a, b, c, d) - f(a, b, r, 0) + f(a, b, c + r, d) = 0 \\ & -f(a, b, c, d) - f(r_1, r_2, c, d) + f(a + r_1, b + r_2, c, d) = 0 \\ & -f(a, b, c, d) - f(a, b, r_1, r_2) + f(a, b, c + r_1, d + r_2) = 0 \\ & f(a, b, c, r) - f(a, b, c, d + r) - f(r, b, c, d) \\ & \quad + f(a + r, b, c, d) = 0 \\ & -f(a, b, c, d) - f(a, b, c, r) + f(a, b, c, d + r) \\ & \quad - f(a, r, c, d) + f(a, b + r, c, d) = 0 \\ & -f(a, b, c, d) - f(a, b, c, r) + f(a, b, c, d + r) \\ & \quad - f(a, b, r, d) + f(a, b, c + r, d) = 0 \\ & -d2rf(a1, b1, c1, d1) - \text{DPM}(a1, b1, c1, d1, a2, b2, c2, d2) \\ & \quad + \text{DPM}(a1, b1, c1, d1, a2 + r, b2, c2, d2) = 0 \\ & 3f(a, b, c, d) - f(a, b, c, d + r_4) - f(a, b, c + r_3, d) \\ & \quad - f(a, b + r_2, c, d) - f(r_1, r_2, r_3, r_4) \\ & -f(a + r_1, b, c, d) + f(a + r_1, b + r_2, c + r_3, d + r_4) = 0 \end{aligned} $
A03. $\text{tr}(A)$	$ \begin{aligned} & -r - f(a, b, c, d) + f(a + r, b, c, d) = 0 \\ & -s - f(a, b, c, d) + f(a, b, c, d + s) = 0 \\ & -f(a, b, c, d) + f(a + r, b, c, d - r) = 0 \\ & -f(x, b, c, z) + f(x + y, b, c, -y + z) = 0 \\ & -r - s - f(a, b, c, d) + f(a + r, b, c, d + s) = 0 \\ & f(a, b, c, d + s) - f(r, b, c, s) - f(a - r, b, c, d) = 0 \\ & -f(a, b, c, d - s) - f(r, b, c, s) + f(a + r, b, c, d) = 0 \\ & -f(r, b, c, s) - f(x, b, c, y) + f(r + x, b, c, s + y) = 0 \\ & f(x, b, c, y) + f(y, b, c, x) - 2f\left(\frac{x+y}{2}, b, c, \frac{x+y}{2}\right) = 0 \\ & 2f(a, b, c, d) - f(a, b, c, d - s) - f(r, b, c, s) \\ & \quad - f(a - r, b, c, d) = 0 \\ & f(a_1, b, c, d_1) + f(a_2, b, c, d_2) - f(a_1 + a_2, b, c, d_1 + d_2) = 0 \\ & f(a_1, b, c, d_1) - f(a_2, b, c, d_2) - f(a_1 - a_2, b, c, d_1 - d_2) = 0 \\ & -f(a, b, c, d - s) + f(2a, b, c, 2d) - f(r, b, c, s) \\ & \quad - f(a - r, b, c, d) = 0 \\ & -2f(a_2, b, c, d_2) - f(a_1 - a_2, b, c, d_1 - d_2) \\ & \quad + f(a_1 + a_2, b, c, d_1 + d_2) = 0 \\ & f(a_1, b, c, d_1) + f(a_2, b, c, d_2) + f(a_3, b, c, d_3) \\ & \quad - f(a_1 + a_2 + a_3, b, c, d_1 + d_2 + d_3) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A04. $\ q\ ^2$ (add.)	$ \begin{aligned} & -2f(a, b, c, d) - 2f(r, r, 0, 0) + f(a - r, b - r, c, d) \\ & \quad + f(a + r, b + r, c, d) = 0 \\ & -2f(0, 0, t, t) - 2f(a, b, c, d) + f(a, b, c - t, d - t) \\ & \quad + f(a, b, c + t, d + t) = 0 \\ & -2f(a, b, c, d) - 2f(r, s, t, 0) + f(a - r, b - s, c - t, d) \\ & \quad + f(a + r, b + s, c + t, d) = 0 \\ & -2f(a, b, c, d) - 2f(r, s, t, u) + f(a - r, b - s, c - t, d - u) \\ & \quad + f(a + r, b + s, c + t, d + u) = 0 \\ & -4f(a, b, c, d) - 4f(r, s, 0, 0) + f(a - r, b - s, c, d) \\ & \quad + f(a - r, b + s, c, d) + f(a + r, b - s, c, d) + f(a + r, b + s, c, d) = 0 \end{aligned} $
A05. $\ q_1 q_2\ ^2$	$ \begin{aligned} & -k^2 \text{QP}(a1, b1, c1, d1, a2, b2, c2, d2) \\ & \quad + \text{QP}(a1k, b1k, c1k, d1k, a2, b2, c2, d2) = 0 \\ & -k^2 \text{QP}(a1, b1, c1, d1, a2, b2, c2, d2) \\ & \quad + \text{QP}(a1, b1, c1, d1, a2k, b2k, c2k, d2k) = 0 \\ & -2 \text{QN}(a1, b1, c1, d1) - 2 \text{QN}(a2, b2, c2, d2) \\ & \quad + \text{QN}(a1 - a2, b1 - b2, c1 - c2, d1 - d2) \\ & \quad + \text{QN}(a1 + a2, b1 + b2, c1 + c2, d1 + d2) = 0 \\ & -2 \text{QP}(a1, b1, c1, d1, a2, b2, c2, d2) - 2 \text{QP}(a1, b1, c1, d1, x, y, z, w) \\ & \quad + \text{QP}(a1, b1, c1, d1, a2 - x, b2 - y, c2 - z, d2 - w) \\ & \quad + \text{QP}(a1, b1, c1, d1, a2 + x, b2 + y, c2 + z, d2 + w) = 0 \\ & -2 \text{QP}(a1, b1, c1, d1, a2, b2, c2, d2) - 2 \text{QP}(x, y, z, w, a2, b2, c2, d2) \\ & \quad + \text{QP}(a1 - x, b1 - y, c1 - z, d1 - w, a2, b2, c2, d2) \\ & \quad + \text{QP}(a1 + x, b1 + y, c1 + z, d1 + w, a2, b2, c2, d2) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A06. $\text{tr}(A^2)$	$ \begin{aligned} & -k^2 f(a, b, c, d) + f(ak, bk, ck, dk) = 0 \\ & -4ar - f(a - r, b, c, d) + f(a + r, b, c, d) = 0 \\ & -4dr - f(a, b, c, d - r) + f(a, b, c, d + r) = 0 \\ & -4cr - f(a, b - r, c, d) + f(a, b + r, c, d) = 0 \\ & -4br - f(a, b, c - r, d) + f(a, b, c + r, d) = 0 \\ & -4bt - 4cs - f(a, b - s, c - t, d) + f(a, b + s, c + t, d) = 0 \\ & -2f(a, b, c, d) + f(a, b - r, c, d) + f(a, b + r, c, d) = 0 \\ & -2f(a, b, c, d) + f(a, b, c - r, d) + f(a, b, c + r, d) = 0 \\ & -2r(b + c + r) - f(a, b, c, d) + f(a, b + r, c + r, d) = 0 \\ & -2ar - 2dt - r^2 - t^2 - f(a, 0, 0, d) + f(a + r, 0, 0, d + t) = 0 \\ & -2b^2 - 2f(a, c, d, e) + f(a - b, c, d, e) + f(a + b, c, d, e) = 0 \\ & -4st - 2f(a, b, c, d) + f(a, b - s, c - t, d) + f(a, b + s, c + t, d) = 0 \\ & -2f(a, b, c, d) - 2f(r, 0, 0, 0) + f(a - r, b, c, d) \\ & \quad + f(a + r, b, c, d) = 0 \\ & -2f(0, 0, 0, r) - 2f(a, b, c, d) + f(a, b, c, d - r) \\ & \quad + f(a, b, c, d + r) = 0 \\ & -2ar - 2bt - 2cs - 2du - f(a, b, c, d) - f(r, s, t, u) \\ & \quad + f(a + r, b + s, c + t, d + u) = 0 \\ & -2f(a, b, c, d) - 2f(r, s, t, u) + f(a - r, b - s, c - t, d - u) \\ & \quad + f(a + r, b + s, c + t, d + u) = 0 \end{aligned} $
A07. $e_2(x, y, z)$	$ \begin{aligned} & -c^2 f(x, y, z) + f(cx, cy, cz) = 0 \\ & -r(y + z) - f(x, y, z) + f(r + x, y, z) = 0 \\ & -r(x + z) - f(x, y, z) + f(x, r + y, z) = 0 \\ & -r(x + y) - f(x, y, z) + f(x, y, r + z) = 0 \\ & -r^2 - r(x + y + 2z) - f(x, y, z) + f(r + x, r + y, z) = 0 \\ & -r^2 - r(x + 2y + z) - f(x, y, z) + f(r + x, y, r + z) = 0 \\ & -r^2 - r(2x + y + z) - f(x, y, z) + f(x, r + y, r + z) = 0 \\ & -3r^2 - 2r(x + y + z) - f(x, y, z) + f(r + x, r + y, r + z) = 0 \\ & -rs - r(y + z) - s(x + z) - f(x, y, z) \\ & \quad + f(r + x, s + y, z) = 0 \\ & -rs - r(y + z) - s(x + y) - f(x, y, z) \\ & \quad + f(r + x, y, s + z) = 0 \\ & -rs - r(x + z) - s(x + y) - f(x, y, z) \\ & \quad + f(x, r + y, s + z) = 0 \\ & -f(r, r, r) + 2f(x, y, z) - f(x, y, r + z) \\ & -f(x, r + y, z) - f(r + x, y, z) + f(r + x, r + y, r + z) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A08. $e_3(x, y, z)$	$ \begin{aligned} & -2f(r, s, z) - 2f(r, y, t) - 2f(x, s, t) \\ & -2f(x, y, z) + f(-r + x, -s + y, -t + z) + f(r + x, s + y, t + z) = 0 \\ & -f(r, s, t) - f(r, s, z) - f(r, y, t) - f(r, y, z) \\ & -f(x, s, t) - f(x, s, z) - f(x, y, t) - f(x, y, z) \\ & + f(r + x, s + y, t + z) = 0 \\ & f(r, s, t) + f(r, s, z) - f(r, y, t) - f(r, y, z) \\ & + f(x, s, t) + f(x, s, z) - f(x, y, t) - f(x, y, z) \\ & + f(r + x, -s + y, t + z) = 0 \\ & f(r, s, t) - f(r, s, z) + f(r, y, t) - f(r, y, z) \\ & + f(x, s, t) - f(x, s, z) + f(x, y, t) - f(x, y, z) \\ & + f(r + x, s + y, -t + z) = 0 \\ & f(r, s, t) + f(r, s, z) + f(r, y, t) + f(r, y, z) \\ & - f(x, s, t) - f(x, s, z) - f(x, y, t) - f(x, y, z) \\ & + f(-r + x, s + y, t + z) = 0 \\ & f(r, s, t) - f(r, s, z) - f(r, y, t) + f(r, y, z) \\ & - f(x, s, t) + f(x, s, z) + f(x, y, t) - f(x, y, z) \\ & + f(-r + x, -s + y, -t + z) = 0 \end{aligned} $
A09. $p_2(x, y, z)$	$ \begin{aligned} & n^2 f(x, y, z) - f(nx, ny, nz) = 0 \\ & -c^2 f(x, y, z) + f(cx, cy, cz) = 0 \\ & -4f(x, y, z) + f(x - y, y - z, -x + z) + f(x + y, y + z, x + z) = 0 \\ & -4(ax + by + cz) - f(-a + x, -b + y, -c + z) + f(a + x, b + y, c + z) = 0 \\ & -5f(x, y, z) + f(x, y + z, y - z) + f(x + y, x - y, z) \\ & + f(x + z, y, x - z) = 0 \\ & -2f(r_1, r_2, r_3) - 2f(x, y, z) + f(-r_1 + x, -r_2 + y, -r_3 + z) \\ & + f(r_1 + x, r_2 + y, r_3 + z) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A10. $\ \mathbf{v}\ ^2$ (2D)	$ \begin{aligned} & -c^2 f(x, y) + f(cx, cy) = 0 \\ & 2f(0, s) + 2f(x, y) - f(x, -s + y) \\ & \quad - f(x, s + y) = 0 \\ & -8f(r, 0) - 2f(x, y) + f(2r + x, y) \\ & \quad + f(-2r + x, y) = 0 \\ & -8f(0, s) - 2f(x, y) + f(x, 2s + y) \\ & \quad + f(x, -2s + y) = 0 \\ & -2f(r, s) - 2f(x, y) + f(-r + x, -s + y) \\ & \quad + f(r + x, s + y) = 0 \\ & -2f(r, s) - 2f(x, y) + f(-r + x, s + y) \\ & \quad + f(r + x, -s + y) = 0 \\ & -4f(r, s) - 4f(x, y) + f(-r + x, -s + y) \\ & + f(-r + x, s + y) + f(r + x, -s + y) + f(r + x, s + y) = 0 \\ & 2f(x, y) + f(x, 2s + y) + 3f(-r + x, -s + y) \\ & -4f(-r + x, s + y) - 4f(r + x, -s + y) + f(r + x, s + y) \\ & \quad + f(2r + x, y) = 0 \end{aligned} $
A11. $\ \mathbf{a} \times \mathbf{b}\ ^2$	$ \begin{aligned} & -c^2 f(x_1, y_1, z_1, x_2, y_2, z_2) + f(cx_1, cy_1, cz_1, x_2, y_2, z_2) = 0 \\ & -c^2 f(x_1, y_1, z_1, x_2, y_2, z_2) + f(x_1, y_1, z_1, cx_2, cy_2, cz_2) = 0 \\ & - (ab)^2 f(x_1, y_1, z_1, x_2, y_2, z_2) + f(ax_1, ay_1, az_1, bx_2, by_2, bz_2) = 0 \\ & -b^2 f(x_1, y_1, z_1, x_2, y_2, z_2) + f(x_1, y_1, z_1, ax_1 + bx_2, ay_1 + by_2, az_1 + bz_2) = 0 \\ & -2f(r_1, r_2, r_3, x_2, y_2, z_2) - 2f(x_1, y_1, z_1, x_2, y_2, z_2) \\ & \quad + f(-r_1 + x_1, -r_2 + y_1, -r_3 + z_1, x_2, y_2, z_2) \\ & \quad + f(r_1 + x_1, r_2 + y_1, r_3 + z_1, x_2, y_2, z_2) = 0 \\ & -2f(x_1, y_1, z_1, r_1, r_2, r_3) - 2f(x_1, y_1, z_1, x_2, y_2, z_2) \\ & \quad + f(x_1, y_1, z_1, -r_1 + x_2, -r_2 + y_2, -r_3 + z_2) \\ & \quad + f(x_1, y_1, z_1, r_1 + x_2, r_2 + y_2, r_3 + z_2) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A12. $\ o\ ^2$ (8D)	$ \begin{aligned} & -2t^2 - 2f(a, b, c, d, p, q, r, s) + f(a - t, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b, c, d, p, q, r, s) = 0 \\ & -2t^2 - 2f(a, b, c, d, p, q, r, s) + f(a, b - t, c, d, p, q, r, s) \\ & \quad + f(a, b + t, c, d, p, q, r, s) = 0 \\ & -4t^2 - 2t(a + b - c - d) - f(a, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b + t, c - t, d - t, p, q, r, s) = 0 \\ & -4t^2 - 2t(a + c + p + r) - f(a, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b, c + t, d, p + t, q, r + t, s) = 0 \\ & -4t^2 - 2f(a, b, c, d, p, q, r, s) + f(a - t, b + t, c, d, p, q, r, s) \\ & \quad + f(a + t, b - t, c, d, p, q, r, s) = 0 \\ & -4t^2 - 2f(a, b, c, d, p, q, r, s) + f(a - t, b, c + t, d, p, q, r, s) \\ & \quad + f(a + t, b, c - t, d, p, q, r, s) = 0 \\ & -8t^2 - 2f(a, b, c, d, p, q, r, s) + f(a - t, b - t, c - t, d - t, p, q, r, s) \\ & \quad + f(a + t, b + t, c + t, d + t, p, q, r, s) = 0 \\ & -2f(a, b, c, d, p, q, r, s) - 2f(t, t, 0, 0, 0, 0, 0, 0) + f(a - t, b - t, c, d, p, q, r, s) \\ & \quad + f(a + t, b + t, c, d, p, q, r, s) = 0 \\ & -8t^2 - 2t(a + b + c + d + p + q + r + s) - f(a, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b + t, c + t, d + t, p + t, q + t, r + t, s + t) = 0 \\ & \quad - 8t^2 - 2t(a - b + c - d + p - q + r - s) \\ & \quad - f(a, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b - t, c + t, d - t, p + t, q - t, r + t, s - t) = 0 \\ & \quad - 8t^2 - 2t(a + b + c + d - p - q - r - s) \\ & \quad - f(a, b, c, d, p, q, r, s) \\ & \quad + f(a + t, b + t, c + t, d + t, p - t, q - t, r - t, s - t) = 0 \\ & \quad - 2t_1^2 - 2t_2^2 \\ & -2f(a, b, c, d, p, q, r, s) + f(a - t_1, b - t_2, c, d, p, q, r, s) \\ & \quad + f(a + t_1, b + t_2, c, d, p, q, r, s) = 0 \\ & \quad - 2t_1^2 - 2t_2^2 \\ & -2f(a, b, c, d, p, q, r, s) + f(a - t_1, b, c - t_2, d, p, q, r, s) \\ & \quad + f(a + t_1, b, c + t_2, d, p, q, r, s) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A12. $\ o\ ^2$ (8D) (cont.)	$ \begin{aligned} & -f(a, b, c - t, d - t, p, q, r, s) \\ & -f(a, b, c + t, d + t, p, q, r, s) \\ & +f(a - t, b - t, c, d, p, q, r, s) + f(a + t, b + t, c, d, p, q, r, s) = 0 \\ & -f(a, b - t, c, d - t, p, q, r, s) \\ & -f(a, b + t, c, d + t, p, q, r, s) \\ & +f(a - t, b, c - t, d, p, q, r, s) + f(a + t, b, c + t, d, p, q, r, s) = 0 \\ & -16t^2 - 2f(a, b, c, d, p, q, r, s) \\ & +f(a - t, b - t, c - t, d - t, p - t, q - t, r - t, s - t) \\ & +f(a + t, b + t, c + t, d + t, p + t, q + t, r + t, s + t) = 0 \\ & -2(ar_1 + br_2 + cr_3 + dr_4 + pr_5 + qr_6 + rr_7 + r_8s) \\ & -f(a, b, c, d, p, q, r, s) - f(r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) \\ & +f(a + r_1, b + r_2, c + r_3, d + r_4, p + r_5, q + r_6, r + r_7, r_8 + s) = 0 \end{aligned} $
A13. $\ o_1 o_2\ ^2$	$ \begin{aligned} & -k_1^2 k_2^2 \text{OP}(a_1, b_1, c_1, d_1, p_1, q_1, r_1, s_1, \\ & \quad a_2, b_2, c_2, d_2, p_2, q_2, r_2, s_2) \\ & + \text{OP}(a_1 k_1, b_1 k_1, c_1 k_1, d_1 k_1, k_1 p_1, k_1 q_1, k_1 r_1, k_1 s_1, \\ & \quad a_2 k_2, b_2 k_2, c_2 k_2, d_2 k_2, k_2 p_2, k_2 q_2, k_2 r_2, k_2 s_2) = 0 \\ & -2 \text{OP}(a_1, b_1, c_1, d_1, p_1, q_1, r_1, s_1, \\ & \quad a_2, b_2, c_2, d_2, p_2, q_2, r_2, s_2) \\ & -2 \text{OP}(r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8, \\ & \quad a_2, b_2, c_2, d_2, p_2, q_2, r_2, s_2) \\ & + \text{OP}(a_1 - r_1, b_1 - r_2, c_1 - r_3, d_1 - r_4, p_1 - r_5, q_1 - r_6, r_1 - r_7, -r_8 + s_1, \\ & \quad a_2, b_2, c_2, d_2, p_2, q_2, r_2, s_2) \\ & + \text{OP}(a_1 + r_1, b_1 + r_2, c_1 + r_3, d_1 + r_4, p_1 + r_5, q_1 + r_6, r_1 + r_7, r_8 + s_1, \\ & \quad a_2, b_2, c_2, d_2, p_2, q_2, r_2, s_2) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A14. $\text{Cl}(3, 0)$ conj.	$ \begin{aligned} & -c^2 f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) + f(cs, cv_1, cv_2, cv_3, b_1c, b_2c, b_3c, ct) = 0 \\ & -2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) + f(-r + s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) \\ & \quad + f(r + s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) = 0 \\ & 2f(0, 0, 0, 0, 0, 0, 0, r) + 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & -f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) - f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) = 0 \\ & 2f(0, 0, 0, 0, r, 0, 0, 0) - 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & + f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) + f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) = 0 \\ & 2f(0, r, 0, 0, 0, 0, 0, 0) + 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & -f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) - f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) = 0 \\ & 2f(r, 0, 0, 0, 0, 0, 0, 0) - 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & + f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) + f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) = 0 \\ & -f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) - f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) \\ & + f(s, -r + v_1, v_2, v_3, b_1, b_2, b_3, t) + f(s, r + v_1, v_2, v_3, b_1, b_2, b_3, t) = 0 \\ & 2f(0, 0, 0, r_2, 0, 0, r_3, 0) + 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad - f(s, v_1, v_2, -r_2 + v_3, b_1, b_2, b_3 - r_3, t) \\ & \quad - f(s, v_1, v_2, r_2 + v_3, b_1, b_2, b_3 + r_3, t) = 0 \\ & 2f(0, 0, r_2, 0, 0, r_3, 0, 0) + 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad - f(s, v_1, v_2, -r_2 + v_3, b_1, b_2, b_3 - r_3, t) \\ & \quad - f(s, v_1, v_2, r_2 + v_3, b_1, b_2, b_3 + r_3, t) = 0 \\ & 2f(0, 0, 0, 0, r_1, r_2, r_3, 0) + 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad - f(s, v_1, v_2, v_3, b_1 - r_1, b_2 - r_2, b_3 - r_3, t) \\ & \quad - f(s, v_1, v_2, v_3, b_1 + r_1, b_2 + r_2, b_3 + r_3, t) = 0 \\ & 2f(0, r_1, r_2, r_3, 0, 0, 0, 0) - 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad + f(s, v_1, v_2, v_3, b_1 - r_1, b_2 - r_2, b_3 - r_3, t) \\ & \quad + f(s, v_1, v_2, v_3, b_1 + r_1, b_2 + r_2, b_3 + r_3, t) = 0 \\ & -2f(r_1, r_2, 0, 0, r_3, 0, 0, 0) - 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad + f(-r_1 + s, -r_2 + v_1, v_2, v_3, b_1 - r_3, b_2, b_3, t) \\ & \quad + f(r_1 + s, r_2 + v_1, v_2, v_3, b_1 + r_3, b_2, b_3, t) = 0 \\ & \quad - f(s, v_1, v_2, -r_2 + v_3, b_1, b_2, b_3 - r_3, t) \\ & -f(s, v_1, v_2, r_2 + v_3, b_1, b_2, b_3 + r_3, t) + f(s, v_1, -r_2 + v_2, v_3, b_1, b_2 - r_3, b_3, t) \\ & \quad + f(s, v_1, r_2 + v_2, v_3, b_1, b_2 + r_3, b_3, t) = 0 \\ & -4f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) + f(s, v_1, v_2, v_3, b_1, b_2, b_3, -r + t) \\ & + f(s, v_1, v_2, v_3, b_1, b_2, b_3, r + t) + f(-r + s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & \quad + f(r + s, v_1, v_2, v_3, b_1, b_2, b_3, t) = 0 \\ & -2f(r_1, r_2, r_3, r_4, r_5, r_6, r_7, r_8) - 2f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) \\ & + f(-r_1 + s, -r_2 + v_1, -r_3 + v_2, -r_4 + v_3, b_1 - r_5, b_2 - r_6, b_3 - r_7, -r_8 + t) \\ & + f(r_1 + s, r_2 + v_1, r_3 + v_2, r_4 + v_3, b_1 + r_5, b_2 + r_6, b_3 + r_7, r_8 + t) = 0 \\ & -4f(s, v_1, v_2, v_3, b_1, b_2, b_3, t) + f(s, v_1, v_2, v_3, b_1 - r_1, b_2 - r_2, b_3 - r_3, t) \\ & \quad + f(s, v_1, v_2, v_3, b_1 + r_1, b_2 + r_2, b_3 + r_3, t) \\ & + f(s, -r_1 + v_1, -r_2 + v_2, -r_3 + v_3, b_1, b_2, b_3, t) \\ & + f(s, r_1 + v_1, r_2 + v_2, r_3 + v_3, b_1, b_2, b_3, t) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A15. $\text{Cl}(2, 0)$ det.	$ \begin{aligned} & -2 \text{DT}(r, a, b, c) - 2 \text{DT}(s, 0, 0, 0) \\ & + \text{DT}(-r + s, a, b, c) + \text{DT}(r + s, a, b, c) = 0 \\ & -4 \text{DT}(s, a, b, c) + \text{DT}(s, a, b, c - r) \\ & + \text{DT}(s, a, b, c + r) + \text{DT}(s, a, b - r, c) \\ & + \text{DT}(s, a, b + r, c) = 0 \\ & \text{DP}(-r + s1, a1, b1, c1, s2, a2, b2, c2) + \text{DP}(r + s1, a1, b1, c1, s2, a2, b2, c2) \\ & -2 \text{DT}(r, 0, 0, 0) \text{DT}(s2, a2, b2, c2) \\ & -2 \text{DT}(s1, a1, b1, c1) \text{DT}(s2, a2, b2, c2) = 0 \\ & \text{DP}(s1, a1, b1, c1, -r + s2, a2, b2, c2) + \text{DP}(s1, a1, b1, c1, r + s2, a2, b2, c2) \\ & -2 \text{DT}(r, 0, 0, 0) \text{DT}(s1, a1, b1, c1) \\ & -2 \text{DT}(s1, a1, b1, c1) \text{DT}(s2, a2, b2, c2) = 0 \\ & -4 \text{DP}(s1, a1, b1, c1, s2, a2, b2, c2) + \text{DP}(s1, a1, b1, c1 - r, s2, a2, b2, c2) \\ & + \text{DP}(s1, a1, b1, c1 + r, s2, a2, b2, c2) + \text{DP}(s1, a1 - r, b1, c1, s2, a2, b2, c2) \\ & + \text{DP}(s1, a1 + r, b1, c1, s2, a2, b2, c2) = 0 \\ & -4 \text{DP}(s1, a1, b1, c1, s2, a2, b2, c2) + \text{DP}(s1, a1, b1, c1 - r, s2, a2, b2, c2) \\ & + \text{DP}(s1, a1, b1, c1 + r, s2, a2, b2, c2) + \text{DP}(s1, a1, b1 - r, c1, s2, a2, b2, c2) \\ & + \text{DP}(s1, a1, b1 + r, c1, s2, a2, b2, c2) = 0 \end{aligned} $
A16. $\text{tr}([A, B]^2)$	$ \begin{aligned} & -k^2 f(a_1, b_1, c_1, d_1, a_2, b_2, c_2, d_2) + f(a_1 k, b_1 k, c_1 k, d_1 k, a_2, b_2, c_2, d_2) = 0 \\ & -k^2 f(a_1, b_1, c_1, d_1, a_2, b_2, c_2, d_2) + f(a_1, b_1, c_1, d_1, a_2 k, b_2 k, c_2 k, d_2 k) = 0 \\ & -k^4 f(a_1, b_1, c_1, d_1, a_2, b_2, c_2, d_2) + f(a_1 k, b_1 k, c_1 k, d_1 k, a_2 k, b_2 k, c_2 k, d_2 k) = 0 \end{aligned} $

Table 21. RSR Properties Discovered by Claude Opus 4.1 (Agentic Bitween) across the algebraic benchmarks (continued)

Function	Discovered RSR Properties
A17. $\mathfrak{sl}(2)$ Killing	$ \begin{aligned} & -f(a, b, ck) + f(a, bk, c) = 0 \\ & -2f(a, b, c) + f(a, b - s, c) + f(a, b + s, c) = 0 \\ & -2f(a, b, c) + f(a, b, c - t) + f(a, b, c + t) = 0 \\ & -f(0, 2a, 2r) - f(a - r, b, c) + f(a + r, b, c) = 0 \\ & -f(0, b_2, c) - f(a, b_1, c) + f(a, b_1 + b_2, c) = 0 \\ & -f(0, b, c_2) - f(a, b, c_1) + f(a, b, c_1 + c_2) = 0 \\ & f(a, 0, d) - f(a, b, d) - f(a, c, d) + f(a, b + c, d) = 0 \\ & f(a, b, 0) - f(a, b, c) - f(a, b, d) + f(a, b, c + d) = 0 \\ & 2f(0, b, c) + 2f(a, b, 0) - f(a, b, c - t) \\ & \quad - f(a, b, c + t) = 0 \\ & -2f(a, b, c) - 2f(r, 0, 0) + f(a - r, b, c) \\ & \quad + f(a + r, b, c) = 0 \\ & -2f(a, b, 0) - 2f(r, b, c) + f(a - r, b, c) \\ & \quad + f(a + r, b, c) = 0 \\ & -6f(a, b, 0) - f(a, b, c - t) - f(a, b, c + t) \\ & \quad + 2f(2a, b, c) = 0 \\ & -f(a, b, c - t) - f(a, b, c + t) + f(a, b - s, c) \\ & \quad + f(a, b + s, c) = 0 \\ & -2a_1a_2 + bc - f(a_1, b, c) - f(a_2, b, c) \\ & \quad + f(a_1 + a_2, b, c) = 0 \\ & f(a - r, b - s, c) - f(a - r, b + s, c) - f(a + r, b - s, c) \\ & \quad + f(a + r, b + s, c) = 0 \\ & 2f(0, c, d) - 2f(a, c, d) - 2f(b, c, d) \\ & \quad + f(a - b, c, d) + f(a + b, c, d) = 0 \\ & -4f(a, b, c) - 2f(r, 0, 0) - 2f(r, s, 0) \\ & + f(a - r, b - s, c) + f(a - r, b + s, c) + f(a + r, b - s, c) \\ & \quad + f(a + r, b + s, c) = 0 \end{aligned} $