Audience Sentiment (مشاعر الجمهور)

Supporting materials for the YouTube API Services quota extension request · API client: **Audience Sentiment** · https://app.sky-develop.net · prepared 2026-09-16

1. What the application is

An Arabic-first audience-monitoring service for YouTube creators, marketing agencies and media companies in the Arabic-speaking market. A channel owner connects **their own channel** through Google OAuth; the service catalogues the channel's uploads, reads comments and replies on the videos the owner selects, classifies each comment's sentiment with an Arabic-dialect model run on our own server and its topic, and shows the owner trends over time, comparisons between videos, and the underlying comments. It is **read-only**: no write endpoint of the YouTube Data API is called, and no channel is read except through its owner's authorization.

Independent value to the YouTube ecosystem: Arabic is the largest language without a working comment-sentiment tool; existing tools are English-first and mis-classify dialectal Arabic. Creators and agencies in the region currently read thousands of comments by hand or not at all. The service gives them a measured, honestly-labelled view of how their audience reacts — with YouTube's data shown as YouTube's, and our analysis shown as ours.

2. Endpoints, scopes and quota cost

Endpoint	When	Cost	Why
`channels.list` (`mine=true`)	once, at connection	1 unit	identifies the channel the token belongs to — ownership is never taken from a typed URL
`playlistItems.list`	catalogue discovery, per plan interval	1 per 50 videos	lists the uploads playlist
`videos.list` (`snippet,statistics,contentDetails`)	discovery; and `statistics` only at every scheduled check	1 per 50 videos	titles, dates, reported comment counts; change detection before any comment read
`commentThreads.list`	only for selected videos whose comment count moved	1 per 100 comments	the comments themselves

`comments.list`	replies of read threads	1 per page	reply coverage

Scopes: `https://www.googleapis.com/auth/youtube.readonly` and `https://www.googleapis.com/auth/youtube.force-ssl`. Reading `commentThreads.list` on the owner's own videos with `youtube.readonly` alone is refused with `insufficientPermissions`; Google offers no narrower scope that permits reading comments as the owner, so `force-ssl` is requested although the application performs no write. This is documented in the application's source (`supabase/functions/oauth-start/index.ts`).

3. Measured usage (live project, 2026-09-15/16)

Operation	Measured
Discovery of a 4,456-video channel (2,194 videos, 2,253 shorts, 9 streams)	≈ 12 units in 78 seconds
Scheduled check, first pass over 100 selected videos (no stored count yet)	2 `videos.list` units + the comment pages
Scheduled check, second pass over the same 100 videos (nothing changed)	**2 units, zero `commentThreads.list` calls — "100 unchanged, 0 to read"**

4. Expected traffic and why 10,000 units/day is insufficient

Load	Units
Connect + discover a large channel (≈4,500 videos)	≈ 180 once
First read of a large channel (≈170,000 comments)	≈ 1,700 once
Daily scheduled checks, one creator (20 selected videos, daily)	1 + new comments
Daily scheduled checks, one agency (10 channels × 20 videos × 4 checks)	≈ 16 + new comments
Steady state at 100 subscribers	≈ 600 – 1,500 / day
Peak day: five large onboardings + steady state	≈ 12,000

The quota is per Google Cloud project, not per user. A single day with two or three large-channel onboardings reaches 10,000 units and blocks every other customer's scheduled read until midnight Pacific. **Requested: 50,000 units/day** — headroom for onboarding days at 300 subscribers without failing anyone's scheduled reads. Change detection (§3) keeps steady-state usage low regardless of the number of channels.

5. Data handling

Data	Stored	Retention
Google account e-mail	yes (sign-in identity)	until the account is deleted on request
OAuth tokens	encrypted at rest (AES-GCM; key held only by the server). The worker receives a one-hour access token per job and never the refresh token	until disconnected or revoked
Video metadata (id, title, published date, reported counts)	yes	refreshed at every check
Comment metadata (id, author channel id, published date, like count)	yes	refreshed at every check
Comment text	yes	**purged automatically 30 days after collection** (daily job `purge_comment_text`)
Our own labels (sentiment, topic)	yes — derived data	kept for the owner's history; clearly labelled as ours

- Each workspace's rows are isolated by Postgres row-level security; tenants cannot read each other, verified by tests against direct requests.
- No data is sold, shared with other users, or aggregated across channels.
- **Revocation:** the user can disconnect the channel in the application (two-step confirmation), or revoke at myaccount.google.com/permissions; an `invalid_grant` answer marks the connection revoked and cancels pending work immediately.
- **Deletion:** on request by e-mail; completed within 7 days.
- The privacy policy (/privacy-policy) and terms (/terms) link the YouTube Terms of Service and the Google Privacy Policy and state the above.

6. Compliance statements

- The application name does not contain "YouTube".
- YouTube data is displayed alongside our own analysis, each clearly labelled; the service does not replace YouTube's own metrics.
- Authorized data is not stored beyond 30 days without being refreshed (comment text purged; metadata refreshed each check).
- No write, rating, commenting or moderation action is performed through the API.

- A user may withdraw access at any time; the withdrawal takes effect at the next scheduled check.

7. Contact

Mohammed Lubbad · engmlubbad@gmail.com · sky-develop.net

Attachments: architecture-diagram.png, user-flow-diagram.png, privacy-policy-page.png (browser screenshot with address bar).