

International SMS platform API docking instructions

Version : 3.2

Table of contents

International SMS platform API docking instructions	1
1. signature rules	1
2. send messages	4
A. Request method & request header & request address	4
B. Interface description	4
C. Query parameters	4
D. Body Parameters	5
E. Response Parameters	5
F. Examples	6
3. Query SMS records	8
A. Request method & request header & request address	8
B. Interface description	8
C. Query parameters	8
D. Body parameters	8
E. Response parameters	9
F. Examples	10
G. SMS status description	11
4. Query Account Balance	11
A. Request method & request header & request address	11
B. Interface description	11
C. Query parameters	11
D. Body parameters	12
E. Response parameters	12
F. Examples	13

1. signature rules

- a. Contact the salesperson to obtain the interface key

apiKey.

b. Sort the transmitted values according to the ASCII code and concatenate them with "&". **Note** : Class or collection attributes cannot be converted to JSON, please refer to the example.

c. Finally, splicing key=apiKey. **Note** : Must be spliced with "&".

d. The spliced string is encrypted according to the signature type to generate a signature string.

Example:

Before signature encryption:

Send messages(ordinary):

```
content=                                OpenAPI                                Sign
test.&nonceStr=JX9p99IlsYC8qVyWJD5y&phones=[{phone=8615789894545}]&signType=MD5
&spNumber=123456&timestamp=1702459528858&username=Your User Name&key=Your Api Key
```

Send messages(variables):

```
content=                                OpenAPI                                Sign
test.&nonceStr=JX9p99IlsYC8qVyWJD5y&phones=[{phone=8615789894545, variables=[1,
2]}]&signType=MD5&spNumber=123456&timestamp=1702459528858&username=Your    User
Name&key=Your Api Key
```

Query SMS records:

```
nonceStr=JX9p99IlsYC8qVyWJD5y&signType=MD5&timestamp=1702459528858&traceId=
836124539279773696&username=Your User Name&key=Your Api Key
```

After signature encryption:

Send messages(ordinary): 46cd8c2136f40d34436bcc6c453b0269

Send messages(variables): c28fbb83e153f5e0a2526ddbc1347cdb

Query SMS records: 57e683f2b25d2842bfe509d6d3e9788e

2. send messages

A. Request method & request header & request address

Request method: POST

Request header : Content-Type: application/json
ta-version: v2

Request address: domain name + /ta-sms/openapi/submittal

B. Interface description

This interface supports the sending of ordinary SMS and variable SMS, which can be selected according to the business. Up to 100 numbers can be sent .

Ordinary SMS : The variable set is empty, and it will be sent directly with the sending content.

Variable SMS : The variable collection is not empty, and there is a placeholder "{}" in the sent content, and the variable is filled into the sent content. If the number of variables is less than or greater than the placeholder, there will be a placeholder in the sent content or some variables are not included in the sent content .

Interface request frequency: 1r/s

C. Query parameters

parameter name	Parameter Description	must	type of data
none			

D. Body Parameters

parameter name	Is it mandatory	type of data	Parameter Description
username	yes	String	channel number. The platform can be viewed
nonceStr	yes	String	Random string to prevent tampering
timestamp	yes	String	Timestamp (milliseconds), preventing replay
signType	yes	String	Signature type (MD5, SHA256, SHA384, SM3, RIPEMD160, SHA224, SHA512)
sign	yes	String	Signature string, refer to signature rules
spNumber	no	String	Send ID. Default random 6 digits
content	yes	String	Send Content. The placeholder "{}" can be used instead of variables, such as: Dear {} customer, hello! Your {} order has been shipped.
phones	yes	List<Phone>	collection of numbers. Up to 100 numbers.
phone		Object	number object
phone	yes	String	cell phone number . Must include the country code (eg: China 86 15789894545)
variables	no	List<String>	collection of variables

E. Response Parameters

parameter name	Parameter Type	Parameter Description
code	String	response code . "200": success, others : failure
message	String	Response message
data	List<Result>	Submit results

parameter name	Parameter Type	Parameter Description
Result	Object	
traceId	Long	Tracking ID
msgIds	List<Submitted>	A collection of message IDs. A number corresponds to a message ID
Submitted	Object	
phone	String	Number
msgId	String	Message ID

F. Examples

The screenshot displays a REST client interface with a request and its corresponding response.

Request:

- HEADERS:** Content-Type: application/json
- BODY:** A JSON object containing fields: username, nonceStr, spNumber, signType, timestamp, sign, content, and phones.

Response:

- Status:** 200 OK
- HEADERS:** Connection: keep-alive, Transfer-Encoding: chunked, Content-Type: application/json, Date: Sun, 25 Jun 2023 09:09:13 GMT
- BODY:** A JSON object containing fields: code, message, data, and msgIds. The data field contains a traceId and a Submitted object with phone and msgId fields.

HEADERS ⓘ

Form ▾

☒ Content-Type

:

application/json

×

➕ Add header

ⓘ Add authorization

⊞

BODY ⓘ

Text ▾

```
1 {
2   "username": "1x8Yv7",
3   "nonceStr": "VKIzw4UaP8X89MF241Y2",
4   "spNumber": "153456",
5   "signType": "MD5",
6   "timestamp": "1702400553008",
7   "sign": "c365dc67b414e93362535f59f44bb4c",
8   "content": "Talk2all OpenAPI Sign test. 参数1: [] ; 参数2: []",
9   "phones": [
10    {
11      "phone": "8615789894545",
12      "variables": ["1", "2"]
13    }
14  ]
15 }
```

Test JSON XML HTML | Format body | ☒ Enable body evaluation | length: 343 bytes

Response

Cache Detected - Elapsed Time: 77ms

200 OK

HEADERS ⓘ

pretty ▾

Connection: keep-alive

Transfer-Encoding: chunked

Content-Type: application/json

Date: Wed, 13 Dec 2023 09:42:54 GMT

▶ COMPLETE REQUEST HEADERS

BODY ⓘ

pretty ▾

▼

{

code: "200",

message: "SUCCESS",

data: ▼

traceId: 335476267090579456,

msgIds: ▼

{

phone: "8615789894545",

msgId: "3F2DA607FA008E7E002"

}

}

}

lines: 10/10

⌂ copy

⌕ Top

⌕ Bottom

⌕ Collapse

⌕ Open

🔍 2Request

🔍 Copy

⌕ Download

3. Query SMS records

A. Request method & request header & request address

Request method: POST

Request header: Content-Type: application/json
ta-version: v2

Request address: domain name + / ta-sms /openapi/records

B. Interface description

Select one of tracking ID and message ID to query SMS records.
Message ID allows a maximum of **100** queries.

Interface request frequency: 1r/s

C. Query parameters

parameter name	Parameter Description	must	type of data
none			

D. Body parameters

parameter name	Is it mandatory	type of data	Parameter Description
username	yes	String	channel number. The platform can be viewed
nonceStr	yes	String	Random string to prevent tampering
timestamp	yes	String	Timestamp (milliseconds), preventing replay

parameter name	Is it mandatory	type of data	Parameter Description
signType	yes	String	Signature type (MD5, SHA256, SHA384, SM3, RIPEMD160, SHA224, SHA512)
sign	yes	String	Signature string, refer to signature rules
traceId	no	Long	Tracking ID . Choose one from msgIds
msgIds	no	Set<String>	A collection of message IDs. Choose one with traceId

E. Response parameters

parameter name	Parameter Type	Parameter Description
code	String	Response Code. "200" : success, others: failure
message	String	Response message
data	List<Record>	SMS record collection
record	Object	
phone	String	Number. Country area code+phone number, such as 8613245789635
status	String	SMS status. Refer to SMS Status Description
reason	String	Failure reason
createdAt	Date	Submission time. Time zone: GMT+8 Format: yyyy-MM-dd HH:mm:ss
replies	List<Reply>	Upstream reply
Reply	Object	
msgId	String	Message ID, unique

parameter name	Parameter Type	Parameter Description
respAt	Date	Submission time. Time zone: GMT+8 Format: yyyy-MM-dd HH:mm:ss
respStatus	String	Response status
respMsg	String	Response result
reportStatus	String	Receipt status
reportSendAt	String	Submission time Format: yyMMddHHmm
reportDoneAt	String	Complete time Format: yyMMddHHmm
reportMsg	String	Receipt result
reportAt	Date	Report time. Time zone: GMT+8 Format: yyyy-MM-dd HH:mm:ss
price	Double	SMS Price. Keep 8 decimal places

F. Examples

HEADERS ⓘ

Form

☒ Content-Type

application/json

×

☒ ia-version

v2

×

➕ Add header

⚙️ Add authorization

⌵

BODY ⓘ

Text

```
1 {
2   "username": "zUqbhd",
3   "nonceStr": "KazRDtIPjIDzmrj6usCa",
4   "signType": "SHA224",
5   "timestamp": "1702523072636",
6   "sign": "3305cc8cd3f2c3aad85018641514667d75901e80c0814354e9256709",
7   "traceId": "376183722022866944"
8 }
```

Text JSON XML HTML | Format body | Enable body evaluation | length: 219 bytes

Response

Cache Deleted - Elapsed Time: 247ms

200 OK

HEADERS ⓘ

pretty

Connection:

keep-alive

Transfer-Encoding:

chunked

Content-Type:

application/json

Date:

Mon, 03 Jun 2024 08:29:54 GMT

➕ COMPLETE REQUEST HEADERS

BODY ⓘ

pretty

```
{
  code: "200",
  message: "SUCCESS",
  data: {
    [phone: "8615773211880", status: "SENT", reason: null, createdAt: "2024-04-09 14:07:05",...]
  ]
}
```

lines: numts | copy | length: 383 bytes

G. SMS status description

state	illustrate
WAITING	to be sent. Exceeded sending rate or timed SMS
SENDING	sending. Sorting Routing Completed
SENT	submitted. Sent upstream
CANCELED	Cancel sending. Scheduled SMS Cancellation
SORT_FAIL	Sorting failed. Sorting exception
SEND_FAIL	Failed to send. Routing exception

4. Query Account Balance

A. Request method & request header & request address

Request method: POST

Request header: Content-Type: application/json
ta-version: v2

Request address: domain name + / ta-sms /openapi/balance

B. Interface description

View account balance (in Euros)

Interface request frequency: 1r/s

C. Query parameters

parameter name	Parameter Description	must	type of data
----------------	-----------------------	------	--------------

parameter name	Parameter Description	must	type of data
none			

D. Body parameters

parameter name	Is it mandatory	type of data	Parameter Description
username	yes	String	channel number. The platform can be viewed
nonceStr	yes	String	Random string to prevent tampering
timestamp	yes	String	Timestamp (milliseconds), preventing replay
signType	yes	String	Signature type (MD5, SHA256, SHA348, SM3, RIPEMD160, SHA224, SHA512)
sign	yes	String	Signature string, refer to signature rules

E. Response parameters

parameter name	Parameter Type	Parameter Description
code	String	Response Code. "200": success, others: failure
message	String	Response message
data	List<Result>	SMS record collection
Result	Object	
balance	Double	Account balance (in Euros) Keep two decimal places

F. Examples

HEADERS ⓘ 1!

Form ▾

☒ Content-Type

:

application/json

×

☒ Ia-version

:

v2

×

➕ Add header

🔗 Add authorization

🗑

BODY ⓘ

Text ▾

```
1 {
2   "username": "IzEYe7",
3   "nonceStr": "0XVtGX3Dpctf6wIIdw9Z",
4   "sigType": "MD5",
5   "timestamp": "1732006169052",
6   "sign": "ecd87666cf9ba2ec8cb795114a86276"
7 }
```

Test JSON XML HTML | 📄 Format body | ☒ Enable body evaluation | 📏 length: 159 bytes

Response

Elapsed Time: 318ms

200 OK

HEADERS ⓘ

pretty ▾

Connection: keep-alive

Transfer-Encoding: chunked

Content-Type: application/json

Date: Tue, 19 Nov 2024 08:58:19 GMT -la 33s

➤ COMPLETE REQUEST HEADERS

BODY ⓘ

pretty ▾

▼

code: "200",

message: "SUCCESS",

data: ▼ {

balance: 20383.0

}

}

lines nums | 📄 copy | length: 61 bytes