

HW3: Tidyverse Work

Mike Maccia

Loading libraries

```
library(tidyverse)
```

```
-- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
v dplyr      1.1.4      v readr      2.1.5
v forcats    1.0.0      v stringr    1.5.1
v ggplot2    3.5.2      v tibble     3.2.1
v lubridate  1.9.4      v tidyr      1.3.1
v purrr      1.0.4
-- Conflicts ----- tidyverse_conflicts() --
x dplyr::filter() masks stats::filter()
x dplyr::lag()     masks stats::lag()
i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become
```

```
library(palmerpenguins)
```

Attaching package: 'palmerpenguins'

The following objects are masked from 'package:datasets':

penguins, penguins_raw

Task 1

Question a: Why `read_csv` cannot be used to read the `data.txt` file

The function `read_csv()` can only be used to read in files that use the delimiters of commas or tabs. The function `read_csv2()` must be used in files with semicolons as the separator (commas can be used for decimal points).

```
data <- read.csv2('~/.ST558 Repo/HW3_/Data/data.txt',
                 header = T)
data
```

```
  x y z
1 1 2 3
2 5 3 8
```

Question b: Reading in 2nd file

In this file, “6” is the delimiter.

```
data_2 <- read_delim('~/.ST558 Repo/HW3_/Data/data2.txt',
                    delim = '6',
                    col_types= 'fdc')
data_2
```

```
# A tibble: 3 x 3
  x         y z
  <fct> <dbl> <chr>
1 1         2 3
2 5         3 8
3 7         4 2
```

Task 2

Data tidying skills

Question a: Reading Data

Reading in the trailblazer.csv data

```
trailblazer <- read_csv('~/.ST558 Repo/HW3_/Data/trailblazer.csv',
                       col_names= TRUE)
```

```

Rows: 9 Columns: 11
-- Column specification -----
Delimiter: ","
chr  (1): Player
dbl (10): Game1_Home, Game2_Home, Game3_Away, Game4_Home, Game5_Home, Game6_...

i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.

```

```
trailblazer
```

```

# A tibble: 9 x 11
  Player      Game1_Home Game2_Home Game3_Away Game4_Home Game5_Home Game6_Away
  <chr>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
1 Damian Lill~      20        19        12        20        25        14
2 CJ McCollum      24        28        20        25        14        25
3 Norman Powe~      14        16        NA        NA        12        14
4 Robert Covi~       8         6         0         3         9         6
5 Jusuf Nurkic      20         9         4        17        14        13
6 Cody Zeller       5         5         8        10         9         6
7 Anfernee Si~      11        18        12        17         5        19
8 Larry Nance~       2         8         5         8         3         8
9 Nassir Litt~       7        11         5         9         8         8
# i 4 more variables: Game7_Away <dbl>, Game8_Away <dbl>, Game9_Home <dbl>,
#   Game10_Home <dbl>

```

Question b: Pivoting the data longer

```

trailblazer_longer <- trailblazer |>
  pivot_longer(cols = 2:11,
    names_to = c('Game', 'Location'),
    names_prefix = 'Game',
    names_sep = '_',
    values_to = 'Points')

print(trailblazer_longer, n=5)

```

```

# A tibble: 90 x 4
  Player      Game Location Points
  <chr>      <chr> <chr>      <dbl>

```

```

1 Damian Lillard 1      Home      20
2 Damian Lillard 2      Home      19
3 Damian Lillard 3      Away      12
4 Damian Lillard 4      Home      20
5 Damian Lillard 5      Home      25
# i 85 more rows

```

Question c: Who scored more when playing at home versus away

```
library(kableExtra)
```

Attaching package: 'kableExtra'

The following object is masked from 'package:dplyr':

group_rows

```

trailblazer_wider <- trailblazer_longer |>
  pivot_wider(names_from = (Location),
              values_from = Points) |> #pivot wider
  group_by(Player) |>
  summarize(mean_home = mean(Home, na.rm=T), #creating mean of home points/away points
            #by player
            mean_away = mean (Away, na.rm=T)) |>
  mutate(diff_points = (mean_home - mean_away)) |> #creating different in means
  arrange(desc(diff_points)) |>#arrange by descending
  kbl(digits=2)

trailblazer_wider

```

Player	mean_home	mean_away	diff_points
Jusuf Nurkic	14.17	7.50	6.67
Robert Covington	9.50	3.00	6.50
Nassir Little	8.33	4.25	4.08
Damian Lillard	18.83	18.00	0.83
Cody Zeller	5.83	5.25	0.58
Larry Nance Jr	4.50	5.00	-0.50
CJ McCollum	20.83	21.50	-0.67
Anfernee Simons	12.83	15.75	-2.92
Norman Powell	16.00	19.67	-3.67

While they did not necessarily score the most points, Jusuf Nurkic (6.67) and Robert Covington (6.5) scored on average more points at home than away through the first 10 games of the season.

Task 3

Question a. Describing what some values mean

indicates that there were no values within a column. For example, there were no bill_length measurements for Gentoo species on Torgersen island.

<dbl [52]> indicates that within that cell there would be 52 observations (which are doubles) for bill length.

indicates a list-column within a tribble. List-columns occur when each element within a column is a list. For example, the above cell of Adelie species on Torgersen island, there is a list of 52 doubles within that cell / element.

Question b. Creating a new table

```
penguins_island_ct <- penguins |>
  select(species, island) |>
  group_by(species, island) |>
  summarize(count=n(), .groups='drop') |>
  pivot_wider(names_from = island,
              values_from = count,
              values_fill = 0)

penguins_island_ct
```

```
# A tibble: 3 x 4
  species    Biscoe Dream Torgersen
  <fct>      <int> <int>      <int>
1 Adelie      44    56         52
2 Chinstrap    0    68         0
3 Gentoo     124    0         0
```

Task 4

Replacing 2 missing values for bill length

```
penguins_fixed_bill_length <- penguins |>
  mutate(bill_length_mm =
    case_when(species == "Gentoo" & is.na(bill_length_mm)
              ~ 30, TRUE ~ bill_length_mm )) |>
  #finding where gentoo is missing change to 30
  mutate(bill_length_mm =
    case_when(species == "Adelie" & is.na(bill_length_mm)
              ~ 26, TRUE ~ bill_length_mm )) |>
  #finding where adelie is missing change to 26
  arrange(bill_length_mm)

print(penguins_fixed_bill_length, n = 10)
```

```
# A tibble: 344 x 8
  species island    bill_length_mm bill_depth_mm flipper_length_mm body_mass_g
  <fct>   <fct>          <dbl>          <dbl>          <int>      <int>
1 Adelie Torgersen         26             NA             NA         NA
2 Gentoo Biscoe          30             NA             NA         NA
3 Adelie Dream          32.1          15.5          188       3050
4 Adelie Dream          33.1          16.1          178       2900
5 Adelie Torgersen        33.5           19           190       3600
6 Adelie Dream          34           17.1          185       3400
7 Adelie Torgersen        34.1          18.1          193       3475
8 Adelie Torgersen        34.4          18.4          184       3325
9 Adelie Biscoe          34.5          18.1          187       2900
10 Adelie Torgersen        34.6          21.1          198       4400
# i 334 more rows
# i 2 more variables: sex <fct>, year <int>
```