Active Parameters, Not Total Parameters: MoE Models and the Deployment Gap

V. Michael Maloney
Neuralift; University of New Hampshire
mike@neuralift.ai

Preprint. Work in progress.

Abstract

Paper I found accuracy and deployment success uncorrelated ($\rho = 0.09$, $p = 0.76$) across 13 dense models. MoE architectures promised a way out: 35B parameters of knowledge at 3B of compute. We tested this claim. The real story is more interesting than a simple yes or no.

We evaluate Qwen3.5-35B-A3B (35B total, 3B active per token) alongside 12 dense models (0.8B–9B) on Apple Silicon via MLX, running 3,000 prompts per model across 6 structured output tasks (39,000 total evaluations). Four of those dense models belong to the same Qwen3.5 family as the MoE, sharing the Gated DeltaNet architecture, tokenizer, and training pipeline. This gives us the first architecture-controlled MoE deployment comparison.

The MoE achieves 55.0% accuracy but ranks only 9th of 13 models overall. Its own dense siblings outperform it: Qwen3.5-4B reaches 77.2%, Qwen3.5-9B reaches 74.1%. Median MoE latency: 25,055 ms. S@SLO at the Interactive tier: 0.0%.

Model	**Type**	**Active**	**Acc (%)**	**S@SLO$_{2s}$**	**S@SLO$_{5s}$**
Qwen3.5-0.8B	Dense	0.8B	64.0%	59.5%	62.3%
Llama-3.2-3B	Dense	3.2B	72.7%	**61.5%**	**72.7%**
Qwen3.5-4B	Dense	4.0B	**77.2%**	26.4%	56.6%
Qwen3.5-9B	Dense	9.0B	74.1%	13.6%	40.8%
Gemma-2-9B	Dense	9.2B	57.5%	20.8%	26.8%
Qwen3.5-35B-A3B	**MoE**	**3.0B**	**55.0%**	**0.0%**	**0.3%**

A confound explains the extreme verbosity. The Qwen3.5 family ships with a "thinking mode" that generates chain-of-thought reasoning by default (`enable_thinking=True`). The MoE evaluation ran with thinking mode on, producing ∼1,500 tokens per response. The dense Qwen3.5 models ran with thinking mode off, producing concise output. When we briefly tested the dense 4B with thinking on, it exhibited the same verbosity pattern. The MoE's catastrophic latency is not an architectural consequence of sparse routing. It is a training-mode artifact shared across the Qwen3.5 family.

Three other results matter. The deployment gap is hardware-independent: it persists on Apple Silicon ($\rho = +0.209$, $p = 0.494$ at the Interactive tier across all 13 models). MLX is 3–9× faster than CUDA ($\bar{\alpha} = 0.177$). And a small, fast model (Qwen3.5-0.8B at 59.5% S@SLO and 735 ms median) nearly matches Llama-3.2-3B (61.5% S@SLO, 968 ms) as a viable deployment target.

1 Introduction

Paper I found that accuracy and deployment success are essentially uncorrelated. Across 13 models and 29,900 evaluations, Spearman $\rho = +0.09$ at a 2-second SLO deadline. Twelve of thirteen



Figure 1: **MoE latency does not scale with active parameters.** All 13 models: 8 original dense (blue), 4 Qwen3.5 dense siblings (orange triangles), and MoE (purple diamond). (a) Against total parameters, the MoE is the slowest by far at 25,055 ms, consistent with generating ∼1,500 tokens of chain-of-thought. Its dense siblings (0.8B–9B, orange) follow the expected trend. (b) Against active parameters, the MoE is a dramatic *upward* outlier at 3B, 28× slower than Qwen2.5-3B (884 ms). Active parameters do not predict MoE latency.

models achieved exactly 0% Success@SLO despite near-perfect accuracy [11]. The message was stark: bigger models are more accurate but too slow, and the only model fast enough to finish was the smallest and least accurate.

But there was a loophole in that finding—and we knew it.

The 13 models in Paper I were all *dense*. Every parameter activates on every token. For dense models, total parameters perfectly predict compute cost: a 12B model does exactly 12× the work per token of a 1B model. The deployment gap in Paper I is, at its core, a consequence of this arithmetic. Large models are more accurate because they have more parameters. They are slower because they activate all of them. You can't have one without the other.

Mixture-of-Experts (MoE) models break this coupling—or so the theory goes.

An MoE model contains far more total parameters than it activates on any given token. A learned routing function selects a small subset of "expert" subnetworks for each token, leaving the rest dormant [18, 3]. The result is a model that stores the knowledge of a large model (because it *is* a large model) but pays the compute cost of a small one (because only a fraction of the parameters fire).

Consider Qwen3.5-35B-A3B, released in January 2026 by the Qwen team [16]. It has 35 billion total parameters spread across 256 experts per layer, but a top-k routing mechanism activates only 3 billion parameters per token. On accuracy benchmarks, it competes with dense models in the 8B–9B range. On a compute budget, it should behave like a 3B model.

That is the hypothesis. It does not survive contact with structured output evaluation under SLO constraints, though it fails differently than expected.

Figure 1 makes this concrete: against active parameters, the MoE is a 28× upward outlier. There is a second question embedded in this investigation. All four papers in this series (the deployment

gap [11], capacity thresholds [10], benchmark [9], and training dynamics [12]) were conducted on a single NVIDIA RTX 4090 using GGUF-quantized models served through LM Studio. The findings could be hardware-specific. We address this by running 8 of the original 13 models on Apple Silicon via the MLX framework, and adding 4 dense models from the same Qwen3.5 family as the MoE for architecture-controlled comparison, 13 models total. If the deployment gap persists, it is hardware-independent.

It does. And along the way, a surprise: MLX on Apple Silicon is *faster* than LM Studio on CUDA, with per-model P50 latency ratios from 0.11 to 0.39 (MLX/CUDA). The gap persists not because Apple Silicon is slow but because structured output is hard everywhere.

What we contribute. Five findings, ranked by how much they upset prior assumptions:

1. **Architecture-controlled MoE comparison.** Four dense Qwen3.5 models (0.8B–9B) share the MoE's Gated DeltaNet architecture, tokenizer, and training pipeline. With thinking mode disabled, the dense siblings reach 77.2% accuracy (Qwen3.5-4B) and 59.5% S@SLO (Qwen3.5-0.8B). The MoE (thinking mode on by default) manages 55.0% accuracy and 0.0% S@SLO. Ninth of thirteen. Outperformed by its own siblings.

2. **The thinking-mode confound.** We expected the MoE's extreme verbosity (∼1,500 tokens/response, 25,055 ms median) to reflect sparse routing overhead. It does not (Figure 2). The Qwen3.5 family ships with `enable_thinking=True` by default, and a brief test of the dense 4B with thinking on produced the same verbosity pattern. The catastrophic latency is a training-mode artifact that happens to manifest most dramatically in the MoE.

3. **Cross-hardware replication.** Same protocol as Paper I, different hardware entirely. The accuracy–deployment disconnect persists on Apple Silicon ($\rho = +0.209$, $p = 0.494$ at Interactive across all 13 models). Not a CUDA artifact.

4. **MLX outpaces CUDA.** We assumed Apple Silicon would be slower. It is not. Normalization factor $\bar{\alpha} = 0.177$, meaning models finish in 17.7% of the time on MLX versus LM Studio/CUDA. The hardware recommendation calculus flips.

5. **Small dense models work.** Llama-3.2-3B: 72.7% accuracy, 61.5% S@SLO at the 2-second Interactive tier. Qwen3.5-0.8B, a 0.8B model, reaches 64.0% accuracy and 59.5% S@SLO at 735 ms median. Five papers searching for deployment-viable models, and the answer turns out to be small dense models on efficient hardware.

Section 2 covers MoE architectures, unified memory hardware, and the series so far. Section 3 describes our 13 models, tasks, and protocol. Sections 4 and 5 present the core results: cross-hardware validation and MoE deployment under SLO constraints. Section 6 digs into memory, throughput, and the thinking-mode confound. Edge deployment implications follow in Section 7, with limitations in Section 9.

2 Background and Related Work

2.1 Mixture-of-Experts Architectures

MoE is conditional computation. Instead of routing every token through every parameter, a gating network picks a handful of expert subnetworks for each token [18]. The rest of the parameters sit



The loophole is closed. MoE verbosity is a thinking-mode confound, not an architecture trait.

Figure 2: **The MoE hypothesis, confounded.** The MoE achieves competitive accuracy (55.0%, 9th of 13) through massive chain-of-thought, but this verbosity is a thinking-mode artifact shared across the Qwen3.5 family, not an MoE architectural consequence. Dense Qwen3.5-4B with thinking off reaches 77.2% accuracy at 2,188 ms. The deployment gap is not bypassed by MoE, but the reason is a training confound, not sparse routing.

there, loaded in memory, doing nothing. This means the model knows more than it computes on any given forward pass.

The idea is not new. Shazeer *et al.* [18] showed in 2017 that a sparsely-gated MoE layer could scale capacity without proportional compute. GShard [8] pushed this to 600 billion parameters across 2,048 experts. The Switch Transformer [3] simplified routing to one expert per token, reducing communication overhead and enabling trillion-parameter models. Then Mixtral [5] brought MoE to practitioners: 46.7 billion total parameters, 12.9 billion active, matching Llama 2 70B on benchmarks while running considerably faster.

The ratio keeps getting more extreme. DeepSeek-MoE [2] split experts into finer-grained units for better routing flexibility. Qwen3 [16] adopted MoE across its model family. Qwen3.5-35B-A3B (the model we evaluate) pushes the ratio to 12:1. It has 35 billion total parameters and activates 3 billion per token via top-k routing across 256 experts with 8 active per token. Its hybrid architecture alternates Gated DeltaNet linear attention layers with standard self-attention in a 3:1 ratio, reducing the overhead of full quadratic attention while preserving long-range reasoning capability.

Here is the theory that motivated this paper. A dense 3B model has 3B parameters of knowledge and pays 3B parameters of compute. A 35B-A3B MoE model has 35B parameters of knowledge and pays, in theory, only 3B parameters of compute per token. If the deployment gap is fundamentally about compute, MoE should behave like its active parameter count.

In practice, two things go wrong. First, routing is not free: the gating network must evaluate all 256 experts to pick the top 8, adding constant-time overhead to every forward pass. Second, the hybrid attention architecture introduces latency from layer-type switching that does not appear in standard dense models. Our results show these costs are not negligible; they push the MoE model's latency well above its 3B active-parameter peers.

2.2 Unified Memory and Apple Silicon

Apple Silicon (M1 through M4) has one trick that matters here: unified memory. CPU, GPU, and Neural Engine share a single memory pool [4]. There is no PCIe bus between them. For dense

models this is nice but not transformative. For MoE models it changes the game; or rather, it changes what game is playable.

On NVIDIA hardware, model weights live in GPU VRAM. A 35B model at 4-bit quantization needs roughly 20 GB. An RTX 4090 has 24 GB, leaving almost nothing for KV cache. In practice, the MoE model does not fit on consumer NVIDIA hardware under realistic inference conditions. On Apple Silicon, the 35B model sits in the same memory pool the GPU reads from. An M4 Max with 64 GB leaves 44 GB of headroom. Apple Silicon is the only consumer hardware on which this experiment is possible.

The bandwidth story is more complicated than we expected. We assumed CUDA would dominate. It doesn't. MLX achieves faster inference across the board ($\bar{\alpha} = 0.177$, MLX/CUDA), meaning models finish in about 18% of the time. This likely reflects LM Studio's serving stack overhead and GGUF quantization costs, not raw hardware differences.

MLX [4], Apple's inference framework, provides the serving stack. It implements lazy evaluation and unified memory management optimized for the Metal GPU backend. The MLX Community [13] maintains pre-quantized weights in INT4 format for the models we evaluate.

2.3 The Deployment Gap Series

This is the fifth paper in a series. A quick recap:

Paper I [11] found the deployment gap: accuracy and S@SLO are uncorrelated ($\rho = 0.09$) across 13 models and 29,900 evaluations. Twelve of thirteen models scored 0% S@SLO at a 2-second deadline despite near-perfect accuracy. Only Llama-3.2-1B survived. Everything ran on a single RTX 4090.

Paper II [10] tried to train out of the gap. GRPO with a 6-component reward, 11 models. Result: capacity thresholds are task-dependent. Simple tasks learn at 1B. Complex tasks need 9B+. Small models forget.

Paper III [9] turned the evaluation into a reusable benchmark: tiered SLO deadlines, per-request S@SLO, 42,900 evaluations. The gap held.

Paper IV [12] looked at *why* capacity thresholds exist. Reward decomposition, forgetting matrices, curve taxonomies. Architecture matters as much as size.

Every one of those papers evaluated dense models on NVIDIA hardware. That is two limitations in one sentence. This paper addresses both, and discovers that neither MoE nor hardware change explains away the gap.

2.4 MoE Deployment Studies

The MoE deployment literature cares about throughput. DeepSpeed-MoE [17] builds multi-GPU inference kernels, getting 4.5× speedups over dense models of equivalent accuracy on clusters. EdgeMoE [21] targets on-device inference through expert-wise weight loading for mobile and IoT. MoE-Infinity [19] handles models that don't fit in memory via offloading.

What nobody has measured is MoE under *structured output contracts with explicit latency deadlines*. Tokens per second is not the same as Success@SLO. Time to first token tells you nothing about whether the full response beats your deadline. The question we ask (does a 35B MoE model achieve non-zero S@SLO at the Interactive tier?) has no prior answer in the literature. Now it does. The answer is no.

Table 1: Hardware comparison between this paper (Apple Silicon / MLX) and Papers I–IV (NVIDIA / LM Studio). The platforms differ in architecture, memory model, and serving stack.

Attribute	**Papers I–IV (CUDA)**	**This Paper (MLX)**
GPU	NVIDIA RTX 4090	Apple M-series Max GPU
VRAM / Memory	24 GB GDDR6X	64–96 GB Unified
Memory Architecture	Discrete (PCIe 4.0)	Unified (on-chip)
Memory Bandwidth	1,008 GB/s	400–546 GB/s
Framework	LM Studio / llama.cpp	MLX / mlx-lm
Quantization	GGUF Q4_K_M	MLX INT4
OS	Linux (Ubuntu 22.04)	macOS (Sequoia 15)

3 Experimental Setup

3.1 Hardware

Everything runs on Apple Silicon with MLX. Table 1 compares this platform to the RTX 4090 setup from Papers I–IV.

Why Apple Silicon? Two reasons. First, it is the second-largest platform for local LLM inference after NVIDIA consumer GPUs, and we need cross-hardware validation on the obvious candidate. Second, unified memory means the full 35B MoE model fits without partitioning: the only consumer hardware on which this evaluation is feasible. The cross-hardware comparison turned up a surprise: MLX is faster than LM Studio/GGUF on this task suite, reversing our prior assumption.

3.2 Models

Thirteen models: 12 dense and 1 MoE. Table 2 has the lineup. Eight dense models overlap with Paper I for cross-hardware validation. Four dense Qwen3.5 models (0.8B, 2B, 4B, 9B) share the MoE's Gated DeltaNet architecture, enabling architecture-controlled comparison.

The MoE model is why we started this investigation. At 35B total parameters it dwarfs everything else, nearly 4× larger than Gemma-2-9B. But at 3B active, it sits between Qwen3.5-2B and Llama-3.2-3B in compute cost per token. The central question: which number determines deployment behavior?

The four Qwen3.5 dense models serve a specific purpose. They share the MoE's Gated DeltaNet architecture, tokenizer, and training pipeline, differing only in scale. If the MoE's problems stem from its architecture rather than its size or training mode, the dense siblings should show similar patterns. They do not; they outperform the MoE, revealing that the MoE's failure is a thinking-mode confound (Section 6).

Five models from Paper I are absent (Yi-1.5-6B, Falcon-Mamba-7B, GPT-OSS-20B, Llama-3.1-8B, Gemma-3-12B) due to MLX compatibility constraints. The 8 that remain, plus 4 Qwen3.5 dense models, give us 12 dense models spanning 0.8B to 9.2B across five architecture families.

3.3 Tasks

We use the same six task types from Papers I and III:

- **T1: Intent Classification (CLINC-150)** [7]. Classify user utterances into 150 intent categories. Short outputs, fast turnaround. **500 prompts.**

Table 2: Model lineup. Eight dense models overlap with Paper I for cross-hardware validation. Four Qwen3.5 dense models (marked †) share the MoE's Gated DeltaNet architecture, tokenizer, and training pipeline. The MoE model (Qwen3.5-35B-A3B) has 35B total parameters but activates only 3B per token. All models run in INT4 quantization via MLX.

#	Model	Type	Total	Active	Ratio	MLX Model ID
1	Qwen3.5-0.8B†	Dense	0.8B	0.8B	1:1	`mlx-community/Qwen3.5-0.8B-4bit`
2	Llama-3.2-1B	Dense	1.2B	1.2B	1:1	`mlx-community/Llama-3.2-1B-Instruct-4bit`
3	Qwen3.5-2B†	Dense	2.0B	2.0B	1:1	`mlx-community/Qwen3.5-2B-4bit`
4	Llama-3.2-3B	Dense	3.2B	3.2B	1:1	`mlx-community/Llama-3.2-3B-Instruct-4bit`
5	Qwen2.5-3B	Dense	3.1B	3.1B	1:1	`mlx-community/Qwen2.5-3B-Instruct-4bit`
6	Phi-3-mini	Dense	3.8B	3.8B	1:1	`mlx-community/Phi-3-mini-4k-instruct-4bit`
7	Qwen3.5-4B†	Dense	4.0B	4.0B	1:1	`mlx-community/Qwen3.5-4B-4bit`
8	Qwen3-4B	Dense	4.0B	4.0B	1:1	`mlx-community/Qwen3-4B-4bit`
9	Mistral-7B-v0.3	Dense	7.2B	7.2B	1:1	`mlx-community/Mistral-7B-Instruct-v0.3-4bit`
10	Ministral-8B	Dense	8.0B	8.0B	1:1	`mlx-community/Ministral-8B-Instruct-2410-4bit`
11	Gemma-2-9B	Dense	9.2B	9.2B	1:1	`mlx-community/gemma-2-9b-it-4bit`
12	Qwen3.5-9B†	Dense	9.0B	9.0B	1:1	`mlx-community/Qwen3.5-9B-4bit`
13	**Qwen3.5-35B-A3B†**	**MoE**	**35.2B**	**3.0B**	**12:1**	`mlx-community/Qwen3.5-35B-A3B-4bit`

† Qwen3.5 family (Gated DeltaNet architecture). Dense models ran with `enable_thinking=False`.

- **T2: Grounded QA (HotpotQA)** [20]. Multi-hop question answering over provided documents. Medium outputs. **1,000 prompts.**
- **T3: Tool Calling (Custom)**. Select and parameterize tools from a provided registry. Structured JSON outputs. **500 prompts.**
- **T4: Function Routing (BFCL)** [15, 14]. Route requests to appropriate function signatures. Structured outputs. **500 prompts.**
- **T5: Code Patching (SWE-bench)** [6]. Generate unified diffs for bug fixes. Long, structured outputs. **300 prompts.**
- **T6: Mathematical Reasoning (GSM8K)** [1]. Solve grade-school math problems with structured step-by-step outputs. **200 prompts.**

That is 3,000 prompts per model, 39,000 individual measurements across all 13 models. Every output must conform to a task-specific JSON Schema contract. Fail validation, fail the request, regardless of whether the answer inside was correct. T1, T3, T4, T5, and T6 require structured JSON output. T2 (HotpotQA) accepts free-text answers. This distinction proves less critical than expected for the MoE failure mode: the MoE achieves reasonable accuracy on both free-text and structured tasks, but its extreme verbosity (∼1,500 tokens per response) destroys SLO compliance across all task types.

3.4 SLO Tiers

Same three SLO tiers as Paper III:

- **Interactive (2s).** Chatbot, search, real-time UI. User-facing, latency-critical.
- **Standard (5s).** API endpoints, customer-facing workflows. Moderate latency tolerance.

- **Batch (30s).** Background processing, async pipelines. Generous deadlines.

S@SLO is per-request: a response succeeds only if it is valid JSON matching the schema, correct by task-specific evaluation, *and* delivered before the deadline. Same definition as Paper III, no changes.

3.5 Evaluation Protocol

One model at a time, one request at a time. No batching, no concurrency. We want clean latency measurements without resource contention. For each request we record:

- Wall-clock latency (ms) from request submission to complete response
- Token count (input and output)
- JSON validity (passes schema validation)
- Task-specific accuracy
- Tokens per second (output tokens / generation time)
- Peak memory usage

MLX inference runs through `mlx-lm` [4] with temperature 0.0 and a 2,048-token output limit. No constrained decoding, no grammar enforcement. Outputs are unconstrained, matching the Paper I baseline. If the model emits broken JSON, that is the model's problem. Schema validation happens post-hoc.

Thinking mode. The Qwen3.5 family ships with a "thinking mode" (`enable_thinking=True`) that generates chain-of-thought reasoning in `<think>...</think>` blocks before the answer. This is the default behavior. We ran the MoE evaluation with thinking mode on (the default), producing ∼1,500 tokens per response. We ran the four Qwen3.5 dense models with thinking mode *off* (`enable_thinking=False`), producing concise output. This asymmetry was initially unintentional (we discovered it post-hoc) and constitutes a confound that we analyze in Section 6. The Qwen3.5-9B dense model ran with a reduced 512-token output limit due to memory constraints at 2,048 tokens, producing shorter average output (112 tokens vs 239–262 for other dense models).

4 Cross-Hardware Validation

Before we get to MoE, a prerequisite: does the deployment gap even exist on this hardware? If the gap were a CUDA artifact, nothing in this paper would generalize. So we start by running the 8 overlapping dense models on Apple Silicon and comparing to the Paper I results.

4.1 Replicating Paper I on Apple Silicon

Table 3 presents side-by-side results for the 8 models evaluated on both platforms. The accuracy column reflects task-averaged correctness; the latency columns show P50 values in seconds.

MLX is *much* faster than CUDA for every model. Llama-3.2-1B drops from 3.5 s median on CUDA to 0.40 s on MLX, 8.8× faster. Mistral-7B-v0.3 drops from 20.3 s to 2.65 s, 7.7× faster. The

Table 3: Cross-hardware comparison for 8 dense models evaluated on both CUDA (Paper I, RTX 4090, GGUF Q4_K_M, LM Studio) and MLX (this paper, Apple Silicon, INT4). Accuracy is task-averaged. Latency is median across all tasks. The deployment gap persists on both platforms. MLX is 3–9× faster than CUDA.

	Accuracy (%)		**P50 Latency (s)**		**S@SLO$_{2s}$ (%)**	
Model	**CUDA**	**MLX**	**CUDA**	**MLX**	**CUDA**	**MLX**
Llama-3.2-1B	63.5	37.8	3.5	0.40	6.3	37.7
Llama-3.2-3B	—	72.7	7.5	0.97	—	61.5
Qwen2.5-3B	75.0	38.6	7.4	0.88	0.0	28.1
Phi-3-mini	70.9	48.1	10.9	3.04	0.0	17.9
Qwen3-4B	80.2	47.2	12.2	4.70	0.0	0.6
Mistral-7B-v0.3	78.3	55.6	20.3	2.65	0.0	22.6
Ministral-8B	80.7	56.7	18.5	2.43	0.0	22.3
Gemma-2-9B	82.2	57.5	22.9	2.95	0.0	20.8

slowest MLX model (Qwen3-4B at 4.70 s) is still faster than several CUDA models. We did not expect this. Section 4.2 explains why.

Accuracy diverges between platforms, though. Llama-3.2-1B goes from 63.5% on CUDA to 37.8% on MLX, a 25.7 percentage-point drop. Too large for quantization alone (INT4 vs Q4_K_M). It likely reflects evaluation conditions, model IDs, and task prompt formatting differences between Paper I and this evaluation. We flag this and focus on within-platform conclusions.

The result that matters: Llama-3.2-3B stands out. At 72.7% accuracy and 968 ms median latency, it achieves 61.5% S@SLO at the Interactive tier. It is the only model with both high accuracy and strong deployment compliance. Paper I couldn't find this: a model that breaks the deployment gap not through MoE trickery but through being the right size.

Accuracy comparison. The rank ordering across models is broadly preserved between platforms (Spearman $\rho = +0.619$, $p = 0.059$), though with large absolute differences. Models that score high on CUDA tend to score relatively high on MLX. The absolute magnitude of the gap (25.7 pp for Llama-3.2-1B, 21.4 pp for Qwen2.5-3B) is too large for quantization alone and deserves investigation in future work.

Latency comparison. MLX is 3–9× faster in absolute terms. This is the opposite of our prior expectation (Apple Silicon has lower memory bandwidth: 400–546 GB/s vs 1,008 GB/s for the RTX 4090). The likely explanation: LM Studio's serving overhead for GGUF models is significant, and MLX's native INT4 execution with lazy evaluation avoids much of it. The rank ordering for latency is preserved ($\rho = +0.643$, $p = 0.044$). The hardware changes the scale, by a lot, but not the shape.

4.2 Hardware Normalization Protocol

Comparing raw numbers across platforms requires a conversion factor. For each model m evaluated on both platforms:

$$\alpha_m = \frac{\text{P50}_{\text{MLX}}(m)}{\text{P50}_{\text{CUDA}}(m)} \tag{1}$$

The aggregate normalization factor is the geometric mean across all overlapping models:

Table 4: Hardware normalization factors. Each α_m is the ratio of MLX P50 latency to CUDA P50 latency for the same model. All values are below 1.0, confirming MLX is faster on this workload. The geometric mean provides the aggregate platform conversion factor.

Model	$\mathbf{P50_{CUDA}}$ **(s)**	$\mathbf{P50_{MLX}}$ **(s)**	α_m	**Note**
Llama-3.2-1B	3.5	0.40	0.114	8.8× faster
Llama-3.2-3B	7.5	0.97	0.129	7.7× faster
Qwen2.5-3B	7.4	0.88	0.119	8.4× faster
Phi-3-mini	10.9	3.04	0.279	3.6× faster
Qwen3-4B	12.2	4.70	0.385	2.6× faster
Mistral-7B-v0.3	20.3	2.65	0.131	7.7× faster
Ministral-8B	18.5	2.43	0.131	7.6× faster
Gemma-2-9B	22.9	2.95	0.129	7.8× faster
Geometric Mean $\bar{\alpha}$			**0.177**	5.6× faster (avg)

$$\bar{\alpha} = \left(\prod_{m=1}^{8} \alpha_m \right)^{1/8} \tag{2}$$

Geometric mean, not arithmetic, because latency ratios are multiplicative. A model that is 2× faster on one platform and 4× faster on another should contribute symmetrically.

Table 4 shows per-model normalization factors. Every $\alpha_m < 1$, confirming that MLX is faster for every model.

With $\bar{\alpha} = 0.177$ in hand, we can estimate what the MoE model would do on CUDA: $\hat{L}_{\text{CUDA}} = L_{\text{MLX}}/\bar{\alpha}$. The MoE P50 on MLX is 25,055 ms; the estimated CUDA P50 is 25,055/0.177 ≈ 141,554 ms, over two minutes per request. This is a rough estimate (MoE memory access patterns may not normalize like dense models), but it confirms that the MoE model would be completely nonviable on CUDA at any practical SLO tier.

4.3 Does the Deployment Gap Transfer?

Now the real question. Is the deployment gap a CUDA artifact, or does it follow you to Apple Silicon?

Figure 3 shows the accuracy vs Success@SLO scatter for all 13 models on Apple Silicon. The deployment gap pattern holds: Spearman $\rho = +0.209$ ($p = 0.494$) at the Interactive tier, weak and not significant, consistent with Paper I ($\rho = +0.09$). Most models at moderate-to-high accuracy achieve moderate-to-low S@SLO.

Two models break the pattern. Llama-3.2-3B occupies the upper right: 72.7% accuracy and 61.5% S@SLO. Qwen3.5-0.8B is the surprise: a 0.8B model reaches 64.0% accuracy and 59.5% S@SLO at 735 ms median, nearly matching the 3B model. Both break the gap not through architectural novelty but through being small enough to be fast.

At the other extreme, the Qwen3.5 family illustrates the accuracy–latency trade-off within a single architecture. Qwen3.5-4B reaches the highest accuracy in the study (77.2%) but only 26.4% S@SLO. Qwen3.5-9B: 74.1% accuracy, 13.6% S@SLO. And the MoE (the largest model, run with thinking mode on) sits on the x-axis at 55.0% accuracy and 0.0% S@SLO. It achieves lower accuracy than its own dense siblings and is orders of magnitude slower.



Figure 3: **The deployment gap on Apple Silicon.** All 13 models. The gap persists: $\rho = +0.209$, $p = 0.494$ at Interactive. Llama-3.2-3B and Qwen3.5-0.8B (orange triangles) occupy the upper region: high accuracy with viable S@SLO. Qwen3.5-4B reaches the highest accuracy (77.2%) but moderate S@SLO (26.4%). The MoE (purple diamond) achieves 55.0% accuracy but zero S@SLO, the pure embodiment of the deployment gap.

Interpretation. The deployment gap follows you everywhere. Different GPU architecture, different memory model, different quantization scheme, different serving stack. Same gap. Not about CUDA. Not about GGUF. Not about LM Studio. And now we can add: not about dense architectures either. MoE does not escape it.

5 The MoE Deployment Gap

The gap is real on Apple Silicon. Now we test whether MoE breaks it. It does not.

5.1 RQ1: Does MoE Latency Scale with Active or Total Parameters?

If active parameters determine latency, Qwen3.5-35B-A3B should sit between Qwen3.5-2B and Llama-3.2-3B, around 800–1,000 ms. Neither prediction holds. The MoE's chain-of-thought verbosity produces latency far beyond what even total parameter count would predict. Table 5 shows the results.

P50 latency: 25,055 ms. Worst in the study by a factor of five; Qwen3-4B at 4,695 ms is the distant runner-up. The MoE's own dense sibling Qwen3.5-2B achieves 856 ms. Same architecture, fewer parameters, 29× faster.

Table 5: **Latency comparison: all 13 models.** Ordered by active parameter count. Qwen3.5 dense models (†) share the MoE's architecture with thinking mode off. The MoE (thinking on) appears at the bottom at 25,055 ms, 28× slower than Qwen2.5-3B, driven by ∼1,500 tokens of chain-of-thought per response.

Model	Type	Total	Active	P50 (ms)	P95 (ms)	tok/s
Qwen3.5-0.8B†	Dense	0.8B	0.8B	735	7,673	106.9
Llama-3.2-1B	Dense	1.2B	1.2B	398	1,468	115.3
Qwen3.5-2B†	Dense	2.0B	2.0B	856	15,663	73.1
Llama-3.2-3B	Dense	3.2B	3.2B	968	2,738	42.9
Qwen2.5-3B	Dense	3.1B	3.1B	884	2,961	44.0
Phi-3-mini	Dense	3.8B	3.8B	3,042	7,226	48.3
Qwen3.5-4B†	Dense	4.0B	4.0B	2,188	31,706	30.2
Qwen3-4B	Dense	4.0B	4.0B	4,695	7,346	54.5
Mistral-7B-v0.3	Dense	7.2B	7.2B	2,645	7,877	20.7
Ministral-8B	Dense	8.0B	8.0B	2,431	7,141	19.5
Gemma-2-9B	Dense	9.2B	9.2B	2,945	9,263	13.9
Qwen3.5-9B†	Dense	9.0B	9.0B	4,014	14,681	20.9
Qwen3.5-35B-A3B†	**MoE**	**35.2B**	**3.0B**	**25,055**	—	**∼50**

The tok/s numbers reveal the mechanism. MoE: ∼50 tok/s. Qwen3.5-2B: 73 tok/s. *Per-token throughput is comparable.* The chasm is output length. With thinking mode on, the MoE wraps every answer in chain-of-thought reasoning, producing ∼1,500 tokens per response. At 50 tok/s, that is 30 seconds. The dense Qwen3.5 models with thinking off produce 112–262 tokens. Verbosity, not routing, is the bottleneck.

Within the Qwen3.5 dense family, P50 latency scales predictably: 735 ms (0.8B), 856 ms (2B), 2,188 ms (4B), 4,014 ms (9B). The P95 values tell a different story: 15,663 ms for the 2B, 31,706 ms for the 4B. Even with thinking off, the Gated DeltaNet architecture occasionally produces long-tail responses on complex tasks.

Figure 4 makes this visually clear. Dense models follow an imperfect but discernible relationship between active parameters and latency. The MoE model is an extreme upward outlier at its active parameter count of 3.0B. It should sit at roughly 900–1,000 ms based on the dense trend. It is at 25,055 ms, 28 times too slow.

Why this matters. Neither parameter count predicts MoE deployment latency. Active parameters? 3B should mean ∼900 ms. Total parameters? Even Gemma-2-9B, with far fewer total parameters, is 8.5× faster. The MoE occupies its own latency class, not because routing is slow but because the model generates ∼1,500 tokens of chain-of-thought per response. At ∼50 tok/s (competitive with dense 3B models), that volume of output text means 25 seconds per request. Simply put, you cannot use parameter counts as a proxy for MoE deployment latency. Output token count dominates, and it depends on task, prompt, and inference configuration in ways that no model card reports.

5.2 RQ2: Does MoE Accuracy Match Its Active or Total Parameter Class?

Speed like a 3B model was already falsified, badly. What about accuracy? Does the 35B of stored knowledge show up in the answers? Here the story is different.

Table 6 breaks it down by task.



Figure 4: **MoE latency does not follow the active-parameter trend.** Dense models (blue circles, orange triangles for Qwen3.5 siblings) follow a roughly predictable relationship. The Qwen3.5 dense models track the same trend as other architectures. The MoE (purple diamond) is an extreme outlier at 3B active, at 25,055 ms versus 856 ms for its own dense sibling Qwen3.5-2B. The verbosity stems from thinking mode, not sparse routing.

The architecture-controlled comparison is damning. At 55.0% overall accuracy the MoE ranks 9th of 13, below every one of its own dense siblings. Qwen3.5-4B hits 77.2%. The 9B: 74.1%. Even the 0.8B, with one-forty-fourth the total parameters, reaches 64.0%.

Where chain-of-thought reasoning pays off, though, it pays handsomely. T6 (math): 71.5%, best in the study by a wide margin (the nearest dense model, Qwen3.5-9B, manages 28.0%). T5 (code patching): 60.3%, triple the best dense result. But these gains come with collateral damage. T1 (intent classification) drops to 2.2%: the model generates thousands of tokens of reasoning for a task requiring a single label.

But there's a confound. The MoE ran with `enable_thinking=True` (default), producing ∼1,500 tokens per response. The dense Qwen3.5 models ran with thinking off, producing 112–262 tokens. So we aren't comparing MoE vs dense architecture. We're comparing thinking-on vs thinking-off within the same family. The MoE's lower overall accuracy likely reflects thinking mode's interference with structured output formatting, not a deficiency in sparse routing.

Task-averaged accuracy: 55.0%. Weighted by task size, the MoE places 9th of 13. The top four (Qwen3.5-4B, Qwen3.5-9B, Llama-3.2-3B, Qwen3.5-0.8B) include three members of the MoE's own family, all run with thinking off.

Table 6: **Accuracy by task, all 13 models.** The MoE (highlighted) scores 55.0% overall, 9th of 13. Its own dense siblings outperform it: Qwen3.5-4B reaches 77.2%, Qwen3.5-9B reaches 74.1%. The MoE's T5 (60.3%) and T6 (71.5%) are strong, but its T1 (2.2%) is a near-total failure. Dense Qwen3.5 models (†) ran with thinking mode off.

Model	Active	T1	T2	T3	T4	T5	T6	Avg
Qwen3.5-0.8B†	0.8B	30.0	85.6	25.8	53.6	5.8	4.0	64.0
Llama-3.2-1B	1.2B	16.4	40.3	13.0	46.4	0.8	7.5	37.8
Qwen3.5-2B†	2.0B	40.2	55.1	32.4	57.6	4.4	9.0	56.8
Llama-3.2-3B	3.2B	45.6	93.7	67.4	57.2	14.7	13.5	72.7
Qwen2.5-3B	3.1B	64.0	44.1	48.4	54.2	15.1	13.0	38.6
Phi-3-mini	3.8B	51.2	74.4	60.8	49.8	3.2	20.0	48.1
Qwen3.5-4B†	4.0B	76.8	99.8	61.0	62.2	17.4	24.5	**77.2**
Qwen3-4B	4.0B	14.6	100.0	46.2	33.2	0.0	13.0	47.2
Mistral-7B-v0.3	7.2B	71.8	96.2	60.4	59.6	2.2	10.5	55.6
Ministral-8B	8.0B	64.0	100.0	55.0	53.0	13.2	16.0	56.7
Gemma-2-9B	9.2B	74.0	100.0	38.0	56.0	4.8	22.5	57.5
Qwen3.5-9B†	9.0B	79.6	100.0	56.4	65.0	17.3	28.0	74.1
Qwen3.5-35B-A3B†	**3.0B**	**2.2**	**88.7**	**43.4**	**49.8**	**60.3**	**71.5**	**55.0**

5.3 RQ3: Does MoE Achieve Non-Zero S@SLO at the Interactive Tier?

This is the question that matters. S@SLO requires three things simultaneously: valid JSON, correct answer, within deadline. Table 7 presents Success@SLO across all three tiers for all 13 models.

Zero. Not low—zero. At 25,055 ms median, no MoE request finishes within 2 seconds. Standard (5s): 0.3%. Batch (30s): 37.0%, still below its own 55.0% accuracy because many correct answers arrive too late to count.

The dense Qwen3.5 family tells a clearer story. Qwen3.5-0.8B, a 0.8B model, achieves 59.5% S@SLO at 2s, nearly matching Llama-3.2-3B (61.5%). Fast enough (735 ms median) that most correct answers arrive in time. Qwen3.5-4B leads accuracy at 77.2% but drops to 26.4% S@SLO at 2s; its 2,188 ms median pushes too many responses past the deadline. Give it 30 seconds and it recovers to 76.2%, close to full accuracy. Qwen3.5-9B: same pattern, 74.1% accuracy, 13.6% at 2s, 74.1% at 30s.

The within-family gradient sharpens the trade-off. Each doubling of Qwen3.5 model size buys 5–13 percentage points of accuracy and costs 30–50 percentage points of Interactive S@SLO. At the extreme sits the MoE: accuracy below all its dense siblings (55.0% vs 64–77%), S@SLO at zero. The thinking-mode confound explains why.

Per-task S@SLO breakdown. Table 8 shows S@SLO at the Interactive tier broken down by task.

The per-task breakdown is telling. Qwen3.5-0.8B and Qwen3.5-2B dominate short-output tasks: 86–98% S@SLO on T1 and T4, fast enough that the 2-second deadline barely matters. T2 (long output) drops sharply for the 2B model (26.8%), and T5/T6 hover near zero; these tasks demand more reasoning than sub-1B models can muster.

Qwen3.5-4B produces the most striking contrast: 99.4% S@SLO on T4 (function routing), 0.0% on T2 (HotpotQA). It routes functions flawlessly within the deadline but cannot generate long QA responses fast enough. The MoE: six zeros. Every task, every response, past the 2-second deadline. Thinking-mode verbosity is indiscriminate.

Table 7: **Success@SLO (%) across SLO tiers, all 13 models.** Qwen3.5-0.8B (59.5% at 2s) nearly matches Llama-3.2-3B (61.5%). Qwen3.5-4B leads accuracy at 77.2% but trades speed. The MoE: 0.0% at Interactive, 0.3% at Standard, despite 55.0% accuracy. Dense Qwen3.5 models (†) ran with thinking off.

		Success@SLO (%)			Diagnostics		
Model	**Type**	**2s**	**5s**	**30s**	**Acc%**	**JSON%**	**P95 (s)**
Qwen3.5-0.8B†	Dense	59.5	62.3	64.0	64.0	87.0	7.67
Llama-3.2-1B	Dense	37.7	37.8	37.8	37.8	57.3	1.47
Qwen3.5-2B†	Dense	47.4	55.9	56.8	56.8	77.2	15.66
Llama-3.2-3B	Dense	**61.5**	**72.7**	**72.7**	**72.7**	**85.3**	**2.74**
Qwen2.5-3B	Dense	28.1	38.6	38.6	38.6	55.1	2.96
Phi-3-mini	Dense	17.9	34.1	48.1	48.1	66.9	7.23
Qwen3.5-4B†	Dense	26.4	56.6	76.2	77.2	92.1	31.71
Qwen3-4B	Dense	0.6	14.1	47.2	47.2	72.6	7.35
Mistral-7B-v0.3	Dense	22.6	31.5	55.6	55.6	77.0	7.88
Ministral-8B	Dense	22.3	41.9	56.7	56.7	73.4	7.14
Gemma-2-9B	Dense	20.8	26.8	57.5	57.5	76.6	9.26
Qwen3.5-9B†	Dense	13.6	40.8	74.1	74.1	91.8	14.68
Qwen3.5-35B-A3B†	**MoE**	**0.0**	**0.3**	**37.0**	**55.0**	**66.8**	—

5.4 RQ4: Does MoE Change the Accuracy–S@SLO Correlation?

Paper I's headline number: $\rho = 0.09$. Accuracy and S@SLO, uncorrelated. Does one MoE model change the math?

The correlation depends on how tight the deadline is. At Interactive (2s), accuracy and S@SLO remain uncorrelated: $\rho = +0.209$, $p = 0.494$. The Qwen3.5 family shows why: Qwen3.5-4B has the highest accuracy (77.2%) but only moderate S@SLO (26.4%), while the 0.8B has lower accuracy (64.0%) and nearly the highest S@SLO (59.5%). Knowing which model is most accurate tells you nothing about which one will meet a 2-second deadline.

Loosen the deadline and the picture changes. At Standard (5s): $\rho = +0.604$, $p = 0.029$, significant. At Batch (30s): $\rho = +0.945$, $p < 0.001$. The deployment gap is, at bottom, a function of how much time you are willing to give. Generous deadlines let accuracy dominate. Tight deadlines let speed dominate. Neither correlates with the other.

What this means. Dense and sparse architectures. Five model families. Two hardware platforms. The gap persists across all of them. Accurate models are large, large models are slow, and at tight deadlines the speed penalty overwhelms whatever accuracy advantage size confers. Two exceptions (Llama-3.2-3B and Qwen3.5-0.8B) are small models that happen to be accurate enough. MoE does not escape the gap. Its thinking-mode verbosity makes it the most extreme example we have measured.

6 MoE-Specific Analysis

6.1 Memory Profile

The catch is real. MoE gets you routing overhead and hybrid attention costs that push latency above the dense 3B class, but all 35B parameters still need to live in memory. Speed does not scale

Table 8: Success@SLO (%) at Interactive tier (2s) by task, all 13 models. Qwen3.5-0.8B achieves strong multi-task S@SLO despite being a 0.8B model: 86.0% on T1, 72.2% on T2, 96.8% on T4. The MoE achieves 0.0% on all six tasks.

Model	**Active**	**T1**	**T2**	**T3**	**T4**	**T5**	**T6**
Qwen3.5-0.8B†	0.8B	86.0	72.2	25.8	96.8	4.0	4.0
Llama-3.2-1B	1.2B	16.4	40.3	13.0	46.4	0.8	7.5
Qwen3.5-2B†	2.0B	98.4	26.8	32.4	98.0	0.0	4.5
Llama-3.2-3B	3.2B	45.6	93.7	67.4	57.2	14.7	13.5
Qwen2.5-3B	3.1B	64.0	26.5	30.2	12.6	0.3	3.0
Phi-3-mini	3.8B	17.6	26.1	11.2	12.2	0.3	2.5
Qwen3.5-4B†	4.0B	21.6	0.0	34.8	99.4	0.0	7.0
Qwen3-4B	4.0B	0.0	0.0	0.6	0.0	0.0	2.5
Mistral-7B	7.2B	30.2	16.2	22.6	39.4	0.0	4.5
Ministral-8B	8.0B	28.6	16.4	22.6	42.4	0.3	3.0
Gemma-2-9B	9.2B	12.4	10.0	12.4	4.0	0.0	0.0
Qwen3.5-9B†	9.0B	0.0	0.0	30.0	49.0	0.0	6.0
Qwen3.5-35B-A3B†	**3.0B**	**0.0**	**0.0**	**0.0**	**0.0**	**0.0**	**0.0**

Table 9: Spearman correlation between accuracy and S@SLO at three tiers. The deployment gap persists across all model sets. At Batch (30s), the correlation strengthens to +0.945 ($p < 0.001$); the gap is most severe at tight deadlines.

Model Set	n	ρ **(2s)**	p**-value**	**Result**
Dense only (P1, CUDA)	13	+0.09	0.76	Uncorrelated
Orig 8 dense (MLX)	8	+0.048	0.911	Effectively zero
All 12 dense (MLX)	12	+0.140	0.665	Weak, not significant
All 13 incl. MoE (MLX)	13	+0.209	0.494	Weak, not significant
Additional tiers (all 13 models):				
All 13, ρ (5s)	13	+0.604	0.029	Moderate, significant
All 13, ρ (30s)	13	+0.945	<0.001	Strong

with active parameters. Memory still scales with total parameters.

Table 10 shows peak memory usage across models.

21.0 GB at INT4, before accounting for KV cache. On an RTX 4090 with 24 GB, this does not run under realistic inference conditions. On Apple Silicon with 64 GB unified memory, the model loads with 43 GB to spare. Memory is not the binding constraint here, but it is why the experiment was conducted on Apple Silicon at all.

Name the asymmetry plainly: MoE models are *not* faster than dense models of matching active parameters (we observe the opposite), and they require *far more* memory than dense models of matching latency class. Twenty-four gigabytes of VRAM? Does not fit. Sixty-four gigabytes of unified memory? Fits, but runs slowly. No consumer hardware gives you both competitive speed and fit-in-memory for this model.

6.2 Tokens Per Second

Raw generation speed, stripped of task effects and output length variation.

Per-token speed does scale with active parameters. The MoE at ∼50 tok/s sits between Qwen3.5-2B (73 tok/s) and Qwen3.5-4B (30 tok/s), right where a 3B-active model should land.

Table 10: Peak memory usage during inference. The MoE model requires memory proportional to its total parameter count (35B) at 21.0 GB. Dense models range from 0.7 GB to 5.4 GB. On Apple Silicon with 64 GB, this fits with room to spare. On a 24 GB GPU, the model cannot run under realistic inference conditions.

Model	Type	Total	Active	Peak Memory	Fits 24 GB?
Qwen3.5-0.8B	Dense	0.8B	0.8B	0.5 GB	Yes
Llama-3.2-1B	Dense	1.2B	1.2B	0.7 GB	Yes
Qwen3.5-2B	Dense	2.0B	2.0B	1.2 GB	Yes
Llama-3.2-3B	Dense	3.2B	3.2B	1.9 GB	Yes
Qwen2.5-3B	Dense	3.1B	3.1B	1.8 GB	Yes
Phi-3-mini	Dense	3.8B	3.8B	2.3 GB	Yes
Qwen3.5-4B	Dense	4.0B	4.0B	2.4 GB	Yes
Qwen3-4B	Dense	4.0B	4.0B	2.4 GB	Yes
Mistral-7B-v0.3	Dense	7.2B	7.2B	4.3 GB	Yes
Ministral-8B	Dense	8.0B	8.0B	4.8 GB	Yes
Gemma-2-9B	Dense	9.2B	9.2B	5.4 GB	Yes
Qwen3.5-9B	Dense	9.0B	9.0B	5.3 GB	Yes
Qwen3.5-35B-A3B	**MoE**	**35.2B**	**3.0B**	**21.0 GB**	**No**

The Qwen3.5 family traces a clean throughput gradient: 107 tok/s (0.8B), 73 (2B), 30 (4B), 21 (9B). Active parameters predict per-token speed. They do not predict deployment latency.

Here is the arithmetic that matters. The MoE generates ∼1,500 tokens per response (thinking on). The dense Qwen3.5 models: 112–262 tokens (thinking off). At 50 tok/s, 1,500 tokens is 30 seconds. At 73 tok/s, 262 tokens is 3.6 seconds. Throughput accounts for part of the gap (50 vs 73 tok/s). Output length accounts for nearly all of it (1,500 vs 262 tokens).

This points to a fix. Run the MoE with thinking off and its ∼50 tok/s yields sub-5-second responses for typical 200-token outputs. The deployment failure isn't baked into the architecture. It's a training-mode default you can override by disabling thinking, capping output length, or fine-tuning for concise structured output.

6.3 Expert Utilization and Routing Overhead

Qwen3.5-35B-A3B uses top-k expert routing [16]: 256 experts per layer, 8 activated per token, plus a shared expert that fires on every token. Three of every four layers use Gated DeltaNet linear attention (subquadratic in sequence length); every fourth layer uses standard grouped-query attention.

Routing overhead analysis. The tok/s comparison allows us to estimate routing overhead. A pure dense 3B model with 44 tok/s and the MoE at ∼50 tok/s suggests the routing mechanism does not impose a significant per-token computation penalty relative to pure dense computation. However, the DeltaNet hybrid architecture introduces a different overhead: the state-tracking mechanism in linear attention layers requires additional memory operations per forward pass that accumulate over long sequences.

The 25,055 ms median latency at ∼50 tok/s throughput implies an average response length of $25{,}055 \times 0.050 \approx 1{,}253$ output tokens. The actual measured average is approximately 1,500 tokens. Dense 3B models at 44 tok/s and 884 ms median imply $884 \times 0.044 \approx 39$ output tokens. The MoE model generates roughly 38× more tokens per response on average. This is the dominant source of

Table 11: Tokens per second across models. The MoE model's tok/s (∼50) is comparable to dense 3B models (42.9–44.0 tok/s), faster than many larger dense models. The latency problem is not tok/s; it is total output token count: the MoE generates ∼1,500 tokens per response vs ∼39 for dense 3B models.

Model	Type	Active	Mean tok/s	P50 tok/s	P5 tok/s
Qwen3.5-0.8B	Dense	0.8B	110.8	106.9	17.2
Llama-3.2-1B	Dense	1.2B	118.4	115.3	45.4
Qwen3.5-2B	Dense	2.0B	69.3	73.1	24.6
Llama-3.2-3B	Dense	3.2B	48.6	42.9	17.7
Qwen2.5-3B	Dense	3.1B	46.6	44.0	15.4
Phi-3-mini	Dense	3.8B	48.9	48.3	7.3
Qwen3.5-4B	Dense	4.0B	29.6	30.2	7.1
Qwen3-4B	Dense	4.0B	56.4	54.5	34.8
Mistral-7B-v0.3	Dense	7.2B	23.3	20.7	6.0
Ministral-8B	Dense	8.0B	21.1	19.5	5.7
Gemma-2-9B	Dense	9.2B	16.2	13.9	5.0
Qwen3.5-9B	Dense	9.0B	19.2	20.9	6.5
Qwen3.5-35B-A3B	**MoE**	**3.0B**	**51.3**	**50.1**	**35.0**

latency: not routing overhead, not per-token slowness, but massive chain-of-thought output. The model wraps correct answers in extensive reasoning traces, producing verbose outputs that push every response past SLO deadlines.

Figure 5 makes the thinking-mode confound visible. The MoE CDF (purple dashed) sits in a different latency regime from every other model. Qwen3.5-0.8B (red-orange) shows an interesting shape: fast median (735 ms) but a long tail extending past 7 seconds. This reflects occasional complex responses where even a 0.8B model generates extended output. Still, it clears the 2-second deadline for most requests. The MoE, with thinking mode producing 1,500 tokens per response, cannot clear any practical deadline.

7 Edge Deployment Implications

The theoretical tension resolves, but not how we expected. The MoE *can* produce correct answers (55.0% accuracy), and on reasoning-heavy tasks it is the best model in the study. But its dense siblings outperform it overall (Qwen3.5-4B: 77.2%), and the thinking-mode confound muddies what would otherwise be a clean architectural comparison. The deployment story turns out to be about model size, output length, and inference configuration. Not MoE vs dense.

7.1 Apple Silicon as an MoE Platform

Apple Silicon provides the memory headroom to run 35B MoE models. That is real. But memory capacity is a necessary condition for deployment, not a sufficient one. Our results show it is not sufficient.

Apple Silicon is the only consumer platform *capable* of running large MoE models, for two reasons:

1. **Memory capacity.** A 35B model at INT4 needs about 21 GB. An M4 Max with 64 GB has 43 GB of headroom for KV cache, context, and OS overhead. An RTX 4090 with 24 GB cannot fit this model under realistic inference conditions.



Figure 5: **Latency CDFs reveal the thinking-mode verbosity problem.** The MoE (purple dashed, thinking on) generates ∼1,500 tokens per response. Qwen3.5-0.8B (red-orange, thinking off) has a long tail (P95 = 7,673 ms) but its P50 (735 ms) clears the 2-second deadline for most requests. At the 2s SLO, the MoE captures 0%; Qwen3.5-0.8B captures ∼80%; Llama-3.2-3B captures ∼85%. The MoE's CDF is a different latency regime entirely, a training-mode artifact.

2. **Unified memory eliminates the bus bottleneck.** MoE models have irregular memory access patterns: different tokens route to different experts, creating unpredictable reads across the weight matrix. Unified memory removes the CPU-GPU bus entirely. And while Apple Silicon's bandwidth (400–546 GB/s) is lower than the RTX 4090's (1,008 GB/s), the tok/s results show bandwidth is not the binding constraint. The MoE hits 50 tok/s, adequate for its active parameter count.

When Apple Silicon is the right platform. Our normalization results ($\bar{\alpha} = 0.177$) show MLX is 3–9× faster than LM Studio/CUDA on this task suite. For dense models in the 1B–9B range, Apple Silicon with MLX is a strong deployment platform: faster than we expected, memory-efficient, and portable.

For the MoE model specifically: Apple Silicon is the only consumer platform that can run it, but running it does not mean running it well. The latency results and structured output failure are not hardware artifacts. They are model behavior.

7.2 MoE Is Not Viable for Structured Output Deployment

Under our evaluation conditions (structured JSON output, schema validation, per-request SLO constraints, no constrained decoding), the MoE with default settings (thinking on) cannot be deployed at any SLO tier below 30 seconds.

At 30 seconds, it achieves only 37.0% S@SLO, below its 55.0% accuracy and below every dense model at the same tier. Qwen3.5-4B achieves 76.2% S@SLO at Batch with 2.4 GB memory. The MoE requires 21 GB for worse results.

That said, the MoE was not tested with thinking off. Given its competitive per-token speed (∼50

tok/s), disabling thinking mode could reduce output to ∼200 tokens and latency to ∼4 seconds, potentially viable at Standard (5s) and certainly at Batch (30s). The current results characterize default-configuration MoE performance, not the optimized ceiling. On T6 (math, 71.5%) and T5 (code, 60.3%), the MoE is best in the study, and these accuracy gains may justify the engineering effort to optimize its inference configuration.

7.3 Practical Deployment Guidance

Practical guidance, ordered by SLO tier:

For Interactive SLOs (≤2s): Two viable options. Llama-3.2-3B: 61.5% S@SLO, 72.7% accuracy, 968 ms median. Qwen3.5-0.8B: 59.5% S@SLO, 64.0% accuracy, 735 ms median. The 3B model is more accurate; the 0.8B model is faster and uses half the memory. MoE: 0.0%, not viable.

For Standard SLOs (≤5s): Llama-3.2-3B dominates at 72.7% S@SLO. Qwen3.5-0.8B (62.3%), Qwen3.5-4B (56.6%), and Qwen3.5-2B (55.9%) offer alternatives. MoE: 0.3%, not viable.

For Batch SLOs (≤30s): Qwen3.5-4B leads at 76.2% S@SLO with 77.2% accuracy, the best batch-tier model. Qwen3.5-9B (74.1%), Llama-3.2-3B (72.7%), Gemma-2-9B (57.5%). MoE: 37.0%, worse than every dense model.

For MoE specifically: Viable only for latency-insensitive batch processing on tasks requiring complex reasoning. MoE excels on T5 (code patching, 60.3%) and T6 (math, 71.5%), best-in-study on both. But its thinking-mode verbosity can likely be addressed by running with `enable_thinking=False`, which would reduce output to ∼200 tokens and potentially achieve sub-5-second latency. We have not tested this configuration.

Hardware: MLX on Apple Silicon is 3–9× faster than LM Studio/CUDA for this task suite. The MoE model requires ≥32 GB of unified memory.

8 Discussion

8.1 What MoE Changes, and Does Not Change, About the Deployment Gap

Four papers, one finding: in dense models, accuracy and latency are coupled through total parameter count. MoE was supposed to sever that coupling. Thirteen models later, the story is more nuanced than a clean yes or no.

At 55.0% overall accuracy the MoE ranks 9th of 13. Its own dense siblings outscore it across the board: 77.2% for the 4B, 74.1% for the 9B, 64.0% for the 0.8B. Thirty-five billion parameters of stored knowledge, and a well-matched 4B dense model from the same family produces better structured output.

Most of this traces to the thinking-mode confound. The MoE ran with `enable_thinking=True` (the Qwen3.5 default), generating ∼1,500 tokens of chain-of-thought per response. The dense siblings ran with thinking off, producing 112–262 tokens. So what we measured is not MoE-vs-dense architecture. It is thinking-on-vs-thinking-off within a single family.

What we can say with confidence: thinking mode on buys complex-reasoning performance (T5: 60.3%, T6: 71.5%, both best in study) at ruinous latency. Thinking mode off buys higher overall accuracy at viable latency. The deployment gap persists not because MoE routing fails, but because the default inference mode produces verbose output that no SLO can accommodate.

8.2 The Thinking-Mode Confound

We owe the reader a candid account of how we found this. When we first evaluated the MoE, we used default settings, not realizing that Qwen3.5's thinking mode was silently generating 1,500 tokens of chain-of-thought before each answer. When we later added the four dense Qwen3.5 models, we disabled thinking mode to match the output behavior of the other dense models in the study.

The asymmetry was unintentional. We only spotted it during post-hoc analysis, after the dense siblings outperformed the MoE despite having far fewer parameters. A quick test of the dense 4B with thinking on confirmed our suspicion: same verbosity pattern.

So the MoE's extreme latency (25,055 ms) is not evidence that sparse routing is slow. It is evidence that generating 1,500 tokens at 50 tok/s takes 30 seconds. Per-token speed is competitive. Output volume is the problem, and that problem lives in the training mode, not the architecture.

For the deployment gap thesis, this cuts both ways. It limits what we can say about MoE routing *per se*. But it surfaces a new class of deployment failure that deserves attention: models whose default configuration ships with verbose behavior, forcing practitioners to actively reconfigure inference settings before deployment. The "out of the box" experience matters, and few benchmarks measure it.

8.3 The Small-Model Finding

After four papers of bad news, a genuine positive. Not one model but two.

Llama-3.2-3B: 968 ms median, 72.7% accuracy, 61.5% S@SLO at Interactive. Qwen3.5-0.8B: 735 ms median, 64.0% accuracy, 59.5% S@SLO. Both do what five papers in this series failed to find: models that are accurate and deployment-compliant at the same time.

Consider the trajectory. Paper I had only Llama-3.2-1B surviving the Interactive tier, at a meager 37.8% accuracy. Now we have two models above 60% S@SLO with 64–73% accuracy. The Qwen3.5-0.8B result surprised us most: half the size of Paper I's sole survivor, yet 59.5% S@SLO. The Gated DeltaNet architecture's efficiency (107 tok/s) combined with concise output (thinking off) makes this possible.

The practitioner trade-off is clean. At Interactive: Llama-3.2-3B for higher accuracy (72.7%), Qwen3.5-0.8B for lower memory (0.5 GB vs 1.9 GB) and faster median response. Both viable. At Batch: Qwen3.5-4B (77.2% accuracy, 76.2% S@SLO) wins outright.

8.4 Implications for the Series

What this changes for the rest of the series:

- **Paper I:** Core finding confirmed as hardware-independent ($\rho = +0.209$ on Apple Silicon vs $+0.09$ on CUDA). Now extended to sparse architectures and 13 models.
- **Paper II:** The thinking-mode confound opens a training question: can GRPO with a length penalty compress MoE output while preserving accuracy? The MoE's reasoning advantage on T5/T6 suggests the knowledge is there; only the output format needs optimization. Paper VI investigates GRPO training on consumer hardware via MLX, where output-length management becomes a training objective.
- **Paper III:** The benchmark needs MoE models, Qwen3.5 dense models, and Apple Silicon as a reference platform. The normalization protocol from Section 4.2 enables cross-hardware comparison.

Table 12: Estimated CUDA performance for the MoE model, derived from MLX measurements and the hardware normalization factor. These are projections with significant uncertainty; MoE memory access patterns may not normalize like dense models, and the RTX 4090 cannot run this model anyway.

Metric	Measured (MLX)	Estimated (CUDA)
P50 Latency (ms)	25,055	∼141,554
Mean tok/s	∼50	∼9
S@SLO$_{2s}$ (%)	0.0	0.0
S@SLO$_{5s}$ (%)	0.3	0.0
S@SLO$_{30s}$ (%)	37.0	∼0

Projections assume $\bar{\alpha} = 0.177$ applies to MoE (uncertain).
Actual CUDA requires >24 GB VRAM (e.g., A100 40 GB). RTX 4090 cannot run.

- **Paper IV:** The curve taxonomies were derived from dense models. MoE expert routing might exhibit distinct training dynamics. The Qwen3.5 dense models provide within-family baselines.

8.5 The Active Parameter Principle, Revised

We entered this study with a clean heuristic: active parameters predict deployment latency, total parameters predict accuracy. The data partially confirm it and partially tear it apart.

Within the Qwen3.5 dense family (thinking off), active parameters predict both latency and accuracy: 0.8B (735 ms, 64.0%), 2B (856 ms, 56.8%), 4B (2,188 ms, 77.2%), 9B (4,014 ms, 74.1%). Clean gradient. For the MoE with thinking on, active parameters still predict per-token throughput (∼50 tok/s, consistent with 3B active), but deployment latency? 25,055 ms. The heuristic breaks.

A revised principle, messier but more honest:

> *Active parameters predict per-token throughput. Output token count predicts deployment latency. Accuracy depends on both architecture and inference configuration. The variable missing from deployment heuristics is output verbosity: training-mode-dependent, task-dependent, and not predictable from parameter counts alone.*

One flag. `enable_thinking`. Thirty-times latency difference within the same model family. That is the kind of variable no parameter-count heuristic can capture.

8.6 Estimated CUDA Performance

What would this MoE model do on CUDA? We can estimate using the normalization factor ($\bar{\alpha} = 0.177$):

The estimated CUDA performance is dismal. An estimated P50 of ∼142 seconds (over two minutes per request) means the model would fail every SLO tier. Even the Batch (30s) tier would see approximately 0% S@SLO. The $\bar{\alpha}$ normalization may not transfer perfectly to MoE (the output verbosity that dominates MoE latency may interact differently with CUDA vs MLX characteristics), but the direction is unambiguous.

9 Limitations

1. **Thinking-mode confound.** The MoE ran with `enable_thinking=True` (default); dense Qwen3.5 models ran with thinking off. This asymmetry was unintentional and means MoE vs dense com-

parisons within the Qwen3.5 family are confounded by inference configuration. A controlled comparison (MoE with thinking off) would isolate the architectural effect. We have not run this experiment.

2. **One MoE model.** We evaluate Qwen3.5-35B-A3B and nothing else. Mixtral, DeepSeek-MoE, and Switch Transformer use different routing strategies. Our results may not generalize. Qwen3.5-35B-A3B's 12:1 ratio is the most extreme among openly available models, but still $n = 1$.

3. **No constrained decoding or output length control.** Paper I used unconstrained generation and we match that protocol. Output length limits or `enable_thinking=False` on the MoE would likely cut latency by an order of magnitude. Our results characterize default-configuration performance, not the optimized upper bound.

4. **Quantization mismatch across platforms.** Paper I used Q4_K_M (GGUF); we use INT4 (MLX). The large accuracy differences between platforms (e.g., 63.5% vs 37.8% for Llama-3.2-1B) suggest more than quantization; evaluation conditions and prompt formatting likely differ. We focus on within-platform conclusions.

5. **One Apple Silicon config.** We tested one machine. Different M-series chips have different bandwidth and GPU cores. Rank orderings should persist but absolute latencies will vary.

6. **Qwen3.5-9B token limit.** The 9B model ran with a 512-token output limit (vs 2,048 for other models) due to memory constraints. This may undercount its accuracy on tasks requiring longer output (T5 especially) and inflate its S@SLO by producing shorter, faster responses.

7. **Normalization might not transfer to MoE.** The $\bar{\alpha}$ factor was computed from dense models. MoE routing overhead may interact differently with CUDA vs MLX. The estimated CUDA performance in Table 12 carries significant uncertainty.

8. **Memory cost.** Twenty-one gigabytes for the MoE model. Real deployments must account for KV cache, context length, and concurrent model loading.

10 Conclusion

Paper I declared a universal trade-off: accuracy and SLO compliance are uncorrelated. Four papers later, it still held. MoE was the obvious next test: decouple total parameters from active compute, see if the gap breaks. It does not. But the reason is not what we expected.

The MoE ranks 9th of 13 at 55.0% accuracy. Its own dense siblings outscore it: 77.2% (4B), 74.1% (9B). Its 25,055 ms median latency and 0.0% Interactive S@SLO reflect a thinking-mode confound, not an architectural limitation of sparse routing. Per-token speed ($\sim$50 tok/s) is competitive with dense 3B models. Output volume ($\sim$1,500 tokens of chain-of-thought) is what makes it unusable.

That thinking-mode finding matters beyond this paper. One inference flag shifts output length by 6$\times$ and latency by 30$\times$ within the same model family. Parameter counts miss it. Benchmark accuracy misses it. Tok/s misses it too. You only see the problem by measuring under realistic inference configuration.

On the positive side: the deployment gap is hardware-independent ($\rho = +0.209$ at Interactive across 13 models on Apple Silicon, consistent with +0.09 on CUDA). MLX is 3–9$\times$ faster than LM Studio/CUDA ($\bar{\alpha} = 0.177$), a surprise that flips the hardware recommendation. And small

dense models are genuinely deployment-viable: Llama-3.2-3B (72.7% accuracy, 61.5% S@SLO) and Qwen3.5-0.8B (64.0%, 59.5%) both clear the Interactive tier. At Batch, Qwen3.5-4B leads with 77.2% accuracy and 76.2% S@SLO.

The research question has shifted. Not "can MoE bypass the deployment gap?" but "what inference configuration makes MoE deployment-viable?" Running with thinking off, applying output length limits, fine-tuning for concise structured output. Any of these could preserve the MoE's reasoning advantage while achieving reasonable latency. The per-token speed is already there. Output-length management is not.

This paper is part of a six-paper series. Paper I documented the deployment gap across 13 dense models [11]. Paper II investigated training to close the gap [10]. Paper III formalized AgentSLO-Bench [9]. Paper IV analyzed training dynamics [12]. This paper (V) tests MoE under the deployment gap, provides cross-hardware validation on Apple Silicon, and discovers the thinking-mode confound. Paper VI tests whether GRPO training can move from datacenter GPUs to consumer hardware, comparing MLX on Apple Silicon against CUDA.

Reproducibility. All code, datasets, and evaluation artifacts are available at:

`https://github.com/mmaloney007/agentops-fw`

The experiments reported here can be reproduced on Apple Silicon hardware with 64 GB+ unified memory using the MLX framework.

References

[1] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems, 2021.

[2] Damai Dai, Chengqi Deng, Chenggang Zhao, R.X. Xu, Huazuo Gao, Deli Chen, Jiashi Li, Wangding Zeng, Xingkai Yu, Y. Wu, et al. DeepSeekMoE: Towards ultimate expert specialization in mixture-of-experts language models, 2024.

[3] William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

[4] Awni Hannun, Jagrit Digani, Angelos Katharopoulos, and Ronan Collobert. MLX: An array framework for Apple silicon. `https://github.com/ml-explore/mlx`, 2023. Apple's machine learning framework for unified memory architectures.

[5] Albert Q. Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts, 2024.

[6] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *Proceedings of ICLR*, 2024.

[7] Stefan Larson et al. An evaluation dataset for intent classification and out-of-scope prediction. In *Proceedings of EMNLP-IJCNLP*, 2019.

[8] Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. GShard: Scaling giant models with conditional computation and automatic sharding, 2020.

[9] V. Michael Maloney. AgentSLO-Bench: An SLO-aware benchmark for LLM agent deployment. *arXiv preprint*, 2025. Paper III of this series.

[10] V. Michael Maloney. Capacity thresholds in schema-aware training: Why small models can't close the deployment gap. *arXiv preprint*, 2025. Paper II of this series.

[11] V. Michael Maloney. The deployment gap: Why benchmark accuracy fails to predict production readiness. *arXiv preprint*, 2025. Paper I of this series.

[12] V. Michael Maloney. Training dynamics of schema-aware reinforcement learning for LLM agents: Reward decomposition, forgetting, and early prediction. *arXiv preprint*, 2025. Paper IV of this series.

[13] MLX Community. MLX community: Pre-quantized models for Apple silicon. `https://huggingface.co/mlx-community`, 2024. Community-maintained collection of MLX-compatible model weights.

[14] Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive APIs, 2023.

[15] Shishir G. Patil, Huanzhi Mao, Fanjia Yan, Charlie Cheng-Jie Ji, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. The Berkeley function calling leaderboard (BFCL): From tool use to agentic evaluation of large language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *PMLR*, pages 48371–48392, 2025.

[16] Qwen Team. Qwen3 technical report, 2025.

[17] Samyam Rajbhandari, Conglong Li, Zhewei Yao, Minjia Zhang, Reza Yazdani Aminabadi, Ammar Ahmad Awan, Jeff Rasley, and Yuxiong He. DeepSpeed-MoE: Advancing mixture-of-experts inference and training to power next-generation AI scale, 2022.

[18] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc V. Le, Geoffrey E. Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer, 2017.

[19] Leyang Xue, Yao Fu, Zhan Lu, Luo Mai, and Mahesh Marina. MoE-Infinity: Efficient MoE inference on personal machines with sparsity-aware expert cache, 2024.

[20] Zhilin Yang et al. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of EMNLP*, 2018.

[21] Rongjie Yi, Liwei Guo, Shiyun Wei, Ao Zhou, Shangguang Wang, and Mengwei Xu. EdgeMoE: Empowering sparse large language models on mobile devices, 2023.

Table 13: Per-task average latency (ms) for all 13 models. The Qwen3.5 dense models (†, thinking off) show a clean size-latency gradient. The MoE (†, thinking on) is the slowest on every task, a training-mode artifact, not a routing-overhead effect.

Model	Active	T1	T2	T3	T4	T5	T6
Qwen3.5-0.8B†	0.8B	730	1,959	309	359	6,341	598
Llama-3.2-1B	1.2B	390	754	200	268	1,173	231
Qwen3.5-2B†	2.0B	819	2,431	604	653	14,762	1,769
Llama-3.2-3B	3.2B	949	1,866	463	510	2,673	535
Qwen2.5-3B	3.1B	879	2,103	498	524	2,742	342
Phi-3-mini	3.8B	2,182	5,631	615	2,837	4,155	2,945
Qwen3.5-4B†	4.0B	2,077	5,977	931	1,009	23,666	8,353
Qwen3-4B	4.0B	4,704	6,438	3,394	3,462	4,642	3,416
Mistral-7B-v0.3	7.2B	2,594	5,501	1,228	1,247	7,339	2,387
Ministral-8B	8.0B	2,362	4,817	1,051	1,115	7,005	1,343
Gemma-2-9B	9.2B	2,912	6,399	1,637	1,634	8,981	2,240
Qwen3.5-9B†	9.0B	3,895	8,658	1,925	2,054	15,670	3,856
Qwen3.5-35B-A3B†	**3.0B**	**32,238**	**29,718**	**17,603**	**17,222**	**24,995**	**22,086**

A Per-Task Latency Distributions

Table 13 provides average latency (ms) for all 13 models across all 6 tasks.

Two patterns stand out. First, the Qwen3.5 dense models show high T5 latency relative to other models at similar sizes: Qwen3.5-4B averages 23,666 ms on T5 (code patching) despite only 2,188 ms P50 overall. This suggests the Gated DeltaNet architecture generates longer output on complex tasks even with thinking off. Second, the MoE's longest latency is on T1 (32,238 ms), the task requiring the shortest output, because thinking mode generates extensive reasoning regardless of task complexity.

B Cross-Hardware Accuracy Deltas

Table 14 shows per-task accuracy for the 8 models evaluated on MLX. CUDA per-task data from Paper I uses different task implementations and prompt formats; direct per-task comparison is not valid, so we report MLX values and overall CUDA accuracy for reference.

C Normalization Factor Stability

To assess whether the hardware normalization factor is stable across tasks, we note that the per-model geometric mean $\bar{\alpha} = 0.177$ is derived from overall P50 latency. Task-level normalization factors may vary because different tasks generate different output lengths, and longer outputs amplify hardware differences. We report the per-model factors with their ranges in Table 15.

The range (0.114–0.385) indicates meaningful model-level variation in the normalization factor. Phi-3-mini and Qwen3-4B have higher α_m values (smaller MLX advantage) than the Llama and Mistral family models. The Llama, Qwen2.5, Mistral, Ministral, and Gemma models cluster tightly around $\alpha \approx 0.12$–0.13, suggesting a common serving-stack overhead factor of $\sim 8\times$. Phi-3-mini and Qwen3-4B's hybrid or non-standard attention mechanisms may interact differently with the two serving stacks.

Table 14: Per-task accuracy (%) on MLX for all 13 models. The Qwen3.5 dense models (†) show strong accuracy scaling: 0.8B to 9B covers 64–77% overall. The MoE (thinking on) achieves best-in-study on T5 (60.3%) and T6 (71.5%) but ranks 9th overall at 55.0%.

Model	T1	T2	T3	T4	T5	T6	Avg
Qwen3.5-0.8B†	30.0	85.6	25.8	53.6	5.8	4.0	64.0
Llama-3.2-1B	16.4	40.3	13.0	46.4	0.8	7.5	37.8
Qwen3.5-2B†	40.2	55.1	32.4	57.6	4.4	9.0	56.8
Llama-3.2-3B	45.6	93.7	67.4	57.2	14.7	13.5	72.7
Qwen2.5-3B	64.0	44.1	48.4	54.2	15.1	13.0	38.6
Phi-3-mini	51.2	74.4	60.8	49.8	3.2	20.0	48.1
Qwen3.5-4B†	76.8	99.8	61.0	62.2	17.4	24.5	77.2
Qwen3-4B	14.6	100.0	46.2	33.2	0.0	13.0	47.2
Mistral-7B-v0.3	71.8	96.2	60.4	59.6	2.2	10.5	55.6
Ministral-8B	64.0	100.0	55.0	53.0	13.2	16.0	56.7
Gemma-2-9B	74.0	100.0	38.0	56.0	4.8	22.5	57.5
Qwen3.5-9B†	79.6	100.0	56.4	65.0	17.3	28.0	74.1
Qwen3.5-35B-A3B†	**2.2**	**88.7**	**43.4**	**49.8**	**60.3**	**71.5**	**55.0**

Table 15: Hardware normalization factor α_m per model, with range and interpretation. All values are well below 1.0, confirming MLX consistently outperforms LM Studio/GGUF on this workload. Variation across models reflects output-length sensitivity to hardware characteristics.

Model	CUDA P50 (s)	MLX P50 (s)	α_m	MLX speedup
Llama-3.2-1B	3.5	0.40	0.114	8.8×
Llama-3.2-3B	7.5	0.97	0.129	7.7×
Qwen2.5-3B	7.4	0.88	0.119	8.4×
Phi-3-mini	10.9	3.04	0.279	3.6×
Qwen3-4B	12.2	4.70	0.385	2.6×
Mistral-7B-v0.3	20.3	2.65	0.131	7.7×
Ministral-8B	18.5	2.43	0.131	7.6×
Gemma-2-9B	22.9	2.95	0.129	7.8×
Geometric Mean	—	—	**0.177**	**5.6**×
Range	—	—	0.114–0.385	2.6–8.8×

D MoE Verbosity and Deployment Failure Analysis

With 4 dense siblings from the same family in the evaluation, the MoE's failure mode is easier to dissect than in a cross-architecture comparison.

Thinking-mode verbosity (primary cause). The MoE ran with `enable_thinking=True`, producing ∼1,500 tokens per response. The dense Qwen3.5 models ran with thinking off, producing 112–262 tokens. At ∼50 tok/s, 1,500 tokens takes 30 seconds. This single setting is the primary SLO failure mechanism. It is a training-mode artifact, not an MoE architectural property.

Architecture-controlled comparison. Same Gated DeltaNet architecture, thinking off: the dense siblings achieve 64–77% accuracy with S@SLO from 13.6% (9B at 2s) to 59.5% (0.8B at 2s). The MoE, thinking on: 55.0% accuracy, 0.0% S@SLO. If thinking mode alone explains the latency

gap, then MoE routing per se may not cause deployment failure. A controlled test (MoE with thinking off) would settle the question.

Task-dependent reasoning value. Chain-of-thought helps on reasoning-heavy tasks: T6 (math, 71.5%) and T5 (code, 60.3%) are both best-in-study. It hurts everywhere else. T1 (intent classification, 2.2%), where the model generates thousands of tokens for a task requiring a single label. Qwen3.5-4B with thinking off: 76.8% on T1, 24.5% on T6. Thinking mode trades T1 accuracy for T5/T6 accuracy.

There is no single correct configuration. Reasoning-heavy tasks benefit from thinking mode. Latency-constrained deployment requires it off. What practitioners need is per-task configuration, not a model-wide toggle.