

# Supplementary Material: Sparse Feature Selection, Not Capacity, Drives Spatial Transfer in Crop Classification

Michael L. Mann, Sairam Venkatachalam, Disha Kacha, Devarsh Sheth, Ryan Engstrom, Amir Jafari

---

This document collects supporting material for the main paper. Section S-A details the dataset, feature set, and model definitions; Section S-B defines the metrics; Section S-C reports training cost; and Section S-D presents the ablation studies. Equation, figure, table, and section labels are prefixed “S”.

## S-A. Dataset Details, Feature Set, and Model Definitions

*Supports main paper Sec. 2–3.*

### S-A.1. Exploratory Data Analysis

The five crop classes are heavily imbalanced (Fig. S1(a)). Lucerne/medics dominates both regions despite having the smallest mean field area (Fig. S1(b)). Spectral responses overlap substantially across crops (Fig. S2(a)), and wheat and barley are especially similar (Fig. S2(b)), the dominant source of persistent confusion noted in the main paper.

### S-A.2. *xr\_fresh* Feature Set

Table S1 lists the time-series features extracted from each pixel’s 10-month spectral profile with *xr\_fresh* (Mann et al., 2026; Mann, 2025), forming the 174-dimensional per-pixel vector used by the classical learners (Fig. S3 illustrates the extraction).

### S-A.3. Baseline Classical Model Definitions


For a feature vector  $\mathbf{x}_i$  and class  $c \in \{1, \dots, C\}$ , the four baselines are as follows. Logistic regression (James et al., 2013) (multinomial):

$$P(y_i = c \mid \mathbf{x}_i) = \frac{\exp(\mathbf{w}_c^\top \mathbf{x}_i + b_c)}{\sum_{c'=1}^C \exp(\mathbf{w}_{c'}^\top \mathbf{x}_i + b_{c'})}. \quad (\text{S1})$$


Random Forest (Breiman, 2001): majority vote over  $K$  trees,  $\hat{y}_i = \text{mode}\{T_1(\mathbf{x}_i), \dots, T_K(\mathbf{x}_i)\}$ . LightGBM (Ke et al., 2017): additive boosting with rate  $\eta$ ,  $\hat{y}_i^{(t)} = \hat{y}_i^{(t-1)} + \eta f_t(\mathbf{x}_i)$ . XGBoost (Chen and Guestrin, 2016; Friedman, 2001): regularized boosting objective  $\mathcal{L} = \sum_i l(y_i, \hat{y}_i) + \sum_k \Omega(f_k)$  with  $\Omega(f_k) = \gamma T_k + \frac{1}{2} \lambda \sum_j w_j^2$ . The field-level XGBoost was tuned with Optuna over 150 trials; the top configurations appear in Table S2. Field-level pixel features are aggregated by the mean within each polygon. For the pixel ensemble, RF, XGBoost, and LightGBM probabilities are soft-voted; the field-level stacked ensemble uses RF and XGBoost base learners with a logistic-regression meta-learner, and a confidence-margin rule falls back to pixel-mode voting when the top two field-level class probabilities differ by less than 0.10.

### S-A.4. Deep Model Definitions

*CNN-BiLSTM.* An input tensor of shape  $(B, 6, T)$  passes a 1D convolution (64 filters, kernel 5) and a bidirectional LSTM (hidden size 64), with the final timestep classified via a softmax head (Fig. S4). Class imbalance is handled with focal loss  $\mathcal{L}_{\text{focal}} = -\alpha_t(1 - p_t)^\gamma \log(p_t)$ ,  $\gamma = 2.0$ ,  $\alpha_t$  the inverse class frequency. Five seeds are ensembled by averaging logits.




(a)




(b)

Figure S1: Crop-field composition of the training and holdout regions. (a) Number of labeled fields per crop type: lucerne/medics dominates (43% of training and 56% of holdout fields), followed by wheat, barley, canola, and small-grain grazing. This heavy class imbalance motivates macro-F1 as the primary metric and the class-imbalance handling used during training. (b) Mean field area by crop type (hectares); lucerne/medics is the most frequent class despite having among the smallest fields.



(a)



(b)

Figure S2: Spectral separability of the crop classes, shown as box plots of standardized (z-score) intensity for each Sentinel-2 band and index (B2, B6, B11, B12, EVI, hue). (a) Distributions for all five crops overlap substantially across every band, so no single feature cleanly separates the classes. (b) Wheat versus barley are especially similar in every band—the dominant source of the persistent wheat–barley confusion seen across all models in the main paper.




Figure S3: Time-series feature generation with `xr_fresh`. For each pixel, the 10-month profile of every band and index is summarized by the statistical and temporal descriptors of Table S1 (e.g., linear trend, autocorrelation, quantiles, day-of-year of the maximum), producing the 174-dimensional per-pixel feature vector used by the classical learners.




Figure S4: Architecture of the CNN-BiLSTM model. The  $(B, 6, T)$  input (six bands/indices over  $T$  months) passes a 1D convolution (64 filters, kernel 5) for temporal feature extraction, then a bidirectional LSTM (hidden size 64) whose final time step is classified by a softmax head. Training uses weighted focal loss to counter class imbalance, and five seeds are ensembled by averaging logits.

Table S1: Time-series features extracted from each pixel’s spectral profile with `xr_fresh`.

| Feature                          | Description                                                              |
|----------------------------------|--------------------------------------------------------------------------|
| Absolute Energy                  | Sum of squared values.                                                   |
| Absolute Sum of Changes          | Total absolute difference between consecutive measurements.              |
| Autocorrelation (1, 2-month lag) | Correlation with one- and two-month lagged versions.                     |
| Count Above Mean                 | Number of points above the series mean.                                  |
| Day of Year of Max/Min           | Julian day of the maximum and minimum.                                   |
| Kurtosis                         | Tail heaviness of the distribution.                                      |
| Linear Trend                     | Slope of a least-squares fit.                                            |
| Longest Strike Above/Below Mean  | Longest consecutive run above or below the mean.                         |
| Max/Min                          | Absolute extreme values.                                                 |
| Mean/Median                      | Measures of central tendency.                                            |
| Mean Absolute Change/Mean Change | Average magnitude and signed change between points.                      |
| Mean Second Derivative           | Mean of the series’ second differences.                                  |
| Quantiles (0.05, 0.95)           | 5th and 95th percentiles.                                                |
| Ratio Beyond $r\sigma$           | Proportion of points more than $r$ s.d. ( $r = 1, 2, 3$ ) from the mean. |
| Skewness                         | Asymmetry around the mean.                                               |
| Standard Deviation/Variance      | Spread measures.                                                         |
| Sum of Values                    | Total sum of observations.                                               |
| Symmetry Looking                 | Similarity under series reversal.                                        |
| Time Series Complexity           | Complexity-Invariant Distance metric of irregularity.                    |

Each descriptor is computed independently for every band and index from a pixel’s 10-month series; stacked across the six bands/indices (B2, B6, B11, B12, EVI, hue) they form the 174-dimensional per-pixel vector fed to the classical learners. For the Ratio-Beyond features,  $r$  is the threshold in standard deviations ( $r = 1, 2, 3$ ).

Table S2: XGBoost hyperparameter search: top 5 Optuna trials with validation accuracy.

| Trial | Acc.          | Est. | Depth | LR     | SubS   | ByTree | Gamma   | Reg $\alpha$ | Reg $\lambda$ | MinCW |
|-------|---------------|------|-------|--------|--------|--------|---------|--------------|---------------|-------|
| 32    | <b>76.61%</b> | 1141 | 13    | 0.0215 | 0.5749 | 0.6986 | 0.5589  | 0.00184      | 0.00259       | 5     |
| 12    | 76.46%        | 984  | 12    | 0.0145 | 0.6675 | 0.6946 | 0.0799  | 0.00503      | 0.00455       | 7     |
| 24    | 76.40%        | 1165 | 11    | 0.0162 | 0.7831 | 0.6403 | 0.00413 | 0.00481      | 0.00478       | 9     |
| 13    | 76.29%        | 995  | 12    | 0.0277 | 0.6345 | 0.6829 | 0.3999  | 0.00011      | 0.00567       | 6     |
| 18    | 76.29%        | 915  | 13    | 0.0121 | 0.6784 | 0.5958 | 0.1612  | 0.00491      | 0.1732        | 8     |

Top five of 150 Optuna trials, ranked by in-region validation accuracy (Acc.); trial 32 (bold) was selected for the field-level XGBoost. Est.: number of estimators; Depth: maximum tree depth; LR: learning rate; SubS: row subsample; ByTree: column subsample per tree; Gamma: minimum split-loss reduction; Reg $\alpha$ /Reg $\lambda$ : L1/L2 regularization; MinCW: minimum child weight.

*TabNet*. At each of  $n_{\text{steps}}$  decision steps, an attentive transformer produces a sparse feature mask via *sparsemax*,

$$\begin{aligned}\mathbf{M}[i] &= \text{sparsemax}(\mathbf{P}[i-1] \odot h_i(\mathbf{a}[i-1])), \\ \mathbf{P}[i] &= \prod_{j=1}^i (\gamma - \mathbf{M}[j]),\end{aligned}\tag{S2}$$

with relaxation  $\gamma = 1.5$ ; the masked features are handled by a feature transformer. We use  $n_d = n_a = 64$ , 5 decision steps, batch size 1024, and ensemble five seeds by averaging softmax outputs. The *sparsemax* masks are the mechanism the main paper’s L-TAE-S grafts onto a temporal-attention backbone (Arik and Pfister, 2021; Muruganatham et al., 2024).

*L-TAE*. Given an embedded sequence  $\{\mathbf{z}_t\}_{t=1}^T$ , a learned master query attends over time; for a single head

$$\mathbf{o} = \sum_{t=1}^T \alpha_t \mathbf{v}_t, \quad \alpha_t = \frac{\exp(\mathbf{q}^\top \mathbf{k}_t / \sqrt{d})}{\sum_{t'} \exp(\mathbf{q}^\top \mathbf{k}_{t'} / \sqrt{d})},\tag{S3}$$

with channel grouping keeping the encoder lightweight (Garnot and Landrieu, 2020). Evaluated at pixel and field level as a five-seed ensemble.

*Transformer encoder.* After the same band embedding and month-aware positional encoding as L-TAE, the sequence passes three pre-norm multi-head self-attention layers ( $d_{\text{model}} = 128$ , 8 heads, feed-forward width 256), is mean-pooled, and classified (Vaswani et al., 2017; Rußwurm and Körner, 2020). Unlike L-TAE-S it has no feature-sparsity mechanism, serving as the capacity-versus-sparsity control. Five-seed ensemble under the same weighted-focal objective.

*TempCNN.* Stacked 1D convolutions along the temporal axis with batch normalization and dropout, followed by a softmax head (Pelletier et al., 2019); pixel and field variants, five seeds.

*Patch models.* Each field is tiled into 100 m patches ( $\sim 10 \times 10$  pixels) resampled to  $128 \times 128$  (Fig. S5). The multi-channel 2D CNN treats each band $\times$ month as a channel ( $C = 60$ ) through two convolutional blocks; the 3D CNN treats each patch as a spatiotemporal volume ( $T = 10$ ,  $C = 6$ ) through three 3D-convolutional blocks with a weighted focal loss (Fig. S6). Both are five-seed ensembles aggregated to a field label by majority vote.

## S-B. Performance Metric Definitions

*Supports main paper Sec. 3.* Let  $N$  be the number of samples,  $C$  the classes, and  $n_c$  the support of class  $c$ . Cohen’s Kappa is  $\kappa = (p_o - p_e)/(1 - p_e)$  with  $p_o$  the observed agreement and  $p_e = \sum_c (n_{c,\text{true}}/N)(n_{c,\text{pred}}/N)$ . Macro-F1 (primary) and weighted F1 are

$$\text{F1}_m = \frac{1}{C} \sum_{c=1}^C \text{F1}_c, \quad \text{F1}_w = \sum_{c=1}^C \frac{n_c}{N} \text{F1}_c, \quad (\text{S4})$$

with  $\text{F1}_c = 2 \text{Prec}_c \text{Rec}_c / (\text{Prec}_c + \text{Rec}_c)$ . Cross-entropy (Xent) is the AI4FoodSecurity field-level scoring metric (AI4EO, 2021); because submissions are hard labels, it is evaluated on the one-hot predicted label clipped to  $[\epsilon, 1 - \epsilon]$ ,  $\epsilon = 10^{-7}$ :

$$\begin{aligned} \text{Xent} &= -\frac{1}{N} \sum_{i=1}^N \sum_{c=1}^C y_{i,c} \ln \hat{q}_{i,c}, \\ \hat{q}_{i,c} &= \text{clip}(\mathcal{K}[\hat{y}_i = c], \epsilon, 1 - \epsilon). \end{aligned} \quad (\text{S5})$$

## S-C. Training Cost

*Supports main paper Sec. 3 and the Discussion.* Table S3 reports wall-clock training time for a single run of each model on one workstation (RTX 3080 Ti). The robust models that transfer best (the `xr_fresh` tree ensembles and the field-level L-TAE-S) are among the cheapest to train, while the most expensive (the patch CNNs and the pixel-level Transformer) do not lead the holdout ranking.

## S-D. Ablation Studies

*Supports main paper Sec. 5 (“Two Robustness Levers”).* We attribute the holdout ranking primarily to two levers—built-in sparse feature selection and field-level aggregation—and show that ensemble size and the imbalance-handling objective are second-order: they shift absolute scores but never reorder the robust and fragile model groups.

(i) *Field-level aggregation* (main Table 2) recovers most of the transfer gap for dense temporal nets (L-TAE  $-0.20 \rightarrow -0.07$ ; L-TAE-S  $-0.17 \rightarrow -0.04$ ) but harms TabNet ( $0.60 \rightarrow 0.43$ ). (ii) *Sparse selection versus attention capacity*: a plain Transformer with far greater capacity transfers no better than L-TAE (both ST  $\text{F1}_m = 0.58$ ), whereas grafting a sparse channel gate (L-TAE-S) lifts transfer to 0.60. (iii) *Resampling*: the *Stacking* and *SMOTE Stacked* ensembles differ only in SMOTETomek resampling; resampling widens the gap ( $-0.11 \rightarrow -0.21$ ) and lowers holdout  $\text{F1}_m$  ( $0.53 \rightarrow 0.49$ ).

## Example of Generated Patches by Field




Figure S5: Patch generation per field. Each field is tiled into 100 m patches—only  $\sim 10 \times 10$  pixels at the 10 m Sentinel-2 resolution—and resampled to  $128 \times 128$ . These patches are the input to the patch-based 2D and 3D CNNs, whose per-patch predictions are later aggregated to a field label by majority vote.






Figure S6: Patch-level 3D CNN pipeline: each field is tiled into 100 m patches resampled to  $128 \times 128$ ; a five-seed ensemble averages softmax outputs, and per-patch predictions are aggregated to a field label by majority vote.

Table S3: Per-seed training time for each model.

| Model                                    | Level | Features | Time / run          |
|------------------------------------------|-------|----------|---------------------|
| <i>Classical, field-level</i>            |       |          |                     |
| XGBoost                                  | field | xr_fresh | 12 s                |
| LightGBM                                 | field | xr_fresh | 31 s                |
| Voting                                   | field | xr_fresh | 109 s               |
| Stacking                                 | field | xr_fresh | 109 s               |
| SMOTE Stacked                            | field | xr_fresh | 99 s                |
| <i>Classical, pixel-level</i>            |       |          |                     |
| XGBoost                                  | pixel | xr_fresh | 31 s                |
| LightGBM                                 | pixel | xr_fresh | 31 s                |
| Logistic Regression                      | pixel | xr_fresh | 8.0 min             |
| Random Forest                            | pixel | xr_fresh | 73 min              |
| <i>Deep, field-level (raw sequences)</i> |       |          |                     |
| TabNet (xr_fresh)                        | field | xr_fresh | 34 s                |
| TabNet (raw, field-avg)                  | field | raw      | 39 s                |
| CNN-BiLSTM                               | field | raw      | 53 s                |
| L-TAE                                    | field | raw      | 61 s                |
| TempCNN                                  | field | raw      | 64 s                |
| L-TAE-S                                  | field | raw      | 18 s                |
| <i>Deep, pixel-level (raw sequences)</i> |       |          |                     |
| CNN-BiLSTM                               | pixel | raw      | 10 min              |
| L-TAE-S                                  | pixel | raw      | 24 min              |
| TempCNN                                  | pixel | raw      | 29 min              |
| L-TAE                                    | pixel | raw      | 38 min              |
| TabNet (raw)                             | pixel | raw      | 61 min <sup>‡</sup> |
| Transformer                              | pixel | raw      | 97 min              |
| <i>Deep, patch-level (raw sequences)</i> |       |          |                     |
| 3D CNN                                   | patch | raw      | 22 min              |
| Multi-Channel 2D CNN                     | patch | raw      | 38 min              |

Deep-model times are the mean per seed of a 5-seed ensemble (total wall-clock divided by five); classical models are a single best-configuration fit, excluding the one-time Optuna search. <sup>‡</sup>Measured on the 75% training fraction, the best-transferring TabNet pixel configuration.

Table S4: Ablation (iv): spatial-transfer holdout performance versus seed-ensemble size.

| Model              | Ensemble | $F1_m$          | $\kappa$        |
|--------------------|----------|-----------------|-----------------|
| TabNet (field)     | 1 seed   | $0.31 \pm 0.02$ | $0.18 \pm 0.03$ |
|                    | 3 seeds  | 0.39            | 0.29            |
|                    | 5 seeds  | 0.43            | 0.34            |
| L-TAE-S (field)    | 1 seed   | $0.56 \pm 0.02$ | $0.47 \pm 0.02$ |
|                    | 3 seeds  | 0.58            | 0.50            |
|                    | 5 seeds  | 0.60            | 0.52            |
| CNN-BiLSTM (field) | 1 seed   | $0.48 \pm 0.02$ | $0.31 \pm 0.02$ |
|                    | 3 seeds  | 0.52            | 0.34            |
|                    | 5 seeds  | 0.51            | 0.33            |

By re-inference of saved per-seed checkpoints. Single-seed rows report mean $\pm$ s.d. across five seeds.

(iv) *Ensemble size* (Table S4): seed-ensembling gives a small, monotone lift but does not change the ordering—a single-seed L-TAE-S ( $F1_m = 0.56$ ) already exceeds the five-seed CNN-BiLSTM and TabNet field ensembles. (v) *Imbalance-handling objective* (Table S5): the robust L-TAE-S is almost invariant across five loss/sampler settings (0.59–0.60), whereas the fragile CNN-BiLSTM is sensitive (0.41–0.56); even CNN-BiLSTM’s best setting (0.56) stays below L-TAE-S’s worst (0.59), so the objective never reorders the two.

## References

AI4EO, 2021. AI4FoodSecurity challenge (South Africa). European Space Agency (ESA), in partnership with Planet, TUM,

Table S5: Ablation (v): effect of the imbalance-handling objective and resampling on spatial-transfer holdout performance.

| Model              | Loss                          | Resample | F1 <sub>m</sub> | $\kappa$ |
|--------------------|-------------------------------|----------|-----------------|----------|
| TabNet (field)     | Weighted focal ( $\gamma=2$ ) | no       | 0.43            | 0.34     |
|                    | Weighted CE ( $\gamma=0$ )    | no       | 0.42            | 0.33     |
|                    | Plain CE                      | no       | 0.35            | 0.25     |
|                    | Weighted focal ( $\gamma=2$ ) | yes      | 0.40            | 0.23     |
|                    | Plain CE                      | yes      | 0.46            | 0.37     |
| L-TAE-S (field)    | Weighted focal ( $\gamma=2$ ) | no       | 0.60            | 0.52     |
|                    | Weighted CE ( $\gamma=0$ )    | no       | 0.60            | 0.50     |
|                    | Plain CE                      | no       | 0.59            | 0.50     |
|                    | Weighted focal ( $\gamma=2$ ) | yes      | 0.60            | 0.49     |
|                    | Plain CE                      | yes      | 0.60            | 0.50     |
| CNN-BiLSTM (field) | Weighted focal ( $\gamma=2$ ) | no       | 0.51            | 0.34     |
|                    | Weighted CE ( $\gamma=0$ )    | no       | 0.49            | 0.34     |
|                    | Plain CE                      | no       | 0.41            | 0.30     |
|                    | Weighted focal ( $\gamma=2$ ) | yes      | 0.56            | 0.39     |
|                    | Plain CE                      | yes      | 0.50            | 0.34     |

Field-level, 5-seed ensembles. “Resample” denotes class-balanced oversampling.

- DLR and Radiant Earth, <https://platform.ai4eo.eu/ai4food-security-south-africa>.
- Arik, S.Ö., Pfister, T., 2021. TabNet: Attentive interpretable tabular learning. *Proceedings of the AAAI Conference on Artificial Intelligence* 35, 6679–6687. doi:10.1609/aaai.v35i8.16826.
- Breiman, L., 2001. Random forests. *Machine Learning* 45, 5–32. doi:10.1023/A:1010933404324.
- Chen, T., Guestrin, C., 2016. XGBoost: A scalable tree boosting system, in: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 785–794. doi:10.1145/2939672.2939785.
- Friedman, J.H., 2001. Greedy function approximation: A gradient boosting machine. *Annals of Statistics* 29, 1189–1232. doi:10.1214/aos/1013203451.
- Garnot, V.S.F., Landrieu, L., 2020. Lightweight temporal self-attention for classifying satellite images time series, in: *Advanced Analytics and Learning on Temporal Data (AALTD 2020)*, ECML PKDD Workshops, Springer. pp. 171–181. doi:10.1007/978-3-030-65742-0\_12.
- James, G., Witten, D., Hastie, T., Tibshirani, R., 2013. *An Introduction to Statistical Learning*. Springer.
- Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., Liu, T.Y., 2017. LightGBM: A highly efficient gradient boosting decision tree, in: *Advances in Neural Information Processing Systems (NeurIPS)*.
- Mann, M.L., 2025. xr\_fresh: Automated time series feature extraction for remote sensing and gridded data. *Journal of Open Source Software* 10, 9009. doi:10.21105/joss.09009.
- Mann, M.L., Colson, L., Nealon, R., Engstrom, R., Nakacwa, S., 2026. Lite learning: Efficient crop classification in Tanzania using feature extraction with machine learning and crowd sourcing. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing* In press.
- Muruganantham, P., Wibowo, S., Grandhi, S., Islam, N., 2024. A deep learning approach for dealing with tabular data in crop classification, in: *Proceedings of the IEEE International Conference on ICT Convergence (ICTC)*, pp. 2054–2059. doi:10.1109/ICTC62082.2024.10826760.
- Pelletier, C., Webb, G.I., Petitjean, F., 2019. Temporal convolutional neural network for the classification of satellite image time series. *Remote Sensing* 11, 523. doi:10.3390/rs11050523.
- Rußwurm, M., Körner, M., 2020. Self-attention for raw optical satellite time series classification. *ISPRS Journal of Photogrammetry and Remote Sensing* 169, 421–435. doi:10.1016/j.isprsjprs.2020.06.006.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., Polosukhin, I., 2017. Attention is all you need, in: *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 5998–6008.