PRACTICAL – 1

Implementation and Time Analysis of Sorting Algorithms

Objective:

The objective of this practical is to implement and compare the performance of ***Bubble Sort, Selection Sort, Insertion Sort, Merge Sort, and Quick Sort***. We will analyze the time complexity and execution time of each algorithm to understand their efficiency and identify the most suitable algorithm for different applications.

1. Bubble Sort
Algorithm:

1. Start

2.For i= 0 to n-2

3. For j=0 to n-i-2

4. IfA[j]>A[j+1]

5. SwapA[j]and A[j + 1]

6. End If

7. End For

8. End For

9. Stop

Code:

```
import time

# Bubble Sort Function
def bubble_sort(arr, n):
    for i in range(n - 1):
        swapped = False

        for j in range(n - i - 1):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
                swapped = True

        # If no swapping occurs, array is already sorted
        if not swapped:
            break


# Take input from the user
n = int(input("Enter the number of elements: "))
```

```
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))

# Measure execution time
start_time = time.perf_counter()


bubble_sort(arr, n)

end_time = time.perf_counter()

# Display the sorted array
print("\nSorted Array:", arr)

# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f}
seconds".format(execution_time))
#Enter your EN.No
print("EN.No:92460118698")
```

OUTPUT:



Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*O(n)*	*The array is already sorted. With the optimized version (using a swapped flag), only one pass is required.*
Average Case	*$O(n^2)$*	*The array is in random order, requiring multiple comparisons and swaps.*
Worst Case	*$O(n^2)$*	*The array is sorted in reverse order, requiring the maximum number of comparisons and swaps.*

Space Complexity:

Space Complexity	*Description*
O(1)	*Uses only a temporary variable for swapping.*

2. Selection Sort

Algorithm:

1. Start
2. For i = 0 to n - 2
3. min = i
4. For j = i + 1 to n - 1
5. If A[j] < A[min]
6. min = j
7. End If
8. End For
9. Swap A[i] and A[min]
10. End For
11. Stop

Code:

```
import time

# Selection Sort Function
def selection_sort(arr):
    n = len(arr)
```

```
    for i in range(n):
        min_index = i

        # Find the minimum element in the unsorted part
        for j in range(i + 1, n):
            if arr[j] < arr[min_index]:
                min_index = j

        # Swap the found minimum element with the first unsorted element
        arr[i], arr[min_index] = arr[min_index], arr[i]


# Take input from the user
n = int(input("Enter the number of elements: "))

arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))

# Measure execution time
start_time = time.perf_counter()

selection_sort(arr)

end_time = time.perf_counter()

# Display the sorted array
print("\nSorted Array:", arr)

# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))
#Enter your EN.No
print("EN.No:92460118698")
```

OUTPUT:

```
PS C:\Users\manvi\AppData\Local\Programs\Microsoft VS Code> & C:\Users\manvi\AppData\Local\Python\pythoncore-3.14-64\python.exe c:/Users/manvi/OneDrive/Desktop/Daa-Sorting/Selectionsort.py
Enter the number of elements: 6
Enter 6 elements:
9
7
5
3
2
1
Sorted array: 1 2 3 5 7 9

Time Complexity:
Best Case: O(n^2)
Average Case: O(n^2)
Worst Case: O(n^2)
Space Complexity: O(1)

Enrollment Number: 92460118698
PS C:\Users\manvi\AppData\Local\Programs\Microsoft VS Code>
```

Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*$O(n^2)$*	*Even if the array is already sorted, the algorithm scans the remaining unsorted elements to find the minimum in every pass.*
Average Case	*$O(n^2)$*	*The array is in random order, requiring the same number of comparisons in each pass.*
Worst Case	*$O(n^2)$*	*The array is in reverse order, but the algorithm still performs the same number of comparisons and selects the minimum element in each pass.*

Space Complexity:

Space Complexity	*Description*
O(1)	*Sorts in place using constant extra memory.*

3. Insertion Sort

Algorithm:

1. Start
2. For i = 1 to n - 1
3. key = A[i]
4. j = i - 1
5. While j >= 0 AND A[j] > key
6. A[j + 1] = A[j]
7. j = j - 1
8. End While
9. A[j + 1] = key
10. End For
11. Stop

Code:

```
import time

# Insertion Sort Function
def insertion_sort(arr):
    n = len(arr)

    for i in range(1, n):
        key = arr[i]
        j = i - 1
        # Move elements greater than key one position ahead
        while j >= 0 and arr[j] > key:
            arr[j + 1] = arr[j]
            j -= 1
        arr[j + 1] = key
# Take input from the user
n = int(input("Enter the number of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
# Measure execution time
start_time = time.perf_counter()
insertion_sort(arr)
end_time = time.perf_counter()
# Display the sorted array
print("\nSorted Array:", arr)
```

```
# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))
#Enter your EN.No
print("EN.No:92460118698")
```

OUTPUT:



Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	***O(n)***	The array is already sorted, so each element is compared only once without any shifting.
Average Case	***O(n²)***	The array is randomly ordered, requiring comparisons and shifts for inserting elements into their correct positions.
Worst Case	***O(n²)***	The array is sorted in reverse order, requiring the maximum number of comparisons and shifts for every element.

Space Complexity:

Space Complexity	*Description*
O(1)	***Uses one extra variable for inserting elements.***

4. Merge Sort :

Algorithm:

1. If left < right
2. mid = (left + right) / 2
3. MergeSort(A, left, mid)
4. Merge Sort(A, mid + 1, right)
5. Merge(A, left, mid, right)
6. End If

Code:

```
import time
# Merge Sort Function
def merge_sort(arr):
    if len(arr) > 1:
        # Find the middle of the array
        mid = len(arr) // 2
        # Divide the array into two halves
        left = arr[:mid]
        right = arr[mid:]
        # Recursively sort both halves
        merge_sort(left)
        merge_sort(right)
        i = j = k = 0
        # Merge the sorted halves
        while i < len(left) and j < len(right):
            if left[i] < right[j]:
                arr[k] = left[i]
                i += 1
            else:
                arr[k] = right[j]
                j += 1
            k += 1
        # Copy remaining elements of left half
        while i < len(left):
            arr[k] = left[i]
            i += 1
            k += 1
```

```
    # Copy remaining elements of right half
    while j < len(right):
        arr[k] = right[j]
        j += 1
        k += 1
# Take input from the user
n = int(input("Enter the number of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
# Measure execution time
start_time = time.perf_counter()
merge_sort(arr)
end_time = time.perf_counter()
# Display the sorted array
print("\nSorted Array:", arr)
# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))
#Enter your EN.No
print("EN.No:92460118698")
```

OUTPUT:

```
PS C:\Users\manvi\AppData\Local\Programs\Microsoft VS Code> & C:\Users\manvi\AppData\Local\Python\pythoncore-3.14-64\python.exe c:/Users/manvi/OneDrive/Desktop/Daa-Sorting/Mergesort.py
Enter the number of elements: 6
Enter 6 elements:
8
6
5
3
2
1
Sorted array: 1 2 3 5 6 8

Time Complexity:
Best Case: O(n log n)
Average Case: O(n log n)
Worst Case: O(n log n)
Space Complexity: O(n)

Enrollment Number: 92460118698
```

Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*O(n log n)*	*The array is recursively divided and merged efficiently regardless of its initial order.*
Average Case	*O(n log n)*	*Randomly ordered elements are divided into subarrays and merged in sorted order.*
Worst Case	*O(n log n)*	*Even in the worst arrangement, the algorithm performs the same divide-and-conquer operations.*

Space Complexity:

Space Complexity	*Description*
O(n)	*Uses an additional array during merging.*

5. Quick Sort:

Algorithm:

if low < high:

pivot = Partition(arr, low, high)

QuickSort(arr, low, pivot - 1)

QuickSort(arr, pivot + 1, high)

return arr

Code:

```
import time
# Partition Function
def partition(arr, low, high):
    pivot = arr[high]      # Choose last element as pivot
    i = low - 1
    for j in range(low, high):
        if arr[j] <= pivot:
            i += 1
            arr[i], arr[j] = arr[j], arr[i]
    arr[i + 1], arr[high] = arr[high], arr[i + 1]
    return i + 1
# Quick Sort Function
def quick_sort(arr, low, high):
    if low < high:
```

```
        pi = partition(arr, low, high)
        quick_sort(arr, low, pi - 1)
        quick_sort(arr, pi + 1, high)
# Take input from the user
n = int(input("Enter the number of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
# Measure execution time
start_time = time.perf_counter()
quick_sort(arr, 0, n - 1)
end_time = time.perf_counter()

# Display the sorted array
print("\nSorted Array:", arr)

# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))
#Enter your EN.No
print("EN.No:92460118698")
```

OUTPUT:



Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*O(n log n)*	*The pivot divides the array into two nearly equal halves at every recursive step.*
Average Case	*O(n log n)*	*On average, the pivot creates reasonably balanced partitions, resulting in efficient sorting.*
Worst Case	*O(n²)*	*The pivot is always the smallest or largest element, creating highly unbalanced partitions (e.g., an already sorted array with a poor pivot choice).*

Space Complexity:

Space Complexity	*Description*
O(log n) (Average)	Uses recursion stack during sorting.
O(n) (Worst Case)	Occurs when partitions are highly unbalanced.