Software Requirements Specification

Transport Management System — Backend API (REST + WebSocket), version 1.0.0

Document	**SRS-1.0.0** — API Requirements Documentation
Asset	Name **transport**, type **API**, asset code **TRANSPORT-API-001**, version **1.0.0**
System	Freight/transport management backend serving shipper, driver, company/dispatcher and admin clients — 208 routes / 289 operations, 104 database tables, real-time Socket.IO layer
Platform	Node.js ≥ 20 · Express 5 · MySQL 8 · Redis · Socket.IO v4 · PM2
Environments	Production `https://app.dynamicsroute.tech` · staging `https://dev.dynamicsroute.tech`
Related documents	System & Architecture Design (SDD); API Technical Specifications (TDD/LLD) package; Request/Response package with endpoint inventory and live captures
Submitting entity	**[LEGAL NAME OF COMPANY / LICENCEE]**
Contact person	**[NAME, TITLE, EMAIL, TELEPHONE]**
Date of submission	**[DD MONTH YYYY]**

Status of this document

This specification describes the API *as implemented* in the deployed service. Every requirement listed here is present in the running system; no forward-looking features are specified. Fields shown in **amber** are administrative placeholders that the submitting entity completes before submission.

Contents

1	Introduction
2	Overall description
3	Functional requirements
4	External interface requirements
5	Data requirements
6	Non-functional requirements
7	Business rules and journey state model
8	Requirements traceability
A	Appendix A — glossary of acronyms

How to read this document

§3 contains the numbered functional requirements (prefix `FR–`), grouped by subsystem, each with a priority. §4 specifies every external interface of the system (REST, WebSocket, files, third-party services). §6 contains non-functional requirements (`NFR–`). §7 defines the journey state model that most functional requirements refer to, and §8 traces each requirement group to its design section in the companion SDD and to its verification evidence. Requirement identifiers are stable so a reviewer can follow a requirement from this document to its design element and to its implementation.

> **Verification baseline**
>
> All counts in this document were extracted from the source and validated against a running instance of the API: **208 distinct routes / 289 operations** (probe-verified, only non-404 routes counted), **104 MySQL tables**, **20 journey statuses**, **12 user roles**, **78 typed real-time message kinds**. The full route table ships in the Request/Response package (`endpoints.md`).

1. Introduction

1.1 Purpose

This document specifies the requirements for the **Transport Management System Backend API** (the “system”), the server-side component of a freight/transport management platform. It is the API Requirements Documentation (SRS) for the asset **transport** version 1.0.0 submitted for asset registration, and it is written for external review as well as for the project's own development and test baseline.

1.2 Scope

The system provides the complete server-side functionality of the platform:

- Identity: registration, contact verification by one-time password (OTP), authentication (JWT) and role-based authorization for 12 platform roles.
- Transport demand: shipper requests with a 20-state journey lifecycle, driver bidding, company-target batch dispatch, assignment and replacement workflows.
- Journey execution: loading stages, GPS route tracking, proof of delivery and delivery confirmation with photo evidence.
- Supply: company registration and approval, memberships and roles, fleet and driver–vehicle assignment, a FIFO dispatch queue for queue organizations.
- Real-time features: location exchange between driver and shipper, queue boards, typed in-app notifications over Socket.IO.
- Finance: deposits completed by payment-gateway webhook, balances, commissions, refunds and tariff rates.
- Supporting functions: document/media management, SMS/e-mail/FCM notifications, ratings, delinquency governance, subscriptions, administration and health endpoints.

Out of scope: the web and mobile client applications (separate systems that consume this API) and the external payment, SMS, e-mail and push providers themselves. All business records of account — journey state, permissions, financial entries — are held by this system; clients hold no business logic of record.

1.3 Definitions and acronyms

Term	Meaning
Shipper	Cargo owner who posts transport requests (role 1).
Driver	Person who receives or bids on transport requests (role 2).
Company	Transport company bidding on batched orders; operates fleet and staff (roles 7/8/10).
Journey	Execution record of one accepted transport, from loading through delivery to proof of delivery.
Journey status	One of 20 states (`journeyStatusId` 1–20) that every request moves through; defined in §7.
Request mode	`individual` (offer to single drivers) or `company_target` (companies bid on a batch).

Term	Meaning
Batch	A multi-vehicle order (`ShipperRequestBatch`) split into vehicle slots, each a request with its own status.
Decision	Immutable server-side record of a status move by an actor (`JourneyDecisions`).
POD	Proof of delivery: receiver identity, photos and confirmation captured at drop-off.
OTP / JWT	One-time password (second authentication factor) / JSON Web Token (bearer credential, 24 h).
Queue organization	Organization operating a FIFO dispatch queue for drivers (roles 11/12).
SRS / SDD / TDD	Requirements / System & Architecture Design / Technical (low-level) design documents of this package.

1.4 References

- API Endpoint Inventory — 208 routes / 289 operations, probe-validated (Request/Response package).
- API System & Architecture Design Document (SDD) — companion document of this package.
- API Technical Specifications (TDD/LLD) package — conventions, data model, status machine, socket protocol.
- Request/Response package — six live request/response captures (redacted).

2. Overall description

2.1 Product perspective

The system is a self-contained backend service executed under PM2 behind an Nginx TLS terminator. It persists data in MySQL (104 tables), uses Redis for caching and for scaling Socket.IO across nodes, and integrates outboundly with SMS, e-mail, push and payment services. It is the single authority for all business state of the platform: clients render, the server decides.




Figure 2.1 — Level 0 context: clients, platform, infrastructure and external services with numbered data flows

2.2 User classes and actors

Actor	Role id	Primary capabilities through the API
Shipper	1	Create/cancel transport requests, select bids, confirm delivery, manage documents, deposits.
Driver	2	Receive offers, bid/accept/reject, drive loading stages, report location, queue check-in, view earnings.
Admin / super admin	3 / 6	User and role governance, force status changes, delinquency decisions, system maintenance, analytics.
Vehicle owner	4	Register vehicles, assign drivers, maintain vehicle documents.
Company admin / staff / dispatcher	7 / 8 / 10	Company profile, memberships and roles, fleet, bids, assignments, dispatch.

Actor	Role id	Primary capabilities through the API
Queue org admin / dispatcher	11 / 12	Operate the dispatch queue: orders, driver check-in/out, FIFO offers, audit trail.
Payment provider	—	Delivers signed webhooks for deposit completion (public endpoint).
Monitoring system	—	Polls health endpoints (public).

2.3 Operating environment

- Runtime: Node.js ≥ 20, Express 5, PM2 process manager, Linux server (production).
- Data stores: MySQL 8 (primary), Redis/Upstash over TLS (cache + Socket.IO adapter).
- Clients: browser SPA and React Native mobile app over HTTPS and WSS.
- Environments: production (`app.dynamicsroute.tech`), staging (`dev.dynamicsroute.tech`), local development.

2.4 Constraints

- All traffic over TLS; JSON bodies (1 MB limit), multipart only for uploads.
- JWT lifetime fixed at 24 hours; no refresh-token endpoint in v1.0.0; every token is bound to a revocable server-side session.
- Personal data (names, phones, e-mail, GPS traces) processed under access control; production error responses must never expose stack traces.
- Status transitions and financial postings must be transactional and audited.

2.5 Assumptions and dependencies

- Clients enforce UI validation; the server remains the authority for all rules.
- SMS/e-mail delivery is provided by configured providers; outside production the test OTP `101010` is used.
- MySQL, Redis, SMTP, SMS, FCM and the payment gateway are external availability dependencies; the design degrades gracefully (see NFR-04).

3. Functional requirements

Priority: **M** = must (release-blocking), **H** = high. All requirements below are implemented in version 1.0.0; identifiers are stable and referenced by the SDD (§12 traceability) and by the automated test suites.

3.1 Identity and access — FR-01

ID	Requirement	Pri
FR-01.1	The system shall allow self-registration with name, phone, e-mail and password, creating the user, credential and role-mapping records. `POST /api/user/createUser`	M
FR-01.2	The system shall verify e-mail and phone ownership via OTP delivered by e-mail/SMS, with resend and "wrong e-mail" reporting. `/api/user/verify-email`, `/api/user/verify-phone`, `/api/user/report-wrong-email`	M
FR-01.3	The system shall authenticate by password hash and complete login with a second-factor OTP, issuing a signed JWT of 24 hours bound to a server-side session. `POST /api/user/loginUser`, `POST /api/user/verifyUserByOTP`	M
FR-01.4	The system shall reject calls to protected endpoints without a valid bearer token with `401`. Exactly 17 of 289 operations are public (listed in §4.1).	M
FR-01.5	The system shall authorize actions by role (12 roles), by ownership and by company scope, denying with `401/403`.	M
FR-01.6	The system shall support logout and forced logout on phone change (typed notification `force_logout_phone_change`), revoking the affected server-side session(s) immediately. `POST /api/user/logout`	M
FR-01.7	The system shall track per-role account status (active/suspended) with full history, so a suspension takes effect without deleting the user.	H
FR-01.8	The system shall record each login as a device session (platform, device, version, locale, IP, first/last seen, expiry) and reject any token whose session is revoked or expired with `401 Invalid token`. Users may list devices, revoke one, or revoke all others; administrators may revoke all sessions of a user. `GET /api/user/sessions`, `DELETE /api/user/sessions/:sessionUniqueId`, `DELETE /api/user/sessions`, `DELETE /api/admin/users/:userUniqueId/sessions`	M

3.2 Shipper requests — FR-02

ID	Requirement	Pri
FR-02.1	The system shall let a shipper create a transport request: origin/destination with coordinates, item name, quantity in quintal, shipping/delivery dates, individual or company-target mode, POD requirement.	M
FR-02.2	The system shall list a shipper's requests with pagination and sorting, defaulting to *connected-first* order (rows with a connected driver first), each row carrying request, status, driver, decisions and batch context. `GET /api/user/getShipperRequest4allOrSingleUser`	M

ID	Requirement	Pri
FR-02.3	The system shall allow updating a request while it is active, and deletion only when the status permits it.	M
FR-02.4	The system shall cancel requests per actor — shipper, driver, admin, system — producing distinct statuses (10/12/13/15) with actor-tagged cancellation reasons served per context (`individual | company | both`).	M
FR-02.5	The system shall create batches of vehicle slots for company-target orders and support partial batch cancellation: batch status `partiallyCancelled` (20) while each slot keeps its own terminal status.	M

3.3 Bidding and assignment — FR-03

ID	Requirement	Pri
FR-03.1	The system shall dispatch an offer to a driver (status 2) and record accept, reject and no-answer outcomes (3/18/16), automatically re-offering after a no-answer.	M
FR-03.2	The system shall accept a driver's acceptance together with a bidding price, moving the request to status 3 and storing the bid amount.	M
FR-03.3	The system shall let the shipper select one bid (status 4) while marking the others `notSelectedInBid` (17) or `rejectedByShipper` (11).	M
FR-03.4	The system shall let companies submit, view and manage bids on batches (mark-as-seen, status transitions); the shipper awards a company which assigns drivers and vehicles per slot.	M
FR-03.5	The system shall support driver replacement under company assignment (status 19) and bulk/automatic assignment operations for companies.	H

3.4 Journey execution — FR-04

ID	Requirement	Pri
FR-04.1	The system shall enforce the 20-state journey status model: transitions occur only through dedicated action endpoints executed inside database transactions; clients cannot write the status column.	M
FR-04.2	The system shall drive the loading stages `goToLoadingPlace → loading → loaded` (5→6→7) and `journeyStarted` (8), stamping time and GPS coordinates on the journey record.	M
FR-04.3	The system shall record every decision — actor, time, resulting status, shipping/delivery dates and cost — in the decision log, and every status mutation in history tables.	M
FR-04.4	The system shall capture proof of delivery with receiver identity and photo evidence, producing status 9 `journeyCompleted` .	M
FR-04.5	The system shall record the driver's route as GPS points and expose ongoing/completed journey queries.	H

ID	Requirement	Pri
FR-04.6	The system shall reconcile stale statuses automatically for *active* requests only; terminal statuses are never rewritten, so a cancelled order cannot be resurrected onto the offerable board.	M
FR-04.7	The system shall support administrative overrides: cancel (13) and force-complete (14).	M

3. Functional requirements (continued)

3.5 Company and fleet — FR-05

ID	Requirement	Pri
FR-05.1	The system shall register companies with an admin approval workflow and profile history.	M
FR-05.2	The system shall manage company memberships (invite, reactivate, deactivate) and company-defined roles.	M
FR-05.3	The system shall manage the fleet: vehicles, vehicle types, vehicle status types, ownership, and active/inactive driver–vehicle assignments with date ranges.	M
FR-05.4	The system shall compute and expose company ratings and enforce company bans and delinquency blocking.	H

3.6 Dispatch queue — FR-06

ID	Requirement	Pri
FR-06.1	The system shall manage queue organizations with admin/dispatcher memberships.	M
FR-06.2	The system shall maintain a FIFO driver queue with entry/exit operations, broadcasting every board change to subscribed sockets in organization and day rooms.	M
FR-06.3	The system shall audit queue operations (who entered/left/reordered, when).	H

3.7 Finance — FR-07

ID	Requirement	Pri
FR-07.1	The system shall accept deposit-completion webhooks from the payment provider on a public, signature-verified endpoint and credit the user balance idempotently. `POST /api/finance/userDeposit/santimPay/webhook`	M
FR-07.2	The system shall manage deposit requests, refund flows, balance transfers and financial-institution accounts.	M
FR-07.3	The system shall apply commission rules (rates → user/company commissions) and tariff rates per vehicle type.	H
FR-07.4	The system shall record journey payments linked to journeys.	H

3.8 Document and media management — FR-08

ID	Requirement	Pri
FR-08.1	The system shall accept multipart uploads, re-encode images, and serve files under access control from `/uploads` and `/Assets`.	M
FR-08.2	The system shall validate documents against per-role document requirements, rejecting duplicate and wrong-type documents.	M

ID	Requirement	Pri
FR-08.3	The system shall keep a history of document changes.	H

3.9 Notifications — FR-09

ID	Requirement	Pri
FR-09.1	The system shall deliver in-app notifications over Socket.IO on the `messages` channel using a catalog of 78 typed message payloads (e.g. `driver_accepted_shipper_request`).	M
FR-09.2	The system shall send FCM push to registered device tokens for users without a live socket.	H
FR-09.3	The system shall send transactional e-mail and SMS (OTP, verification, alerts).	M
FR-09.4	The system shall notify the shipper of every journey status change in real time.	M

3.10 Administration and governance — FR-10

ID	Requirement	Pri
FR-10.1	The system shall expose admin endpoints for user/role management, online/offline driver views, database statistics and table maintenance.	M
FR-10.2	The system shall implement a delinquency lifecycle: types, user and company delinquencies with responses, admin decisions, bans.	H
FR-10.3	The system shall record entity history for every create/update in paired history tables.	M
FR-10.4	The system shall expose health endpoints for liveness and database checks (public, used by monitoring). `GET /api/health`, `GET /api/health/database`	M

3.11 Ratings — FR-11 · 3.12 Subscriptions — FR-12

ID	Requirement	Pri
FR-11.1	The system shall capture ratings between parties after journeys and expose company ratings.	H
FR-12.1	The system shall manage subscription plans, pricing and user subscriptions with history.	H

4. External interface requirements

4.1 REST API — IR-01

- **Volume:** 208 distinct routes / 289 operations in 27 groups (`/api/user`, `/api/company`, `/api/finance`, `/api/queue…`, `/api/admin`, `/api/vehicle`, plus root-mounted utility routes). The full table with an auth column per route ships as `endpoints.md` in the Request/Response package.
- **Protocol:** HTTPS, JSON bodies (UTF-8); multipart/form-data for uploads; production base `https://app.dynamicsroute.tech`.
- **Authentication:** `Authorization: Bearer <JWT>`. 17 operations are public: registration/verification/login/OTP/logout, two health endpoints, the SantimPay webhook, and a small set of maintenance endpoints (database stats, cache clear, create/drop-table helpers, role-status helper).
- **Success envelope:** HTTP 2xx with at least a `message` field plus resource data.
- **Error envelope:** `{ status:"fail", message, error:{ statusCode, status, isOperational } }` for 400/401/403/404/409/429/5xx; stack traces only in development.
- **Pagination and sorting:** `page`, `limit`, `sortBy`, `sortOrder`.
- **Validation:** Joi schemas per route — all violations reported at once, unknown fields stripped, empty POST body rejected with 400.
- **Rate limits:** a global limiter plus a stricter limiter on `/api/user` auth routes; 429 when exceeded.

4.2 WebSocket — IR-02

- Socket.IO over `/socket.io` (websocket and polling transports, Engine.IO v3 compatible), JWT supplied in the handshake auth, CORS allow-list, optional Redis adapter for multi-node fan-out.
- Client→server: `queue:subscribe`, `queue:unsubscribe`, `locationUpdateToDriver`, `locationUpdateToShipper`, `message`.
- Server→client: `queue` board events, `queue:subscribed/unsubscribed` acks, `messages` typed notifications (78 kinds), location events (with replay of last position), `response` acks, structured error frames.
- Rooms: `queueOrg:<id>` and `queueOrg:<id>:<date>`.

4.3 File interface — IR-03

- Upload: multipart with size limits; images re-encoded; document type and duplicate checks before persistence.
- Serving: static `/uploads` and `/Assets` behind access rules.

4.4 Third-party services — IR-04

Service	Interface
Payment gateway (SantimPay)	Inbound signed webhook for deposit completion; must be idempotent (the provider retries).
SMS provider	Outbound SMS (OTP, alerts) through the SMSSender integration.
SMTP e-mail	Outbound e-mail: verification, OTP, notifications.

Service	Interface
Firebase Cloud Messaging	Outbound push to registered device tokens.
Redis (Upstash)	Cache and Socket.IO pub/sub adapter over TLS.

5. Data requirements

- **104 MySQL tables** grouped as: identity (users, credentials, roles, OTP, devices, sessions), transport core (requests, batches, driver requests/bids, journeys, decisions, statuses, route points, cancellations, POD), companies and fleet, dispatch queue, bidding/assignment, finance (deposits, balances, commissions, tariffs), documents, delinquency/governance, ratings, subscriptions and reference data. The full list with relations is in the TDD package (`data-model.md`).
- **Keys:** UUID business keys (`*UniqueId`) used in routes and payloads; numeric surrogate ids for status maps and legacy joins.
- **Audit:** paired `*History` tables record every mutation with actor and timestamp; status history and a queue audit log are first-class.
- **Retention:** soft delete (`*DeletedAt`) on business entities; history rows are append-only.
- **Integrity:** parameterized SQL only; multi-step writes execute in database transactions; reference values (statuses, roles, document types) are seeded rows joined on read.

> **Sensitive-data inventory**
>
> Personal data held: names, phone numbers, e-mail addresses (users and receivers), GPS traces (`JourneyRoutePoints`, last-location store), document images (IDs, licences), financial records (deposits, balances). All are access-controlled by bearer authentication plus role/ownership scoping; none appear in production error responses or logs at info level.

6. Non-functional requirements

ID	Category	Requirement
NFR-01	Security	bcrypt password hashing; JWT with 24 h expiry bound to a revocable server-side session; helmet headers; explicit CORS allow-list; CSRF origin checks for cookie sessions; rate limiting; bot/UA blocking; parameterized SQL; fail-closed production boot checks; secrets in environment only; masked 5xx in production.
NFR-02	Performance	Paged list endpoints on indexed sort keys (connected-first ordering via an EXISTS subquery); Redis cache for hot reads; pooled MySQL connections; 1 MB body cap.
NFR-03	Scalability	Stateless REST (JWT) allows horizontal scaling; Socket.IO Redis adapter keeps rooms consistent across nodes; PM2 cluster-capable.
NFR-04	Availability	Health endpoints for liveness/readiness; supervised PM2 restarts; graceful degradation — Redis adapter failures fall back to single-server mode, socket errors never crash the process.
NFR-05	Observability	Request IDs on every request; structured logs (request logger, client/server error classes); query performance capture; socket error logging with stacks.
NFR-06	Integrity	Status transitions and money movements transactional; append-only history; automatic reconciliation restricted to active statuses.

ID	Category	Requirement
NFR-07	Maintainability	Layered architecture (routes → middleware → controllers → services → CRUD); shared validator/responder/error types; seeded reference data in code; 102 unit tests and a 248-check E2E suite.
NFR-08	Compatibility	Engine.IO v3 clients accepted; websocket and polling transports; browser (CORS) and bearer-token clients interchangeable.

7. Business rules and journey state model

Every transport request moves through a 20-state machine held in the `JourneyStatus` table and enforced by server-side services. Clients never write the status; they call action endpoints (offer, accept, reject, select, loading-stage, cancel, confirm-delivery) and the server derives the next state transactionally.




Figure 7.1 — Journey status machine: main execution path, decision outcomes and terminal states

7.1 Status classes (business rules)

Class	Status ids	Rule
Active	2, 3, 4, 5, 6, 7, 8	Live requests; the only statuses automatic reconciliation may rewrite; driver connection and enrichment apply.
Supporting (decision-backed)	2–9	A positive decision still evidences a live/completed request; list output attaches the connected driver and decisions for these rows (connected-first ordering).
Terminal	10, 12, 13, 14, 15	Deliberate end states; never re-opened, never reconciled — rewriting one to `waiting` would resurrect a cancelled order.
Pre-connection	1	`waiting` : created but no driver connected; rendered as an inactive order until a decision appears.
Completed	9	Terminal but decision-backed; still receives journey/POD enrichment on read.
Batch	20	`partiallyCancelled` : applies to batches; per-slot rows keep their own terminal statuses.

7.2 Key business rules

1. Offers expire without an answer → status 16 and automatic re-offer to the next driver.
2. A bid can be accepted only once the driver's acceptance (3) precedes shipper selection (4); losing bids become 17 or 11.
3. Loading-stage transitions (5→6→7→8) require the selecting decision and stamp time + GPS.
4. Cancellation reason lists and allowed actors differ by context (`individual` vs `company`) and role (shipper 1, driver 2, admin 3, queue org admin 11).
5. Company assignment may replace an individual driver link → status 19 on the replaced link.
6. Batch partial cancellation (20) never rewrites completed or in-transit slots.
7. Only statuses inside the active set may be corrected by reconciliation; all corrections write a decision/history row.

8. Requirements traceability

Each requirement group maps to its design section in the companion SDD and to verification evidence shipped in this package or produced by the automated suites.

Requirement group	Design section (SDD)	Verification evidence
FR-01 identity & access	§6 API design · §8 Security architecture	Login/OTP/401 example captures; E2E registration→login chain; jest auth tests
FR-02 shipper requests	§4 Component design · §5 Data architecture	E2E create/list/cancel flows; list capture with connected-first page 1
FR-03 bidding & assignment	§4 Component design (dispatch)	E2E bid/selection/rejection scenarios (incl. known-failure baselines)
FR-04 journey execution	§4 status machine & transition choreography	E2E lifecycle suites; status-history rows; POD tests
FR-05 company & fleet	§5 Data architecture (company domain)	E2E company bid/assignment scenarios
FR-06 dispatch queue	§7 Real-time architecture	Socket harness: subscribe/room broadcast checks
FR-07 finance	§3 Data flow (entry points) · §8 Security	Webhook tests; deposit→balance E2E checks
FR-08 documents	§4 Component design (media)	Upload/duplicate/type rejection tests
FR-09 notifications	§7 Real-time architecture	Socket harness message/room assertions; 78-type catalog
FR-10..12 admin, ratings, subscriptions	§9 Deployment · §5 Data architecture	Admin endpoint probes; health checks
NFR-01..08	§8 Security · §9 Deployment · §11 Testing	E2E negative probes (401/400/404); prod fail-closed checks; rate-limit tests

> **Package completeness**
>
> This SRS is submitted together with the SDD (system & architecture design), the TDD/LLD ZIP (conventions, data model, status machine, socket protocol, endpoint inventory) and the Request/Response ZIP (inventory + six live captures). Together they satisfy the four document requirements of the Add Asset form.

Appendix A — glossary of acronyms

Acronym	Expansion
API	Application Programming Interface
CPE	Critical Product Element (optional asset-register classification)
CRUD	Create / Read / Update / Delete

Acronym	Expansion
DFD	Data Flow Diagram
E2E	End-to-End (test suite)
FCM	Firebase Cloud Messaging
FR / NFR / IR	Functional / Non-functional / Interface Requirement
GPS	Global Positioning System
JWT	JSON Web Token
LLD	Low-Level Design
OTP	One-Time Password
POD	Proof of Delivery
PM2	Node.js process manager
REST	Representational State Transfer
SDD / SRS / TDD	System Design Description / Software Requirements Specification / Technical Design Document
Session	Server-side login record whose identifier (`sid`) is carried in the JWT and whose revocation signs that device out
TLS	Transport Layer Security
WSS	WebSocket Secure