

Wazuh Agent Configuration

R. Frohman, M. Martin, H. Walden

Agent Settings

The main configuration file for Wazuh agents is also `ossec.conf`, located in the `/var/ossec/etc/` directory on the agent machines.

```
<ossec_config>
  <client>
    <server-ip>192.168.1.1</server-ip>
  </client>
</ossec_config>
```

Log Monitoring

Log data collection involves gathering and consolidating logs from different log sources within a network. Log data collection helps security teams to meet regulatory compliance, detect and remediate threats, and identify application errors and other security issues.

```
<ossec_config>
  <localfile>
    <log_format>syslog</log_format>
    <location>/var/log/messages</location>
  </localfile>
</ossec_config>
```

Active Response

Wazuh has an active response module that helps security teams automate response actions based on specific triggers, enabling them to effectively manage security incidents.

```
<ossec_config>
  <active-response>
    <disabled>no</disabled>
    <command>host-deny</command>
    <location>any</location>
  </active-response>
</ossec_config>
```

Adding and Managing Agents

Add an Agent:

```
/var/ossec/bin/manage_agents -a
```

Extract Agent Key:

```
/var/ossec/bin/manage_agents -e <agent_id>
```

Import Agent Key on Agent Machine:

```
/var/ossec/bin/manage_agents -i < /path/to/agent/key
```

Restarting Wazuh Services

After making Configuration changes, you need to restart the Wazuh Services.

```
sudo systemctl restart wazuh-manager  
sudo systemctl restart wazuh-agent
```

Monitoring and Troubleshooting

Check Wazuh Logs:

```
tail -f /var/ossec/logs/ossec.log
```

Verify Agent Connection:

```
/var/ossec/bin/agent_control -ls
```

Sources

Wazuh. (n.d.). Wazuh documentation. <https://documentation.wazuh.com/current/index.html>

<https://chatgpt.com/c/b6a45085-e1cf-4d4a-856b-4f0858395f57>