```
HostGator... 2.75 m
```

FileZilla

W3c validator - Para verificar se o site esta a funcionar corretamente. (Separador file)

```
Netlify.com
```

```
<head>
<script src="https://ajax.googleapis.com/ajax/libs/
jquery/3.5.1/jquery.min.js"></script>
<script src="my_jquery_functions.js"></script>
</head>
```

More Examples of jQuery Selectors

| Syntax | Description | |
|---------------------------|--|--|
| \$("*") | Selects all elements | |
| \$(this) | Selects the current HTML element | |
| \$("p.intro") | Selects all elements with class="intro" | |
| \$("p:first") | Selects the first element | |
| \$("ul li:first") | Selects the first element of the first | |
| \$("ul li:first-child") | Selects the first <ii> element of every </ii> | |
| \$("[href]") | Selects all elements with an href attribute | |
| \$("a[target='_blank']") | Selects all <a> elements with a target attribute value equal to "_blank" | |
| \$("a[target!='_blank']") | Selects all <a> elements with a target attribute value NOT equal to "_blank" | |
| \$(":button") | Selects all <button> elements and <input/> elements of type="button"</button> | |
| \$("tr:even") | Selects all even elements | |
| \$("tr:odd") | Selects all odd elements | |

```
$(document).ready(function(){
   $("button").click(function(){
      $("#test").hide();
   });
```

});

EVENTOS

| Mouse Events | Keyboard Events | Form Events | Document/Window Events |
|--------------|------------------------|-------------|------------------------|
| click | keypress | submit | load |
| dblclick | keydown | change | resize |
| mouseenter | keyup | focus | scroll |
| mouseleave | | blur | unload |

```
$("p").click(function(){
 $(this).hide();
});
$("p").dblclick(function(){
 $(this).hide();
});
$("#p1").mouseenter(function(){
 alert("You entered p1!");
});
$("#p1").mouseleave(function(){
 alert("Bye! You now leave p1!");
});
$("#p1").hover(function(){
 alert("You entered p1!");
},
function(){
 alert("Bye! You now leave p1!");
});
$("input").focus(function(){
 $(this).css("background-color", "#cccccc");
});
$("input").focus(function(){
 $(this).css("background-color", "#cccccc");
});
```

```
$("p").on({
    mouseenter: function(){
        $(this).css("background-color", "lightgray");
    },
    mouseleave: function(){
        $(this).css("background-color", "lightblue");
    },
    click: function(){
        $(this).css("background-color", "yellow");
    }
});
```

jQuery hide() and show()

```
$("button").click(function(){
    $("p").hide(1000);
}):
```

jQuery toggle() mostra e esconde

```
$("button").click(function(){
   $("p").toggle();
});
```

jQuery Fading Methods

```
$("button").click(function(){
    $("#div1").fadeIn();
    $("#div2").fadeIn("slow");
    $("#div3").fadeIn(3000);
});

$("button").click(function(){
    $("#div1").fadeOut();
    $("#div2").fadeOut("slow");
    $("#div3").fadeOut(3000);
});
```

jQuery Sliding Methods

```
$("#flip").click(function(){
  $("#panel").slideDown();
});
$("#flip").click(function(){
  $("#panel").slideUp();
});
$("#flip").click(function(){
  $("#panel").slideToggle();
});
<style>
#panel, #flip {
  padding: 5px;
  text-align: center;
  background-color: #e5eecc;
  border: solid 1px #c3c3c3;
}
#panel {
  padding: 50px;
  display: none;
}
</style>
</head>
<body>
<div id="flip">Click to slide down panel</div>
<div id="panel">Hello world!</div>
</body>
```

Get Content - text(), html(), and val()

```
$("#btn1").click(function(){
    alert("Text: " + $("#test").text());
});
$("#btn2").click(function(){
    alert("HTML: " + $("#test").html());
});
$("#btn1").click(function(){
    alert("Value: " + $("#test").val());//FROM INPUT
});
```

Get Attributes - attr()

```
$("button").click(function(){
   alert($("#w3s").attr("href"));
});
```

Set Content - text(), html(), and val()

```
$("#btn1").click(function(){
   $("#test1").text("Hello world!");
});
$("#btn2").click(function(){
   $("#test2").html("<b>Hello world!</b>");
```

```
});
$("#btn3").click(function(){
   $("#test3").val("Dolly Duck");//FROM INPUT
});
```

A Callback Function for text(), html(), and val()

```
$("#btn1").click(function(){
    $("#test1").text(function(i, origText){
        return "Old text: " + origText + " New text:
Hello world!
        (index: " + i + ")";
    });
});

$("#btn2").click(function(){
    $("#test2").html(function(i, origText){
        return "Old html: " + origText + " New html:
Hello <b>world!</b>
        (index: " + i + ")";
    });
});
```

Set Attributes - attr()

```
$("button").click(function(){
   $("#w3s").attr("href", "https://www.w3schools.com/
jquery/");
});

$("button").click(function(){
   $("#w3s").attr({
```

```
"href" : "https://www.w3schools.com/jquery/",
    "title" : "W3Schools jQuery Tutorial"
    });
});
```

jQuery append() Method

```
$("p").append("Some appended text.");
$("p").prepend("Some prepended text.");
```

jQuery remove() Method

```
$("#div1").remove();
$("#div1").empty();//remove all Childs
```

jQuery Manipulating CSS

```
$("button").click(function(){
    $("h1, h2, p").addClass("blue");
    $("div").addClass("important");
});

$("button").click(function(){
    $("h1, h2, p").removeClass("blue");
});

$("button").click(function(){
    $("h1, h2, p").toggleClass("blue");//alternate classes
```

Return a CSS Property

```
$("p").css("background-color");
```

Set a CSS Property

```
$("p").css("background-color", "yellow");
$("p").css({"background-color": "yellow", "font-
size": "200%"});
```

jQuery parent() Method

```
$(document).ready(function(){
   $("span").parent().css();
});

$(document).ready(function(){
   $("span").parents();//all ancestors
});
```

jQuery children() Method

```
$(document).ready(function(){
   $("div").children();
```

```
});

$(document).ready(function(){
   $("div").children("p.first");
});

$(document).ready(function(){
   $("div").find("span");
});
```