

- Tool to automate download condor tarballs ([github issue](#))
 - Shipped as a standalone tool with glideinwms (but doesn't have any dependency)
 - Uses a yaml configuration file to select which tarballs to download:

```
DESTINATION_DIR: "/var/lib/gwms-factory/condor/"
TARBALL_BASE_URL: "https://research.cs.wisc.edu/htcondor/tarball/"
DEFAULT_TARBALL_VERSION: ["9.0.16"] # Can be set to "latest"
CONDOR_TARBALL_LIST:
  - MAJOR_VERSION: "9.0"
    WHITELIST: ["9.0.7", "9.0.16", "latest"]
  - MAJOR_VERSION: "10.0"
    WHITELIST: ["latest"]
    CHECK_LATEST: True
  - MAJOR_VERSION: "10.x"
    DOWNLOAD_LATEST: True # Same as adding "latest" to a WHITELIST. Default False
  - MAJOR_VERSION: "23.0"
    WHITELIST: ["23.0.0"]
FILENAME_LIST: ["condor-{version}-x86_64_CentOS7-stripped.tar.gz", "condor-{version}-x86_64_CentOS8-stripped.tar.gz",
  "condor-{version}-x86_64_AlmaLinux8-stripped.tar.gz", "condor-{version}-x86_64_Ubuntu18-stripped.tar.gz",
  "condor-{version}-x86_64_Ubuntu20-stripped.tar.gz",
  "condor-{version}-aarch64_Stream8-stripped.tar.gz", "condor-{version}-ppc64le_CentOS8-stripped.tar.gz",
  "condor-{version}-ppc64le_AlmaLinux8-stripped.tar.gz",
  "condor-{version}-aarch64_AlmaLinux8-stripped.tar.gz"]
OS_MAP: { "CentOS7": "default, rhel7, linux-rhel7", "CentOS8": "rhel8, linux-rhel8", "AlmaLinux8": "rhel8, linux-rhel8", "Ubuntu18":
  "ubuntu18, linux-ubuntu18",
  "Ubuntu20": "ubuntu20, linux-ubuntu20" }
ARCH_MAP: { "x86_64": "default", "ppc64le": "ppc64le", "aarch64": "aarch64" }
XML_OUT: "/etc/gwms-factory/config.d/01-condor-tarballs.xml"
```

- Can generate xml tarball snippet that can be put in config.d to fully automate the process

- Feature to allow pilot overloading for whole nodes
 - See talk at recent F2F CMS management meeting attached to the [github issue](#)
 - Two new knobs added called GLIDEIN_OVERLOAD_CPUS and GLIDEIN_OVERLOAD_MEMORY
 - Allow to add virtual cores and memory and schedule more work to improve efficiency

