BetterWayViewController

+ mapView : MKMapView
- routeOverlayView : UICRouteOverlayMapView
+ destinationLocation : AddressLocation
+ originLocation : AddressLocation
+ locationManager : CLLocationManager
- routeRecalculatorClock : RouteRecalculatorClock

+ (void)requestRouteWithDestinationAddress:
  (AddressLocation)toDestination
   withOrigin:(AddressLocation)toOrigin;
+ (void)recalculateRouteWithCurrentLocation:
  (AddressLocation)toDestination

BetterWayAppDelegate

+ betterWayViewController : BetterWayViewController
+ listContentQueryAddress : NSMutableArray
+ listFavoriteQueryAddress : NSMutableArray
+ internetReachable : Reachability
- registerClock : RegisterClock
- eventClock : EventClock

- (void)loadDatabase
+ (void)checkNetworkStatus:(NSNotification)notice

RouteMenuViewController

- tableView : UITableView
- listOptions : NSArray

SearchAddressViewController

- tableView : UITableView
- listContentQueryAddress : NSArray
- filteredListContent : NSMutableArray

- (void) searchButtonClicked: (UISearchBar)searchBar

FavoriteListViewController

- listFavoriteQueryAddress : NSMutableArray
- tableView : UITableView

FavoriteAddViewController

- addressLocation : AddressLocation

- (void)saveButtonClicked: (id)sender

CheckAddressViewController

- mapView : MKMapView
- addressLocation : AddressLocation

- (IBAction)confirmButtonClicked:(id)sender
- (void)saveAddress
- (void)sendEmail

MFMailComposeViewController

+ (BOOL)canSendMail
- (void)setSubject:(NSString)subject
- (void)setToRecipients:(NSArray)toRecipients
- (void)setCcRecipients:(NSArray)ccRecipients
- (void)setBccRecipients:(NSArray)bccRecipients
- (void)setMessageBody:(NSString)body isHTML:(BOOL)isHTML