 Human0 # Maxey0 ### The Context Plane: where any task belongs, and who should handle it Give Maxey0 a task. It places it on one path (domain → topic → concept → skill → agents → MCP servers) and shows that path in a live 3D map, in your browser or inside Claude. [![release](https://img.shields.io/badge/release-v1.1.0%20Prefederation-c2410c)](CHANGELOG.md) [![MCP](https://img.shields.io/badge/MCP-read--only%20server-0e7490)](docs/MCP_SERVER.md) [![license](https://img.shields.io/badge/license-Apache--2.0-eab308)](LICENSE) [![by](https://img.shields.io/badge/by-Human0-334155)](https://app.maxey0.com/) **[Open the app](https://app.maxey0.com/app)** · [Documentation](https://app.maxey0.com/docs/) · [Research](https://app.maxey0.com/research/) · [Getting started](#getting-started) · [Use it inside Claude](#use-it-inside-claude)

Maxey0 is a context plane for agent systems. Before an agent acts on a task it has to answer *what kind of work is this?* and *who, with which tools, should do it?* Maxey0 answers both from one structured, versioned map of **11 domains, 128 topics, 711 concepts, 1,998 skills, 1,021 agents and 117 real MCP servers**, every node embedded in one shared space. It returns a candidate path, never an authorization: nothing runs until your orchestrator decides.

Why Maxey0?

- **One path per task:** the topic, concept and skill a task falls under, plus the agents who should do it, check it and support it
- **Real tools:** the MCP servers agents hold are real, published servers; concepts, skills and agents are generated and structurally checked
- **Two signals:** TF-IDF plus dense bge-m3 embeddings in one inner-product space (exact-skill recovery 93.3% → 98.7% on the live server)
- **An observer lens with drift:** each level is read from the nodes chosen above it, and every route records how far each node moved to fit the task
- **Inside Claude:** a public MCP server and an MCP App that draws the graph in your conversation
- **Hand-off to Claude Code:** export a route as a project with one subagent per chosen agent

How it works


How it works: 1 your task, 2 domain and topic, 3 concept and skill, 4 agents (primary, checker, support), 5 the MCP servers they hold, 6 the route with drift and a harness


An isolated path in the Maxey0 Context Plane Graph: one concept, its skills, the agents that handle them and the MCP servers those agents use, each on its own level ring

Getting started

	How	Where
Use it here	Open the app, type a task, press Submit task	app.maxey0.com/app
Use it inside Claude	Add a custom connector (below)	`https://app.maxey0.com/mcp`
Install the plugin	`/plugin marketplace add mmc7676/Human0` then `/plugin install maxey0-context-plane-graph@human0`	plugin/
Build with Claude Code	Route a task in the app, then **Send to Claude Code**	the downloaded project folder

Use it inside Claude

1. In Claude: **Customize → Connectors → + Add → Add custom connector**
2. Name: `Maxey0 Context Plane`
3. URL: `https://app.maxey0.com/mcp`
4. Sign-in: none (the server is read-only)

Then ask Claude: *"Route this task with Maxey0: ..."* or *"Open the Maxey0 graph."*

Research

The papers behind Maxey0 (the Context Plane, Structured Context Worlds, System One and more) are at **app.maxey0.com/research**, each with a summary, a question-and-answer frame and a PDF.

What's in the map

11 domains	Agentic Systems and Software Engineering · Data Science and Quantitative Methods · Mathematical and Physical Sciences · Engineering · Life, Health and Mind Sciences · Earth, Environment and Place · Business, Finance and Economics · Society, Governance and Ethics · Languages, Literatures and Communication · Area and Identity Studies · Humanities and Arts
128 topics	formed from the concepts up, from Agent Harnesses and MCP Contracts to Derivatives, Quantum Physics and Translation Studies
711 concepts · 1,998 skills	3–8 concepts per topic, 1–17 skills per concept
1,021 agents	every one a permanent **MaxeyN** key (Maxey0 is the orchestrator); each skill has a primary, a checker and support agents
117 MCP servers · 556 links	real, existence-checked servers, linked to the agents whose skills they fit

Agents in the map are **context records**: a role, the skills it serves and the tools it would hold. They are not running agents.

Use it

In your browser

Open **maxey0-context-plane-mcp.maxey0.workers.dev/app**. No sign-in, nothing to install. Type a task, press **Submit task**, and the graph lights up the route.

In Claude, as a connector

1. **Customize → Connectors → Add custom connector**
2. URL: `https://maxey0-context-plane-mcp.maxey0.workers.dev/mcp` · Authentication: none
3. Ask:
4. *"Open the Maxey0 Context Plane graph for the task: price a call option."*
5. *"Use Maxey0 Context Plane to route: build a website for a real estate office."*
6. *"Which MaxeyN agent checks entanglement entropy results, and with which tools?"*

Where the host supports MCP Apps (Claude Desktop, for example), the graph opens inside the conversation.

In Claude, as a plugin

Install `plugin/maxey0-context-plane-graph` . It adds the same connector plus two skills: one that teaches Claude to route with the map, and `topic-graph-generator` , which writes and validates a new topic when a task has no route.

From any MCP client

```
{
  "mcpServers": {
    "maxey0-context-plane": { "type": "http", "url": "https://maxey0
  }
}
```


The graph app


Routing a task

Route a task. The best path is highlighted; the panel names it, the method, and the next candidates.


Rotating the graph

Turn it any way. Drag to rotate in any direction, Shift-drag to roll, 720° to tumble, Fit view to reset.


Isolated path

Isolate a path. Each level is a ring; the path spreads around it and stays readable as the graph turns.


Full map

See the whole map. 4,000 nodes on five stacked levels, with agent-to-server gates.

- **Route** any task with the same method the server uses; a task with no route offers to generate the missing topic.
- **Isolate** a topic, concept, skill, agent or server and its full path; **spread** it on the level rings; **drag** a node and everything below it follows on its own level.
- **Browse** by topic and concept, search any node, read its details, and tick which MCP gates place an agent.
- **Generate topics** with Claude, validate them, add them to the graph, keep or remove each one, and view new topics alone or with the full map.
- **Save state** (topics, layout, view) to the browser or a file; a state saved against another version of the map is refused rather than loaded wrong.
- **Inside Claude**, the app takes the task Claude passes in, can go full screen, and sends generation requests straight to the conversation.

The user guide walks through every control.

The MCP server

Fifteen read-only tools, one prompt, nine resources and one resource template, over the MCP 2026-07-28 stateless protocol (and the earlier `initialize` handshake for older clients).

Tool	Answers
`route_task`	Which topic, concept, skill, agents and servers fit this task? Flat ranking, or

Tool	Answers
	`mode: "lens"` to read each level from the nodes chosen above it
`search`	Which nodes match these words?
`nearest`	Which nodes, at any level, lie nearest this node or text in the shared embedding field?
`list_domains · list_topics · children · trace`	Browse the map and walk any node's parents
`get_topic · get_concept · get_skill · get_agent · get_mcp_server`	One node in detail
`get_harness`	One topic in full: every concept, skill, agent and server
`open_context_plane_graph`	Show the graph (MCP App), optionally routed to a task or opened on a topic
`validate_topic_pack`	Check a generated topic against the schema and the live map

Prompt: `topic-graph-generator`. Endpoints: `/mcp` serves every domain; `/mcp/<domain id>` serves one domain. Full reference: docs/MCP_SERVER.md.

Only what a call asks for is returned: about 7 KB of tool definitions up front, 3–10 KB per lookup, and one topic in full is about 49 KB. The full map stays on the server.

How routing works

One method scores everything: search, routing, agent-to-server links and related concepts. Text is reduced to words (lower case, stop words removed, plurals folded), weighted by TF-IDF, and compared by cosine similarity. A match must share at least two words, so a single rare word is never enough.

Use	Threshold
A task matches a skill	cosine ≥ 0.08
An agent holds an MCP server	cosine ≥ 0.10, top 2 agents per server
Two concepts in different topics are related	cosine ≥ 0.40

One embedding field for all six levels. Every node (domain, topic, concept, skill, agent, MCP server) has a vector in the same TF-IDF space: domains and topics from their own text and their concepts, agents from the skills they serve, servers from their description and tools. A truncated SVD of all of them gives every node a location in one shared field, at one scale. In the graph, **Embedding field** places each node at that location on its level, so nodes that mean the same thing line up across levels; `nearest` answers the same question over MCP.

A **checker** agent holds every server its primary holds for the same skill, so it can verify by re-running the work, not just by reading it. More in docs/ARCHITECTURE.md.

Limits

- **Generated content.** Concepts, skills and agents are generated and structurally checked, not expert-reviewed. MCP servers are real projects whose existence was checked; whether a server suits your use is yours to judge.
- **Lexical, not semantic.** Routing matches words. A task phrased in words the map doesn't use returns no route rather than a wrong one; rephrasing, or generating the missing topic, fixes it.
- **Context, not execution.** A route is a candidate, never an authorization. Some listed servers can place orders or move money; this project never calls them.

Privacy

The server is read-only and has no accounts. It stores nothing you send it, and the app keeps its saved state in your own browser. See PRIVACY.md.

Repository

```
server/   MCP server (TypeScript, Cloudflare Workers) and its tests
app/      the graph app: build script, built page, browser tests
SCW1/     the map: source topic packs, the ontology spec, the built
tools/    the map builder and topic-pack generator (Python)
plugin/   the Claude plugin
docs/     user guide, server reference, architecture, development
```

Build, test and deploy: docs/DEVELOPMENT.md. Changes: CHANGELOG.md.

Support

Questions and bug reports: GitHub Issues.

License and credit

Apache License 2.0. Redistributions keep the NOTICE file.

Structured Context Windows (SCW), Maxey0 and Human0 were created by **Human0 (Mike Cohan)**; SCWs were first published on 27 September 2025. To cite this project, use **Cite this repository** on the Human0 repository page.

Built with Claude.