

# 1 Complexity, Games, Polytopes and Gale Strings

## 1.1 Some Complexity Classes

references - cite Papadimitriou (book) for general; Papadimitriou 1994 for PPAD

A *computational problem* is given by the combination of an *input* and a related *output*. A specific input gives an *instance* of the problem.

Computational problems can be classified according to the form of their output. A *function problem*  $P$  returns for an instance  $x$  an output  $y$  that satisfies a given binary relation  $R(x, y)$ . In the case of a *decision problems*,  $y$  is either “YES” or “NO”. The *complement* of a decision problem  $P$  is the problem  $\bar{P}$  that returns “NO” for each instance of  $P$  that returns “YES”, and vice versa.

*Search problems* are function problems that return either an output  $y$  such that  $R(x, y)$ , or “NO”, if it’s not possible to find any such  $y$ . If  $y$  is guaranteed to exist, the problem is called a *total function problem*. *Counting problems* return the *number* of  $y$ ’s that satisfy  $R(x, y)$ ; given a problem  $R$  we denote the associated counting problem  $\#R$ .

An example of decision problem is: “(input) given a graph, (question) is it possible to find an Euler tour of the graph?” Its complement is “(input) given a graph, (question) is it possible that there isn’t any Euler of the graph?” A search problem is: “(input) given a graph, (output) return one Euler tour of the graph, or “NO” if no such tour exists.” A total function problem is: “(input) given an Euler graph, (output) return one of its Euler tours.” Finally, a counting problem is “(input) given a graph, (output) return the number of its Euler tours.”

Computational problems are also classified according to their *computational complexity*, given by the *reducibility* from each other.

Turing machines: here - not that in the following deterministic TM

Let  $P_1$  be a computational problem. For an instance  $x$  of  $P_1$ , let  $|x|$

be the the number of bits needed to encode  $x$ .  $P_1$  *reduces to the problem*  $P_2$  *in polynomial time*, denoted  $P_1 \leq_P P_2$ , if there exists a *polynomial-time reduction*, that is, a function  $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$  and a Turing machine  $\mathcal{M}$  such that for all  $x \in \{0, 1\}^*$

1.  $x \in P_1 \iff f(x) \in P_2$ ;
2.  $\mathcal{M}$  computes  $f(x)$ ;
3.  $\mathcal{M}$  stops after  $p(|x|)$  steps, where  $p$  is a polynomial.

For any class  $C$  of decision problems, the class of all complements of the problems in  $C$  is the *complement class*  $\text{co} - C$ . A problem  $P$  is *hard* for a class  $C$  if for every problem  $P_C$  in  $C$  there is a polynomial-time reduction to  $P$ ; that is, if  $P$  is hard to solve at least as every problem in  $C$ . A  $C$  - *hard* problem in  $C$  is *complete* for  $C$ .

The complexity class **P** contains all the *polynomially decidable problems*, that is, all problems  $P$  such that there exists a Turing machine  $\mathcal{M}$  that outputs either “YES” or “NO” for all inputs  $x \in \{0, 1\}^*$  of  $P$  after  $p(|x|)$  steps, where  $p$  is a polynomial. Intuitively, a decision problem is in **P** if the answer to its question can be found in a number of steps that is polynomial in the input of the problem.

A problem  $P$  belongs to the class **NP**, *non-deterministic polynomial-time problems*, if there exists a Turing machine  $\mathcal{M}$  and polynomials  $p_1, p_2$  such that

1. for all  $x \in P$  there exists a *certificate*  $y \in \{0, 1\}^*$  which satisfies  $|y| \leq p_1(|x|)$ ;
2.  $\mathcal{M}$  accepts the combined input  $xy$ , stopping after at most  $p_2(|x| + |y|)$  steps;
3. for all  $x \notin P$  there does not exist  $y \in \{0, 1\}^*$  such that  $\mathcal{M}$  accepts the combined input  $xy$ .

This means that a decision problem is in **NP** if it takes polynomial time to verify whether the “certificate solution”  $y$  is, indeed, a correct answer to the question posed by the problem. The class **#P** is the class of all problems that output the number of possible certificates for a problem in **NP**.

check formal def of # P (?)

In [7], Megiddo and Papadimitriou introduce the classes **FNP**, *function non-deterministic polynomial*, and **TFNP**, *total function non-deterministic polynomial*. The former is defined as the class of binary relations  $R(x, y)$  such that there is a polynomial-time algorithm that decides whether  $R(x, y)$  holds for given  $x, y$  satisfying  $|y| \leq p(|x|)$ , where  $p$  is a polynomial. The latter is the class of all such problems for which  $y$  is guaranteed to exist. Intuitively, **FNP** and **TFNP** are similar to **NP**, but they allow for problems of (respectively) function and total function form.

In [7], Megiddo and Papadimitriou also prove that, unless **NP** = **co-NP**, it's impossible to find a **TFNP**-complete problem. To circumvent this limitation of **TFNP**, Papadimitriou ([9]) focused on the problems for which the existence of a solution is proved by a “parity argument”, introducing the classes **PPA** (*Proof by Parity Argument*) and **PPAD** (*Proof by Parity Argument, Directed version*).

definition of PPA(D): one in Papadimitriou 1994 and one in DGP - the second w END OF THE LINE, use that one.

## 1.2 Normal Form Games and Nash Equilibria

$n$ -NASH in TFNP and typical problem pushing the def of PPAD ([9]); in fact, PPAD-complete ([3] for  $n \geq 3$ , [2] for  $n = 2$ ).

until here

## 1.3 Best Response Polytopes

file: polytopes

## 1.4 Cyclic Polytopes and Gale Strings

## 1.5 The Problem ANOTHER GALE

file: gale-def

merge in one section "Gale strings" or "CP and GS"?

## References

- [1] M. M. Casetti, J. Merschen, B. von Stengel (2010). “Finding Gale Strings.” *Electronic Notes in Discrete Mathematics* 36, pp. 1065–1082.
  - [2] X. Chen, X. Deng (2006). “Settling the Complexity of 2-Player Nash Equilibrium.” *Proc. 47th FOCS*, pp. 261–272.
  - [3] C. Daskalakis, P. W. Goldberg, C. H. Papadimitriou (2006). “The Complexity of Computing a Nash Equilibrium.” *SIAM Journal on Computing*, 39(1), pp. 195–259.
  - [4] J. Edmonds (1965). “Paths, Trees, and Flowers.” *Canad. J. Math.* 17, pp. 449–467.
  - [5] D. Gale (1963), “Neighborly and Cyclic Polytopes.” *Convexity, Proc. Symposia in Pure Math.*, Vol. 7, ed. V. Klee, American Math. Soc., Providence, Rhode Island, pp. 225–232.
  - [6] C. E. Lemke, J. T. Howson, Jr. (1964). “Equilibrium Points of Bimatrix Games.” *J. Soc. Indust. Appl. Mathematics* 12, pp. 413–423.
  - [7] N. Megiddo, C. H. Papadimitriou (1991). “On Total Functions, Existence Theorems and Computational Complexity.” *Theoretical Computer Science* 81, pp. 317–324.
  - [8] J. Merschen (2012). “Nash Equilibria, Gale Strings, and Perfect Matchings.” PhD Thesis, London School of Economics and Political Science.
  - [9] C. H. Papadimitriou (1994). “On the Complexity of the Parity Argument and Other Inefficient Proofs of Existence.” *J. Comput. System Sci.* 48, pp. 498–532.
  - [10] R. Savani, B. von Stengel (2006). “Hard-to-solve Bimatrix Games.” *Econometrica* 74, pp. 397–429.
- better other article, “Exponentially many steps for finding a NE in a bimatrix game” In the 45th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2004.?
- [11] L. Végh, B. von Stengel “Oriented Euler Complexes and Signed Perfect Matchings.” arXiv:1210.4694v2 [cs.DM]