

Abstract

This thesis presents a report on original research, published as joint work with Merschen and von Stengel in *Electronic Notes in Discrete Mathematics* [1]. Our result shows a polynomial time algorithm to solve two problems related to labeled Gale strings, a combinatorial structure consisting of a string of labels and a bitstring satisfying certain conditions introduced by Gale in [5].

Gale strings can be used in the representation of a particular class of games that Savani and von Stengel [10] used as an example of exponential running time for the classical Lemke-Howson algorithm to find a Nash equilibrium of a bimatrix game [7]. It was conjectured that solving these games via the Lemke-Howson algorithm was complete in the class PPAD (Proof by Parity Argument, Directed version). A major motivation for the definition of this class by Papadimitriou [9] was, in turn, to capture the pivoting technique of many results related to the Nash equilibrium, including the Lemke-Howson algorithm.

Our result, on the contrary, sets apart this class of games as a case for which there is a polynomial-time algorithm to find a Nash equilibrium. Since Daskalakis, Goldberg and Papadimitriou [3] and Chen and Deng [2] proved the PPAD-completeness of finding a Nash equilibrium in general normal-form games, we have a special class of games, unless $\text{PPAD} = \text{P}$.

Our proof exploits two results. The first one is the representation of the Nash equilibria of these games as Gale strings, as seen in Savani and von Stengel [10]. The second one is the polynomial-time solvability of the problem of finding a perfect matching in a graph, proven by Edmonds [4].

Further results by Merschen [6] and Végé and von Stengel [11] will be mentioned.

An appendix relates an amendment to the proof of the PPAD-completeness result by Daskalakis, Goldberg and Papadimitriou [3].

1 Introduction

2 Complexity, Games, Polytopes and Gale Strings

2.1 The Complexity Classes P and PPAD

2.2 Normal Form Games and Nash Equilibria

file: background-subsection

2.3 Bimatrix Games and Best Response Polytopes

file: polytopes-subsection

2.4 Cyclic Polytopes and Gale Strings

2.5 Labeling and the Problem ANOTHER GALE

file: gale-def-subsection

3 Algorithmic and Complexity Results

3.1 Pivoting

3.2 The Lemke-Howson Algorithm and Parity

file: pivoting-LH-subsection

3.3 The Complexity of GALE and ANOTHER GALE

file: main-result-subsection - done!

4 Further results

Appendix A: A result about PPAD completeness of Nash

Appendix B: Notation

References

- [1] M. M. Casetti, J. Merschen, B. von Stengel (2010). “Finding Gale Strings.” *Electronic Notes in Discrete Mathematics* 36, pp. 1065–1082.
 - [2] X. Chen, X. Deng (2006). “Settling the Complexity of 2-Player Nash Equilibrium.” *Proc. 47th FOCS*, pp. 261–272.
 - [3] C. Daskalakis, P. W. Goldberg, C. H. Papadimitriou (2006). “The Complexity of Computing a Nash Equilibrium.” *SIAM Journal on Computing*, 39(1), pp. 195–259.
 - [4] J. Edmonds (1965). “Paths, Trees, and Flowers.” *Canad. J. Math.* 17, pp. 449–467.
 - [5] D. Gale (1963), “Neighborly and Cyclic Polytopes.” *Convexity, Proc. Symposia in Pure Math.*, Vol. 7, ed. V. Klee, American Math. Soc., Providence, Rhode Island, pp. 225–232.
 - [6] J. Merschen (2012). “Nash Equilibria, Gale Strings, and Perfect Matchings.” PhD Thesis, London School of Economics and Political Science.
 - [7] C. E. Lemke, J. T. Howson, Jr. (1964). “Equilibrium Points of Bimatrix Games.” *J. Soc. Indust. Appl. Mathematics* 12, pp. 413–423.
 - [8] N. Megiddo, C. H. Papadimitriou (1991). “On Total Functions, Existence Theorems and Computational Complexity.” *Theoretical Computer Science* 81, pp. 317–324.
 - [9] C. H. Papadimitriou (1994). “On the Complexity of the Parity Argument and Other Inefficient Proofs of Existence.” *J. Comput. System Sci.* 48, pp. 498–532.
 - [10] R. Savani, B. von Stengel (2006). “Hard-to-solve Bimatrix Games.” *Econometrica* 74, pp. 397–429.
- better other article, “Exponentially many steps for finding a NE in a bimatrix game” In the 45th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2004.?
- [11] L. Végh, B. von Stengel “Oriented Euler Complexes and Signed Perfect Matchings.” arXiv:1210.4694v2 [cs.DM]