Plain range: Excel sees cells, identified by column letters and row numbers

No name: formulas must refer to cell addresses — *Formula copied by hand*

	A	G	H	K	P
1	SalesInvoiceLineID	Quantity	BaseListPrice	LineTotal	ListAmount
10645	10644	6.00	374.22	2,177.94	2,245.32
10646	**10645**	**2.00**	**382.45**	**688.42**	**764.90**
10647	10646	3.74	856.08	2,817.53	3,201.74
10648	10647	0.68	563.52	344.88	383.19

Column formula, copied by hand:
P10646 holds =ROUND(G10646*H10646,2). The formula was typed in P2 and copied down, so every row has its own copy, and nothing ensures that rows added below the data get one.

Total: =SUM(K2:K27934)
The formula names fixed cells. Rows added below row 27934 are left out of the total, and nothing warns you.

Excel Table: Excel sees a named dataset with named columns

Table name: SalesInvoiceLine — *Calculated column*

	A	G	H	K	P
1	SalesInvoiceLineID ▾	Quantity ▾	BaseListPrice ▾	LineTotal ▾	ListAmount ▾
10645	10644	6.00	374.22	2,177.94	2,245.32
10646	**10645**	**2.00**	**382.45**	**688.42**	**764.90**
10647	10646	3.74	856.08	2,817.53	3,201.74
10648	10647	0.68	563.52	344.88	383.19

Calculated column:
=ROUND([@Quantity]*[@BaseListPrice],2)
One formula for the whole column. Excel fills it into every row, including rows added later.

Total: =SUM(SalesInvoiceLine[LineTotal])
Includes every row the Table holds, however many there are.

Both views show the same cells. Shaded row: line 10645, the Alder Desk sold on invoice SI-2025-007947, which you traced in Tutorial 3.2. The selected cell holds the plain range's formula for that line.