Audit.sql

```
-- Tutorial 12.2, test P4: purchase order approvals
-- Population: all purchase orders; expected: no rows
WITH ApprovalExceptions AS (
    SELECT 'Self-approved' AS Test, po.PONumber, po.OrderTotal
    FROM PurchaseOrder AS po
    WHERE po.CreatedByEmployeeID = po.ApprovedByEmployeeID
    UNION ALL
    SELECT 'Above approver limit', po.PONumber, po.OrderTotal
    FROM PurchaseOrder AS po
        INNER JOIN Employee AS e
            ON e.EmployeeID = po.ApprovedByEmployeeID
    WHERE po.OrderTotal > e.MaxApprovalAmount
    UNION ALL
    SELECT 'Dated after approver left', po.PONumber, po.OrderTotal
    FROM PurchaseOrder AS po
        INNER JOIN Employee AS e
            ON e.EmployeeID = po.ApprovedByEmployeeID
    WHERE e.TerminationDate IS NOT NULL
        AND po.OrderDate > e.TerminationDate
)
SELECT Test, COUNT(*) AS Orders, ROUND(SUM(OrderTotal), 2) AS OrderValue
FROM ApprovalExceptions
GROUP BY Test
ORDER BY Orders DESC;
```

	Test	Orders	OrderValue
1	Above approver limit	13	705779.39
2	Self-approved	9	651830.75
3	Dated after approver left	3	15419.28

```
Execution finished without errors.
Result: 3 rows returned
At line 247:
WITH ApprovalExceptions AS (
```

Outlined: the three tests, with the number of purchase orders each flags and their value. Most of the fourteen orders fail two tests.