

New Database

Open Database ▾

Write Changes

Revert Changes

Database Structure

Browse Data

Edit Pragmas

Execute SQL

Open SQL file(s)

Save SQL file ▾

▶ Execute all/selected SQL

Audit.sql

```
109 Classified AS (  
110     SELECT si.SubTotal,  
111            strftime('%Y', sh.DeliveryDate) AS DeliveryYear,  
112     CASE  
113         WHEN strftime('%Y', p.PostingDate)  
114              <> strftime('%Y', sh.DeliveryDate)  
115             THEN 'Revenue posted in another year'  
116         WHEN si.InvoiceDate < sh.ShipmentDate  
117             THEN 'Invoice dated before shipment'  
118         ELSE 'In the year of delivery'  
119     END AS Finding  
120 FROM SalesInvoice AS si  
121     INNER JOIN Shipped AS sh  
122         ON sh.SalesInvoiceID = si.SalesInvoiceID  
123     INNER JOIN Posted AS p ON p.SalesInvoiceID = si.SalesInvoiceID  
124 )  
125 SELECT Finding, DeliveryYear, COUNT(*) AS Invoices,  
126        ROUND(SUM(SubTotal), 2) AS SubTotal  
127 FROM Classified  
128 WHERE Finding <> 'In the year of delivery'  
129 GROUP BY Finding, DeliveryYear  
130 ORDER BY Finding, DeliveryYear;
```

	Finding	DeliveryYear	Invoices	SubTotal
1	Invoice dated before shipment	2024	3	7487.67
2	Invoice dated before shipment	2025	3	649.05
3	Invoice dated before shipment	2026	2	1349.19
4	Revenue posted in another year	2024	15	90138.93
5	Revenue posted in another year	2025	8	19540.86

Execution finished without errors.
Result: 5 rows returned
At line 93:
WITH Shipped AS (

The editor is scrolled past the two CTEs that find each invoice's shipment and posting dates. Outlined: revenue for December deliveries posted in January of the next year.